District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe. NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

			balla i c, i viv	107505	to the approp	THAT THE OUT DIS	and onice.
15649	Propo	P sed Alternative	it, Below-Grad		e Plan Appli	cation	
	_	Below grade tan Permit of a pit of	k registration r proposed alternati	ve method		OIL CONS. DI	V DIST. 3
		☐ Modification to ☐ Closure plan on	below-grade tank, of an existing permit/of by submitted for an ex-	r registration		NOV 0 4 ed pit, below-grad	
	or proposed alter						
nvironment. Nor o	nat approval of this re	quest does not relieve the the operator of its respon	e operator of liability sh	ould operations res	sult in pollution of su	rface water, ground	water or the
ı. Operator: <u>BP A</u>	merica Productio	on Company		OGRID #:_	778	5 to	
Address:200	Energy Court, F	armington, NM 87	401				
Facility or well n	ame: GALLEC	GOS CANYON UN	NIT 216				
		11621					
U/L or Qtr/Qtr _	N Secti	on 14 Tow	nship <u>28N</u>	Range 12W	County:S	San Juan	
Center of Propose	ed Design: Latitude	36.65816	Longitud	le <u>-108.088</u>	331	NAD: 🔲1	927 🛛 1983
		Private Tribal Tr					
	tion F, G or J of 19.		* Construct Additional	S Above C C-141 Re	Josue Stans Quirel	AARS 07 19.	15.17.13. <b>N</b> MA(
	-	vitation P&A N	Aulti-Well Fluid Mana	gement	Low Chloride Dr	illing Fluid 🔲 yes	□no
Lined Un	nlined Liner type:	Thicknessn	nil LLDPE H	IDPE PVC	Other	*	
String-Reinfo	rced						
Liner Seams:	Welded  Factory	Other	Vo	lume:	_bbl Dimensions:	Lx W	x D
3.			and the second		e ii		
⊠ <u>Below-grade</u>	tank: Subsection	I of 19.15.17.11 NMAG	TANK TANK	<u>A</u>			
Volume:	95	_bbl Type of fluid: _	Produced water				
Tank Constructio	n material:Stee						
☐ Secondary co	ontainment with leak	detection  Visible	sidewalls, liner, 6-inc	h lift and automati	c overflow shut-off		
☐ Visible sidew	valls and liner 🔲 🕽	isible sidewalls only [	Other Double	wall/ Double bo	ottom; no visible	e sidewalls	
Liner type: Thick	cness	mil HDF	PE PVC Other	r			
4.	Mathad:	s to difference			= a <sub>A</sub> n		

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital,							
institution or church)  ☐ Four foot height, four strands of barbed wire evenly spaced between one and four feet ☐ Alternate. Please specify							
Thermac. Troube specify							
6.  Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  □ Screen □ Netting □ Other							
☐ Monthly inspections (If netting or screening is not physically feasible)							
7. Signs: Subsection C of 19.15.17.11 NMAC							
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers							
☐ Signed in compliance with 19.15.16.8 NMAC							
8.  Variances and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.							
9. <u>Siting Criteria (regarding permitting)</u> : 19.15.17.10 NMAC <u>Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below.</u> Siting criteria does not apply to drying pads or above-grade tanks.	ptable source						
General siting							
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No						
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No						
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No						
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No						
Within a 100-year floodplain. (Does not apply to below grade tanks)  - FEMA map							
Below Grade Tanks							
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site							
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)							
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No								
application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image									
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site									
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site									
Temporary Pit Non-low chloride drilling fluid									
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No								
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Permanent Pit or Multi-Well Fluid Management Pit									
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site									
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image									
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.									
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No								
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.									
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC									
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:									
11.  Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the document of the following items must be attached to the application.	uments are								
attached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	15.17.9 NMAC								
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC									
Previously Approved Design (attach copy of design) API Number: or Permit Number:									

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.  Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment	documents are						
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC							
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan  Emergency Response Plan  Oil Field Waste Stream Characterization  Monitoring and Inspection Plan  Erosion Control Plan							
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	,						
13.  Proposed Closure: 19.15.17.13 NMAC  Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.  Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit						
☐ Alternative  Proposed Closure Method: ☐ Waste Excavation and Removal ☐ Waste Removal (Closed-loop systems only) ☐ On-site Closure Method (Only for temporary pits and closed-loop systems) ☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method							
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC							
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.							
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No						
Ground water is between 25-50 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells    Yes   No   NA   NA							
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells    Yes   No   NA							
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site							
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image							
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site							
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No						
Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Yes No							
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance							

Within the area overlying a subsurface mine.  Within an unstable area.  Brighnering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain.  FEMA map  Waste Material Sampling Plan based upon the appropriate requirements of 19.15.17.13 NMAC  Beat flood fl		
Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society, Topographic map  Within a 100-year floodplain.  FEMA map    Year Minis a 100-year floodplain.	adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		☐ Yes ☐ No
Within a 100-year floodplain. FEMA map    Year		
NEMO_Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Pleaby a check murk in the box, that the documents are attached.	그는 그는 그들은 그들은 그는 그들은 그는 그는 그는 그는 그는 그들은 그는 그들은 그는 그들은 그는 그들은 그를 가는 것이다.	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Plea by a check mark in the box, that the documents are attached.    Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC   Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC   Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.13 NMAC   Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC   Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC   Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC   Since Plan Plan Plan Plan Plan Plan Plan Plan		☐ Yes ☐ No
Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.  Name (Print):	On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure put by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
Signature:    Date:	Operator Application Certification:	ief.
e-mail address:	Name (Print): Title:	
e-mail address:	Signature: Date:	
OCD Approval:		
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date: 2/12/2016  Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-loop system If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by mark in the box, that the documents are attached.  Proof of Closure Notice (surface owner and division)	OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature:  Approval Date:	1997
Closure Method:  ☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-loop system of different from approved plan, please explain.  ☐ If different from approved plan, please explain.  ☐ Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by mark in the box, that the documents are attached.  ☐ Proof of Closure Notice (surface owner and division)	Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by mark in the box, that the documents are attached.  Proof of Closure Notice (surface owner and division)	Closure Method:  ☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo	oop systems only)
☐ Plot Plan (for on-site closures and temporary pits) ☐ Confirmation Sampling Analytical Results (if applicable) ☐ Waste Material Sampling Analytical Results (required for on-site closure) ☐ Disposal Facility Name and Permit Number ☐ Soil Backfilling and Cover Installation ☐ Re-vegetation Application Rates and Seeding Technique ☐ Site Reclamation (Photo Documentation)	Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached.  □ Proof of Closure Notice (surface owner and division) □ Proof of Deed Notice (required for on-site closure for private land only) □ Plot Plan (for on-site closures and temporary pits) □ Confirmation Sampling Analytical Results (if applicable) □ Waste Material Sampling Analytical Results (required for on-site closure) □ Disposal Facility Name and Permit Number □ Soil Backfilling and Cover Installation □ Re-vegetation Application Rates and Seeding Technique	
		7 🕅 1983

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure repo belief. I also certify that the closure complies with all applicable closure requirement	
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature:	Date: October 31, 2016
e-mail address: steven.moskal@bp.com	Telephone: (505) 326-9497

#### BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

# Gallegos Canyon Unit 216 API No. 3004511621 Unit Letter N, Section 14, T28N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

#### **General Closure Plan**

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
  - Notice was not provided to the surface owner, the Navajo Tribe, due to an BP internal communication breakdown. The Tribe was aware of activities on location.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
  Notice was provided and is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.037
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.073
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<u>760</u>
Chlorides	US EPA Method 300.0 or 4500B	250 or background	57

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for TPH, BTEX and chloride with all concentrations below the stated limits, with the exception of TPH. The field report and laboratory reports are attached.

- BP shall notify the division District III office of its results on form C-141.
   C-141 is attached. Laboratory results indicated a release had occurred. BP fully remediated the location.
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
   Sampling results indicate a release had occurred. Attached is a laboratory report and C-141.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area
  - Sampling results indicate a release had occurred. Attached is a laboratory report and field report. The location was fully remediated. The site will be reclaimed once the production well is plugged and abandoned.
- 10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

    Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

#### State of New Mexico Energy Minerals and Natural Resources

Form C-141
Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			n and Co	orrective A	ction								
							OPERATOR						
Name of Co	mpany: B	P				Contact: Steve Moskal							
Address: 20	0 Energy	Court, Farmi	ington, N	M 87401		Telephone 1	No.: 505-326-94	97					
		os Canyon U				Facility Typ	e: Natural gas v	vell				1	
Surface Ow	ner: Feder	al/Tribal		Mineral (	Owner:	: Federal		A	PI No	. 30045116	521		
				LOCA	ATIO	N OF RE	LEASE						
Unit Letter N	Section 14	Township 28N	Range 12W	Feet from the 1,550		h/South Line	Feet from the 1,850	East/West I West	Line	County: Sa	an Jua	n	
			La	titude <u>36.65</u>	816°	Longitu	de108.083	31°					
				NAT	URE	OF REL	EASE						
Type of Rele	ase: Below	Grade Tank/F	ormer Ea		-		Release: unknow	n Vol	ume F	Recovered: n	one		
				g removal of belo	w		Hour of Occurrence		e and	Hour of Dis	covery	y: February	
grade tank -	95 bbl (A)					unknown		11,	2016				
Was Immedia	ate Notice (			_		If YES, To	Whom?						
			Yes 🗵	No Not R	equired	1							
By Whom?						Date and Hour							
Was a Watercourse Reached?				If YES, Volume Impacting the Watercourse.									
			Yes 🗵										
If a Watercou	irse was Im	pacted, Descr	ibe Fully.	*									
Describe Cau	se of Probl	em and Reme	dial Actio	n Taken.* Sampli	ng of th	he soil beneath	the BGT was do	ne during ren	noval.	Soil analys	is resu	ilted for	
BTEX and ch	loride belo	w BGT closur	re standard	ls. TPH analysis	indica	eated a release had occurred. Field reports and laboratory results are attached.					ached.		
	1.00 . 1	1.01		t mit t	0.11				1.	1.			
Describe Are	a Affected	and Cleanup A	Action Tal	cen.* The site was	s fully i	remediated wit	h a closure report	to be filed at	a late	r date.			
I hereby certi	fy that the i	nformation gi	ven above	is true and comp	lete to	the best of my	knowledge and u	nderstand tha	t purs	uant to NM	OCD 1	rules and	
							nd perform correc						
							arked as "Final R						
							on that pose a three						
				otance of a C-141	report	does not reliev	e the operator of	responsibility	for co	ompliance w	ith an	y other	
federal, state, or local laws and/or regulations.						OIL CONCEDIATION DIVISION							
Man 15					OIL CONSERVATION DIVISION								
Signature:													
A						Approved by Environmental Specialist:							
Printed Name: Steve Moskal													
Title: Field E	eld Environmental Coordinator					Approval Date: Expiration				Date:			
	-												
E-mail Addre	ss: steven.r	noskal@bp.co	om			Conditions of Approval:							
D-4- N	1 - 2 001	,	DI.	- 505 326 0407									
Date: Noven  * Attach Addit				e: 505-326-9497						L			
Attach Addi	nonai Sne	ous 11 Necess	ary										

#### Moskal, Steven

From:

Moskal, Steven

Sent:

Monday, February 08, 2016 2:55 PM

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)

Cc:

Railsback, Farrah (CH2M HILL); jeffcblagg@aol.com; blagg\_njv@yahoo.com

Subject:

BP Pit Close Notification - GCU 216

#### **BP America Production Company**

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

February 8, 2016

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

#### RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 216 API 30-045-11621 (N) Section 14 – T28N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close one 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around February 11, 2016.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

(505) 326-9497

CLIENT: BP	113	API #: 3004 TANK ID (if applicble):	A	1				
FIELD REPORT:	(circle one): BGT CONFIRMATION /	/ RELEASE INVESTIGATION / OTHER:		PAGE#:1	of	1_		
SITE INFORMATION QUAD/UNIT: N SEC: 14 TWP:	28N RNG: 12W PM:	NM CNTY: SJ ST:		DATE STARTED: DATE FINISHED:	02/11/1	6		
1/4-1/4/FOOTAGE: 1,150'S / 1,8 LEASE #: SF078828A		YPE: FEDERAL STATE / FEE / II STRIKE ONTRACTOR: MBF - B. SCHUN		ENVIRONMENTAL SPECIALIST(S):	NJV			
REFERENCE POINT	GPS COORD.: 36,	36.65812 X 10 6.65816 X 108.08331	D8.08380 DISTANCE/BEAF DISTANCE/BEAF	RING FROM W.H.:	- max	3'		
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # O		Dig		O REA	OVM ADING ppm)		
1) SAMPLE ID: 5PC - TB @' 2) SAMPLE ID: 3) SAMPLE ID: 4) SAMPLE ID:	SAMPLE DATE:  SAMPLE DATE:	SAMPLETIME LAB ANALYS  SAMPLETIME LAB ANALYS	SIS:			NA		
SOIL DESCRIPTION								
SOIL COLOR: DARK YELLOWISH ORANGE  COHESION (ALL OTHERS) NON COHESIVE SLIGHTLY COHESIVE / COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD  CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE  MOISTURE: DRY SLIGHTLY MOIST MOIST / WET / SATURATED / SUPER SATURATED  SAMPLE TYPE: GRAB (COMPOSITE) # OF PTS								
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER:	D AND/OR OCCURRED : YES / NO EXPL	ANATION:	GRADE TAN	NK TO BE SET ATOP	BGT POSIT	TION.		
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <50' N	NA ft. XNA EAREST WATER SOURCE: >1,000'	2.6 2.8 2.8 2.0 2.0		FIMATION (Cubic Yard CD TPH CLOSURE STD:	ds): <u>NA</u> 100	A ppm		
SITE SKETCH  STEE CONTAIN RING  W.H.   GCU 250 W & PUMP JA  NOTES: BGT = BELOWGRADE TANK; E.D. = EXCAVATIO	PROD TANKS	FENCE PBGTL T.B. ~ 5' B.G.  X - S.	N OMITIME:  W RI VI P.O OTAN	MISCELL.  /O:  EF #: P - 265  ID: VHIXONE  J #:  ermit date(s):  CD Appr. date(s):  OVM = Organic \ ppm = parts per	ppm NATE: NA	)		
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELI	OW-GRADE TANK LOCATION; SPD = SAMPLE PO E WALL; DW - DOUBLE WALL; SB - SINGLE BOTT	POINT DESIGNATION; R.W. = RETAINING WALL; NA-	NOT M	lagnetic declinatio	n: 10°E	1,, 8		

#### **Analytical Report**

Lab Order 1602519

Date Reported: 2/16/2016

#### Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Client Sample ID: 5PC-TB@6'95

Project: GCU #216

Collection Date: 2/11/2016 9:15:00 AM

Lab ID: 1602519-001

Matrix: MEOH (SOIL) Received Date: 2/12/2016 8:00:00 AM

Analyses	Result	PQL Qual	Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS			EX	80	Analyst:	LGT
Chloride	57	30	mg/Kg	20	2/12/2016 10:47:59 AM	23725
EPA METHOD 8015M/D: DIESEL RANGE	ORGANIC	s			Analyst:	JME
Diesel Range Organics (DRO)	300	9.8	mg/Kg	1	2/13/2016 1:03:47 AM	23703
Motor Oil Range Organics (MRO)	460	49	mg/Kg	1	2/13/2016 1:03:47 AM	23703
Surr: DNOP	106	70-130	%Rec	1	2/13/2016 1:03:47 AM	23703
EPA METHOD 8015D: GASOLINE RANGE	E 1				Analyst:	NSB
Gasoline Range Organics (GRO)	ND	3.7	mg/Kg	1	2/12/2016 11:21:22 AM	23685
Surr: BFB	90.3	66.2-112	%Rec	1	2/12/2016 11:21:22 AM	23685
EPA METHOD 8021B: VOLATILES					Analyst:	NSB
Benzene	ND	0.037	mg/Kg	1	2/12/2016 11:21:22 AM	23685
Toluene	ND	0.037	mg/Kg	1	2/12/2016 11:21:22 AM	23685
Ethylbenzene	ND -	0.037	mg/Kg	1	2/12/2016 11:21:22 AM	23685
Xylenes, Total	ND	0.073	mg/Kg	1	2/12/2016 11:21:22 AM	23685
Surr: 4-Bromofluorobenzene	105	80-120	%Rec	1	2/12/2016 11:21:22 AM	23685

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Chain-of-Custody Record			Tum-Around	1	SAME	E		7		2- 46	- W	- 268	and the same		- No. 1984	Many and the	THE STATE OF THE STATE OF	NTA	to the		
ent:	BLAG	G ENGR.	/ BP AMERICA	☐ Standard Project Name	Standard Rush DAY							-1 - Page	Yan	1 29	,			4.74	TO	RY	,
alling A	ddress:	P.O. BO	¥ 87		GCU # 21	6		40	or U		100	7	4	viro				n 87109	i		
	THE STATE OF THE S	A STATE OF THE STA	FIELD, NIM 87413	Project #:		The Continue of the Continue o						* 6+		ax !	20 17	*			t.		
one #:		(505) 63								9 9		Street Street		ysis	Marithur J	- 18860114 J	- Spinnelly	·			
nail or i				Project Mana	gen		11 4	1	7	Plan 6 T	Mary 5		1000 - 1 mg		2 17	12	2.2	H	* * * * * * * * * * * * * * * * * * * *	1.	
VOC Pa	Application of the second		Level 4 (Full Validation)	1	NELSON VI	ELEZ	B4s (8021B)	+ TPH (Gas only)	/ DRO / MRO)			(S)	1 d d d d d d d d d d d d d d d d d d d	PO, SO	2808 PCB's		manifest company and a	ter - 300,1)		e	
credita	7			Sampler:	NELSON VI	The state of the s	) *	H (Ga	DRO	11	î	OSIIV		NO <sub>2</sub> ,	308			a/wa	187	ampl	_
NELAF		□ Other		On Ice:	X Yes / ↑	□ No	Į₹	1	0	418	504	827	×	Q,			SO.	300		tes	or N
EDD (	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX MATE	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method 504:1)	PAH (8310 or 827051MS)	RCRA & Metals	Arriens (F,Cl,NOs,NOs,POs,SO)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil + 300.0./ water	Grab sample	5 pt. composite sample	Air Bubbles (Y or N)
/11/16	0915	SOIL	SPC-TB@ 6 (95)	4 02 1	Cool	-001	V		V			T percent					13	٧		V	
	· ·	4						4 2		e e		2 2 4 5 7 7 7 7 7 7						A MARKET CO.		10090	
	1								2			11 1			The County of the	1				_	
12	J						-			- 1		-			F 244			SCOOL STATE		-	
	*	i						-								A 7000			+		
		741	State of the state				1			1	7 . 1										
1 1 Septimber 1 Septimber 1				20000 XP		the same original	1 -					4					1 1				
			k				-				1	4									
		- In the state of					-	7	i. Gelek							.a 4	er i			+	
parties (12)				1000		7						enter i	4 3				Mar is in			4	
/11/16	Times 1704	Reinquish	In VI	Received by:	Wooden	Date Time 7/04	BI		RECT		St. 10 1			, 1	<u>i</u>	L			· vi		<u></u>
rific	Time: [8] ]	Retinguishe	othe Welso	Received by:	aut ozl	Date Time 12/16 0800		4	- 10			nerg P-26		42.				M 87	401 )NEV82	-	

#### Hall Environmental Analysis Laboratory, Inc.

WO#: 1602519

16-Feb-16

Client:

**Blagg Engineering** 

Project:

GCU #216

Sample ID MB-23725

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 23725

PQL

RunNo: 32148

Prep Date:

2/12/2016

Units: mg/Kg

Analysis Date: 2/12/2016 Result

SeqNo: 982758

HighLimit

**RPDLimit** %RPD

Qual

Analyte Chloride

ND 1.5

Sample ID LCS-23725

Prep Date: 2/12/2016

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Batch ID: 23725

1.5

RunNo: 32148 SeqNo: 982759

Units: mg/Kg

Analyte

Analysis Date: 2/12/2016 PQL

SPK value SPK Ref Val

%REC LowLimit

HighLimit

%RPD

Result

15.00

96.0

Chloride

14

0

SPK value SPK Ref Val %REC LowLimit

90

110

**RPDLimit** 

Qual

#### Qualifiers:

ND

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D Holding times for preparation or analysis exceeded H
- Not Detected at the Reporting Limit R RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix
- В Analyte detected in the associated Method Blank
- Value above quantitation range E
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit Sample container temperature is out of limit as specified
- Page 2 of 5

#### Hall Environmental Analysis Laboratory, Inc.

WO#: 1602519

16-Feb-16

Client:

**Blagg Engineering** 

Project:

GCU #216

Sample ID	MB-23659

SampType: MBLK

TestCode: EPA Method 8015M/D: Diesel Range Organics

Client ID:

PBS

Batch ID: 23659

RunNo: 32107

Analyte

Prep Date: 2/10/2016

Analysis Date: 2/12/2016 PQL

SeqNo: 981633

%REC

93.3

Units: %Rec

**RPDLimit** Qual

Surr: DNOP

Result

SPK value SPK Ref Val 10.00

LowLimit

LowLimit

HighLimit %RPD 130

Sample ID LCS-23659

2/10/2016

SampType: LCS

TestCode: EPA Method 8015M/D: Diesel Range Organics

Client ID: LCSS

Batch ID: 23659 Analysis Date: 2/12/2016

**PQL** 

RunNo: 32107 SeqNo: 981634

Units: %Rec

130

Analyte

Prep Date:

Result

9.3

SPK value SPK Ref Val

%REC

**HighLimit** 

**RPDLimit** 

Qual

Surr: DNOP

3.9

5.000

77.4

70

%RPD

Sample ID MB-23703

SampType: MBLK

SeqNo: 982134

TestCode: EPA Method 8015M/D: Diesel Range Organics

Client ID: Prep Date: 2/12/2016

Batch ID: 23703

Analysis Date: 2/12/2016

RunNo: 32107

Units: mg/Kg

Analyte

Diesel Range Organics (DRO)

Result 10 SPK value SPK Ref Val %REC LowLimit

HighLimit %RPD **RPDLimit** 

Qual

Motor Oil Range Organics (MRO) Surr: DNOP

ND ND 50 8.7

10.00

87.3

70

Sample ID LCS-23703

SampType: LCS

TestCode: EPA Method 8015M/D: Diesel Range Organics

RunNo: 32107

130

Client ID:

Prep Date: 2/12/2016

LCSS

Batch ID: 23703

Analysis Date: 2/12/2016

SeqNo: 982135

%REC

Units: mg/Kg

%RPD

**RPDLimit** Qual

Page 3 of 5

Analyte Diesel Range Organics (DRO) Surr: DNOP

Result 45 PQL SPK value SPK Ref Val. 10 50.00

89.6 77.3 65.8 70

LowLimit

**HighLimit** 136 130

3.9 5.000

# Qualifiers:

H

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- ND Not Detected at the Reporting Limit R RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix

Holding times for preparation or analysis exceeded

- В Analyte detected in the associated Method Blank
- E Value above quantitation range J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

#### Hall Environmental Analysis Laboratory, Inc.

WO#: 1602519

16-Feb-16

Client:

**Blagg Engineering** 

Project:

GCU #216

Sample ID MB-23685 SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range Client ID: **PBS** Batch ID: 23685 RunNo: 32099 Prep Date: 2/11/2016 Analysis Date: 2/12/2016 SeqNo: 982038 Units: mg/Kg Analyte Result **PQL** SPK value SPK Ref Val %REC LowLimit HighLimit %RPD **RPDLimit** Qual Gasoline Range Organics (GRO) ND 5.0 Surr: BFB 910 1000 91.1 66.2 112

TestCode: EPA Method 8015D: Gasoline Range Sample ID LCS-23685 SampType: LCS Client ID: LCSS Batch ID: 23685 RunNo: 32099 Prep Date: 2/11/2016 Analysis Date: 2/12/2016 SeqNo: 982039 Units: mg/Kg Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD **RPDLimit** Qual Analyte Gasoline Range Organics (GRO) 24 5.0 25.00 0 96.0 79.6 122 Surr: BFB 970 97.1 66.2 112 1000

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Page 4 of 5

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

# Hall Environmental Analysis Laboratory, Inc.

WO#: 1602519

16-Feb-16

Client:

**Blagg Engineering** 

Project:

GCU #216

Sample ID MB-23685	SampType: MBLK			Tes							
Client ID: PBS	Batch ID: 23685			F	RunNo: 3						
Prep Date: 2/11/2016	Analysis D	ate: 2/	12/2016	SeqNo: 982081 Units:			Units: mg/K	ng/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	ND	0.050									
Toluene	ND	0.050									
Ethylbenzene	ND	0.050									
Xylenes, Total	ND	0.10									
Surr: 4-Bromofluorobenzene	1.1		1.000		110	80	120				

Sample ID LCS-23685	Sample ID LCS-23685 SampType: LCS			TestCode: EPA Method 8021B: Volatiles							
Client ID: LCSS	Batch ID: 23685			RunNo: 32099							
Prep Date: 2/11/2016		Analysis [	Date: 2/	12/2016	8	SeqNo: 9	82082	Units: mg/k	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	8	0.99	0.050	1.000	0	99.5	80	120		-	
Toluene		0.97	0.050	1.000	0	97.5	80	120			
Ethylbenzene		0.98	0.050	1.000	0	98.3	80	120			
Xylenes, Total		3.0	0.10	3.000	0	98.4	80	120			
Surr: 4-Bromofluorobenzen	е	1.0		1.000		105	80	120			

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix
- В Analyte detected in the associated Method Blank
- E
- Analyte detected below quantitation limits
- P Sample pH Not In Range
- RLReporting Detection Limit
- Sample container temperature is out of limit as specified

Value above quantitation range

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

# Sample Log-In Check List

Client Name:	BLAGG	Work Order Number:	160251	9		Rcpt	No: 1
Received by/date	e: Qu	02/12/16					
Logged By:	Joe Archuleta	2/12/2016 8:00:00 AM		200	Gt.		
		2/12/2016 8:17:31 AM		JE1 200	21		
Completed By:	Joe Archuleta	1 1		and a	<i>(61</i>		
Reviewed By:	1.7	02/12/10					
Chain of Cus	1				1.3		
	ils intact on sample bottles?		Yes		lo []	Not Present	
	Custody complete?		Yes	Z N	lo []	Not Present	J
<ol><li>How was the</li></ol>	e sample delivered?		Courie	<u>ır</u>			
Log In							
4. Was an atte	empt made to cool the samples	3?	Yes	M 1	1o []	NA	
5. Were all san	nples received at a temperatur	re of >0° C to 6.0°C	Yes 5	N	o LT	NA [	_1
6. Sample(s) in	n proper container(s)?		Yes	<b>•</b>	No []		
7. Sufficient sa	mple volume for indicated test	(s)?	Yes	<b>A</b>	lo 🗔		
8. Are samples	(except VOA and ONG) propo	Yes	<b>₽</b>	lo []			
9. Was preserv	vative added to bottles?		Yes [	N	lo 🕏	NA	
10.VOA vials ha	ave zero headspace?		Yes [	] . N	lo []	No VOA Vials	
	ample containers received bro	ken?	Yes		No 🗭		
						# of preserved bottles checked	1
	work match bottle labels?		Yes	<b>∌</b> N	lo [ ]	for pH:	(2) as 342 - mlass mated)
` .	pancies on chain of custody)	of Custodia	Vaa [	<b>₽</b> N	lo []	Adjusted	<2 or >12 unless noted) ?
	s correctly identified on Chain of at analyses were requested?	of Custody?		_	lo [_]	4	
	ding times able to be met?		Yes		lo 🗆	Checked 1	oy:
(If no, notify	customer for authorization.)						
	lling (if applicable)		,		1		rui
16. Was client n	otified of all discrepancies with	this order?	Yes		io []	NA	
Persor	n Notified:	Date	I. L. Albite Proceeding Service	Japan (12) Steeleskill (2015) (12)	Con Lesiale 2504/76		
By Wh	ACCOUNT OF THE PARTY AND ADDRESS OF THE PARTY ADDRESS OF THE PARTY AND	Via: [	eMai	Phone	Fax	In Person	duat*
Regard	A Section of the American Control of the Section of the American	eternel yaqilindari isi od 50 dilla 18 ayyaqana suunuvadibilistuska baarq kerssa selusid		makki kili wa usi kawa ya maki kiliki wa wa	ومرطاعية أواجعه أدعية	o to a na made distribui de de contra a ravi do tras de indra sub-serio	on.
Client	Instructions:						
17. Additional re	emarks:						
18. Cooler Info		Seal Intact   Seal No	Seal Dat	e   Signe	d Bv	Visit 8	
1		es					



