Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

5.	Lease Serial No.
	NMSF078384

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

6. If Indian, Allottee or Tribe Name

SUBMIT IN	7. If Unit or CA/Agreement, Name and/or No.					
Type of Well		8. Well Name and No. NEWSOM B 16				
Name of Operator COLEMAN OIL & GAS INCOI		9. API Well No. 30-045-23920-00-S1				
3a. Address	Ph: 5	ione No. (include area code) 505-327-0356 Ext: 106 05-327-9425		10. Field and Pool or Exploratory Area BALLARD PICTURED CLIFFS BASIN FRUITLAND COAL		
FARMINGTON, NM 87499 4. Location of Well (Footage, Sec., T		05-327-9425	11. County or Parish, State			
Sec 9 T26N R8W NWNW 108 36.505829 N Lat, 107.693207	35FNL 0840FWL		SAN JUAN COUNTY, NM			
12. CHECK THE AI	PPROPRIATE BOX(ES) TO IN	DICATE NATURE OF	NOTICE, I	REPORT, OR OTH	ER DATA	
TYPE OF SUBMISSION						
☐ Notice of Intent	☐ Acidize	□ Deepen	☐ Production (Start/Resume)		☐ Water Shut-Off	
	☐ Alter Casing	☐ Hydraulic Fracturing	□ Reclamation		■ Well Integrity	
Subsequent Report	☐ Casing Repair	■ New Construction	□ Recomplete		☐ Other	
☐ Final Abandonment Notice	☐ Change Plans	▶ Plug and Abandon	□ Temporarily Abandon			
	☐ Convert to Injection	☐ Plug Back	■ Water Disposal			
determined that the site is ready for f See the attached P&A Report been reclaimed. 14. I hereby certify that the foregoing is	for the Newsom B16. Dry hole n	narker installed. Access	and locatio	n have		
Commi	Electronic Submission #365183	NCORPORATED, sent to ABDELGADIR ELMADAN	d by the BLM Well Information System ORATED, sent to the Farmington GADIR ELMADANI on 02/22/2017 (17AE0157SE) Title ENGINEER			
WIIOTIALL		- LITOINE			v	
Signature (Electronic S	Submission)	Date 01/27/20)17	2		
	THIS SPACE FOR FEI	DERAL OR STATE (OFFICE US	E		
Approved By ACCEPT	ED		GADIR ELMANDANI DEEUM ENGINEER Date 02/22/201			
Conditions of approval, if any, are attache certify that the applicant holds legal or eq which would entitle the applicant to condu	uitable title to those rights in the subject	lease	Office Farmington			
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a crime for statements or representations as to any m		willfully to mal	ke to any department or a	gency of the United	
(Instructions on page 2) ** BLM REV	ISED ** BLM REVISED ** BL	M REVISED ** BLM	REVISED	** BLM REVISED) **	

A-PLUS WELL SERVICE, INC.

P.O. BOX 1979 Farmington, New Mexico 87499 505-325-2627 *fax: 505-325-1211

Coleman Oil & Gas Inc. Newsom B 16 December 13, 2016

Page 1 of 1

1085' FNL and 840' FWL, Section 9, T-26-N, R-8-W San Juan County, NM Lease Number: NMSF078384 API #30-045-23920

Plug and Abandonment Report Notified NMOCD and BLM on 12/9/16

Plug and Abandonment Summary:

Plug #1 with 53 sxs (62.54 cf) Class B cement pressure at 800 PSI, displace 12 bbls of water from 2200' to 250' SI pressure 800 PSI. Tag TOC at 343'.

Plug #2 with bi-wire holes at 230' spot 64 sxs (75.52 cf) Class B cement from 230' to surface to cover the surface casing shoe.

Plug #3 with 30 sxs Class B cement top off casings and Install P&A marker with coordinates N 36° 30' 18.00" / W 107° 41' 37.68".

Plugging Work Details:

- 12/12/16 Rode rig and equipment to location. Spot in and RU. Check well pressures: tubing 400 PSI, casing 280 PSI and bradenhead 0 PSI. Blow well down. ND wellhead. NU BOP. PU 4 jnts to verify open perfs. LD and tally 66 joints of total 1-1/4" IJ, 23# tubing with steel length. RU pump to bradenhead valve. Pump 5 bbls water, found hole down 2' in 7-5/8" casing, unable to test. Note: Jamie Joe, BLM and Brandon Powell, NMOCD approved procedure change. **Spot plug #1** with calculated TOC at 250'. Travel to previous well. SDFD.
- 12/13/16 Open up well; no pressures. RU relief lines. Pressure test casing to 1000 PSI, OK. RU A-Plus wireline. PU 1-1/4" bar and RIH, Tag TOC at 343'. Perforate 4 bi-wire holes at 230'. Establish rate of 2 bpm at 0 PSI. ND BOP. NU wellhead. Establish circulation. **Spot plug #2** with TOC at surface. Dig out wellhead. Write Hot Work Permit. RU air saw. Cut off wellhead. Found cement down 10' in 2-7/8" and down 3' on backside. **Spot plug #3** top off casings and install P&A marker with coordinates N 36° 30' 18.00" / W 107° 41' 37.68". RD and MOL.

Bobby Espinoza, Coleman O&G representative, was on location. Jamie Joe, BLM representative, was on location. Ray Espinoza, BLM representative, was on location.