District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

۴.,

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, beoverlation, snoo Tick or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1. Operator: <u>BP America Production Company</u> OGRID #: <u>778</u>
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: GALLEGOS CANYON UNIT 133
API Number: 30045508365 20-045-08365 OCD Permit Number:
U/L or Qtr/Qtr <u>G</u> Section <u>17</u> Township <u>29N</u> Range <u>12W</u> County: <u>San Juan</u>
Center of Proposed Design: Latitude <u>36.729554</u> Longitude <u>-108.119525</u> NAD: □1927 ⊠ 1983
Surface Owner: 🛛 Federal 🗋 State 🗋 Private 🗋 Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. 3. Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A Volume: 95 bbl Type of fluid: Produced water
Tank Construction material: Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
Visible sidewalls and liner Visible sidewalls only Other Single wall/ Double bottom; no visible sidewalls
Liner type: Thicknessmil
4. Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

 5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify				
 6. <u>Netting</u>: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible) 				
 <u>Signs</u>: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC 				
 8. <u>Variances and Exceptions</u>: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. <i>Please check a box if one or more of the following is requested, if not leave blank:</i> Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 				
9. <u>Siting Criteria (regarding permitting)</u> : 19.15.17.10 NMAC <i>Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate material are provided below.</i> Siting criteria does not apply to drying pads or above-grade tanks.	ptable source			
General siting				
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.				
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	□ NA □ Yes □ No			
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No			
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No			
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map				
Below Grade Tanks				
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No			
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. Image: Second				
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)				
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No			

`*

. -

 Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No				
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site					
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 					
Temporary Pit Non-low chloride drilling fluid					
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 					
	Yes No				
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No				
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes No				
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No				
Permanent Pit or Multi-Well Fluid Management Pit					
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No				
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 					
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of					
 initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes No				
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No				
10. <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 N <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the down attached</i>					
attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC					
Previously Approved Design (attach copy of design) API Number: or Permit Number:					
11. <u>Multi-Well Fluid Management Pit Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached.</i>	cuments are				
 Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC 	.15.17.9 NMAC				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC					
Previously Approved Design (attach copy of design) API Number: or Permit Number:					

7

. -

12. <u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the</i>	documents are			
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatelogical Factors Assessment				
 Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC 				
13. <u>Proposed Closure</u> : 19.15.17.13 NMAC				
<i>Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.</i> Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit			
Alternative Proposed Closure Method: Waste Excavation and Removal				
 Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) 				
In-place Burial On-site Trench Burial Alternative Closure Method				
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC				
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.				
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA			
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells				
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 				
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site				
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 				
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No			
Written confirmation or verification from the municipality; Written approval obtained from the municipality \Box Yes \Box No				
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance				
Form C-144 Oil Conservation Division Page 4 o	f 6			

*

6

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality							
······································	Yes No						
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 							
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological							
Society; Topographic map	Yes No						
Within a 100-year floodplain. - FEMA map	Yes No						
 ^{16.} <u>On-Site Closure Plan Checklist</u>: (19.15.17.13 NMAC) <i>Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.</i> Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 							
17. Operator Application Certification:							
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed and be	ief.						
Name (Print): Title:							
Signature: Date:							
e-mail address: Telephone:							
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Oversion Approval Date: 333 Title: OUTOMENTAL Occ2LiSt OCD Permit Number:	2017						
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: OCD State 331	,2017						
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Ocosto Approval Date: 333 Title: OCD Permit Number: OCD Permit Number:	DOIT						
18. OCD Approval: Permit Application (including closure plan) (including closure plan) (including closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 3/3/2 Title: OCD Permit Number: 3/3/2 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not	DOIT						
18. OCD Approval: Permit Application (including closure plan) (including closure plan) (including closure Plan (only)) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 3331 Title: OCD Permit Number: 3331 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.						

.

.

Oil Conservation Division

22. Operator Closu	re Certification:			
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.				
Name (Print):	Steve Moskal	Title: Field Environmental Coordinator		
Signature:	aleres Much	Date: <u>March 3, 2017</u>		
e-mail address:_	steven.moskal@bp.com	Telephone: (505) 326-9497		

.

.

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Gallegos Canyon Unit 133</u> <u>API No. 3004508365</u> Unit Letter G, Section 17, T29N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number. **Notice was provided and is attached.**
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)
 - All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.
- 4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.
 All equipment essessioned with the BCT has been removed.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.017
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.070
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<u><48</u>
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

> Soil under the BGT was sampled for TPH, BTEX and chloride with all concentrations below the stated limits. The field report and laboratory reports are attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The location will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The location will be reclaimed when the well is plugged and abandoned.

 BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The location will be reclaimed when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The location will be reclaimed when the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

	OPERATOR	Initial Report	\boxtimes	Final Report
Name of Company: BP	Contact: Steve Moskal			
Address: 200 Energy Court, Farmington, NM 87401	Telephone No.: 505-326-9497			
Facility Name: Gallegos Canyon Unit 133	Facility Type: Natural gas well			

Surface Owner: Fee

.

Mineral Owner: Fee

API No. 3004508365

				LOCA	ATION OF REI	LEASE		
Unit Letter	Section	Township	Range	Feet from the	North/South Line	Feet from the	East/West Line	County: San Juan
G	17	29N	12W	1.535	North	1.830	East	

Latitude 36.729554°

NATUR

|--|

Type of Release: none	Volume of Release: unknown Volume Recovered: N/A				
Source of Release: below grade tank – 95 bbl	Date and Hour of Occurrence: Date and Hour of Discovery: none none				
Was Immediate Notice Given?	If YES, To Whom?				
By Whom?	Date and Hour				
Was a Watercourse Reached?	If YES, Volume Impacting the Wa	atercourse.			
If a Watercourse was Impacted, Describe Fully.*					
Describe Cause of Problem and Remedial Action Taken.* Sampling of the BTEX, TPH and chloride below BGT closure standards. Field reports and		ing removal.	Soil analysis resulted for		
Describe Area Affected and Cleanup Action Taken.* No action necessary.	. Final laboratory analysis determined	d no remedial	action is required.		
I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.					
Signature: Mars Muc	OIL CONSER	VATION I	DIVISION		
Printed Name: Steve Moskal Approved by Environmental Specialist:					
Title: Field Environmental Coordinator	Approval Date: Expiration Date:				
E-mail Address: steven.moskal@bp.com Date: March 3, 2017 Phone: 505-326-9497	Conditions of Approval:		Attached		

* Attach Additional Sheets If Necessary

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

December 29, 2016

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 133 API #: 3004508365

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 3, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

Moskal, Steven

From:	Moskal, Steven
Sent:	Friday, December 30, 2016 8:17 AM
То:	Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us);
	l1thomas@blm.gov
Cc:	jeffcblagg@aol.com; blagg_njv@yahoo.com; cparks@mbfservices.com
Subject:	RE: BP Pit Close Notification - GALLEGOS CANYON UNIT 133

The BGT is scheduled to be removed at 12:00 PM on January 3rd.

Thank you,

Steve Moskal BP Lower 48 – San Juan – Farmington Field Environmental Coordinator Office: (505) 326-9497 Cell: (505) 330-9179



This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

From: Railsback, Farrah (CH2M HILL)
Sent: Thursday, December 29, 2016 11:03 AM
To: Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (<u>Vanessa.Fields@state.nm.us</u>)
Cc: jeffcblagg@aol.com; blagg_njv@yahoo.com; Moskal, Steven
Subject: BP Pit Close Notification - GALLEGOS CANYON UNIT 133

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

December 29, 2016

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

1

GALLEGOS CANYON UNIT 133 API 30-045-08365 (G) Section 17 – T29N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around January 3, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

(505) 326-9497

Farrah Railsback BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

2

CLIENT: BP		NGINEERING, IN LOOMFIELD, NN		API #: 3004508	365
		5) 632-1199	10/413	TANK ID (if applicble):	
FIELD REPORT:	(circle one): BGT CONFIRMATION /	RELEASE INVESTIGATION / O	THER:	PAGE #:1_ o	of 1
SITE INFORMATION	SITE NAME: GCU #	133		DATE STARTED: 01/0	03/17
QUAD/UNIT: G SEC: 17 TWP:	29N RNG: 12W PM:	NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 1,535'N / 1,8	30'E SW/NE LEASE T		FEE / INDIAN	ENVIRONMENTAL	
LEASE #: SF078370	PROD. FORMATION: DK CO	STRIKE ONTRACTOR: BP - J. GO	NZALES	SPECIALIST(S):	JV
REFERENCE POINT		COORD.: 36.7300		GL ELEV.: 5	.634'
1) 95 BGT (SW/DB)	GPS COORD.: 36.7				
2)				RING FROM W.H.:	
3)	GPS COORD .:		DISTANCE/BEA	RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # C	R LAB USED: HALL			OVM READING
1) SAMPLE ID: 5PC - TB@1'	(95) SAMPLE DATE: 01/03/		LAB ANALYSIS: 801	5B/8021B/300.0 (CI)	(ppm)
2) SAMPLE ID:					
3) SAMPLE ID:					
4) SAMPLE ID:					
SOIL DESCRIPTION					
	RATE BROWN	PLASTICITY (CLAYS): NON PLASTIC		OHESIVE / MEDIUM PLASTIC / HIGH	LY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE SLIGHTL		DENSITY (COHESIVE CLAYS & S			
CONSISTENCY (NON COHESIVE SOILS): LC		HC ODOR DETECTED: YES NO	EXPLANATION -		
MOISTURE: DRY / <u>SLIGHTLY MOIST</u> MOIST / W SAMPLE TYPE: GRAB / <u>COMPOSITE</u> #		ANY AREAS DISPLAYING WETNES			
DISCOLORATION/STAINING OBSERVED: YES		ANT AREAS DISPLATING WEINES	S. TES NO EAFLA		
SITE OBSERVATION	S: LOST INTEGRITY OF EQUIPMENT	YES NO EXPLANATION -			
APPARENT EVIDENCE OF A RELEASE OBSERVE	DAND/OR OCCURRED : YES NO EXPL				
EQUIPMENT SET OVER RECLAIMED AREA: OTHER: WELL PAD SHARED WITH BP'S	YES NO EXPLANATION -		NMOCD REP PR	ESENT TO WITNESS CONF	IRMATION
SAMPLING.			NINCOD REF. FR		
SOIL IMPACT DIMENSION ESTIMATION:		ft. X <u>NA</u> ft.		TIMATION (Cubic Yards) :	NA
	EAREST WATER SOURCE: >1,000'		<1,000' NMOC	CD TPH CLOSURE STD: 10	0 ppm
SITE SKETCH	BGT Located : off / on site	PLOT PLAN circle	e: attached OVM	CALIB. READ. = NA pp	m RF =0.52
\frown	1			CALIB. GAS = NA pp	m
SEPAR	RATOR TO W.H.			: <u>NA</u> am/pm DATE:	NA
		/	'[MISCELL. NOT	ſES
	BERM	×	W	<i>I</i> O:	
			R	EF. #: P - 769	
			V	ID: VHIXONEVB2	
FENO				J#:	
	PBGTL		NCE -	ermit date(s): 11/1	
	T.B. ~ 1' B.G.		Tar		ter
+	2.0.	7			N)
	XX	/ v		BGT Sidewalls Visible: Y /	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO	N DEPRESSION: B.G. = BELOW GRADE: B = BE		- S.P.D.	BGT Sidewalls Visible: Y /	N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGLE	OW-GRADE TANK LOCATION; SPD = SAMPLE P E WALL; DW - DOUBLE WALL; SB - SINGLE BOTT	OINT DESIGNATION; R.W. = RETAINING V		lagnetic declination: 10	°E
NOTES: GOOGLE EARTH IMAGE	ERY DATE: 3/15/2015.	ONSITE: 01/03/1	7		

revised: 11/26/13

.

Hall Environmental Analysis Laboratory, Inc. Date Reported: 1/6/2017												
CLIENT: Blagg Engineering Project: GCU 133					C-TB@1'(95) 5/2017 12:05:00 PM							
Lab ID: 1701041-001	Matrix:	MEOH (SOIL)	Received	Date: 1/4	/2017 7:25:00 AM							
Analyses	Result	PQL Qua	al Units	DF	Date Analyzed	Batch						
EPA METHOD 300.0: ANIONS					Analyst	MRA						
Chloride	ND	30	mg/Kg	20	1/4/2017 12:54:37 PM	29526						
EPA METHOD 8015D MOD: GASOLI	NE RANGE				Analyst	DJF						
Gasoline Range Organics (GRO)	ND	3.5	mg/Kg	1	1/4/2017 10:41:22 AM	G39810						
Surr: BFB	89.1	70-130	%Rec	1	1/4/2017 10:41:22 AM	G39810						
EPA METHOD 8015M/D: DIESEL RA	NGE ORGANIC	s			Analyst	том						
Diesel Range Organics (DRO)	ND	9.7	mg/Kg	1	1/4/2017 11:11:16 AM	29515						
Motor Oil Range Organics (MRO)	ND	48	mg/Kg	1	1/4/2017 11:11:16 AM	29515						
Surr: DNOP	112	70-130	%Rec	1	1/4/2017 11:11:16 AM	29515						
EPA METHOD 8260B: VOLATILES S	HORT LIST				Analyst	DJF						
Benzene	ND	0.017	mg/Kg	1	1/4/2017 10:41:22 AM	S39810						
Toluene	ND	0.035	mg/Kg	1	1/4/2017 10:41:22 AM	S39810						
Ethylbenzene	ND	0.035	mg/Kg	1	1/4/2017 10:41:22 AM	S39810						
Xylenes, Total	ND	0.070	mg/Kg	1	1/4/2017 10:41:22 AM	S39810						
Surr: 1,2-Dichloroethane-d4	124	70-130	%Rec	1	1/4/2017 10:41:22 AM	S39810						
Surr: 4-Bromofluorobenzene	93.3	70-130	%Rec	1	1/4/2017 10:41:22 AM	S39810						
Surr: Dibromofluoromethane	131	70-130 S	%Rec	1	1/4/2017 10:41:22 AM	S39810						
Surr: Toluene-d8	91.2	70-130	%Rec	1	1/4/2017 10:41:22 AM	S39810						

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method Blank
	D	Sample Diluted Due to Matrix	Е	Value above quantitation range
	Н	Holding times for preparation or analysis exceeded	J	Analyte detected below quantitation limits Page 1 of 6
	ND	Not Detected at the Reporting Limit	Р	Sample pH Not In Range
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit
	S	% Recovery outside of range due to dilution or matrix	W	Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory Inc

.

.

Analytical Report Lab Order 1701041

Cł	nain-o	of-Cus	tody Record	I um-Alouitu	1 IIIIC.	SAME	ŀ .	4		н	41		FN	VT	R	DN	MF	IN7			
lient:	BLAG	G ENGR.	/ BP AMERICA	Standard	Rush_	DAY)					-					BC					
				Project Name		and the second			1	1	vww	.hall	envi	ronr	nent	al.co	m				
Aailing A	ddress:	P.O. BO	X 87	1	GCU #13	3		49	01 H	awki	ns N	E - /	Albu	quer	rque,	NM	8710	19			
		BLOOM	FIELD, NM 87413	Project #:			1	Te	el. 50)5-34	5-39	75	Fax	c 50	5-34	5-410	07				
'hone #:		(505) 63	2-1199	1								An	alys	is R	equ	est					
mail or F	ax#:			Project Mana	ger:						Τ		-	41			300.1)				
NA/QC Pa	-		Level 4 (Full Validation)		NELSON VI	ELEZ	MB4s (8021B)	s only)	/ MRO)		100	(12)			Z PUB S		water - 30			е	
ccredita	tion:			Sampler:	NELSON VI		Sa Sa	H (Ga	DRO	1)	F.	OSIN		200	202		/ M			dme	_
I NELAP		□ Other		the second s	NY / ACCOUNT OF THE OWNER OF THE OWNER OF			TPF	101	418	504	87/	s	100	es /	(AO	300.0 /			te si	or N
] EDD (Type)	1		Sample Temp	erature: Z_{i}	2	4	BE +	(GR	hod	hod	Jor .	etal	in line		-in	1		ple	posi	s (Y
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALINO.	BTEX + MI	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO / MRO)	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 82/05IMIS)	ACRA 8 Metals		BUBL PESTICIDES / BUBL PUB BJEAR (V/DA)	8270 (Semi-VOA)	Chloride (soil		Grab sample	5 pt. composite sample	Air Bubbles (Y or N)
1/03/17	1205	SOIL	5PC - TB @ / '(95)	4 oz 1	Cool	- 001	V		V								V			V	
														1							
														+	+					1	
											+			-	-	+			-		
							-	-			+			+	+	+	1		-	-	
n , .											1		-	\uparrow	+	1			1	1	
														+	-				-	-	
												-	+			+			-	1	
													-			+		\square	-+	-	
											-	-	+	+	+	+		\vdash	-		
											+	+	-	+	+				-	-	
			· · · · · · · · · · · · · · · · · · ·								+	+	+	-		-		\square	+		
)ate: /	Time:	Relinquishe	egipy:	Received by:	1 ,	Date Time	Ren	narks	5:							NTACT	WITH	CORRE	SPON	DING	VID
11/03/17	1704	1	my	Shell	alt 12	3/17 1754		ONT	ACT	& REF											
)ate:	Time:	Relinquishe	ed by:	Received by:	V	Date Time	1			VHIX											
317	1734	Sh	Wet	A	× OI	1/04/17 072	Ref	feren	ce #		P - 7	69									
1	If necessary	, samples sub	mitted to Hall Environmental may be su	bcontracted to other	accredited laboratorie	es. This serves as notice	of this	possil	bility.	Any sul	-contr	acted	data w	ill be d	clearly	notated	on the) analyt	ical re	port.	

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering Project: GCU 133

.

Sample ID MB-29526	SampType: mblk	TestCode: EPA Method	TestCode: EPA Method 300.0: Anions				
Client ID: PBS	Batch ID: 29526						
Prep Date: 1/4/2017	Analysis Date: 1/4/2017	Units: mg/Kg					
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual			
Chloride	ND 1.5						
Sample ID LCS-29526	SampType: Ics	TestCode: EPA Method	300.0: Anions				
Sample ID LCS-29526 Client ID: LCSS	SampType: Ics Batch ID: 29526	TestCode: EPA Method RunNo: 39836	300.0: Anions				
	1 31		300.0: Anions Units: mg/Kg				
Client ID: LCSS	Batch ID: 29526 Analysis Date: 1/4/2017	RunNo: 39836		RPDLimit Qual			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

1701041 06-Jan-17

WO#:

Page 2 of 6

QC SUMMARY REPORT

Client: Blagg Engineering **Project:** GCU 133

*

Sample ID MB-29515	SampType: N	BLK	Tes	tCode: E	PA Method	8015M/D: Di	esel Rang	e Organics	
Client ID: PBS	Batch ID: 2	9515	F	RunNo: 3	9801				
Prep Date: 1/4/2017	Analysis Date:	/4/2017	S	SeqNo: 1	247617	Units: mg/M	(g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND 10)							
Motor Oil Range Organics (MRO)	ND 50)							
Surr: DNOP	11	10.00		111	70	130			
Sample ID LCS-29515	SampType: L	cs	Tes	tCode: E	PA Method	8015M/D: Die	esel Rang	e Organics	
Client ID: LCSS	Batch ID: 2	9515	F	RunNo: 3	9801				
Prep Date: 1/4/2017	Analysis Date: 1	/4/2017	S	SeqNo: 1	247704	Units: mg/K	g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	46 10	50.00	0	91.3	63.8	116			
Surr: DNOP	5.1	5.000		103	70	130			
Sample ID 1701041-001AMS	SampType: M	S	Tes	tCode: El	PA Method	8015M/D: Die	esel Rang	e Organics	
Client ID: 5PC-TB@1'(95)	Batch ID: 2	9515	R	aunNo: 3	9801				
Prep Date: 1/4/2017	Analysis Date: 1	/4/2017	S	SeqNo: 1	247824	Units: mg/K	g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	42 9.4	47.04	5.682	78.1	51.6	130			
Surr: DNOP	4.9	4.704		104	70	130			
Sample ID 1701041-001AMS	D SampType: M	SD	Test	tCode: El	PA Method	8015M/D: Die	esel Range	e Organics	
Client ID: 5PC-TB@1'(95)	Batch ID: 2	9515	R	unNo: 3	9801				
Prep Date: 1/4/2017	Analysis Date: 1	/4/2017	S	eqNo: 1	247825	Units: mg/K	g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	47 10	50.05	5.682	82.6	51.6	130	10.4	20	
Surr: DNOP	5.3	5.005		106	70	130	0	0	

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- D Sample Diluted Due to Matrix
- Η Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit ND
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- В Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Ρ Sample pH Not In Range
- RL **Reporting Detection Limit**
- W Sample container temperature is out of limit as specified

1701041

WO#:

Page 3 of 6

06-Jan-17

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering **Project:** GCU 133

•

Samp	Туре: М	BLK	TestCode: EPA Method 8260B: Volatiles Short List							
Batc	h ID: \$3	9810	F	RunNo: 3	9810					
Analysis [Date: 1/	4/2017	5	SeqNo: 1	248250	Units: mg/Kg				
Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
ND	0.025									
ND	0.050									
ND	0.050									
ND	0.10									
0.52		0.5000		103	70	130				
0.47		0.5000		93.2	70	130				
0.55		0.5000		110	70	130				
0.47		0.5000		93.7	70	130				
Sample ID 100ng Ics SampType: LCS						8260B: Vola	tiles Short	List		
Batcl	h ID: S 3	9810	F	RunNo: 3	9810					
Prep Date: Analysis Date: 1/4/2017						Units: mg/H	(g			
Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
1.2	0.025	1.000	0	119	70	130				
1.0	0.050	1.000	0	101	70	130				
0.50		0.5000		100	70	130				
0.49		0.5000		98.9	70	130				
0.53		0.5000		106	70	130				
0.47		0.5000		93.3	70	130				
SampT	Гуре: МS	3	Tes	tCode: El	PA Method	8260B: Volat	tiles Short	List		
Batch	h ID: \$3	9810	RunNo: 39810							
Analysis D	Date: 1/	4/2017	S	SeqNo: 1	248255	Units: mg/k	(g			
Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
0.91	0.017	0.6959	0	130	61.9	146				
0.69	0.035	0.6959	0	98.6	70	130				
0.40		0.3480		116	70	130				
0.33		0.3480		96.2	70	130				
0.42		0.3480		122	70	130				
0.31		0.3480		88.8	70	130				
SampT	ype: MS	D	Test	Code: El	PA Method	8260B: Volat	tiles Short	List		
Client ID: 5PC-TB@1'(95) Batch ID: S39810					9810					
Prep Date: Analysis Date: 1/4/2017				eqNo: 1	248256	Units: mg/K	g			
Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
0.84	0.017	0.6959	0	121	61.9	146	7.32	20		
0.66	0.035	0.6959	0	95.5	70	130	3.22	20		
	Batc Analysis I ND ND ND ND 0.52 0.47 0.55 0.47 Batc Analysis I Result 1.2 1.0 0.50 0.47 Batc 1.2 1.0 0.50 0.47 Batc Analysis I Batc Analysis I Batc Analysis I Batc 0.47	Batch ID: S3 Analysis Date: 1// Result PQL ND 0.025 ND 0.050 ND 0.050 ND 0.10 0.52 0.47 0.55 0.47 0.55 0.47 SampType: LC Batch ID: S3 Analysis Date: 1/ Result PQL 1.2 0.025 1.0 0.50 0.47 0.50 SampType: LC Batch ID: S3 Analysis Date: 1/ Result PQL 0.53 0.47 SampType: MS Batch ID: S3 Analysis Date: 1/ Result PQL 0.31 0.42 0.31 0.42 0.31 S3 Analysis Date: 1// Result PQL 0.84 0.017	ND0.025ND0.050ND0.050ND0.100.520.50000.470.50000.470.50000.470.50000.470.50000.471.0201SampTye:L2BatchNDResultPQL1.20.0251.0001.0001.00.0500.501.0000.500.50000.490.50000.490.50000.470.50000.490.50000.470.50000.400.50000.470.50000.400.17ResultPQLSampTye:MSAnalysis Date:1/4/2017ResultPQL0.690.0350.400.34800.330.34800.420.34800.310.34800.310.34800.31C.34800.340.17ResultPQLSampTye:MSAnalysis Date:1/4/2017Analysis Date:1/4/2017ResultPQLSampTye:MS0.34800.310.420.34800.340.34800.340.34800.340.34800.340.34800.340.34800.340.34800.340.34800.340.420.840.017	Batch ID: S39810 F Analysis Date: 1/4/2017 S Result PQL SPK value SPK Ref Val ND 0.025 S S ND 0.050 S S ND 0.050 S S S ND 0.050 S S S ND 0.10 S S S 0.52 0.5000 O.500 S S 0.47 0.5000 S S S 0.47 S S S S Analysis Date: I/4/2017 S S Analysis Date: S S S S 1.2 0.025 1.000 O O 0.50 1.000 O S S 0.49 S S S S 0.41 O.17 S S S 0.42 S S S S S 0.43 O.017 S S S S<	Batch ID:S39810RunNo:3Analysis Date:i H/2017SeqNo:1ResultPQLSPK valueSPK Ref Val%RECND0.025ND0.050ND0.0501030.520.500093.20.550.500093.20.550.500093.20.550.50001100.470.500093.20.550.500093.20.550.500093.20.550.500093.20.550.500093.20.550.500093.2Analysis Date:1/2017ResultPQLSPK valueSPK Ref Val0.6051.00000.470.50001000.530.50001000.490.50001000.470.50001000.470.500098.90.530.50001000.490.500098.60.400.41296.20.410.4201160.330.448096.20.420.34801220.310.348048.8Analysis Date:1/2017SeqNo:ResultPQLSPK valueSPK Ref Val0.34800.434801220.310.34801220.310.34801220.310.34801220.34800.412 <td< td=""><td>Analysis DeriveND0.025ND0.025ND0.050ND0.0500.5250.50000.93.20.6470.500Analysis DeriveAnalysis DeriveAnalysis Derive10000.0170.60500000Analysis DeriveAnalysis DeriveImageSPK valueSPK Ref Val% RECLowLimitAnalysis DeriveSPK valueSPK Ref Val% RECLowLimitAnalysis DeriveSPK valueSPK Ref Val<</td><td>Batch ID: S39810 RunNo: 39810 Units: mg/k Analysis Det: IV42017 Se Rol Result PQL SPK value SPK Ref Val % REC LowLimit HighLimit ND 0.050 -<td>BathIDS39810RunNo:39810Units:mg/KgResultPQLSPK valueSPK Ref Val% RECLowLimitHighLimit% RPDND0.025KLowLimitHighLimit% RPDND0.050103TO130KND0.05010370130KND0.1093.270130K0.520.500093.270130K0.550.500093.770130K0.470.500093.770130K0.470.500093.770130K0.470.5000RunNo:3910KKAnalysis Date:14/2017KKKMKResultPQLSPK valueSPK Ref Val%RECLowLimitHighLimit%RPD1.20.0251.000011970130K1.20.0251.000010170130K1.30.0501.000010170130K1.40.5000010170130K0.430.5000010670130K0.440.5000010670130K0.450.5000010670130K0.460.50000161</td><td>Balch ID: S39810RunNo: 39810Analysis Date:1/4/2017SeqNo: 1248250Units: mg/KgResultPQLSPK valueSPK Ref Val%RECLowLimitHighLimit%RPDRPDLimitND0.0500.0501037013055</td></td></td<>	Analysis DeriveND0.025ND0.025ND0.050ND0.0500.5250.50000.93.20.6470.500Analysis DeriveAnalysis DeriveAnalysis Derive10000.0170.60500000Analysis DeriveAnalysis DeriveImageSPK valueSPK Ref Val% RECLowLimitAnalysis DeriveSPK valueSPK Ref Val% RECLowLimitAnalysis DeriveSPK valueSPK Ref Val<	Batch ID: S39810 RunNo: 39810 Units: mg/k Analysis Det: IV42017 Se Rol Result PQL SPK value SPK Ref Val % REC LowLimit HighLimit ND 0.050 - <td>BathIDS39810RunNo:39810Units:mg/KgResultPQLSPK valueSPK Ref Val% RECLowLimitHighLimit% RPDND0.025KLowLimitHighLimit% RPDND0.050103TO130KND0.05010370130KND0.1093.270130K0.520.500093.270130K0.550.500093.770130K0.470.500093.770130K0.470.500093.770130K0.470.5000RunNo:3910KKAnalysis Date:14/2017KKKMKResultPQLSPK valueSPK Ref Val%RECLowLimitHighLimit%RPD1.20.0251.000011970130K1.20.0251.000010170130K1.30.0501.000010170130K1.40.5000010170130K0.430.5000010670130K0.440.5000010670130K0.450.5000010670130K0.460.50000161</td> <td>Balch ID: S39810RunNo: 39810Analysis Date:1/4/2017SeqNo: 1248250Units: mg/KgResultPQLSPK valueSPK Ref Val%RECLowLimitHighLimit%RPDRPDLimitND0.0500.0501037013055</td>	BathIDS39810RunNo:39810Units:mg/KgResultPQLSPK valueSPK Ref Val% RECLowLimitHighLimit% RPDND0.025KLowLimitHighLimit% RPDND0.050103TO130KND0.05010370130KND0.1093.270130K0.520.500093.270130K0.550.500093.770130K0.470.500093.770130K0.470.500093.770130K0.470.5000RunNo:3910KKAnalysis Date:14/2017KKKMKResultPQLSPK valueSPK Ref Val%RECLowLimitHighLimit%RPD1.20.0251.000011970130K1.20.0251.000010170130K1.30.0501.000010170130K1.40.5000010170130K0.430.5000010670130K0.440.5000010670130K0.450.5000010670130K0.460.50000161	Balch ID: S39810RunNo: 39810Analysis Date:1/4/2017SeqNo: 1248250Units: mg/KgResultPQLSPK valueSPK Ref Val%RECLowLimitHighLimit%RPDRPDLimitND0.0500.0501037013055	

Qualifiers:

D

- * Value exceeds Maximum Contaminant Level.
 - Sample Diluted Due to Matrix
- Η Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- В Analyte detected in the associated Method Blank E
 - Value above quantitation range
- J Analyte detected below quantitation limits
 - Sample pH Not In Range
- RL Reporting Detection Limit

Р

W Sample container temperature is out of limit as specified Page 4 of 6

WO#: 1701041 06-Jan-17

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering Project: GCU 133

.

Sample ID 1701041-001amsd	SampT	ype: MS	SD	Tes	tCode: El	PA Method	8260B: Vola	tiles Short	List	
Client ID: 5PC-TB@1'(95)	Batch	ID: S 3	9810	F	unNo: 3	9810				
Prep Date:	Analysis D	ate: 1/	4/2017	S	eqNo: 1	248256	Units: mg/h	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 1,2-Dichloroethane-d4	0.38		0.3480		110	70	130	0	0	
Surr: 4-Bromofluorobenzene	0.33		0.3480		94.8	70	130	0	0	
Surr: Dibromofluoromethane	0.41		0.3480		119	70	130	0	0	
Surr: Toluene-d8	0.30		0.3480		86.9	70	130	0	0	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

WO#: 1701041 06-Jan-17

Pa

Page 5 of 6

QC SUMMARY REPORT

.

.

Hall	Environmental	Analysis	Laboratory	, Inc.

WO#: 1701041

06-Jan-17

Client:	Blagg En	gineering									
Project:	GCU 133										
Sample ID	rb	SampT	Type: MI	BLK	Tes	tCode: E	PA Method	8015D Mod:	Gasoline	Range	
Client ID:	PBS	Batcl	h ID: G	39810	F	RunNo: 3	9810				
Prep Date:		Analysis D	Date: 1	/4/2017	5	SeqNo: 1	248288	Units: mg/l	۲g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Rang	ge Organics (GRO)	ND	5.0								
Surr: BFB		440		500.0		87.7	70	130			
Sample ID	2.5ug gro lcs	SampT	Type: LC	s	Tes	tCode: El	PA Method	8015D Mod:	Gasoline	Range	
Client ID:	LCSS	Batch	h ID: G	39810	F	RunNo: 3	9810				
Prep Date:		Analysis D	Date: 1	4/2017	S	SeqNo: 1	248289	Units: mg/l	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Rang	ge Organics (GRO)	25	5.0	25.00	0	99.7	62.9	123			
Surr: BFB		450		500.0		89.2	70	130			
Sample ID	1701041-001ams	SampT	ype: MS	6	Tes	tCode: El	PA Method	8015D Mod:	Gasoline	Range	
Client ID:	5PC-TB@1'(95)	Batch	n ID: G3	39810	F	RunNo: 3	9810				
Prep Date:		Analysis D	ate: 1/	4/2017	S	SeqNo: 1	248290	Units: mg/k	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Rang	ge Organics (GRO)	16	3.5	17.40	0	92.1	52.3	132			
Surr: BFB		310		348.0		90.4	70	130			
Sample ID	1701041-001amsd	g SampT	ype: MS	SD	Tes	tCode: El	PA Method	8015D Mod:	Gasoline	Range	
Client ID:	5PC-TB@1'(95)	Batch	DID: G3	9810	R	unNo: 3	9810				
Dran Data			ate: 1/	4/2017	S	eqNo: 1	248291	Units: mg/k	(g		
Prep Date:		Analysis L									
Analyte		Result	PQL		SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Analyte	ge Organics (GRO)				SPK Ref Val 0	%REC 91.8	LowLimit 52.3	HighLimit 132	%RPD 0.305	RPDLimit 20	Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 6 of 6

HALL ENVIRONMENTAL ANALYSIS LABORATORY	Hall Environmental Albi TEL: 505-345-3975 Website: www.ha	4901 Hawki uquerque, NM 8 FAX: 505-345	ns NE 87105 Sam -4107	ple Log-In Cl	neck List
Client Name: BLAGG	Work Order Number:	1701041		RcptNo:	1
Completed By: Lindsay Mangin 1	01 04 17 14/2017 7:25:00 AM 14/2017 8:02:42 AM		finalsy Alexandry finalsy Alexandry finalsy Alexandry		
Chain of Custody					
1. Custody seals intact on sample bottles?		Yes	No [Not Present	
2. Is Chain of Custody complete?		Yes V	No []	Not Present	
3. How was the sample delivered?		Courier			
Log In					
4. Was an attempt made to cool the samples?		Yes 🖌	No []]	NA	
5. Were all samples received at a temperature of	f >0° C to 6.0°C	Yes 🖌	No	NA	
6. Sample(s) in proper container(s)?		Yes 🖌	No 🗌		
7, Sufficient sample volume for indicated test(s)?	•	Yes 🗹	No []]		
8. Are samples (except VOA and ONG) properly	preserved?	Yes 🖌	No		
9. Was preservative added to bottles?		Yes	No 🗹	NA	
10.VOA vials have zero headspace?		Yes []]	No []	No VOA Vials	
11. Were any sample containers received broken	?	Yes	No 🗹	the of presson and	
12.Does paperwork match bottle labels? (Note discrepancies on chain of custody)		Yes 🖌	No []]	# of preserved bottles checked for pH: (<2 or	>12 unless noted
13. Are matrices correctly identified on Chain of C	ustody?	Yes 🔽	No 🗔	Adjusted?	
14. Is it clear what analyses were requested?		Yes 🖌	No []]		
15. Were all holding times able to be met? (If no, notify customer for authorization.)		Yes 🖌	No	Checked by:	
Special Handling (if applicable)			×		
16. Was client notified of all discrepancies with this	s order?	Yes	No	NA 🖌	
Person Notified:	Date:		minima en segundora antenara		
By Whom:	Via: [] eMail []	Phone [_] Fax	In Person	
Regarding: Client Instructions:	an ya manana ana ana yanan kacamana ang manana ang		al an a second secon	A The block server, an an equip 1.2 Mar the Athendesis enter an ann ann an ann an ann an ann ann an	
17. Additional remarks:			· ·		
18. <u>Cooler Information</u> Cooler No Temp °C Condition Sea	Intact Seal No S	Seal Date	Signed By		
1 2.3 Good Yes					

.



