State of New Mexico

Energy Minerals and Natural Resources

Department

For temporary pits below-grade tanks, and

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

## Proposed Alternative Method Permit or Closure Plan Application

Type of action:  Below grade tank registration  Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method  Modification to an existing permit/or registration  Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
ase be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the ironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances
perator: BP America Production Company OGRID #: 778
ddress: 200 Energy Court, Farmington, NM 87401
acility or well name:GALLEGOS CANYON UNIT 201E
PI Number: 3004526189 OCD Permit Number:
/L or Qtr/Qtr O Section 11 Township 28N Range 12W County: San Juan
enter of Proposed Design: Latitude36.67165
urface Owner: 🛛 Federal 🗌 State 🔲 Private 🔲 Tribal Trust or Indian Allotment
OIL CONS. DIV DIST. 3
Pit: Subsection F, G or J of 19.15.17.11 NMAC
emporary: Drilling Workover MAR 31 2017
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management       Low Chloride Drilling Fluid ☐ yes ☐ no         Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
Lined   Unlined Liner type: Thicknessmil   LLDPE   HDPE   PVC   Other   String-Reinforced   Volume:bbl Dimensions: L x W x D
Lined   Unlined Liner type: Thicknessmil   LLDPE   HDPE   PVC   Other   String-Reinforced   Nelded   Factory   Other Volume:bbl Dimensions: L x W x D   Below-grade tank: Subsection I of 19.15.17.11 NMAC
Lined
Lined   Unlined Liner type: Thicknessmil   LLDPE   HDPE   PVC   Other
Lined   Unlined   Liner type: Thickness   mil   LLDPE   HDPE   PVC   Other     String-Reinforced   Ner Seams:   Welded   Factory   Other   Volume:   bbl Dimensions: L x W x D     Below-grade tank: Subsection I of 19.15.17.11 NMAC   TANK A     Dolume:   95   bbl Type of fluid:   Produced water     Ink Construction material:   Steel     Secondary containment with leak detection   Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
Lined   Unlined   Liner type: Thickness   mil   LLDPE   HDPE   PVC   Other     String-Reinforced   Normal   String-Reinforced   String-Reinforced   Normal   Normal
Lined   Unlined Liner type: Thickness

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC  12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area. (Does not apply to below grade tanks)  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	Yes   No   NA   Yes   No   NA   Yes   No   No   Yes   No   Yes   No   Yes   No   Yes   No   Yes   No   Y
Society; Topographic map  Within a 100-year floodplain. (Does not apply to below grade tanks)  - FEMA map	Yes No
Below Grade Tanks  Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)  Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
<ul> <li>application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,	
or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
<ul> <li>initial application.</li> <li>NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site</li> </ul>	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.  Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	NMAC 15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.10 NMAC	
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	
I I rieviously Approved Design (attach copy of design) Art Number.	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached.  Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment	
<ul> <li>□ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>□ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>□ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>□ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>□ Quality Control/Quality Assurance Construction and Installation Plan</li> <li>□ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>□ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>□ Nuisance or Hazardous Odors, including H₂S, Prevention Plan</li> <li>□ Emergency Response Plan</li> </ul>	
☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan	
☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems)	
☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC	
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel	ief.
Name (Print):	
Signature: Date:	
e-mail address: Telephone:	
e-mail address: Telephone:	
18.  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature: Approval Date: 4	
18.  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature: Approval Date: 4	the closure report.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature: Approval Date:  Title OCD Permit Number:  OCD Permit Number:  19.  Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not	the closure report.
18.  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature: Approval Date: OCD Permit Number:  19.  Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this belief. I also certify that the closure complies with all applicable closure	closure report is true, accurate and complete to the best of my knowledge and requirements and conditions specified in the approved closure plan.
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature: Date:	March 31, 2017
e-mail address: steven.moskal@bp.com	Telephone:(505) 326-9497

## BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

## BELOW-GRADE TANK CLOSURE PLAN

# Gallegos Canyon Unit 201E API No. 3004526189 Unit Letter O, Section 11, T28N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

#### General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

  Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
  - Notice was provided and is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.019
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.075
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<u>&lt;51</u>
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for TPH, BTEX and chloride with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.** 

- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
  - Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area
  - Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.
- 10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The location will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The location will be reclaimed when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The location will be reclaimed when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

#### The location will be reclaimed when the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

    Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

#### State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	atio	n and Co	orrective A	ction				
						<b>OPERA</b>	ΓOR	[	Initia	al Report	$\boxtimes$	Final Report
Name of Co	mpany: B	P				Contact: Ste						
		Court, Farmi		M 87401		Telephone No.: 505-326-9497						
Facility Nar	ne: Galleg	os Canyon U	Jnit 133			Facility Type: Natural gas well						
Surface Ow	ner: Feder	al		Mineral O	wner:	Federal			API No	. 3004526	189	
				LOCA	TIO	N OF RE	LEASE					
Unit Letter O	Section 11	Township 28N	Range 12W	Feet from the 900		/South Line	Feet from the 1.850	East/We	est Line	County: S	an Juar	1
0	11	2019										
			La	titude 36.67			de108.078	331				
Type of Release: none Volume of Release: unknown Volume Recovered: N/A												
		v grade tank –			lour of Occurrenc			Hour of Dis		· none		
Source of Re-	icase. belov	v grade tank			none	iour or occurrenc		Date and	riour or Dis	covery	. Hone	
Was Immedia	ate Notice C		Vec V	No Not Re	anired	If YES, To	Whom?					
By Whom?			103	No 🗀 Not Re	quired	Date and H	lour					
Was a Watercourse Reached?  If YES, Volume Impacting the Watercourse.												
Yes No												
If a Watercou	rse was Imp	pacted, Descri	be Fully.	k								
				n Taken.* Samplir andards. Field rep					removal.	Soil analys	is resul	ted for
DIEA, IFH	and chloride	e below BG1	ciosure su	andards. Field rej	ports a	nd laboratory	results are attache	a.				
Describe Are	a Affected a	and Cleanup A	ction Tak	ten.* No action ne	cessar	y. Final labora	tory analysis deter	rmined no	o remedia	l action is re	quired	
				is true and compl								
				nd/or file certain re								
				ce of a C-141 repo								
				investigate and retance of a C-141 r								
		vs and/or regu		tance of a C-141 i	eport (	does not renev	e the operator of i	responsio	ility for Co	omphance v	iui any	oulei
							OIL CONS	SERVA	ATION	DIVISIO	N	
Signature:	Herson	nu										
Printed Name	: Steve Mo	skal				Approved by	Environmental Sp	pecialist:				
Title: Field E	nvironment	al Coordinato	r			Approval Dat	e:	Ex	xpiration l	n Date:		
E-mail Addre	ss: steven.n	noskal@bp.co	m			Conditions of	Approval:		Attached			
Date: March	31, 2017		Phone: 5	05-326-9497						7 tttached		

<sup>\*</sup> Attach Additional Sheets If Necessary

## bp



**BP America Production Company** 200 Energy Court Farmington, NM 87401

January 17, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

#### VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: GALLEGOS CANYON UNIT 201E

API#: 3004526189

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 20, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

**BP** America Production Company

#### Moskal, Steven

From:

Moskal, Steven

Sent:

Thursday, January 19, 2017 7:09 AM

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us);

l1thomas@blm.gov

Cc:

jeffcblagg@aol.com; blagg\_njv@yahoo.com; cparks@mbfservices.com

Subject:

RE: BP Pit Close Notification - GCU 201E

The BGT is scheduled to be removed tomorrow morning at 9:00 AM.

Thank you,

#### Steve Moskal

Cell: (505) 330-9179

BP Lower 48 – San Juan – Farmington Field Environmental Coordinator Office: (505) 326-9497



This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

**From:** Railsback, Farrah (CH2M HILL) **Sent:** Tuesday, January 17, 2017 10:24 AM

To: Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)

Cc: jeffcblagg@aol.com; blagg\_njv@yahoo.com; Moskal, Steven

Subject: RE: BP Pit Close Notification - GCU 201E

**BP America Production Company** 

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

January 17, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 201E API 30-045-26189 (0) Section 11 – T28N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around January 20, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

(505) 326-9497

Farrah Railsback
BGT Project Support
970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	P.O. BOX 87, BL	GINEERING, INC. OOMFIELD, NM 8 ) 632-1199		API #:	
FIELD REPORT:	(circle one): BGT CONFIRMATION / R	ELEASE INVESTIGATION / OTHE	R:	PAGE #: <b>1</b> o	f <b>1</b>
QUAD/UNIT: 0 SEC: 11 TWP: 1/4-1/4/FOOTAGE: 900'S / 1,850	28N RNG: 12W PM:	NM CNTY: SJ	ST: NM	DATE STARTED: 01/2 DATE FINISHED: ENVIRONMENTAL	20/17
LEASE #: <b>SF078828A</b>	PROD. FORMATION: DK CON	STRIKE TRACTOR: MBF - B. SCH	IURMAN	SPECIALIST(S):	JV
2)	GPS COORD.: 36.6  GPS COORD.: GPS COORD.:		DISTANCE/BEAR DISTANCE/BEAR	GL ELEV.: 5 RING FROM W.H.: 104', S RING FROM W.H.:	12W
			DISTANCE/BEAR	RING FROM W.H.:	OVM
SAMPLING DATA:  1) SAMPLE ID: 5PC - TB @ 5'  2) SAMPLE ID:	SAMPLE DATE:	SAMPLETIME: 0905 LAB A	ANALYSIS:		READING (ppm)
SAMPLE ID:      SAMPLE ID:	SAMPLE DATE:				
SOIL DESCRIPTION					
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY (SLIGHTLY MOIST) MOIST! / MOIST!	OSE FIRM DENSE / VERY DENSE HOUSE TO SATURATED / SUPER SATURATED OF PTS.  S: LOST INTEGRITY OF EQUIPMENT: YES NO EXPLANATION -	ATION:	LANATION -		
SOIL IMPACT DIMENSION ESTIMATION:				IMATION (Cubic Yards) :	NA
OUTE OVETOU	BGT Located : off on site	PLOT PLAN circle:  TO W.H.	attached OVM (	D TPH CLOSURE STD:         10           CALIB. READ. =         NA         ppi           CALIB. GAS =         NA         ppi           NA         am/pm         DATE:           MISCELL.         NO	RF =0.52
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO	PROD. TANK  METER RUN  N DEPRESSION; B.G. = BELOWGRADE; B = BELO	W; T.H. = TEST HOLE; ~ = APPROX.; W.H. =	VII PJ Pe OC Tanil ID A	EF. #: P - 699  D: VHIXONEVB2  J #:  rmit date(s): 06/14  CD Appr. date(s): 09/12  K OVM = Organic Vapor Met ppm = parts per million  BGT Sidewalls Visible: Y /  BGT Sidewalls Visible: Y /	1/10 2/16 er N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELO	WAGRADE TANK LOCATION; SPD = SAMPLE POIN WALL; DW - DOUBLE WALL; SB - SINGLE BOTTON	T DESIGNATION; R.W. = RETAINING WALL		agnetic declination: 10	°E

### **Analytical Report**

#### Lab Order 1701930

Date Reported: 1/24/2017

## Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Client Sample ID: 5PC-TB@5'(95)

GCU 201E Project:

Collection Date: 1/20/2017 9:05:00 AM

1701930-001 Matrix: MEOH (SOIL) Lab ID:

Received Date: 1/21/2017 9:15:00 AM

Analyses	Result	PQL Qua	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	LGT
Chloride	ND	30	mg/Kg	20	1/23/2017 9:46:01 AM	29827
EPA METHOD 8015D MOD: GASOLINE F	RANGE				Analyst	DJF
Gasoline Range Organics (GRO)	ND	3.8	mg/Kg	1	1/22/2017 6:47:25 AM	D40186
Surr: BFB	94.7	70-130	%Rec	1	1/22/2017 6:47:25 AM	D40186
EPA METHOD 8015M/D: DIESEL RANGE	ORGANICS	3			Analyst	MAB
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	1/23/2017 11:19:13 AM	29818
Motor Oil Range Organics (MRO)	ND	51	mg/Kg	1	1/23/2017 11:19:13 AM	29818
Surr: DNOP	116	70-130	%Rec	1	1/23/2017 11:19:13 AM	29818
EPA METHOD 8260B: VOLATILES SHOR	T LIST				Analyst	DJF
Benzene	ND	0.019	mg/Kg	1	1/22/2017 6:47:25 AM	B40186
Toluene	ND	0.038	mg/Kg	1	1/22/2017 6:47:25 AM	B40186
Ethylbenzene	ND	0.038	mg/Kg	1	1/22/2017 6:47:25 AM	B40186
Xylenes, Total	ND	0.075	mg/Kg	1	1/22/2017 6:47:25 AM	B40186
Surr: 1,2-Dichloroethane-d4	82.8	70-130	%Rec	1	1/22/2017 6:47:25 AM	B40186
Surr: 4-Bromofluorobenzene	98.6	70-130	%Rec	1	1/22/2017 6:47:25 AM	B40186
Surr: Dibromofluoromethane	90.7	70-130	%Rec	1	1/22/2017 6:47:25 AM	B40186
Surr: Toluene-d8	98.0	70-130	%Rec	1	1/22/2017 6:47:25 AM	B40186

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- Analyte detected below quantitation limits Page 1 of 5 J
- P Sample pH Not In Range
- Reporting Detection Limit RL
- Sample container temperature is out of limit as specified

### Hall Environmental Analysis Laboratory, Inc.

WO#:

1701930

24-Jan-17

Client:

Blagg Engineering

Project:

GCU 201E

Sample ID MB-29827

Prep Date: 1/23/2017

SampType: MBLK

TestCode: EPA Method 300.0: Anions

TestCode: EPA Method 300.0: Anions

Client ID:

**PBS** 

Batch ID: 29827

RunNo: 40232

Units: mg/Kg

**RPDLimit** 

Qual

Analyte Chloride

Result

Analysis Date: 1/23/2017 PQL

SeqNo: 1261425 SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD

ND 1.5

Sample ID LCS-29827

SampType: LCS

Batch ID: 29827

RunNo: 40232

Prep Date: 1/23/2017

Client ID: LCSS

Analysis Date: 1/23/2017

SeqNo: 1261426

Units: mg/Kg

%RPD

Analyte

SPK value SPK Ref Val %REC

LowLimit

**RPDLimit** 

Qual

Result

14

Page 2 of 5

Chloride

15.00

90.6

PQL 1.5

HighLimit 90

110

Qualifiers:

H

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits % Recovery outside of range due to dilution or matrix

Holding times for preparation or analysis exceeded

В Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH Not In Range

Reporting Detection Limit RL

Sample container temperature is out of limit as specified

### Hall Environmental Analysis Laboratory, Inc.

WO#:

1701930

24-Jan-17

Client:

Blagg Engineering

Project:

GCU 201E

Project: GCU 201									
Sample ID MB-29818	SampType: M	BLK	Tes	tCode: El	PA Method	8015M/D: Die	sel Rang	e Organics	
Client ID: PBS	Batch ID: 29	9818	F	RunNo: 4	0201				
Prep Date: 1/21/2017	Analysis Date: 1	/23/2017	5	SeqNo: 1	260286	Units: mg/K	g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND 10								
Motor Oil Range Organics (MRO)	ND 50								
Surr: DNOP	11	10.00		112	70	130			
Sample ID LCS-29818	SampType: L	cs	Tes	tCode: El	PA Method	8015M/D: Die	sel Rang	Organics	
Client ID: LCSS	Batch ID: 29	9818	F	RunNo: 4	0201				
Prep Date: 1/21/2017	Analysis Date: 1	/23/2017	8	SeqNo: 1	260291	Units: mg/K	g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	48 10	50.00	0	95.5	63.8	116			
Surr: DNOP	6.0	5.000		119	70	130			
Sample ID LCS-29802	SampType: L	cs	Tes	tCode: El	PA Method	8015M/D: Die	sel Range	Organics	
Client ID: LCSS	Batch ID: 29	9802	F	RunNo: 40	0200				
Prep Date: 1/20/2017	Analysis Date: 1	/23/2017	S	SeqNo: 1	261137	Units: %Rec	:		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP	4.9	5.000		97.2	70	130			
Sample ID MB-29802	SampType: M	BLK	Tes	tCode: EF	PA Method	8015M/D: Die	sel Range	Organics	
Client ID: PBS	Batch ID: 29	802	R	RunNo: 40	0200				
Prep Date: 1/20/2017	Analysis Date: 1	/23/2017	S	SeqNo: 12	261138	Units: %Rec	:		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP	11	10.00		106	70	130			

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- Η Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank В
- E
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified

Value above quantitation range

Page 3 of 5

### Hall Environmental Analysis Laboratory, Inc.

0.46

0.49

0.5000

0.5000

WO#:

1701930

24-Jan-17

Client:

Blagg Engineering

Project:

GCU 201E

Sample ID rb1	Samp	Гуре: МЕ	BLK	TestCode: EPA Method 8260B: Volatiles Short List						
Client ID: PBS	Batc	Batch ID: <b>B40186</b>			RunNo: 40186					
Prep Date:	Analysis E	Date: 1/	22/2017	5	SeqNo: 1	259878	Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 1,2-Dichloroethane-d4	0.46		0.5000		91.1	70	130			
Surr: 4-Bromofluorobenzene	0.48		0.5000		96.6	70	130			
Surr: Dibromofluoromethane	0.45		0.5000		90.8	70	130			
Surr: Toluene-d8	0.52		0.5000		104	70	130			
Sample ID 100ng Ics2	SampT	ype: LC	S	Tes	tCode: El	PA Method	8260B: Volat	iles Short	List	
Client ID: LCSS	Batch	n ID: <b>B4</b>	0186	F	RunNo: 4	0186				
Prep Date:	Analysis D	ate: 1/	21/2017	8	SeqNo: 1	259879	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.89	0.025	1.000	0	88.8	70	130			
Toluene	1.0	0.050	1.000	0	100	70	130			
Surr: 1,2-Dichloroethane-d4	0.47		0.5000		93.6	70	130			
Surr: 4-Bromofluorobenzene	0.52		0.5000		104	70	130			

#### Qualifiers:

\* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Surr: Dibromofluoromethane

Surr: Toluene-d8

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

70

70

92.9

97.7

130

130

E Value above quantitation range

J Analyte detected below quantitation limits

Page 4 of 5

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

#### Hall Environmental Analysis Laboratory, Inc.

WO#:

1701930

24-Jan-17

Client:

Blagg Engineering

Project:

**GCU 201E** 

Sample	ID	rh1

SampType: MBLK

TestCode: EPA Method 8015D Mod: Gasoline Range

Batch ID: D40186

PQL

PQL

RunNo: 40186

Client ID: Prep Date:

Analyte

Analysis Date: 1/22/2017

SeqNo: 1259935

Units: mg/Kg

130

HighLimit

Qual

Gasoline Range Organics (GRO)

**PBS** 

Surr: BFB

ND 480

Result

500.0

SPK value SPK Ref Val

96.2

%REC

70

LowLimit

%RPD **RPDLimit** 

SampType: LCS

TestCode: EPA Method 8015D Mod: Gasoline Range

Sample ID 2.5ug gro lcs2 Client ID: LCSS

Batch ID: D40186

RunNo: 40186

Analysis Date: 1/22/2017

SeqNo: 1259936

Units: mg/Kg

Analyte Gasoline Range Organics (GRO)

24

SPK value SPK Ref Val 5.0 25.00

%REC 97.5

LowLimit 62.9

%RPD HighLimit

**RPDLimit** Qual

Surr: BFB

Prep Date:

480

Result

500.0

96.9

70

123 130

#### Qualifiers:

- Value exceeds Maximum Contaminant Level
- Sample Diluted Due to Matrix D
- Holding times for preparation or analysis exceeded H
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank В
- E Value above quantitation range
- Analyte detected below quantitation limits
- P Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

## Sample Log-In Check List

Client Name:	BLAGG	Work Order Number:	130			RcptNo	o: 1							
Received by/dat	e:				12 Sec 24 Comments 11 S									
Logged By:	Lindsay Mangin	1/21/2017 9:15:00 AM			Strucky	Hongo								
Completed By:	Lindsay Mangin	1/21/2017 10:08:23 AM			Junely 1	Happo								
Reviewed By:	DF 1/21/2017													
Chain of Cus	tody													
1. Custody sea	als intact on sample bottles?		Yes		No		Not Present							
2. Is Chain of 0	Custody complete?		Yes	<b>V</b>	No		Not Present							
3. How was the	e sample delivered?		Cour	er										
Log In														
4. Was an atte	empt made to cool the sample	es?	Yes	~	No		NA []							
5. Were all sar	mples received at a temperatu	ure of >0° C to 6.0°C	Yes	<b>V</b>	No		NA 🗔							
6. Sample(s) i	n proper container(s)?		Yes	V	No									
7. Sufficient sa	'. Sufficient sample volume for indicated test(s)?				No									
8. Are samples (except VOA and ONG) properly preserved?				<b>Y</b>	No									
9. Was presen	vative added to bottles?		Yes		No	<b>V</b>	NA [.]							
10.VOA vials ha	ave zero headspace?		Yes		No		No VOA Vials							
11. Were any s	ample containers received bro	oken?	Yes		No	~	# of preserved							
40 -					N.		bottles checked							
	work match bottle labels? pancies on chain of custody)		Yes	<b>V</b>	No	L-J	for pH: (<2	or >12 unless noted)						
	s correctly identified on Chain	of Custody?	Yes	<b>V</b>	No		Adjusted?							
14. Is it clear what analyses were requested?				<b>V</b>	No									
	ding times able to be met? customer for authorization.)		Yes	<b>V</b>	No		Checked by:							
Special Hand	lling (if applicable)													
16. Was client n	otified of all discrepancies wit	h this order?	Yes		No	[]	NA 🗹	1						
Person	n Notified:	Date:	oth or November 1	^ · · · ·										
By Wh	nom:	Via:	] eMa	il 🔲 P	Phone	Fax	In Person							
Regard	ding:													
Client	Instructions:					,								
17. Additional re	emarks:													
18. Cooler Info Cooler N	o Temp °C Condition	Seal Intact   Seal No   S	eal Da	te	Signed B	y								

Chain-of-Custody Record			Turn-Around Time:					HALL ENVIRONMENTAL													
lient: BLAGG ENGR. / BP AMERICA		☐ Standard	ANALYSIS LABORATORY																		
		Project Name:				www.hallenvironmental.com															
Mailing Address: P.O. BOX 87		GCU # 201E			4901 Hawkins NE - Albuquerque, NM 87109																
BLOOMFIELD, NM 87413			Project #:				Tel	. 50	5-345	-3975	;	Fax !	505-	345-	410	7				_	
hone #:		(505) 63	2-1199									Anal	ysis	Red	ques	it					
mail or F	ax#:			Project Manager:									14)				300.1)		$\top$		
A/QC Package:  ☐ Standard ☐ Level 4 (Full Validation)		NELSON VELEZ			FIMB <sup>4</sup> s (8021B)	+ TPH (Gas only)	/ MRO)		(S)		PO4,SC	2 PCB's			water - 30			e			
ccredita	tion:			Sampler: NELSON VELEZ 97 V				(Ga	/ DRO	7 5	NSIN I		102,	808			/ W3			du	
3 NELAF	·	□ Other		On ice: Yes □ No			#	TPH	0	418	827	50	03,	/ Se		(AC	300.0 /			e Sa	or N)
EDD (	EDD (Type)		Sample temperature: Z C			4		GR	pot	or or	eta	CI,N	cide	(A)	ıj-V(	1		e .	osit	3	
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALING.	BTEX + MTBE	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO <sub>3</sub> ,NO <sub>2</sub> ,PO <sub>4</sub> ,SO <sub>4</sub> )	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil			5 pt. composite sample	Air Bubbles (Y or
120/17	0905	SOIL	5PC - TB @ 5 ' (95)	4 oz 1	Cool	-001	٧		V								٧		,	V	
												Г							T	$\top$	
													1							T	
																				T	
																				1	
																				1	
				White or or															$\top$	1	
					***************************************															T	
																			$\top$	T	П
	-		A STATE OF THE STA							$\top$									$\top$	$\top$	П
ate:	Time:	Relinquished by:		Received by: / Date Time			Remarks: BILL DIRECTLY TO BP USING THE CONTACT WITH CORRESPONDING VID														
20/17	1720	70	mVI	Shoute	Jalo	1/20/17 1720	& REFERENCE # WHEN APPLICABLE;  CONTACT: STEVE MOSKAL / VANCE HIXON														
ate:	Time:	Relinquish	ed by:	Received by: Date Time				VID: VHIXONEVB2													
120/-	1904	1/1	Malt	(	X	01/21/170945		eren			- 699										
	If necessary	, samples sub	omitted to Hall Environmental may be su	bcontracted to other	accredited laboratorie	es. This serves as notice of	of this	possib	ility. A	Any sub-	contrac	ted da	a will l	be cle	arly no	tated	on the	analytic	al rep	ort.	



