

State of New Mexico  
Energy, Minerals and Natural Resources Department

**Susana Martinez**  
Governor

**Ken McQueen**  
Cabinet Secretary

**Matthias Sayer**  
Deputy Cabinet Secretary

**David R. Catanach, Division Director**  
Oil Conservation Division



New Mexico Oil Conservation Division approval and conditions listed below are made in accordance with OCD Rule 19.15.7.11 and are in addition to the actions approved by BLM on the following 3160-3 APD form.

Operator Signature Date: 11-3-16

Well information;

Operator WXPX, Well Name and Number Wilybrook Unit #762H

API# 30.045-35844, Section 27, Township 23D N/S, Range 9 E/W

Conditions of Approval: (See the below checked and handwritten conditions)

- ☒ Notify Aztec OCD 24hrs prior to casing & cement.
- ☒ Hold C-104 for directional survey & "As Drilled" Plat
- ☒ Hold C-104 for NSL, NSP, DHC
- ☐ Spacing rule violation. Operator must follow up with change of status notification on other well to be shut in or abandoned
- ☐ Regarding the use of a pit, closed loop system or below grade tank, the operator must comply with the following as applicable:
  - A pit requires a complete C-144 be submitted and approved prior to the construction or use of the pit, pursuant to 19.15.17.8.A
  - A closed loop system requires notification prior to use, pursuant to 19.15.17.9.A
  - A below grade tank requires a registration be filed prior to the construction or use of the below grade tank, pursuant to 19.15.17.8.C
- ☒ Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
- ☐ Submit Gas Capture Plan form prior to spudding or initiating recompletion operations
- ☒ Regarding Hydraulic Fracturing, review EPA Underground Injection Control Guidance 84
- ☒ Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system.
- ☒ Well-bore communication is regulated under 19.15.29 NMAC. This requires well-bore Communication to be reported in accordance with 19.15.29.8.

  
NMOCD Approved by Signature

4-24-2017  
Date

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED  
OMB No. 1004-0137  
Expires October 31, 2014

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM121961
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Single Zone <input checked="" type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator WPX ENERGY LLC		7. If Unit or CA Agreement, Name and No. INITIAL MANCOS PA / NMNM135216A
3a. Address 720 S Main Aztec NM 87410		8. Lease Name and Well No. W LYBROOK UT 762H
3b. Phone No. (include area code) (505)333-1822		9. API Well No. 30-045-35844
4. Location of Well (Report location clearly and in accordance with any State requirements.)* At surface NENW / 1121 FNL / 2446 FWL / LAT 36.202067 / LONG -107.776798 At proposed prod. zone SENE / 2057 FNL / 330 FEL / LAT 36.185012 / LONG -107.750557		10. Field and Pool, or Exploratory LYBROOK MANCOS W / LYBROOK MA
14. Distance in miles and direction from nearest town or post office* 37.8 miles		11. Sec., T. R. M. or Blk. and Survey or Area SEC 27 / T23N / R9W / NMP
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 20 feet	16. No. of acres in lease 320	17. Spacing Unit dedicated to this well 440
18. Distance from proposed location* to nearest well, drilling, completed, 1121 feet applied for, on this lease, ft.	19. Proposed Depth 4461 feet / 15045 feet	20. BLM/BIA Bond No. on file FED: UTB000178
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 6641 feet	22. Approximate date work will start* 12/01/2016	23. Estimated duration 30 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification
6. Such other site specific information and/or plans as may be required by the BLM.

25. Signature (Electronic Submission)	Name (Printed/Typed) Lacey Granillo / Ph: (505)333-1816	Date 11/03/2016
--	--	--------------------

Title  
Permitting Tech III

Approved by (Signature) <i>[Signature]</i>	Name (Printed/Typed) Anthony A. Caceres	Date 4/10/2017
Title AFM - MINERALS	Office FARMINGTON	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

\*(Instructions on page 2)

DRILLING OPERATIONS  
AUTHORIZED ARE SUBJECT TO  
COMPLIANCE WITH ATTACHED  
"GENERAL REQUIREMENTS"

BLM'S APPROVAL OR ACCEPTANCE OF THIS  
ACTION DOES NOT RELIEVE THE LESSEE AND  
OPERATOR FROM OBTAINING ANY OTHER  
AUTHORIZATION REQUIRED FOR OPERATIONS  
ON FEDERAL AND INDIAN LANDS

This action is subject to technical  
and procedural review pursuant to  
43 CFR 3165.3 and appeal  
pursuant to 43 CFR 3165.4

NMOCD IV



Submit one copy to  
Appropriate District Office

OIL CONSERVATION DIVISION  
1220 South St. Francis Drive  
Santa Fe, NM 87505

☐ AMENDED REPORT

District IV  
1220 S. St. Francis Drive, Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

## WELL LOCATION AND ACREAGE DEDICATION PLAT

*API Number 30-045-35844	*Pool Code 98157	*Pool Name LYBROOK MANCOS W
*Property Code 315250	*Property Name W LYBROOK UNIT	*Well Number 762H
*GRID No. 120782	*Operator Name WPX ENERGY PRODUCTION, LLC	*Elevation 6641'

<sup>10</sup> Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
C	27	23N	9W		1121	NORTH	2446	WEST	SAN JUAN

<sup>11</sup> Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
H	35	23N	9W		2057	NORTH	330	EAST	SAN JUAN

<sup>12</sup> Dedicated Acres 440.00 SW/4 NW/4, N/2 SW/4 SE/4 SW/4, SW/4 SE/4 - Section 26 N/2 NE/4, SE/4 NE/4 - Section 27 N/2 NE/4, SE/4 NE/4 - Section 35	<sup>13</sup> Joint or Infill	<sup>14</sup> Consolidation Code	<sup>15</sup> Order No. R-14051 - 12,807.24 Acres
NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION  
UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A  
NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



# 17 OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom-hole location or has a right to drill this well at this location pursuant to a mineral lease or owns a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Signature \_\_\_\_\_ Date \_\_\_\_\_  
Printed Name \_\_\_\_\_  
E-mail Address \_\_\_\_\_

## 18 SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief

Date Revised: OCTOBER 26, 2016  
Date of Survey: MARCH 10, 2016

Signature and Seal of Professional Surveyor



JASON C. EDWARDS

Certificate Number 15269



## **WPX Energy**

### **Operations Plan**

*(Note: This procedure will be adjusted onsite based upon actual conditions)*

**Date:** November 3, 2016  
**Well Name:** W Lybrook #762H  
**SH Location:** NENW Sec 27 23N-09W  
**BH Location:** SENE Sec 35 23N-09W

**Field:** Lybrook Mancos W  
**Surface:**  
**Elevation:** 6641' GR  
**Minerals:**

**Measured Depth:** 15,044.75'

## **I. GEOLOGY**

Surface formation - NACIMIENTO

### **A. FORMATION TOPS: (GR)**

NAME	MD	TVD	NAME	MD	TVD
OJO ALAMO	193.00	193.00	POINT LOOKOUT	3,460.00	3,260.00
KIRTLAND	355.00	355.00	MANCOS	3,653.00	3,435.00
PICTURED CLIFFS	925.00	923.00	GALLUP	4,025.00	3,774.00
LEWIS	1,010.00	1,007.00	KICKOFF POINT	3,917.37	3,674.57
CHACRA	1,232.00	1,224.00	TOP TARGET	5,092.00	4,504.00
CLIFF HOUSE	2,435.00	2,331.00	LANDING POINT	5,201.84	4,513.00
MENEFEE	2,453.00	2,348.00	BASE TARGET	5,201.84	4,513.00
			TD	15,044.75	4,461.00

### **B. MUD LOGGING PROGRAM:**

Mudlogger on location from surface csg to TD.

### **C. LOGGING PROGRAM:**

LWD GR from surface casing to TD.

### **D. NATURAL GAUGES:**

Gauge any noticeable increases in gas flow. Record all gauges in Tour book and on morning reports.

## **II. DRILLING**

### **A. MUD PROGRAM:**

LSND mud (WBM) will be used to drill the 12-1/4" Surface hole, the 8 3/4" Directional Vertical hole, and the curve portion of the wellbore. A LSND (WBM) or (OBM) will be used to drill the lateral portion of well. Treat for lost circulation as necessary. Obtain 100% returns prior to cementing. Notify Engineering of any mud losses.

### **B. BOP TESTING:**



While drill pipe is in use, the pipe rams and the blind rams will be function tested once each trip. The BOPE will be tested to 2,000 psi (High) for 10 minutes and the annular tested to 1,500 psi for 10 minutes. Pressure test surface casing to 1,500 psi for 30 minutes and intermediate casing to 1,500 psi for 30 minutes. Utilize a BOPE Testing Unit with a recording chart and appropriate test plug for testing. All tests and inspections will be recorded in the tour book as to time and results.

### III. MATERIALS

#### A. CASING PROGRAM:

CASING TYPE	OH SIZE (IN)	DEPTH (MD)	CSG SIZE	WEIGHT	GRADE	CONN
SURFACE	12.25"	320.00'	9.625"	36 LBS	J-55 or equiv	STC
INTERMEDIATE	8.75"	5,201.84'	7"	23 LBS	J-55 or equiv	LTC
PRODUCTION	6.125"	5051.84' - 15,044.75'	4.5"	11.6 LBS	P-110 or equiv	LTC
TIE BACK	6.125"	Surf. - 5051.84'	4.5"	11.6 LBS	P-110 or equiv	LTC

#### B. FLOAT EQUIPMENT:

##### 1. SURFACE CASING:

9-5/8" notched regular pattern guide shoe. Run (1) standard centralizer on each of the bottom (4) joints of Surface Casing.

##### 2. INTERMEDIATE CASING:

7" cement nose guide shoe with a self-fill insert float. Place float collar one joint above the shoe. Install (1) centralizer on each of the bottom (3) joints and one standard centralizer every (3) joints to 2,500 ft. Run (1) centralizer at 2,500 ft., 2,300ft., 2,000ft., 1,500 ft., and 1,000 ft. If losses are encountered during the drilling of the intermediate section a DV tool will be utilized and a 2 stage cement job may be planned to ensure cement circ back to surface. The DV tool will be placed 100' above the top of the Chacra formation. If cement is circulated back to surface on the first stage, a cancelation device will be dropped to shift the dv tool closed and the 2nd stage cement job will be aborted at that time, if no cement is seen at surface on the 1st stage the stage tool will be opened and a 2nd stage cement job will be pumped.

##### 3. PRODUCTION LINER:

Run 4-1/2" Liner with cement nose guide Float Shoe + 2jts. of 4-1/2" casing + Landing Collar + 4-1/2" pup joint + 1 RSI (Sliding Sleeve) positioned inside the 330ft Hard line. Centralizer program will be determined by Wellbore condition and when Lateral is evaluated by Geoscientists and Reservoir Engineers. Set seals on Liner Hanger. Test TOL to 1500 psi for 15 minutes.

#### C. CEMENT:

*(Note: Volumes may be adjusted onsite due to actual conditions)*

##### 1. Surface:

5 bbl Fresh Water Spacer, 100 sx (160 cu.ft.) of 14.5 ppg Type I-II (Neat G) + 20% Fly Ash cement w/ 7.41 gal/sack mix water ratio @ 1.61 cu ft/sx yield. Calculated @ volume + 50% excess. WOC 12 hours. Test csg to 600psi. Total Volume: (160 cu-ft/100 sx/ Bbls).TOC at Surface.

##### 2. Intermediate:

Spacer #1: 20 bbl (112 cuft) Chemwash. Lead Cement: 94 bbls, 269 sks, (529 cuft), 12.3 ppg @ 1.97 cuft/sk yield. Tail Cement: 59 bbls, 254 sks, (331 cuft), 13.5 ppg @ 1.3 cuft/sk yield. Displacement: Displace w/ +/- 205 bbl Drilling mud or water. Total Cement: 153 bbls, 523 sks, (860 cuft)

##### 3. Prod Liner:

Spacer #1: 10 bbl (56 cu-ft) Water Spacer. Spacer #2: 40 bbl 9.5 ppg (224.6 cu-ft) Taped Spacer III. Spacer #3: 10 bbl Water Spacer. Lead Cement: Extencem™ System. Yield 1.36 cuft/sk 13.3 ppg (979 sx /1332 cuft /237 bbls). Tail Spacer: 20 BBL of MMCR. Displacement: Displace w/ +/-207bbl Fr Water. Total Cement (979 sx /1332bbls).

**D. COMPLETION:**

Run CCL for perforating

**A. PRESSURE TEST:**

1. Pressure test 4-1/2" casing to 4500 psi max, hold at 1500 psi for 30 minutes. Increase pressure to Open RSI sleeves.

**B. STIMULATION:**

1. Stimulate with approximately 2,805,000# 20/40 mesh sand and 340,000# 16/30 mesh sand in 619,113 gallons water with 42,696 mscf N2 for 17 stages.
2. Isolate stages with flow through frac plug.
3. Drill out frac plugs and flowback lateral.

**C. RUNNING TUBING:**

1. Production Tubing: Run 2-7/8", 6.5#, J-55, EUE tubing with a SN on top of bottom joint. Land tubing near Top of Liner.

If this horizontal well is drilled past the applicable setbacks, an unorthodox location application is not required because the completed interval in this well, as defined by 19.15.16.7 B(1) NMAC, will be entirely within the applicable setbacks. This approach complies with all applicable rules, including 19.15.16.14 A(3) NMAC, 19.15.16.14 B(2) NMAC, 19.15.16.15 B(2) NMAC, and 19.15.16.15. B(4) NMAC.

---

**NOTES:**

A 4-1/2" 11.6# P-110 Liner will be run to TD and landed +/- 150 ft. into the 7" 23# J-55 Intermediate casing with a Liner Hanger and pack-off assembly then cemented to top of liner hanger.

After cementing and TOL clean up operations are complete, the TOL will be tested to 1500 psi (per BLM).

# **WPX Energy**

**T23N R9W**

**2309-27C WLU**

**W Lybrook UT #762H - Slot A1**

**Wellbore #1**

**Plan: Design #1 26May16 sam**

## **Standard Planning Report**

**31 May, 2016**



**WPX**  
Planning Report

<b>Database:</b>	COMPASS	<b>Local Co-ordinate Reference:</b>	Well W Lybrook UT #762H (A1) - Slot A1
<b>Company:</b>	WPX Energy	<b>TVD Reference:</b>	GL @ 6641.00usft (Original Well Elev)
<b>Project:</b>	T23N R9W	<b>MD Reference:</b>	GL @ 6641.00usft (Original Well Elev)
<b>Site:</b>	2309-27C WLU	<b>North Reference:</b>	True
<b>Well:</b>	W Lybrook UT #762H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1 26May16 sam		

<b>Project</b>	T23N R9W		
<b>Map System:</b>	US State Plane 1927 (Exact solution)	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	NAD 1927 (NADCON CONUS)		
<b>Map Zone:</b>	New Mexico West 3003		

<b>Site</b>	2309-27C WLU		
<b>Site Position:</b>		<b>Northing:</b>	1,892,793.57 usft
<b>From:</b>	Map	<b>Easting:</b>	516,861.23 usft
<b>Position Uncertainty:</b>	0.00 usft	<b>Slot Radius:</b>	13.200 in
		<b>Latitude:</b>	36.202053
		<b>Longitude:</b>	-107.776184
		<b>Grid Convergence:</b>	0.03 °

<b>Well</b>	W Lybrook UT #762H - Slot A1		
<b>Well Position</b>	<b>+N/-S</b>	0.00 usft	<b>Northing:</b> 1,892,793.57 usft
	<b>+E/-W</b>	0.00 usft	<b>Easting:</b> 516,861.23 usft
<b>Position Uncertainty</b>	0.00 usft	<b>Wellhead Elevation:</b>	0.00 usft
		<b>Latitude:</b>	36.202053
		<b>Longitude:</b>	-107.776184
		<b>Ground Level:</b>	6,641.00 usft

<b>Wellbore</b>	Wellbore #1		
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination</b>
			(°)
	IGRF2015	5/2/2016	9.32
			<b>Dip Angle</b>
			(°)
			62.89
			<b>Field Strength</b>
			(nT)
			49,846

<b>Design</b>	Design #1 26May16 sam		
<b>Audit Notes:</b>			
<b>Version:</b>	<b>Phase:</b>	PLAN	<b>Tie On Depth:</b> 0.00
<b>Vertical Section:</b>	<b>Depth From (TVD)</b>	<b>+N/-S</b>	<b>+E/-W</b>
	(usft)	(usft)	(usft)
	0.00	0.00	0.00
			<b>Direction</b>
			(bearing)
			128.71

<b>Plan Sections</b>										
Measured Depth (usft)	Inclination (°)	Azimuth (bearing)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,751.40	25.03	9.07	1,711.98	265.63	42.42	2.00	2.00	0.00	9.07	
3,917.37	25.03	9.07	3,674.57	1,170.51	186.91	0.00	0.00	0.00	0.00	
4,765.15	60.00	135.24	4,377.72	1,071.91	525.22	9.00	4.13	14.88	133.98	Start 60 tan #762H
4,865.15	60.00	135.24	4,427.72	1,010.42	586.20	0.00	0.00	0.00	0.00	End 60 tan #762H
5,036.81	75.45	135.24	4,492.59	897.96	697.72	9.00	9.00	0.00	0.00	
5,201.84	90.30	135.24	4,513.00	782.01	812.70	9.00	9.00	0.00	0.00	POE #762H
15,044.75	90.30	135.24	4,461.00	-6,206.94	7,743.40	0.00	0.00	0.00	0.00	BHL #762H



# WPX Planning Report

<b>Database:</b>	COMPASS	<b>Local Co-ordinate Reference:</b>	Well W Lybrook UT #762H (A1) - Slot A1
<b>Company:</b>	WPX Energy	<b>TVD Reference:</b>	GL @ 6641.00usft (Original Well Elev)
<b>Project:</b>	T23N R9W	<b>MD Reference:</b>	GL @ 6641.00usft (Original Well Elev)
<b>Site:</b>	2309-27C WLU	<b>North Reference:</b>	True
<b>Well:</b>	W Lybrook UT #762H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1 26May16 sam		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (bearing)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
320.00	0.00	0.00	320.00	0.00	0.00	0.00	0.00	0.00	0.00	
9 5/8"										
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00	
Start Build 2.00										
1,000.00	10.00	9.07	997.47	42.98	6.86	-21.53	2.00	2.00	0.00	
1,500.00	20.00	9.07	1,479.82	170.61	27.24	-85.45	2.00	2.00	0.00	
1,751.40	25.03	9.07	1,711.98	265.63	42.42	-133.04	2.00	2.00	0.00	
Hold 25.03 Inclination										
2,000.00	25.03	9.07	1,937.24	369.49	59.00	-185.06	0.00	0.00	0.00	
2,500.00	25.03	9.07	2,390.29	578.38	92.36	-289.68	0.00	0.00	0.00	
3,000.00	25.03	9.07	2,843.34	787.26	125.71	-394.30	0.00	0.00	0.00	
3,500.00	25.03	9.07	3,296.39	996.14	159.07	-498.92	0.00	0.00	0.00	
3,917.37	25.03	9.07	3,674.57	1,170.51	186.91	-586.25	0.00	0.00	0.00	
Start Build DLS 9.00 TFO 133.98										
4,000.00	20.53	24.48	3,750.80	1,201.00	195.68	-598.47	9.00	-5.45	18.64	
4,500.00	38.26	121.96	4,204.82	1,198.72	372.52	-459.07	9.00	3.55	19.50	
4,765.15	60.00	135.24	4,377.72	1,071.91	525.22	-260.61	9.00	8.20	5.01	
Hold 60.00 Inclination										
4,865.15	60.00	135.24	4,427.72	1,010.42	586.20	-174.57	0.00	0.00	0.00	
Start Build DLS 9.00 TFO 0.00										
5,000.00	72.14	135.24	4,482.32	923.06	672.83	-52.33	9.00	9.00	0.00	
5,036.81	75.45	135.24	4,492.59	897.96	697.72	-17.22	9.00	9.00	0.00	
Start DLS 9.00 TFO 0.00										
5,201.84	90.30	135.24	4,513.00	782.01	812.70	145.02	9.00	9.00	0.00	
POE at 90.30 Inc 135.24 Deg										
5,202.00	90.30	135.24	4,513.00	781.90	812.81	145.18	0.00	0.00	0.00	
7"										
5,500.00	90.30	135.24	4,511.42	570.30	1,022.64	441.24	0.00	0.00	0.00	
6,000.00	90.30	135.24	4,508.78	215.28	1,374.71	938.00	0.00	0.00	0.00	
6,500.00	90.30	135.24	4,506.14	-139.75	1,726.78	1,434.75	0.00	0.00	0.00	
7,000.00	90.30	135.24	4,503.50	-494.77	2,078.84	1,931.51	0.00	0.00	0.00	
7,500.00	90.30	135.24	4,500.86	-849.80	2,430.91	2,428.26	0.00	0.00	0.00	
8,000.00	90.30	135.24	4,498.22	-1,204.82	2,782.97	2,925.02	0.00	0.00	0.00	
8,500.00	90.30	135.24	4,495.58	-1,559.85	3,135.04	3,421.77	0.00	0.00	0.00	
9,000.00	90.30	135.24	4,492.93	-1,914.87	3,487.11	3,918.52	0.00	0.00	0.00	
9,500.00	90.30	135.24	4,490.29	-2,269.90	3,839.17	4,415.28	0.00	0.00	0.00	
10,000.00	90.30	135.24	4,487.65	-2,624.92	4,191.24	4,912.03	0.00	0.00	0.00	
10,500.00	90.30	135.24	4,485.01	-2,979.95	4,543.30	5,408.79	0.00	0.00	0.00	
11,000.00	90.30	135.24	4,482.37	-3,334.97	4,895.37	5,905.54	0.00	0.00	0.00	
11,500.00	90.30	135.24	4,479.73	-3,690.00	5,247.43	6,402.30	0.00	0.00	0.00	
12,000.00	90.30	135.24	4,477.09	-4,045.02	5,599.50	6,899.05	0.00	0.00	0.00	
12,500.00	90.30	135.24	4,474.44	-4,400.05	5,951.57	7,395.80	0.00	0.00	0.00	
13,000.00	90.30	135.24	4,471.80	-4,755.07	6,303.63	7,892.56	0.00	0.00	0.00	
13,500.00	90.30	135.24	4,469.16	-5,110.10	6,655.70	8,389.31	0.00	0.00	0.00	
14,000.00	90.30	135.24	4,466.52	-5,465.12	7,007.76	8,886.07	0.00	0.00	0.00	
14,500.00	90.30	135.24	4,463.88	-5,820.14	7,359.83	9,382.82	0.00	0.00	0.00	
15,000.00	90.30	135.24	4,461.24	-6,175.17	7,711.90	9,879.58	0.00	0.00	0.00	
15,044.75	90.30	135.24	4,461.00	-6,206.94	7,743.40	9,924.03	0.00	0.00	0.00	
TD at 15044.75										

# WPX Planning Report

<b>Database:</b>	COMPASS	<b>Local Co-ordinate Reference:</b>	Well W Lybrook UT #762H (A1) - Slot A1
<b>Company:</b>	WPX Energy	<b>TVD Reference:</b>	GL @ 6641.00usft (Original Well Elev)
<b>Project:</b>	T23N R9W	<b>MD Reference:</b>	GL @ 6641.00usft (Original Well Elev)
<b>Site:</b>	2309-27C WLU	<b>North Reference:</b>	True
<b>Well:</b>	W Lybrook UT #762H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1 26May16 sam		

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (bearing)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
Start 60 tan #762H - plan hits target center - Point	0.00	0.00	4,377.72	1,071.91	525.22	1,893,865.79	517,385.82	36.204998	-107.774404
End 60 tan #762H - plan hits target center - Point	0.00	0.00	4,427.72	1,010.42	586.20	1,893,804.34	517,446.84	36.204829	-107.774197
BHL #762H - plan hits target center - Point	0.00	0.00	4,461.00	-6,206.94	7,743.40	1,886,591.19	524,608.29	36.184999	-107.749945
POE #762H - plan hits target center - Point	0.00	0.00	4,513.00	782.01	812.70	1,893,576.06	517,673.47	36.204201	-107.773430





Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name		Casing Diameter (in)	Hole Diameter (in)
320.00	320.00	9 5/8"		9.625	12.250
5,202.00	4,513.00	7"		7.000	8.750

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment	
		+N/-S (usft)	+E/-W (usft)		
500.00	500.00	0.00	0.00	Start Build 2.00	
1,751.40	1,711.98	265.63	42.42	Hold 25.03 Inclination	
3,917.37	3,674.57	1,170.51	186.91	Start Build DLS 9.00 TFO 133.98	
4,765.15	4,377.72	1,071.91	525.22	Hold 60.00 Inclination	
4,865.15	4,427.72	1,010.42	586.20	Start Build DLS 9.00 TFO 0.00	
5,036.81	4,492.59	897.96	697.72	Start DLS 9.00 TFO 0.00	
5,201.84	4,513.00	782.01	812.70	POE at 90.30 Inc 135.24 Deg	
15,044.75	4,461.00	-6,206.94	7,743.40	TD at 15044.75	





Well Name: W Lybrook UT #762H  
 Surface Location: 2309-27C WLU  
 NAD 1927 (NADCON CONUS), US State Plane 1927 (Exact solution) New Mexico V 3003  
 Ground Elevation: 6641.00  
 +N/-S 0.00 +E/-W 0.00 Northing 1892793.57 Easting 516861.23 Latitude 36.202053 Longitude -107.776184 Slot A1  
 GL @ 6641.00usft (Original Well Elev)





- 2 As practical, the access road on the well pad will be a teardrop-shape through the area so that the center may be revegetated.
- 3 Within 90 days of installation, production facilities would be painted.
  - The production facilities will be painted Juniper Green to blend with the natural color of the landscape surrounding the well pad and would be located in efforts to the extent practical, to reasonably minimize visual impact.
- 4 Berms will be constructed around all storage facilities sufficient in size to contain the storage capacity of tanks. Berm walls will be compacted with appropriate equipment to assure containment.

After the completion phases and pipeline installation, portions of the project area not needed for operation will be reclaimed. When the wells are plugged, final reclamation will occur within the remainder of the project area. Reclamation is described in detail in the Surface Use Reclamation Plan (Appendix A).

## 7. METHODS FOR HANDLING WASTE

---

### A. Cuttings

- 1 Drilling operations will utilize a closed-loop system. Drilling of the horizontal laterals will be accomplished with water-based mud. All cuttings will be placed in roll-off bins and hauled to a commercial disposal facility or land farm. WPX will follow Onshore Oil and Gas Order No. 1 regarding the placement, operation, and removal of closed-loop systems. No blow pit will be used.
- 2 Closed-loop tanks will be adequately sized for containment of all fluids.

### B. Drilling Fluids

- 1 Drilling fluids will be stored onsite in above-ground storage tanks. Upon termination of drilling operations, the drilling fluids will be recycled and transferred to other permitted closed-loop systems or returned to the vendor for reuse, as practical. All residual fluids will be hauled to a commercial disposal facility.

### C. Spills

- 1 Any spills of non-freshwater fluids will be immediately cleaned up and removed to an approved disposal site.

### D. Sewage

- 1 Portable toilets will be provided and maintained during construction, as needed (see Figures 3 & 4 in Appendix B for the location of toilets).

### E. Garbage and other waste material

- 1 All garbage and trash will be placed in a metal trash basket. The trash and garbage will be hauled off site and dumped in an approved landfill, as needed.

### F. Hazardous Waste

- 1 No chemicals subject to reporting under Superfund Amendments and Reauthorization Act Title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of these wells.
- 2 No extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of these wells.
- 3 All fluids (i.e., scrubber cleaners) used during washing of production equipment will be properly disposed of to avoid ground contamination or hazard to livestock or wildlife.

### G. Produced Water:

- 1 WPX Energy will dispose of produced water from this well at one of the following facilities:
  - Lybrook Yard WDW #1, API #30-039-27533, NMOCD permit #SWD-907, operated by Elm Ridge Resources, located in NE ¼, Section 14, Township 23 North, Range 7 West
  - Jillson Federal #1, NMOCD order #R-10168, operated by ConocoPhillips, located in NW ¼, Section 8, Township 24 North, Range 3 West
  - Basin Disposal, permit #NM-01-005, located in the NW ¼, Section 3, Township 29 North, Range 11 West
  - Sunco SWD #001, API #30-045-28653, NMOCD permit SWD-457, operated by Key Energy, located in NW ¼, Section 2, Township 29 North, Range 12 West



**Directions from the Intersection of US Hwy 550 & US Hwy 64**  
**in Bloomfield, NM to WPX Energy Production, LLC W Lybrook Unit #762H**  
**1121' FNL & 2446' FWL, Section 27, T23N, R9W, N.M.P.M., San Juan County, NM**

**Latitude: 36.202067°N Longitude: 107.776798°W Datum: NAD1983**

From the intersection of US Hwy 550 & US Hwy 64 in Bloomfield, NM, travel Southerly on US Hwy 550 for 37.8 miles to Mile Marker 113.4;

Go Right (South-westerly) on County Road #7890 for 0.8 miles to fork in roadway;

Go Left (Southerly) remaining on County Road #7890 for 1.3 miles to four-way intersection;

Go Left (South-easterly) remaining on County Road #7890 for 0.6 miles to fork in roadway;

Go Right (South-westerly) remaining on County Road #7890 for 0.5 miles to WPX W Lybrook Unit #720H proposed access on right-hand side of County Road #7890;

Go Right (Westerly) exiting County Road #7890 following along WPX W Lybrook Unit #720H proposed access for 3123.1' to fork in proposed access;

Go Left (Westerly) which is straight, following along WPX W Lybrook Unit #726H proposed access for 3937.3' to fork in proposed access;

Go Left (Westerly) which is straight, continuing for 10,437.9' to staked WPX W Lybrook Unit #762H location.

