This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR				Leas	se Name	Well No. 2E					
Location of W	ell: Unit Le	etter	D	Sec	01	Twp	030N	Rge	013W A	PI# <u>30-045-25060</u>	
	Name of Reservoir or Pool			Type of Prod				Method of Prod	Prod Medium		
Upper Completion	FRC				Gas			Flo	w	Casing	
Lower Completion	DK				Gas			Flo	W	Tubing	
				F	re-Flow	Shut-In	Pressu	re Data			
Upper	Hour, Date, Shut-In				Length of Time Shut-In			The second second	Press. PSIG	Stabilized?(Yes or No)	
Completion	5/18/2017				128 hours				94	4 Yes	
Lower	Hour, Date, Shut-In				Length	n of Time S	Shut-In	SIF	Press. PSIG	Stabilized?(Yes or No)	
Completion	5/18/2017				120 hours				482	2 Yes	
Commenced	at:		5/23/20					oducing (Up	per or Lower): L	OWER .	
Time (date/time)		Lapsed Time Since*			PRESSURE pper zone Lower zone		r zone	Temperatu		Remarks	
5/23/2017 8:10:39 AM			8		94	4	82				
5/23/2017 8:11:37 AM 8				94 73			lower zone dropped below its 20% crosso				
Production rat											
Oil:	il: BPOD Based on: B			Bbls. In Hrs.				Grav.	GOR		
Gas		MCF	PD; Te	est thru (C	Orifice or	Meter)					
				,	/lid-Teet	Shut-In	Presen	ire Data			
Upper Completion	Hour, Date, Shut-In					Length of Time Shut-In			Press. PSIG	Stabilized?(Yes or No)	
Lower Completion	Hour, Date, Shut-In			Length of Time Shut-In			SI F	Press. PSIG	Stabilized?(Yes or No)		

(Continue on reverse side)

OIL CONS. DIV DIST. 3

Page 2

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Commenced at:			Zone Pro	Zone Producing (Upper or Lower)				
Time	Lapsed Time	PRES	SURE	Prod Zone				
(date/time)	Since*	Upper zone	Lower zone	Temperature		Remarks		
Production rate durin Oil:BP0	DD Based on:	Bbls. In	Hrs.		Grav.	GOR		
Gas	MCFPD; Test th	nru (Orifice or M	leter)					
Remarks:								
						luced lower zone through		
separator to pit to ge	et 20% crossover, Thon	nas vermersch	WITH NIVIOCD	witnessed the	test			
I hereby certify that t	the information herein o	contained is true	and complete	to the best of	my knowledge	e.		
Approved: 3/	-MAY	20 17	Opera	tor: BR				
New Mexico Oil O	Conservation Division		Ву:	Pete Jim				
By: Jum	Huran		Title:	Multi-Skilled Operator				
	outy Oil & Gas Ins		Date:	Tuesday, May 30, 2017				

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual
 completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.
 Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or
 chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or
 the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when
 requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.