District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: Fields A 020
API Number: 3004527742 OCD Permit Number:
U/L or Qtr/Qtr A Section 25 Township 32N Range 11W County: San Juan
Center of Proposed Design: Latitude 36.960934 Longitude -107.935420 NAD: □1927 ⋈ 1983
Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
2. Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A

OIL CONS. DIV DIST. 3

MAT LO ...

Liner type: Thickness

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off

☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other <u>Single wall/ Double bottom; no visible sidewalls</u>

mil HDPE PVC Other

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
6. Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan	documents are
☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sout provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain.	☐ Yes ☐ No
- FEMA map	163 110
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ief.
Name (Print): Title:	
Signature: Date:	
Signature: Date: e-mail address: Telephone:	
e-mail address: Telephone:	
e-mail address: Telephone:	
e-mail address: Telephone:	
e-mail address: Telephone: OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 5 3	the closure report.
e-mail address: Telephone:	the closure report.
e-mail address: Telephone:	the closure report.

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure report belief. I also certify that the closure complies with all applicable closure requirements	
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature: Shaws Muu	Date: May 17, 2017
e-mail address: steven moskal@hn.com	Telephone: (505) 326-9497

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Fields A 020 API No. 3004527742 Unit Letter A, Section 25, T32N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

 Notice was provided and is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	45 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.015
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.060
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<49
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for TPH, BTEX and chloride with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 - Sampling results indicates no release had occurred. Attached is a laboratory report and C-141.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area
 - Sampling results indicates no release had occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.
- 10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The location will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The location will be reclaimed when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The location will be reclaimed when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The location will be reclaimed when the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Revised August 8, 2011
Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Attached

Form C-141

Release Notification and Corrective Action **OPERATOR** Initial Report Final Report Name of Company: BP Contact: Steve Moskal Address: 200 Energy Court, Farmington, NM 87401 Telephone No.: 505-326-9497 Facility Name: Fields A 020 Facility Type: Natural gas well Surface Owner: Federal Mineral Owner: Federal API No. 3004527742 LOCATION OF RELEASE Unit Letter Section Township Feet from the North/South Line Feet from the East/West Line Range County: San Juan 25 32N 11W Latitude __36.960934° **Longitude** ___ -107.935420° NATURE OF RELEASE Type of Release: none Volume of Release: unknown Volume Recovered: N/A Source of Release: below grade tank – 45 bbl Date and Hour of Occurrence: Date and Hour of Discovery: none Was Immediate Notice Given? If YES, To Whom? ☐ Yes ☒ No ☐ Not Required By Whom? Date and Hour Was a Watercourse Reached? If YES, Volume Impacting the Watercourse. ☐ Yes ☒ No If a Watercourse was Impacted, Describe Fully.* Describe Cause of Problem and Remedial Action Taken.* Sampling of the soil beneath the BGT was done during removal. Soil analysis resulted for TPH, BTEX and chlorides below BGT closure standards. Field reports and laboratory results are attached. Describe Area Affected and Cleanup Action Taken.* No further action necessary. Final laboratory analysis determined no remedial action is required. I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations. OIL CONSERVATION DIVISION Signature: Mus Muy Approved by Environmental Specialist: Printed Name: Steve Moskal Title: Field Environmental Coordinator Approval Date: **Expiration Date:**

Conditions of Approval:

Date: May 17, 2017

E-mail Address: steven.moskal@bp.com

Phone: 505-326-9497

^{*} Attach Additional Sheets If Necessary

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

March 14, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: FIELDS A 020

API#: 3004527742

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about March 17, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

Moskal, Steven

From:

Buckley, Farrah (CH2M HILL)

Sent:

Tuesday, March 14, 2017 3:37 PM

To:

'Smith, Cory, EMNRD'; 'Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)'

Cc:

'jeffcblagg@aol.com'; 'blagg_njv@yahoo.com'; Moskal, Steven

Subject:

BP Pit Close Notification - FIELDS A 020

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

March 14, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

FIELDS A 020 API 30-045-27742 (A) Section 25 – T32N – R11W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT and a 21bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around March 17, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

(505) 326-9497

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	BLAGG EN P.O. BOX 87, BL	GINEERING, IN OOMFIELD, N		API#: 30045	27742
	(505) 632-1199		TANK ID (if applicble):	Α
FIELD REPORT:	(circle one): BGT CONFIRMATION / F	RELEASE INVESTIGATION / (OTHER:	PAGE #: 1	of 1 _
SITE INFORMATION	I: SITE NAME: FIELDS	A # 20		DATE STARTED: 0	3/20/17
QUAD/UNIT: A SEC: 25 TWP:	32N RNG: 11W PM:	NM CNTY: SJ	ST: NM	DATE FINISHED:	¥-1
1/4-1/4/FOOTAGE: 790'N / 790'	E NE/NE LEASE TYP	PE: FEDERAL STATE	/ FEE / INDIAN	ENVIRONMENTAL	
LEASE #: NM010989	PROD. FORMATION: FT COM	STRIKE ITRACTOR: MBF - R. I	POWELL	SPECIALIST(S):	JCB
REFERENCE POINT	: WELL HEAD (W.H.) GPS C	OORD.: 36.9612	24 X 107.93539	GL ELEV.:	6,186'
1) 45 BGT (SW/DB) - A	GPS COORD.: 36.96			RING FROM W.H.: 104.	
2)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
3)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR	LAB USED: HALL	_		OVM READING
1) SAMPLE ID: 45 BGT(A) 5-pt	. @ 6' SAMPLE DATE: 03/20/17	7 SAMPLE TIME:	LAB ANALYSIS: 801	5B/8021B/300.0 (CI)	
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
2) GPS COORD.: DISTANCE/BEARING FROM W.H.: 3) GPS COORD.: DISTANCE/BEARING FROM W.H.: 4) DISTANCE/BEARING FROM W.H.: SAMPLING DATA: CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL OVM. READIN (ppm)					
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND SIL	T / SILTY CLAY / CLAY / GRAV	EL / OTHER		
SOIL COLOR: DARK YEL	LOWISH ORANGE	LASTICITY (CLAYS): NON PLASTI	IC / SLIGHTLY PLASTIC / C	OHESIVE / MEDIUM PLASTIC /	HIGHLY PLASTIC
		C ODOR DETECTED: YES V NO	EXPLANATION -		
		NY AREAS DISPLAYING WETNE	SS: YES NO EXPLA	NATION -	
DISCOLORATION/STAINING OBSERVED: YES					
			ADOVE CDADE TA	NIV TO BE SET ATOD BY	CT I OCATION
OTHER:	YES NO EXPLANATION - 105 BBL	SHALLOW LOW PROFILE	ABOVE-GRADE IA	NK TO BE SET ATOP BO	31 LOCATION.
					N/A
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <100' N	NA ft. X NA IEAREST WATER SOURCE: >1,000'	ft. X NA ft. NEAREST SURFACE WATER:		TIMATION (Cubic Yards) : CD TPH CLOSURE STD:	400
SITE SKETCH					100 ppm
SHESKEICH	BGT Located: off on site	PLOT PLAN cir		CALIB. READ. = 100.6	ppm RF =0.52
	PUMP			CALIB. GAS = 100	ppm
	→ W.H.		N TIME		03/20/17
				MISCELL. N	OTES
				/O:	
				EF. #: P-688	/D0
COMPRI	ESSOR		_	ID: VHIXONEV	B2
				J#:	14 4 14 0
		SEPARATOR			5/14/10 5/02/16
	(45)-A PBGTL (XXX) FEN	ICE	Tar	ovM = Organic Vapo	r Meter
	T.B. ~ 6'	NOE	A	100000000000000000000000000000000000000	
	B.G. BERM			BGT Sidewalls Visible:	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	ON DEDRESSION: B.C. = BELOW/CDADE: B = DELO		(- S.P.D.	BGT Sidewalls Visible:	
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	ON DEPRESSION, B.G BELOW GRADE, B - BELC .OW-GRADE TANK LOCATION; SPD = SAMPLE POI E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTO	NT DESIGNATION; R.W. = RETAINING	NAME AND TOTAL	lagnetic declination:	10° E
NOTES: GOOGLE EARTH IMAG	ERY DATE: 3/15/2015.	ONSITE: 03/20/	117		

Analytical Report

Lab Order 1703A27

Date Reported: 3/22/2017

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 45 BGT(A) 5-pt. @ 6'

Project: Fields A 20

Collection Date: 3/20/2017 8:30:00 AM

Lab ID: 1703A27-001

Matrix: MEOH (SOIL) Received Date: 3/21/2017 7:53:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	MRA
Chloride	ND	30	mg/Kg	20	3/21/2017 11:52:36 AM	30827
EPA METHOD 8015M/D: DIESEL RANG	E ORGANICS	S			Analyst	MAB
Diesel Range Organics (DRO)	ND	9.8	mg/Kg	1	3/21/2017 10:22:18 AM	30814
Motor Oil Range Organics (MRO)	ND	49	mg/Kg	1	3/21/2017 10:22:18 AM	30814
Surr: DNOP	84.2	70-130	%Rec	1	3/21/2017 10:22:18 AM	30814
EPA METHOD 8015D: GASOLINE RANGE	GE				Analyst	NSB
Gasoline Range Organics (GRO)	ND	3.0	mg/Kg	1	3/21/2017 9:04:39 AM	G41547
Surr: BFB	88.5	54-150	%Rec	1	3/21/2017 9:04:39 AM	G41547
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.015	mg/Kg	1	3/21/2017 9:04:39 AM	B41547
Toluene	ND	0.030	mg/Kg	1	3/21/2017 9:04:39 AM	B41547
Ethylbenzene	ND	0.030	mg/Kg	1	3/21/2017 9:04:39 AM	B41547
Xylenes, Total	ND	0.060	mg/Kg	1	3/21/2017 9:04:39 AM	B41547
Surr: 4-Bromofluorobenzene	102	66.6-132	%Rec	1	3/21/2017 9:04:39 AM	B41547

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 6
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

CI	nain-c	of-Cus	stody Record	Turn-Around	Time:	SAME	1			14	AL		BEL	/TY	20	TATE	ME	-	CA		
Client	AG	G ENGR	/ BP AMERICA	☐ Standard	Rush _	DAY)	1	62			NA										
				Project Name							ww.								-		
Mailing A	ddress:	P.Q. BO	X87	1	FIELDS A #	20		49	01 H		ns NE							19			
		BLOOM	FIELD, NM 87413	Project #:							5-397		Fax								
Phone #:		(505) 63	2-1199	1							,,,,,,		lysis								
email or l	Fax#:			Project Mana	ger:							1	-				1				
GA/QC Ps ☑ Stand			Level 4 (Full Validation)		JEFFREY C.	BLAGG	(80218)	(Aluo s	/ MRO)		101	2	PO4,50	PCB's			ter - 300.1)			8	
Accredita	tion			Sampler: JEFFREY C. BLAGG		8) 84	Ga	280	=	1	200	03	3082			300.0 / water			dm		
I NELA		☐ Other		On Ice:	Yes	□ No	#	TP#	10	418	504		0	18		A N	0.00			E Sa	Z
□ EDD (Type)			Sample Temp	erature: 3 7		4	+ 3E	(GR	pod	DO C	etal	N,	cide	F	i-V			11	osit	30
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALNO.	BTEX +- MAT	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO / MRO)	TPH (Method 418.1)	EDB (Method 504.1)	RCRA 8 Metals	Anions (F,Cl,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	Chloride (soll		Grab sample	5 pt, composite sample	Air Bubbles (Y or N)
3/10/17	0830	50IL	45 BGT(A) 5-pt.@ 6 1	4 oz 1	Cool	-001	٧		٧								٧			٧	
3/23/17	0317	SOIL	of Berlinie Jule 5	400 1	Cool	002	*		*								√			4	
																		П			
												T						П			
																		П	\sqcap		
												1						П	\neg		
																			\neg		
												\top									
Date: 20/2017	Time 1630	Relinquishe	Blagg FOR MARPOING	Received by:	1 AZ	Date Time		arks		& REFE	RECTLY RENCE	# WHE	N APP	LICA	BLE;		VITH	ORRES	SPONI	DING	VID
Date:	Time:	Relinquishe		Received by/		Date Time	-				ONEV			-	. III	,,,					
				-			Ref	eren	ce#		P - 68	8_									

Hall Environmental Analysis Laboratory, Inc.

WO#:

1703A27

22-Mar-17

Client:

Blagg Engineering

Project:

Fields A 20

Sample ID MB-30827

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

Batch ID: 30827

RunNo: 41545

LowLimit

Prep Date: 3/21/2017 Analysis Date: 3/21/2017

SeqNo: 1302689

Units: mg/Kg

RPDLimit Qual

Analyte Chloride

Result PQL ND 1.5

HighLimit

%RPD

Sample ID LCS-30827

LCSS

SampType: Ics

TestCode: EPA Method 300.0: Anions

Batch ID: 30827

1.5

RunNo: 41545

Prep Date: 3/21/2017 Analysis Date: 3/21/2017

SeqNo: 1302690

Units: mg/Kg HighLimit

Analyte

Client ID:

Result **PQL**

SPK value SPK Ref Val

%REC 96.8

90

%RPD

Qual

Chloride

0

SPK value SPK Ref Val %REC

110

15

15.00

LowLimit

RPDLimit

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix D

Η Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

% Recovery outside of range due to dilution or matrix

В Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 3 of 6

P Sample pH Not In Range

RL

Reporting Detection Limit Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1703A27

22-Mar-17

Client:

Blagg Engineering

Project:

Fields A 20

Sample ID LCS-30814	SampT	ype: LC	S	Test	TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: LCSS	Batch	ID: 30	814	R	RunNo: 4	1526					
Prep Date: 3/21/2017	Analysis Date: 3/21/2017 SeqNo: 1302332 Units: mg/Kg										
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Diesel Range Organics (DRO)	47	10	50.00	0	94.5	63.8	116				
Surr: DNOP	4.4		5.000		88.0	70	130				

Sample ID MB-30814	SampT	ype: ME	BLK	TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: PBS	Batch	Batch ID: 30814 RunNo: 41526								
Prep Date: 3/21/2017	te: 3/21/2017 Analysis Date: 3/21/2017 SeqNo: 1302333 Units: mg/Kg									
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	8.4		10.00		83.9	70	130			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits

Page 4 of 6

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#: 1703A27

Qual

22-Mar-17

Client:

Blagg Engineering

Project:

Fields A 20

Sample ID RB

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

PBS

Batch ID: G41547

PQL

5.0

RunNo: 41547

LowLimit

LowLimit

Prep Date:

Analysis Date: 3/21/2017

SeqNo: 1303119

Units: mg/Kg

Analyte

Result

%REC

HighLimit

Gasoline Range Organics (GRO)

Surr: BFB

ND 880

1000

SPK value SPK Ref Val

88.5

54 150

Sample ID 2.5UG GRO LCS

Client ID:

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

RunNo: 41547

Prep Date:

LCSS

Batch ID: G41547

PQL

Analyte

Analysis Date: 3/21/2017

SeqNo: 1303120

Units: mg/Kg

125

150

HighLimit

RPDLimit Qual

RPDLimit

Gasoline Range Organics (GRO) Surr: BFB

5.0 25.00 1000 %REC 76.6 92.5

76.4 54

61.3

61.3

54

54

%RPD

%RPD

Sample ID 1703A27-001AMS

SampType: MS

TestCode: EPA Method 8015D: Gasoline Range

Client ID: Prep Date: 45 BGT(A) 5-pt. @ 6'

Result

16

Result

19

930

Batch ID: G41547

RunNo: 41547

Units: mg/Kg

%RPD

Qual

Qual

Analyte

Analysis Date: 3/21/2017

15.12

605.0

15.12

605.0

SPK value SPK Ref Val

SeqNo: 1303121 SPK value SPK Ref Val %REC LowLimit

103

97.1

HighLimit

150

150

RPDLimit

0

Gasoline Range Organics (GRO) Surr: BFB

590

SampType: MSD

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

45 BGT(A) 5-pt. @ 6'

Batch ID: **G41547**

PQL

3.0

RunNo: 41547

Prep Date:

Sample ID 1703A27-001AMSD

Analysis Date: 3/21/2017

3.0

SeqNo: 1303122

Units: mg/Kg

Analyte Gasoline Range Organics (GRO) Surr: BFB

Result PQL

16

590

SPK value SPK Ref Val

0

%REC I owl imit 104

97.4

HighLimit

150

150

%RPD **RPDLimit** 20 1.58

0

Qualifiers:

- Value exceeds Maximum Contaminant Level
- Sample Diluted Due to Matrix D
- H Holding times for preparation or analysis exceeded

% Recovery outside of range due to dilution or matrix

- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits R

- В Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Page 5 of 6

- P Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#: 1703A27

22-Mar-17

Client:

Blagg Engineering

Project:

Fields A 20

Sample ID RB	SampT	уре: МЕ	BLK	Tes	TestCode: EPA Method 8021B: Volatiles					
Client ID: PBS	Batch	n ID: B4	1547	F	RunNo: 4	1547				
Prep Date:	Analysis D	ate: 3/	21/2017	5	SeqNo: 1	303126	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.99		1.000		99.1	66.6	132			
Sample ID 100NG BTEX LCS	SampT	ype: LC	s	Tes	tCode: E	PA Method	8021B: Volat	tiles		
Client ID: LCSS	Batch	n ID: B4	1547	F	RunNo: 4	1547				

Sample ID 100NG BTEX LCS	SampTy	pType: LCS TestCode: EPA Method 8021B: Volatiles								
Client ID: LCSS	Batch	ID: B4	1547	RunNo: 41547						
Prep Date:	Analysis Da	ate: 3/	21/2017	S	SeqNo: 1	303127	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.85	0.025	1.000	0	84.5	80	120			
Toluene	0.86	0.050	1.000	0	85.5	80	120			
Ethylbenzene	0.91	0.050	1.000	0	90.6	80	120			
Xylenes, Total	2.7	0.10	3.000	0	90.1	80	120			
Surr: 4-Bromofluorobenzene	1.0		1.000		101	66.6	132			

Sample ID 1703A27-002AM	03A27-002AMS SampType: MS TestCode: EPA Method 8021B: Volatiles									
Client ID: 95 BGT(B) 5-pt. @ 5' Batch ID: B41547 RunNo: 41547										
Prep Date:	Analysis D	ate: 3/	21/2017	S	SeqNo: 1	303128	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.62	0.015	0.6053	0	102	61.5	138			
Toluene	0.62	0.030	0.6053	0	103	71.4	127			
Ethylbenzene	0.63	0.030	0.6053	0	104	70.9	132			
Xylenes, Total	1.9	0.061	1.816	0	104	76.2	123			
Surr: 4-Bromofluorobenzene	0.65		0.6053		108	66.6	132			

Sample ID 1703A27-002AMS	O02AMSD SampType: MSD TestCode: EPA Method 8021B: Volatiles									
Client ID: 95 BGT(B) 5-pt. (95 BGT(B) 5-pt. @ 5' Batch ID: B41547 RunNo: 41547									
Prep Date: Analysis Date: 3/21/2017 SeqNo: 1303129 Units: mg/Kg										
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.66	0.015	0.6053	0	110	61.5	138	7.03	20	
Toluene	0.68	0.030	0.6053	0	112	71.4	127	8.64	20	
Ethylbenzene	0.70	0.030	0.6053	0	115	70.9	132	10.4	20	
Xylenes, Total	2.1	0.061	1.816	0	115	76.2	123	10.3	20	
Surr: 4-Bromofluorobenzene	0.65		0.6053		108	66.6	132	0	0	

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits

Page 6 of 6

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Number:	1703A27		RcptNo:	1
Received by/date:	C3 Zi 17				
Logged By: Lindsay Mangin	3/21/2017 7:53:00 AM		July Hogo		
Completed By: Lindsay Mangin	3/21/2017 8:03:00 AM		July Hayo		
Reviewed By:	03/21/17	*	000		· ·
Chain of Custody					
1. Custody seals intact on sample bottles?		Yes	No 🗆	Not Present	
2. Is Chain of Custody complete?		Yes 🗹	No 🗌	Not Present	
3. How was the sample delivered?		Courier			
Log In					
4. Was an attempt made to cool the sample	es?	Yes 🗸	No 🗆	NA 🗆	
5. Were all samples received at a temperate	ure of >0° C to 6.0°C	Yes 🗹	No 🗆	NA 🗆	
6. Sample(s) in proper container(s)?		Yes 🗹	No 🗆		
7. Sufficient sample volume for indicated tes	st(s)?	Yes 🗹	No 🗆		
8. Are samples (except VOA and ONG) prop	perly preserved?	Yes 🗹	No 🗆		
9. Was preservative added to bottles?		Yes	No 🗹	NA 🗆	
10.VOA vials have zero headspace?		Yes	No 🗆	No VOA Vials	
11. Were any sample containers received bro	oken?	Yes	No 🗹		
				# of preserved bottles checked	
12. Does paperwork match bottle labels?		Yes 🗹	No 🗆	for pH:	>12 unless noted)
(Note discrepancies on chain of custody) 13. Are matrices correctly identified on Chain	of Custody?	Yes 🗸	No 🗆	Adjusted?	> 12 dilless floted)
14. Is it clear what analyses were requested?		Yes 🗹	No 🗆		
15. Were all holding times able to be met?		Yes 🗸	No 🗆	Checked by:	
(If no, notify customer for authorization.)			Ĺ		
Special Handling (If applicable)					
16. Was client notified of all discrepancies with	h this order?	Yes	No 🗆	NA 🗹	
Person Notified:	Date				
By Whom:	Via: [eMail	Phone Fax	☐ In Person	:
Regarding:					
Client Instructions:				- Commence of the Commence of	
17. Additional remarks:					
18. Cooler Information					
	Seal Intact Seal No 5	Seal Date	Signed By		
J. 5.2 Good 1	00		1		



