

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-043-21308

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V092291

7. Lease Name or Unit Agreement Name

STATE 2207-36D

8. Well Number
#193H

9. OGRID Number
120782

10. Pool name or Wildcat
WC 22N7W36; Gallup(O)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
WPX Energy Production, LLC.

3. Address of Operator
PO Box 640 Aztec NM 87410

4. Well Location

Unit Letter D : 725' feet from the NORTH line and 311' feet from the WEST line
Section 36 Township 22N Range 7W NMPM County SANDOVAL

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
6942'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: Spud/Surface Casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

NOTE: MO-TE SET SURFACE

6/1/17- SPUD @ 13:15 hrs. TD 12-1/4" Surface @ 339'.

6/2/17-RU & run 11 jts 9 5/8" 36# J-55 ST&C csg, set @ 339', float collar @ 311'

Pump 10 bbls FW spacer, dump 28.9 bbls (101 xs) Type I-II cmt w/ 20% flyash @ 14.5 PPG into casing, drop plug & disp w/ 24 bbls H2O, bump plug @ 200 psi, circ 10 bbls good cmt to surface

NOTE: WPX will MI to Install & test BOP at a later date. We will file another sundry at that time. ✓

OIL CONS. DIV DIST. 3

JUN 06 2017

Spud Date:

6/1/17

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Permit Tech III

DATE 6/6/17

Type or print name Lacey Granillo

E-mail address: lacey.granillo@wpxenergy.com

PHONE: 3331816

For State Use Only

APPROVED BY:

TITLE

Deputy Oil & Gas Inspector,
District #3

DATE 6/7/17

Conditions of Approval (if any):

N