



UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: January 31, 2018

OMB	INO. I	004-01	21
Expires:	Janua	ry 31,	201
0 111			

Farmington Field Off ONDRY NOTICES AND REPORTS ON WELLS Bure

4	5. Lease Serial No. NMNM18463
6	6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit of CA/Agreement, Name and/or No.		
1. Type of Well		action on pag			CA NMNM136868		
✓ Oil Well Gas W			8. Well Name and No. HEROS 2308 09L COM 1H				
2. Name of Operator LOGOS Operati			9. API Well No. 30-04	5-35688			
			(include area cod	e)	10. Field and Pool or Exploratory Area		
Farmington, NM 87401 (505) 324-		(505) 324-41	145		Nageezi Gallup		
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)					11. Country or Parish, State		
1476 FSL & 210 FWL, NW/SW, L Sec 9 T23N R08W			San Juan County, NM		NM 		
12. CHE	CK THE APPROPRIATE B	OX(ES) TO INI	DICATE NATURI	E OF NOT	ICE, REPORT OR OTH	IER DATA	
TYPE OF SUBMISSION			TY	PE OF AC	TION		
Notice of Intent	Acidize	Deep		Prod	luction (Start/Resume)	Water Shut-Off	
	Alter Casing		aulic Fracturing		lamation	Well Integrity	
✓ Subsequent Report	Casing Repair		Construction		omplete	✓ Other	
i ge	Change Plans		and Abandon		porarily Abandon	Intermediate Casing Report	
Final Abandonment Notice 13. Describe Proposed or Completed O	Convert to Injection		Back		er Disposal		
04/27/17 MIRU AZ920, 04/28/1	17 NU BOP, PT BOP at 30	000psi/10min.	good test. PT 9-	5/8"csa @	0 1500psi/30min. good	d test. PU MU directional tools. TIH	
w/8-3/4" bit, tag cmt @ 278'. D assbly. Wash & ream. 5/1/17 si needed to 5908'. 5/3/17 RIH w/ Preflush w/10bbls mud, 20bbls	oo cmt, FC & shoe @ 329 tart drilling curve section a /139jts 7" 23# J-55 LTC cs CW & 10bbls FW. Lead a 190bbls Mud. Bump plu	v. Drill ahead of at 4571' and To sg & set @ 584 w/595sx(208b) g @ 01:20hr of good test.	on 8-3/4" hole to D interm hole @ 40' (5245' TVD) v bls, 1168cf) Halc n 05/04/17. Plug	4571', cir 5908' on 9 v/FC @ 5 em Class down @	c hole clean on 4/29/1 5/2/17. TOOH w/bit & 795'. RU Halliburton to G cmt. Tail w/255sx	LD, RIH w/reamer, wash & ream as coment. (59bbls, 331cf) Varicem cmt. Drop Circ 101bbls cmt to surface WOC.	
w/8-3/4" bit, tag cmt @ 278'. D assbly. Wash & ream. 5/1/17 st needed to 5908'. 5/3/17 RIH w/ Preflush w/10bbls mud, 20bbls plug & displace w/38bbls FW & ND BOP, set slips, NU BOP, P' 05/04/17 16:30hr PT 7" csg @1	OC cmt, FC & shoe @ 329 tart drilling curve section a /139jts 7" 23# J-55 LTC cs S CW & 10bbls FW. Lead & 190bbls Mud. Bump plu T BOP at 3000psi/10min, 1500psi for 30mins, good	". Drill ahead of at 4571" and TI sig & set @ 584 w/595sx(208bl g @ 01:20hr or good test.	on 8-3/4" hole to D interm hole @ 40" (5245" TVD) v bis, 1168cf) Halc n 05/04/17. Plug	4571', cir 5908' on 9 v/FC @ 5 em Class down @	c hole clean on 4/29/1 5/2/17. TOOH w/bit & 795'. RU Halliburton to G cmt. Tail w/255sx 01:30hr on 05/04/17. ACCEPTED FOR	7. 4/30/17 TOOH, PU curve LD, RIH w/reamer, wash & ream as a cement. (59bbls, 331cf) Varicem cmt. Drop Circ 101bbls cmt to surface WOC.	
w/8-3/4" bit, tag cmt @ 278'. D assbly. Wash & ream. 5/1/17 st needed to 5908'. 5/3/17 RIH w/ Preflush w/10bbls mud, 20bbls plug & displace w/38bbls FW &	OC cmt, FC & shoe @ 329 tart drilling curve section a /139jts 7" 23# J-55 LTC cs S CW & 10bbls FW. Lead & 190bbls Mud. Bump plu T BOP at 3000psi/10min, 1500psi for 30mins, good	". Drill ahead of at 4571" and TI sig & set @ 584 w/595sx(208bl g @ 01:20hr or good test.	on 8-3/4" hole to D interm hole @ 40" (5245" TVD) v bis, 1168cf) Halc n 05/04/17. Plug	4571', cir. 5908' on 9 v/FC @ 5 em Class g down @	c hole clean on 4/29/1 5/2/17. TOOH w/bit & 795'. RU Halliburton to G cmt. Tail w/255sx 01:30hr on 05/04/17. ACCEPTED FOR	7. 4/30/17 TOOH, PU curve LD, RIH w/reamer, wash & ream as a cement. (59bbls, 331cf) Varicem cmt. Drop Circ 101bbls cmt to surface WOC.	
w/8-3/4" bit, tag cmt @ 278'. D assbly. Wash & ream. 5/1/17 st needed to 5908'. 5/3/17 RIH w/ Preflush w/10bbls mud, 20bbls plug & displace w/38bbls FW & ND BOP, set slips, NU BOP, P' 05/04/17 16:30hr PT 7" csg @1	OC cmt, FC & shoe @ 329 tart drilling curve section a /139jts 7" 23# J-55 LTC cs S CW & 10bbls FW. Lead & 190bbls Mud. Bump plu T BOP at 3000psi/10min, 1500psi for 30mins, good	". Drill ahead of at 4571" and TI sig & set @ 584 w/595sx(208bl g @ 01:20hr or good test.	on 8-3/4" hole to D interm hole @ 40" (5245" TVD) vols, 1168cf) Halon 05/04/17. Plug	4571', cir. 5908' on 9 v/FC @ 5 em Class g down @	c hole clean on 4/29/1 5/2/17. TOOH w/bit & 795'. RU Halliburton to G cmt. Tail w/255sx 01:30hr on 05/04/17. ACCEPTED FOR	7. 4/30/17 TOOH, PU curve LD, RIH w/reamer, wash & ream as o cement. (59bbls, 331cf) Varicem cmt. Drop Circ 101bbls cmt to surface./WOC. RECORD	
w/8-3/4" bit, tag cmt @ 278'. D assbly. Wash & ream. 5/1/17 st needed to 5908'. 5/3/17 RIH w/ Preflush w/10bbls mud, 20bbls plug & displace w/38bbls FW & ND BOP, set slips, NU BOP, P' 05/04/17 16:30hr PT 7" csg @1	true and correct. Name (Pr.	v. Drill ahead of at 4571' and To sig & set @ 584 w/595sx(208b) g @ 01:20hr of good test. MAY 2 inted/Typed)	con 8-3/4" hole to D interm hole @ 40" (5245" TVD) vols, 1168cf) Halcon 05/04/17. Plug	4571', cir 5908' on 5 v/FC @ 5 em Class g down @	c hole clean on 4/29/1 5/2/17. TOOH w/bit & 795'. RU Halliburton to G cmt. Tail w/255sx 01:30hr on 05/04/17. ACCEPTED FOR WAY 182 SARMINGTO HELD BY: 05/08/20	7. 4/30/17 TOOH, PU curve LD, RIH w/reamer, wash & ream as o cement. (59bbls, 331cf) Varicem cmt. Drop Circ 101bbls cmt to surface./WOC. RECORD	
w/8-3/4" bit, tag cmt @ 278'. D assbly. Wash & ream. 5/1/17 st needed to 5908'. 5/3/17 RIH w/ Preflush w/10bbls mud, 20bbls plug & displace w/38bbls FW & ND BOP, set slips, NU BOP, P' 05/04/17 16:30hr PT 7" csg @1	true and correct. Name (Pr.	v. Drill ahead of at 4571' and To sig & set @ 584 w/595sx(208b) g @ 01:20hr of good test. MAY 2 inted/Typed)	con 8-3/4" hole to D interm hole @ 40" (5245" TVD) vols, 1168cf) Halcon 05/04/17. Plug DIV DIST. 2 ZUT/ Regulator Title	4571', cir 5908' on 5 v/FC @ 5 em Class g down @	c hole clean on 4/29/1 5/2/17. TOOH w/bit & 795'. RU Halliburton to G cmt. Tail w/255sx 01:30hr on 05/04/17. ACCEPTED FOR WAY 182 SARMINGTO HELD BY: 05/08/20	7. 4/30/17 TOOH, PU curve LD, RIH w/reamer, wash & ream as o cement. (59bbls, 331cf) Varicem cmt. Drop Circ 101bbls cmt to surface./WOC. RECORD	
w/8-3/4" bit, tag cmt @ 278'. D assbly. Wash & ream. 5/1/17 st needed to 5908'. 5/3/17 RIH w/ Preflush w/10bbls mud, 20bbls plug & displace w/38bbls FW & ND BOP, set slips, NU BOP, P' 05/04/17 16:30hr PT 7" csg @1	true and correct. Name (Pr.	v. Drill ahead of at 4571' and To sig & set @ 584 w/595sx(208b) g @ 01:20hr of good test. MAY 2 inted/Typed)	con 8-3/4" hole to D interm hole @ 40" (5245" TVD) vols, 1168cf) Halcon 05/04/17. Plug DIV DIST. 2 ZUT/ Regulator Title	4571', cir 5908' on 5 v/FC @ 5 em Class g down @	c hole clean on 4/29/1 5/2/17. TOOH w/bit & 795'. RU Halliburton to G cmt. Tail w/255sx 01:30hr on 05/04/17. ACCEPTED FOR MAY 1 8 2 STARMINGTON BY: 05/08/20	7. 4/30/17 TOOH, PU curve LD, RIH w/reamer, wash & ream as o cement. (59bbls, 331cf) Varicem cmt. Drop Circ 101bbls cmt to surface./WOC. RECORD	

(Instructions on page 2)