This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator COF)		Lease	e Name AXI A	Well No14		
ocation of We	ell: Unit	Letter C S	ec 01	Twp 025N	Rge	004W API	# 30-039-21427
	N	lame of Reservoir or Poo	I	Type of Prod		Method of Prod	Prod Medium
Upper Completion	PC		Gas	Gas			Tubing
Lower Completion	MV		Oil	Oil		ial Lift	Tubing
			Pre-Flow S	Shut-In Pressu	ire Data		
Upper Completion		ate, Shut-In 2/2017		Length of Time Shut-In 130 hours		s. PSIG 121	Stabilized?(Yes or No) Yes
Lower Completion	Hour, Da	ate, Shut-In 2/2017	Length	of Time Shut-In	SI Pres	s. PSIG	Stabilized?(Yes or No) Yes
			Flo	w Test No. 1			
Commenced	at:	6/15/2017		Zone Pro	oducing (Upper	or Lower): LO	WER
Time (date/time)		Lapsed Time Since*			Prod Zone		
			Upper zone	Lower zone	Temperature		Remarks
6/15/2017 10:27	:00 AM	10	121	183			
6/15/2017 10:29:45 AM		10	121	55			
6/16/2017 10:25:00 AM		34	121	53			
6/17/2017 10:30:00 AM 58		121	55				
roduction rate	e during t	test					
oil:	BPOD Based on:		Bbls. In	Bbls. In Hrs.		Grav.	GOR
as		MCFPD; Test th	nru (Orifice or M	leter)			
			Mid Toot S	Shut-In Pressu	uro Data		
Upper Completion	Hour, Da	ate, Shut-In		of Time Shut-In		s. PSIG	Stabilized?(Yes or No)
Lower Completion	Hour, Da	ate, Shut-In	Length	Length of Time Shut-In		s. PSIG	Stabilized?(Yes or No)

(Continue on reverse side)

OIL CONS. DIV DIST. 3 JUN 27 2017

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Commenced at:		Zone Producing (Upper or Lower)								
Time	Lapsed Time	PRES	SURE	Prod Zone						
(date/time)	Since*	Upper zone	Lower zone	Temperature	F	Remarks				
Production rate du	uring test									
Oil:B	BPOD Based on:		Hrs.		Grav.	GOR				
Gas	MCFPD; Test thru (Orifice or Meter)									
Remarks:										
I hereby certify that	at the information herein co	ontained is true	and complete	to the best of	my knowledge.					
Approved: 27 June 20 17 Operator: COP										
New Mexico Oil Conservation Division			By:	: Gilbert Lovato						
By: Jam	Title:	Multi-Skilled	Operator							
Title: Deputy Oil & Gas Inspector,				Monday, Jui	ne 26, 2017					
District #3 NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS										

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the
- while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on well: which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3