## NEW MEXICO OIL CONSERVATION DIVISION

This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Page 1

Revised June 10, 2003

Operator \_\_\_\_\_ WPX ENERGY \_\_\_\_\_ Lease Name \_\_Rosa Unit

Well No.<u>117 DK/GL</u>

Location Of Well: Unit Letter D Sec 33 Twp 32N Rge 06W API # 30-0 4526046

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	SAllap	GAS	Flow	Casing
Lower Completion	Do Kayp	GAS	Flow	Tyberry

## **Pre-Flow Shut-In Pressure Data**

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)				
Completion	400 9 pm 4/4/17	15 Doys	Ø					
Lower	Hour, Date, Shut-In,	Length of Time Shut-In	SI Press. Psig	Stabilized? (Tes or No)				
Completion	9AM 4/4/17	15 Davs	794	C				
1. 1. 1.		the second se	· · · · · · · · · · · · · · · · · · ·	S PAGE NO. 8 1				

			Flow To	est No.	1			
Commenced at (hour, date)* $G_{APR} / 4/19/17$ Zo				Zone	Cone producing (Upper or Lower):			
Time	Lapsed Time	Pre	essure		Prod. Zone	Remarks		10
(Hour, Date)	Since*	Upper Compl.	Lower Comp	ol.	Temp.			
9:05 4/14/17 9:10	5 Min	Ø	<b>5</b> 79	¥	NA	Flower	to	Atmospher
9:10 4/9/17	10 mia	Ø	794	/	)	(		
9:15	15 min	Ø	794					
9:20	20 min	Ø	794					
9:25 4/10/17	25 200 min	ø	794			/		
9;30 4/19/17	30 min	ø	794			1		

Production rate during test

Oil:	BOPD	based on	Bbls. In	Hrs	Grav	GOR
Gas:	NA	MCFPD; Test thru (	Orifice or Meter):	=lowed to	Atmosph	L/e

## Mid-Test Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	9 Am 4/4/17	15 days	Ø	2
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	9AM 4/4/17	15 deys	794	
		(Continue on reverse side)	N	

OIL CONS. DIV DIST. 3 APR 2 1 2017

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST Pa Flow Test No. 2							
Commenced	at (hour, date)**		one producing (Upper or Lower): Lower				
Time	Lapsed Time	9;35 AM Pr	essure	Prod. Zone	Remarks	72000	
(Hour, Date)	Since**	Upper Compl.	Lower Comp	l. Temp.			
9.40	5 Min	ø	792	NA	Flowed	Thru	Pipe live
4/19/17	10 MIN	ø	667	´)			
9/19/17	15 min	Ø	583				
9:55 4/19/17	20 min	ø	525			i.	
10:00 4/19/17	25 min	Ø	485				
10.05 4/18/17 Production rate	BO Min	Ø	455				
Production rate	e during test			~~			
Oil:	BOPD based	l on	_Bbls. In	Hrs	Grav.	GC	R
Gas: 14	MCFP	D; Test thru (Ori	tice or Meter):	Mekr -	Pipelin	_	
Remarks: Gn	llup upper 201	ve-Flowed	the Atmusphe	R - DK LOWN	rzone Flo	wed The	In pipelin
I hereby certify	that the informat	ion herein contai	ned is true and	complete to the bes	t of my knowledg	76	
· increasy certify	AO;I	. ^	0	-		1.	
Approved	April 1	7	20//	Operator	WPX CNER.	1	
New Mexico Oil Conservation Division							
Approved <u>April 19</u> 20// Operator <u>WPX Covery</u> New Mexico Oil Conservation Division By <u>Alomua Luchenia</u> <u>By Provid Republic men DR</u> Title <u>Tech</u>							
ilia rillo 2.0							
Title Milling Ville Malle E-mail Address daw 2. roadlemer @ Wer							
				Duto	11.1		Creery Con
Northwest New Mexico Packer Leakage Test Instructions /							

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

DA

2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.

3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.

4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. <u>Note</u>: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).