District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Proposed Alternative Method Permit or Closure Plan Application Type of action: Below grade tank registration Permit of a pit or proposed alternative method
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: Barnes LS 002R
API Number: 3004511317 OCD Permit Number:
U/L or Qtr/Qtr L Section 22 Township 32N Range 11W County: San Juan
Center of Proposed Design: Latitude 36.966904 Longitude -107.980613 NAD: ☐1927 ☐ 1983 Surface Owner: ☐ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no mil Lined Unlined Liner type: Thickness mil LLDPE PVC Other String-Reinforced String-Reinforced Volume: bbl Dimensions: L x W x D
3,
☑ Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A Volume: 95 bbl Type of fluid: Produced water
Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other <u>Single wall/ Double bottom; no visible sidewalls</u> Liner type: Thicknessmil ☐ HDPE ☐ PVC ☐ Other
4. Alternative Method:



Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No							
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image								
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site								
Within 100 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pit Non-low chloride drilling fluid								
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).								
- Topographic map; Visual inspection (certification) of the proposed site	Yes No							
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No							
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Permanent Pit or Multi-Well Fluid Management Pit								
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No							
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of								
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the document of the standard of t								
attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC								
Previously Approved Design (attach copy of design) API Number: or Permit Number:								
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC								
Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC								
Previously Approved Design (attach copy of design) API Number: or Permit Number:								

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Erosion Control Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F. Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Fig. 15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cant Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bell Name (Print): Title:	
Signature: Date:	
Signature: Date:	
Signature: Date:	g the closure report.
Signature:	g the closure report.

22. Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure republished. I also certify that the closure complies with all applicable closure requirement	
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature: Alaus Muu)	Date:June 12, 2017
e-mail address: steven.moskal@bp.com	Telephone:(505) 326-9497

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Barnes LS 002R API No. 300451317 Unit Letter L, Section 22, T32N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

 Notice was provided and is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

- 5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.
 - All equipment associated with the BGT has been removed.
- 6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.020
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.079
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	1250
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for TPH, BTEX and chloride with concentrations of BTEX and chloride below the stated limits. TPH exceed the BGT closure standard and will be addressed via the spill and release guidelines. The field report and laboratory reports are attached.

- 7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicates a release had occurred. TPH exceed the BGT closure standard and will be addressed via the spill and release guidelines. A final C-141 will be submitted at a later date. Attached is a laboratory report and C-141 of the BGT closure activities.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

 Sampling results indicates a release had occurred. TPH exceed the BGT closure standard and will be addressed via the spill and release guidelines. A final C-141 will be submitted at a later date. The location will be reclaimed when the well is plugged and abandoned.
- 10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The location will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The location will be reclaimed when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The location will be reclaimed when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The location will be reclaimed when the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	eation	and Co	rrective A	ction	l					
						OPERA	FOR			al Report	☐ Fin	nal Report		
Name of Co						Contact: Steve Moskal								
		Court, Farmi	ington, N	M 87401		Telephone No.: 505-326-9497								
Facility Na	ne: Barne	s LS 002R				Facility Type: Natural gas well								
Surface Ow	ner: Feder	al		Mineral C	wner: l	Federal			API No	. 30045113	317			
				LOCA	TION	OF REI	EASE							
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/V	Vest Line	County: Sa	an Juan			
L	22	32N	11W	1,500	South		1,190	West						
			Lat	itude <u>36.966</u>	904°	Longitue	le107.980	0613°						
				NAT	URE	OF RELI	EASE							
Type of Rele	ase: none						Release: unknow	/n	Volume F	Recovered: N	J/A			
Source of Re	lease: belov	w grade tank –	- 95 bbl				our of Occurrence	e:	Date and	Hour of Disc	covery: nor	ne		
Was Immedi	ata Matiga (Circan?				none If YES, To	Whom?							
was illilledi	ate Notice (Yes 🗵	No Not Re	equired	11 1 ES, 10	w nom?							
By Whom?						Date and H	our							
Was a Water	course Rea	ched?					lume Impacting t	he Wate	ercourse.					
			Yes 🗵	No		, , , , , , , , , , , , , , , , , , , ,								
If a Watercon	irse was Im	pacted, Descr	ibe Fully.	*										
	below the s	stated limits.		n Taken.* Soil uned the BGT closure										
				ken.* Soil under the BGT closure sta							s of BTEX	and		
regulations a public health should their or or the environ	Il operators or the envi operations h nment. In a	are required to ronment. The nave failed to a	o report are acceptant adequately OCD accept	e is true and comp nd/or file certain r ce of a C-141 repo v investigate and r otance of a C-141	elease no ort by the emediate	otifications are NMOCD m contaminati	nd perform correct arked as "Final Roon that pose a three	etive acti eport" d eat to gr	ons for rele oes not reli ound water	eases which eve the oper , surface wa	may endang ator of liab ter, human	ger bility health		
Signature:	Hous V.	Mey					OIL CONS	SERV	ATION	DIVISIO	<u>N</u>			
Printed Name	e: Steve Mo	skal				Approved by	Environmental S	pecialist	:					
Title: Field E	nvironmen	tal Coordinato	r		1	Approval Dat	e:]	Expiration l	Date:				
E-mail Addre	ess: steven.	moskal@bp.co	om		(Conditions of	Approval:			Attached				
Date: June 12	2, 2017		Phone: 50	5-326-9497										

^{*} Attach Additional Sheets If Necessary

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

April 7, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: BARNES LS 002R

API#: 3004511317

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about April 10, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

Moskal, Steven

From:

Moskal, Steven

Sent:

Monday, April 10, 2017 8:31 AM

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us);

'l1thomas@blm.gov'

Cc:

jeffcblagg@aol.com; blagg_njv@yahoo.com; Powell, Ross L (MBF SERVICES)

Subject:

RE: BP Pit Close Notification - BARNES LS 002R

The BGT is scheduled to be removed at 2:00 PM today.

Thank you,

Steve Moskal

BP Lower 48 – San Juan – Farmington Field Environmental Coordinator Office: (505) 326-9497



This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

From: Buckley, Farrah (CH2M HILL) Sent: Friday, April 07, 2017 11:33 AM

To: Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)

Cc: jeffcblagg@aol.com; blagg njv@yahoo.com; Moskal, Steven

Subject: BP Pit Close Notification - BARNES LS 002R

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

April 7, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

BARNES LS 002R API 30-045-11317 (L) Section 22 – T32N – R11W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around April 10, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

(505) 326-9497

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CHENT: BP	BLAGG EN	NGINEERING, INC.		API#: 3004511	317
CLIENT: DI	· ·	LOOMFIELD, NM 8 5) 632-1199	37413	TANK ID	
			· ·	(if applicble):	<u> </u>
FIELD REPORT:	(circle one): BGT CONFIRMATION /	RELEASE INVESTIGATION / OTHE	:K:	PAGE #:1 o	of
SITE INFORMATION		S LS # 2R		DATE STARTED: 04/1	10/17
QUAD/UNIT: L SEC: 22 TWP:			ST: NM	DATE FINISHED:	
1/4 - 1/4/FOOTAGE: 1,500'S / 1,1		STRIKE		ENVIRONMENTAL	D.
		NTRACTOR: MBF - R. POV	WELL	SPECIALIST(S):	JV
REFERENCE POINT		COORD.: 36.96724 X		201.0	-
95 BGT (SW/DB)	GPS COORD.: 36.9	66904 X 107.980613	DISTANCE/BEAF	RING FROM W.H.: 96', S	14E
2)				RING FROM W.H.:	
3)				RING FROM W.H.:	
	GPS COORD.:		DISTANCE/BEAR	RING FROM W.H.:	OVM
SAMPLING DATA: 1) SAMPLE ID: 5PC - TB @ 5'	CHAIN OF CUSTODY RECORD(S) # 0		201/	5D/9024D/300 0 /CI\	READING (ppm)
					NA
SAMPLE ID:					
	SAMPLE DATE:				
SOIL DESCRIPTION					
SOIL COLOR: MODERATI		PLASTICITY (CLAYS): NON PLASTIC / SL		OHESIVE / MEDIUM PLASTIC / HIGH	HIY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY	COHESIVE COHESIVE / HIGHLY COHESIVE	DENSITY (COHESIVE CLAYS & SILTS			ETTENOTIO
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLY MOIST/ MOIST/ W		HC ODOR DETECTED: YES NO EXP	LANATION -		
SAMPLE TYPE: GRAB COMPOSITE - #	_	ANY AREAS DISPLAYING WETNESS: `	YES NO EXPLAN	IATION -	
DISCOLORATION/STAINING OBSERVED: YES		THE TO STOLE WHITE WELL AND STOLE AN	TEO [NO] EX EX		
SITE OBSERVATION					
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:			N/E-CDADE TAN	NK TO BE SET ATOD BOT I	OCATION
OTHER: NMOCD OR BLM REPS. NOT PR	RESENT TO WITNESS CONFIRMAT	TION SAMPLING.	OVE-GRADE IAN	NK TO BE SET ATOP BGT L	LOCATION.
SOIL IMPACT DIMENSION ESTIMATION:	NAftXNA	ft. X NA ft. E	XCAVATION EST	TMATION (Cubic Yards) :	NA
. 4001	EAREST WATER SOURCE: >1,000'			D TPH CLOSURE STD: 1,0	
SITE SKETCH	BGT Located: off on site	PLOT PLAN circle:	attached 0\/M	CALIB. READ. = NA pp	m pr-0.50
	то			CALIB. GAS = NA pp	111 0.02
	w.H.		N TIME:		NA
	COMPRESS	SOR		MISCELL. NO	TES
SEPARATOR			l w	/O:	
PBG	PR	OD. NK	RI	EF#: P-678	
T.B. ~	-5' - (x x x)	STEEL	VI	D: VHIXONEVB2	
B.G		CONTAINMENT		J#:	4140
		RING		ermit date(s): 06/14	
FEN	NCE		Tan		ter
	BERM		A A	The second second	N)
		V	S.P.D.	BGT Sidewalls Visible: Y /	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	ON DEPRESSION; B.G. = BELOW GRADE; B = BEI			BGT Sidewalls Visible: Y /	N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	OW-GRADE TANK LOCATION; SPD = SAMPLE PC E WALL; DW - DOUBLE WALL; SB - SINGLE BOTT	DINT DESIGNATION; R.W. = RETAINING WALL		agnetic declination: 10	°E
NOTES: GOOGLE EARTH IMAGE		ONSITE: 04/10/17			

Analytical Report

Lab Order 1704364

Date Reported: 4/12/2017

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (95)

Project: BARNES LS #2R

Collection Date: 4/10/2017 2:15:00 PM

Lab ID: 1704364-001

Matrix: SOIL

Received Date: 4/11/2017 7:15:00 AM

Analyses	Result	PQL (Qual	Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS						Analys	t: MRA
Chloride	ND	30		mg/Kg	20	4/11/2017 10:43:26 AM	1 31182
EPA METHOD 8015M/D: DIESEL RANG	E ORGANICS	3				Analys	t: TOM
Diesel Range Organics (DRO)	150	92		mg/Kg	10	4/11/2017 2:57:58 PM	31175
Motor Oil Range Organics (MRO)	1100	460		mg/Kg	10	4/11/2017 2:57:58 PM	31175
Surr: DNOP	0	70-130	S	%Rec	10	4/11/2017 2:57:58 PM	31175
EPA METHOD 8015D: GASOLINE RAN	GE					Analys	t: NSB
Gasoline Range Organics (GRO)	ND	4.0		mg/Kg	1	4/11/2017 10:11:19 AM	1 31164
Surr: BFB	108	54-150		%Rec	1	4/11/2017 10:11:19 AM	1 31164
EPA METHOD 8021B: VOLATILES						Analys	: NSB
Benzene	ND	0.020		mg/Kg	1	4/11/2017 10:11:19 AM	1 31164
Toluene	ND	0.040		mg/Kg	1	4/11/2017 10:11:19 AM	31164
Ethylbenzene	ND	0.040		mg/Kg	1	4/11/2017 10:11:19 AM	31164
Xylenes, Total	ND	0.079		mg/Kg	1	4/11/2017 10:11:19 AM	31164
Surr: 4-Bromofluorobenzene	120	66.6-132		%Rec	1	4/11/2017 10:11:19 AM	31164

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

U	ain-c	T-Cus	toay kecora			SAME		,	1	Н	ALL	F	NV	TE	20	M	4F	NT	ΆΙ		
Client:	BLAG	G ENGR.	/ BP AMERICA	☐ Standard	☑ Rush _	DAY)	_		\exists		IAN										
				Project Name															,,,		
Mailing A	ddress:	P.O. BO	X 87	BARNES LS # 2R 4901 Hawkins NE - Albuquerque, NM 87109																	
		BLOOM	FIELD, NM 87413	Project #:	74					5-345			Fax								
Phone #:		(505) 63	2-1199			X						ysis					1 = 1 (2)	10	: :-:	m	
email or F	ax#:			Project Manag	ger:						Т		-				न	T			
QA/QC Pa	_		Level 4 (Full Validation)		NELSON V	ELEZ	(8021B)	+ TPH (Gas only)	/ MRO)		(S)		PO4, SO.	PCB's			water - 300.1)			a)	
Accreditat	ion:			Sampler:	NELSON V	ELEZ ny	% %	(Ga	DRO	7	SIN		102,	8082			_			sample	
□ NELAP)	□ Other		Married Residential Committee of Association Property and Association Property and Association (Association (/⊼/Yes//	i⊡ No/i i i i i i i i i i i i i i i i i i i	*	TPH	_	418.	8270SIMS)		03,1	-		(A)	300.0			e sa	N J
□ EDD (T	ype)			Sample Temp	apere : //	<u>United to the second of the s</u>	4	BE +	(GR	pot		etal	CI,N	cide	(A)	i-VC	1		e .	osit	7
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	- HEAL No.	BTEX +-MF	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	PAH (8310 or	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil		ap.	5 pt. composite	Air Bubbles (Y or N)
4/10/17	1415	SOIL	5PC-TB@ 5'(95)	4 oz 1	Cool	701	٧		٧								٧		1	٧	
																		-	+	+	_
	,																		#		
																		1	+	+	
																		\pm	+	+	
			-				Н			+	+	\vdash				Н	\dashv	+	+	+	\dashv
Date:, 4/0/17	Time:	Relinquishe	le J	Received by:	I.A.	Date Time 41017 (710		arks		BILL DIF	RENCE #	WHE	N APP	LICAE	BLE;		лтн со	ORRES	POND	ING	VID
Date:	Time: 1840	Relinquishe	ed by:	Received by:	m	Date Time	Refe	eren	VID: ce #	VHIXO P	- 678	2					on the	analytik	al ren	oort.	

Hall Environmental Analysis Laboratory, Inc.

WO#:

1704364

12-Apr-17

Client:

Blagg Engineering

Project:

BARNES LS #2R

Sample ID MB-31182

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 31182

1.5

1.5

RunNo: 42023

Prep Date: 4/11/2017

Analysis Date: 4/11/2017

SeqNo: 1320834

Units: mg/Kg HighLimit

Analyte Result **PQL**

Sample ID LCS-31182

SPK value SPK Ref Val %REC LowLimit

TestCode: EPA Method 300.0: Anions

LCSS

Batch ID: 31182

SampType: Ics

RunNo: 42023

Prep Date: 4/11/2017

Analysis Date: 4/11/2017

SeqNo: 1320835

Units: mg/Kg

%RPD **RPDLimit**

RPDLimit

%RPD

Qual

Qual

PQL

15.00

96.1

Client ID:

Chloride

14

ND

HighLimit

Chloride

SPK value SPK Ref Val %REC

LowLimit

110

Qualifiers:

S

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix D

H Holding times for preparation or analysis exceeded

% Recovery outside of range due to dilution or matrix

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

E

Analyte detected in the associated Method Blank

Analyte detected below quantitation limits

P Sample pH Not In Range

RL Reporting Detection Limit Sample container temperature is out of limit as specified

Value above quantitation range Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1704364 12-Apr-17

Client:

Blagg Engineering

Project:

BARNES LS #2R

Sample ID LCS-31157

SampType: LCS

TestCode: EPA Method 8015M/D: Diesel Range Organics

Client ID:

LCSS

Batch ID: 31157

RunNo: 42017

Prep Date: 4/10/2017

Analysis Date: 4/11/2017 Result

5.1

%REC

LowLimit

70

70

Units: %Rec

Analyte

POL

SeqNo: 1319773

102

130

HighLimit

RPDLimit

Qual

Surr: DNOP

Sample ID LCS-31175

SampType: LCS

RunNo: 42017

TestCode: EPA Method 8015M/D: Diesel Range Organics

%RPD

%RPD

Client ID:

LCSS

Batch ID: 31175

Prep Date: Analyte

4/11/2017

Analysis Date: 4/11/2017

SeqNo: 1319774

Units: mg/Kg

Qual

Diesel Range Organics (DRO)

Result PQL 50

SPK value SPK Ref Val

HighLimit

Surr: DNOP

5.1

10 50.00 5.000 %REC LowLimit 99.4 101

63.8 116 **RPDLimit**

Sample ID MB-31157

SampType: MBLK

TestCode: EPA Method 8015M/D: Diesel Range Organics

%RPD

Client ID: Prep Date: 4/10/2017

PBS

Batch ID: 31157

Analysis Date: 4/11/2017

RunNo: 42017 SeqNo: 1319775

Units: %Rec

130

130

Analyte Surr: DNOP

Result

SPK value SPK Ref Val 10.00

SPK value SPK Ref Val

SPK value SPK Ref Val

5.000

%REC LowLimit 110

HighLimit

%RPD **RPDLimit** Qual

Sample ID MB-31175

PBS

SampType: MBLK

TestCode: EPA Method 8015M/D: Diesel Range Organics RunNo: 42017

%REC

70

Analyte

Surr: DNOP

Client ID:

Prep Date: 4/11/2017

Batch ID: 31175 Analysis Date: 4/11/2017

POL

SeqNo: 1319776

Units: mg/Kg HighLimit

RPDLimit

Qual

Page 3 of 5

Diesel Range Organics (DRO) Motor Oil Range Organics (MRO)

ND 10 ND 50 11

Result

10.00

111

70

LowLimit

130

Oualifiers:

H

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- ND Not Detected at the Reporting Limit R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix

Holding times for preparation or analysis exceeded

- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range

Reporting Detection Limit

RL

Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1704364 12-Apr-17

Client:

Blagg Engineering

Project:

BARNES LS #2R

Sample ID MB-31164

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

PBS

Batch ID: 31164

RunNo: 42032

%REC

Prep Date: 4/10/2017

Analysis Date: 4/11/2017

PQL

5.0

SeqNo: 1320307 Units: mg/Kg

LowLimit

Analyte Gasoline Range Organics (GRO)

Surr: BFB

ND 900

Result

1000

SPK value SPK Ref Val

SPK value SPK Ref Val

90.4

HighLimit

%RPD

RPDLimit

Qual

Sample ID LCS-31164 Client ID: LCSS

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

%REC

0

RunNo: 42032

54

Prep Date: 4/10/2017

Batch ID: 31164 Analysis Date: 4/11/2017

PQL

SeqNo: 1320310

Units: mg/Kg

150

HighLimit %RPD **RPDLimit** Qual

Analyte Gasoline Range Organics (GRO) Surr: BFB

Result 23 980

5.0 25.00 1000 93.2 97.9

76.4 54

LowLimit

125 150

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix D

Holding times for preparation or analysis exceeded H

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

% Recovery outside of range due to dilution or matrix S

Analyte detected in the associated Method Blank

Value above quantitation range E

J Analyte detected below quantitation limits

Sample pH Not In Range

RL Reporting Detection Limit Sample container temperature is out of limit as specified Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1704364

12-Apr-17

Client: Project:

Blagg Engineering BARNES LS #2R

Sample ID MB-31164 SampType: MBLK TestCode: EPA Method 8021B: Volatiles Client ID: **PBS** Batch ID: 31164 RunNo: 42032 Prep Date: 4/10/2017 Analysis Date: 4/11/2017 SeqNo: 1320337 Units: mg/Kg PQL SPK value SPK Ref Val %REC LowLimit Analyte Result HighLimit %RPD **RPDLimit** Qual ND 0.025 Benzene ND 0.050 Toluene Ethylbenzene ND 0.050 ND Xylenes, Total 0.10 Surr: 4-Bromofluorobenzene 1.1 1.000 113 66.6 132

Sample ID LCS-31164	SampType: LCS TestCode: EPA Method 8021B: Volatiles									
Client ID: LCSS	Batch	n ID: 31	164	F	RunNo: 4	2032				
Prep Date: 4/10/2017	Analysis D	ate: 4/	11/2017							
Analyte	Result	Result PQL SPK value SPK Ref Val %REC LowLin						%RPD	RPDLimit	Qual
Benzene	1.1	0.025	1.000	0	112	80	120			
Toluene	1.0	0.050	1.000	0	102	80	120			
Ethylbenzene	1.0	0.050	1.000	0	101	80	120			
Xylenes, Total 2.8 0.10 3.000 0 93.2 80 120										
Surr: 4-Bromofluorobenzene	1.1		1.000		114	66.6	132			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Numbe	r: 1704364		RcptNo:	1
Received By: Anne Thorn	ne 4/11/2017 7:15:00 AN	4	anne Man	_	
Completed By: Anne Thorn	ne 4/11/2017 7:52:17 AN	4	an Ilm		
Reviewed By:	E 04/11/17		ame from		
Chain of Custody					
1. Custody seals intact on sample bottles?		Yes	No 🗌	Not Present	
2. Is Chain of Custody complete?		Yes 🗹	No .	Not Present	
3. How was the sample delivered?		Courier			
<u>Log In</u>					
4. Was an attempt made to cool the samples?		Yes 🗹	No 🗌	NA 🗔	
5. Were all samples received at a temperature of >0° C to 6.0°C		Yes 🗹	No 🗆	NA 🗆	
6. Sample(s) in proper container(s)?		Yes 🗹	No 🗌		
7. Sufficient sample volume for indicated test(s)?		Yes 🗹	No 🗆		
8. Are samples (except VOA and ONG) properly preserved?		Yes 🗸	No 🗌		
9. Was preservative added to bottles?		Yes	No 🗹	NA 🗆	
10. VOA vials have zero headspace?		Yes 🗌	No 🗌	No VOA Vials	
11. Were any sample containers received broken?		Yes	No 🗹	# of preserved	
10 -			N:	bottles checked	
12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)		Yes 🗹	No L	for pH:(<2 or	>12 unless noted)
13. Are matrices correctly identified on Chain of Custody?		Yes 🗸	No 🗆	Adjusted?	
14. Is it clear what analyses were requested?		Yes 🗸	No 🗌		
15. Were all holding times able to be met? (If no, notify customer for authorization.)		Yes 🗹	No 🗆	Checked by:	
(****, *****, *************************	,				
Special Handling (if app	licable)				
16. Was client notified of all discrepancies with this order?		Yes	No 🗆	NA 🗹	
Person Notified:	Date	CALINGA ANACHSTERNA (A Francisco Anachsterna (A CALINGA ANACHST ANACHS			
By Whom:	Via:	eMail	Phone 🗌 Fax	☐ In Person	
Regarding:					
Client Instructions:					
17. Additional remarks:					
18. Cooler Information Cooler No Temp °C Condition Seal Intact Seal No Seal Date Signed By 1 1.0 Good Yes					



