District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name: Sellers LS 005
API Number: 3004560208 OCD Permit Number:
U/L or Qtr/Qtr M Section 30 Township 30N Range 10W County: San Juan
Center of Proposed Design: Latitude 36.77816 Longitude -107.93101 NAD: ☐1927 ☐ 1983 Surface Owner: ☐ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary:
3.
☑ Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A Volume: 95 bbl Type of fluid: Produced water
Tank Construction material: Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other Single wall/ Double bottom; no visible sidewalls
Liner type: Thicknessmil HDPE PVC Other
4. Alternative Method:

22

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,	
or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
 initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the document of the standard of the following items must be attached to the application.	
attached. ☐ Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC ☐ Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	cuments are
☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ A List of wells with approved application for permit to drill associated with the pit. ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC ☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

12.	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
 □ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC □ Quality Control/Quality Assurance Construction and Installation Plan □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC 	
☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Wester Street Characterisation	
☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal	luid Management Pit
☐ Waste Removal (Closed-loop systems only)☐ On-site Closure Method (Only for temporary pits and closed-loop systems)	
☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believes	ief.
Name (Print):	
D-to-	
Signature: Date:	
e-mail address:	
	1/2017
e-mail address: Telephone:	the closure report.
e-mail address: Telephone:	the closure report.
e-mail address: Telephone:	the closure report.

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rep belief. I also certify that the closure complies with all applicable closure requirement	
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature: Slaw Mix	Date: June 13, 2017
e-mail address: steven.moskal@bp.com	Telephone: (505) 326-9497

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Sellers LS 005 <u>API No. 3004560208</u> Unit Letter M, Section 30, T30N, R10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

 Notice was provided and is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.023
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.091
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<47
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for TPH, BTEX and chloride with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicates no release had occurred. Attached is a laboratory report and C-141.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicates no release had occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The location will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The location will be reclaimed when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The location will be reclaimed when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The location will be reclaimed when the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141

			Rele	ease Notific	cation	n and Co	orrective A	ction						
						OPERA'	ГOR	☐ In	tial Report	\boxtimes	Final Report			
Name of Co	ompany: B	P				Contact: Steve Moskal								
Address: 200 Energy Court, Farmington, NM 87401						Telephone No.: 505-326-9497								
Facility Nar	me: Sellers	LS 005				Facility Typ	e: Natural gas v	vell						
Surface Owner: Federal Mineral Owner:						Federal		API	lo. 3004560	208				
				LOCA	TIO	N OF RE	LEASE							
Unit Letter M	Section 30	Township 30N	Range 10W	Feet from the 890	North South	South Line	Feet from the 890	East/West Line West	County: S	an Juan	1			
			La	titude36.77	816°	Longitue	de107.931	01°						
				NAT	URE	OF REL	EASE							
Type of Rele						Volume of	Release: unknow	n Volum	Recovered:	N/A				
Source of Re	lease: belov	w grade tank –	95 bbl			Date and H	lour of Occurrence	e: Date ar	d Hour of Dis	scovery:	: none			
Was Immedia	ate Notice (v	IN DAID	. ,	If YES, To	Whom?							
D W/I 0			Yes 🔀	No Not Re	equired	D . 11								
By Whom? Was a Water	course Reac	shed?				Date and H	lour lume Impacting ti	ha Wataraauraa						
was a water	course reac		Yes 🛚	No		11 1125, VC	nume impacting t	ne watercourse.						
If a Watercou	irse was Im	pacted, Descri	be Fully.*											
							the BGT was don	ne during remov	l. Soil analys	sis resul	ted for TPH,			
BTEX and ch	ilorides belo	ow BGT closu	re standar	ds. Field reports	and labo	oratory results	are attached.							
Describe Are	a Affected a	and Cleanup A	Action Tak	en.* No further a	ction ne	cessary. Fina	l laboratory analy	sis determined i	o remedial ac	tion is r	required.			
I hereby certi	fy that the i	nformation gi	ven above	is true and comp	lete to the	he best of my	knowledge and un	nderstand that p	rsuant to NM	IOCD rı	ules and			
regulations al	ll operators	are required to	report an	d/or file certain re	elease n	otifications ar	nd perform correct	tive actions for a	eleases which	may en	ndanger			
public health	or the envir	ronment. The	acceptance	e of a C-141 repo	rt by the	e NMOCD m	arked as "Final Re	eport" does not r	elieve the ope	rator of	liability			
or the environ	operations n	ddition NMO	CD accen	tance of a C-141	emediat	e contaminati	on that pose a three the operator of r	eat to ground wa	er, surface w	ater, hui	man health			
federal, state,	or local lay	ws and/or regu	lations.	tance of a C-141	report d	oes not renev	e the operator of i	esponsionity for	compilance	with any	other			
							OIL CONS	SERVATIO	N DIVISIO	ON				
Signature:	Mus	nu)												
Printed Name	e: Steve Mo	skal				Approved by	Environmental Sp	pecialist:						
Title: Field E	nvironment	al Coordinato	r			Approval Dat	e:	Expiratio	n Date:					
E-mail Addre	ess: steven.n	noskal@bp.co	m			Conditions of	Approval:		Attach					
Date: June 13	2017	1	Phone: 504	5-326-9497					Attached _					
Date. Julie 13		, ICNI	none. Jul	7-340-747/										

^{*} Attach Additional Sheets If Necessary

Moskal, Steven

From:

Moskal, Steven

Sent:

Wednesday, April 12, 2017 2:10 PM

To:

Smith, Cory, EMNRD

Cc:

Fields, Vanessa, EMNRD; l1thomas@blm.gov; Powell, Ross L (MBF SERVICES);

jeffcblagg@aol.com; blagg_njv@yahoo.com; Hixon, Vance E

Subject:

Re: Sellers LS 005 BGT Closure

We will plan to sample around 11:30 tomorrow morning.

Thank you,

Steve Moskal Field Environmental Coordinator BP San Juan South Cell: (505) 330-9179

Sent from my mobile device

On Apr 12, 2017, at 1:31 PM, Smith, Cory, EMNRD < Cory. Smith@state.nm.us> wrote:

Steve,

One of us could probably make it sometimes after 11:00. We have a meeting in the morning and I'm not sure how long it will go for.

Cory Smith
Environmental Specialist
Oil Conservation Division
Energy, Minerals, & Natural Resources
1000 Rio Brazos, Aztec, NM 87410
(505)334-6178 ext 115
cory.smith@state.nm.us

From: Moskal, Steven [mailto:Steven.Moskal@bp.com]

Sent: Wednesday, April 12, 2017 12:59 PM

To: Smith, Cory, EMNRD < Cory.Smith@state.nm.us >; Fields, Vanessa, EMNRD < Vanessa.Fields@state.nm.us >; 'l1thomas@blm.gov' < l1thomas@blm.gov >

Cc: Powell, Ross L (MBF SERVICES) < Ross.Powell@bp.com >; jeffcblagg@aol.com; blagg njv@yahoo.com;

Hixon, Vance E < <u>Vance.Hixon@bp.com</u>> **Subject:** Sellers LS 005 BGT Closure

All,

The BGT located on site was removed from service and backfilled, outside of NMAC 19.15.17 requirements for sampling during closure. These activities were performed outside of BP's BGT compliance group and was recently brought to our attention. While BP understands the regulation, this is an unfortunate mistake on our part.

BP proposes to immediately sample the BGT location for closure. If possible, we would like to schedule this work for tomorrow, mid-morning. All equipment in the area will be removed and a backhoe will be used to sample the former BGT location for closure. Please let me know if you approve.

Below is the link for the approved BGT permit for your reference.

http://ocdimage.emnrd.state.nm.us/lmaging/FileStore/aztec/wf/302745/30045602080000 47 wf.pdf

API Number: 30-045-60208 ULSTR: M-30-30N-10W

My apologies and thank you,

Steve Moskal

BP Lower 48 – San Juan – Farmington Field Environmental Coordinator Office: (505) 326-9497 Cell: (505) 330-9179 <image001.jpg>

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	P.O. BOX 87, B	NGINEERING, INC LOOMFIELD, NM 8 5) 632-1199		API#: 3004560 TANK ID (if applicble): A	
FIELD REPORT:	(circle one): BGT CONFIRMATION	RELEASE INVESTIGATION / OTH	ER:	PAGE #: 1 o	f 1
SITE INFORMATION	I: SITE NAME: SELLER	RS LS #5		DATE STARTED: 04/1	13/17
QUAD/UNIT: M SEC: 30 TWP:	30N RNG: 10W PM:	NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 890'S / 890'\ LEASE #: SF078195	N SW/SW LEASE T	YPE: FEDERAL STATE / FE		ENVIRONMENTAL SPECIALIST(S):	JV
REFERENCE POINT		COORD.: 36.77805		GL ELEV.: 6	040'
	GPS COORD.: 36			RING FROM W.H.: 71', N	
2)		.77010 X 107.00101			
3)				RING FROM W.H.:	
	GPS COORD.:			RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # C		DIGINIODELA	WHO I HOW WELL.	OVM READING
3AIVIPLING DATA. 1) SAMPLE ID: 5PC - TB @ 6'				5B/8021B/300 0 (CI)	(ppm)
					0.0
2) SAMPLE ID:					
3) SAMPLE ID:	SAMPLE DATE:				
SOIL DESCRIPTION					
SOIL COLOR: DARK YELLON COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LO MOISTURE: DRY / SLIGHTLY MOIST / WOIST / W SAMPLE TYPE: GRAB (COMPOSITE) # DISCOLORATION/STAINING OBSERVED: YES	Y COHESIVE / COHESIVE / HIGHLY COHESIVE DOSE (FIRM) DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED # OF PTS5	PLASTICITY (CLAYS): NON PLASTIC / S DENSITY (COHESIVE CLAYS & SIL' HC ODOR DETECTED: YES NO EX ANY AREAS DISPLAYING WETNESS:	TS): SOFT / FIRM / PLANATION -	STIFF / VERY STIFF / HARD	
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: [OTHER: NMOCD REP. NOT PRESENT TO	LOST INTEGRITY OF EQUIPMENT ED AND/OR OCCURRED: YES NO EXPLANATION - 105 BB	ANATION:	OVE-GRADE TAI	NK TO BE SET ATOP BGT L	OCATION.
SOIL IMPACT DIMENSION ESTIMATION:	NAftXNA	ft. X NA ft. E	EXCAVATION EST	IMATION (Cubic Yards) :	NA
DEPTH TO GROUNDWATER: <100	EAREST WATER SOURCE: >1,000	NEAREST SURFACE WATER:	<1,000' NMOC	D TPH CLOSURE STD:10	00 ppm
SITE SKETCH	BGT Located: off on sit	e PLOT PLAN circle:	attached 0VM	CALIB. READ. = 100.0 pp	m RF =0.52
			A .	CALIB. GAS = 100 pp	14 -0.02
			N TIME	11:40 am/pm DATE: 0	4/13/17
	PROTI		· '' =	MISCELL. NO	TES
FENCE	PBGTL T.B. ~ 5'		l w	/O:	LO
	B.G.		_	EF #: P - 847	
BERM-			1 -	D: VHIXONEVB2	
			P.	J#:	
			Pe	ermit date(s): 06/0	3/10
				CD Appr. date(s): 04/0	
		⊕ w. H.	Tan	ppm = parts per million	
		*****	Α		
		χ.	- S.P.D.	BGT Sidewalls Visible: Y /	
	ON DEPRESSION; B.G. = BELOW GRADE; B = BI .OWGRADE TANK LOCATION; SPD = SAMPLE F E WALL; DW - DOUBLE WALL; SB - SINGLE BOT	POINT DESIGNATION; R.W. = RETAINING WAL		BGT Sidewalls Visible: Y / lagnetic declination: 10	o°E
NOTES: GOOGLE FARTH IMAG	ERY DATE: 3/15/2015	ONSITE: 04/13/17			

Analytical Report

Lab Order 1704614

Date Reported: 4/17/2017

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB@6' (95)

Project: SELLERS LS 5

Collection Date: 4/13/2017 11:35:00 AM

Lab ID: 1704614-001

Matrix: MEOH (SOIL) Received Date: 4/14/2017 7:15:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	LGT
Chloride	ND	30	mg/Kg	20	4/14/2017 1:36:04 PM	31249
EPA METHOD 8015M/D: DIESEL RAN	GE ORGANICS	6			Analyst	TOM
Diesel Range Organics (DRO)	ND	9.4	mg/Kg	1	4/14/2017 10:48:25 AM	31239
Motor Oil Range Organics (MRO)	ND	47	mg/Kg	1	4/14/2017 10:48:25 AM	31239
Surr: DNOP	108	70-130	%Rec	1	4/14/2017 10:48:25 AM	31239
EPA METHOD 8015D: GASOLINE RAN	IGE				Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.6	mg/Kg	1	4/14/2017 10:25:16 AM	31227
Surr: BFB	89.8	54-150	%Rec	1	4/14/2017 10:25:16 AM	31227
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.023	mg/Kg	1	4/14/2017 10:25:16 AM	31227
Toluene	ND	0.046	mg/Kg	1	4/14/2017 10:25:16 AM	31227
Ethylbenzene	ND	0.046	mg/Kg	1	4/14/2017 10:25:16 AM	31227
Xylenes, Total	ND	0.091	mg/Kg	1	4/14/2017 10:25:16 AM	31227
Surr: 4-Bromofluorobenzene	107	66.6-132	%Rec	1	4/14/2017 10:25:16 AM	31227

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

CH	nain-	of-Cus	stody Record	Turn-Around	Time:	SAME				н	IAI		F	NV	/TE	20	NE	VI E	NT	AL	
Client	BLAG	G ENGR.	/ BP AMERICA	Standard Project Name	Rush _	DAY	Ī	3		A	N	AL	YS	515	S L	A		RA	TC	100	
Mailing A	ddress:	P.O. BO	X 87		SELLERS LS	#5		490	01 H	awki									9		
***		BLOOM	FIELD, NIM 87413	Project #:						5-34					-		410				
Phone #:		(505) 63	2-1199				1						nal	ysīs	Rec	ques	st				
email or F	ax#:			Project Mana	ger:		- 1					1.4	4 1	4)			1	(1)		T	T
QA/QC Pa			Level 4 (Full Validation)		NELSON VI	ELEZ	WB/S (8021B)	(kluo s	/ MRO)			(S)		PO4,SO	PCB's			water - 300.1)		0	U
Accreditat	ion:			Sampler:	NELSON VI	ELEZ 977	*	Ga	SRO	F	=	SIN		0	808			1 wa		E	1
□ NELAP		☐ Other		On Ice:	And the second s	□No	#	TPH	70	418	200	827	16	8	15		JA.	000		0	S Z
EDD (T	ype)			Sample Temp	erature: 1.8		1	3E +	GR	po	po	0	etal	N,	cide	F	j-K	- 170		ole per	3 2
Date	Time	Metrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO. 1704614	BTEX ME	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO / MRO)	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.07		Grab sample	Air Bubbles (Yor N)
4/13/17	1135	SOIL	5PC-TB @ 6 (95)	4021	Cool	-001	٧		٧						-	-		٧		V	-
																					T
-								-													T
		-																			
																		_		1	
										1				- 1				- 1			
				A THE STATE OF THE										1							
							J# 13							- 1		-			1		
				P				-				- 4		57 H			-			11 5	
Date: 4/13/17	Time:	Relinquishe Relinquishe	he of	Received by Received by	els i	Date Time	1 12/2	ONTA	CT:	& REF	ERENS	DSK	AL/	LAPP	LICAR	LE		ITH C	ORRESE	ONDU	IGVID
4/13/17	1900	M	MALLS milited to Hall Environmental may be su	(4)	accredited laboratorie	14/17 07/5	-	eren	e#	_	P-8	47		will b	e cles	arty ng	tated o	in the	analytic	al rebo	ert.

Hall Environmental Analysis Laboratory, Inc.

WO#:

1704614

17-Apr-17

Client:

Blagg Engineering

Project:

SELLERS LS 5

Sample ID MB-31249

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 31249

RunNo: 42127

Units: mg/Kg

Analyte

Prep Date: 4/14/2017

Analysis Date: 4/14/2017

SeqNo: 1323689

Qual

Client ID:

Result PQL 1.5

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD

RPDLimit

Chloride

ND

Sample ID LCS-31249

SampType: LCS

PQL

RunNo: 42127

TestCode: EPA Method 300.0: Anions

Prep Date:

LCSS

Batch ID: 31249

Units: mg/Kg

SeqNo: 1323690

Analyte

4/14/2017

Analysis Date: 4/14/2017

SPK value SPK Ref Val %REC

97.8

LowLimit 90

HighLimit

RPDLimit

Page 2 of 5

Qual

Chloride

Result

1.5

15.00

0

%RPD

15

110

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit R

RPD outside accepted recovery limits % Recovery outside of range due to dilution or matrix Analyte detected in the associated Method Blank

Value above quantitation range J Analyte detected below quantitation limits

P Sample pH Not In Range

Reporting Detection Limit

Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#: 1704614

17-Apr-17

Client:

Blagg Engineering

Project: SELLEI	RS LS 5								
Sample ID LCS-31239	SampType: LCS	TestCode: EPA Method 8015M/D: Diesel Range Organics							
Client ID: LCSS	Batch ID: 31239	RunNo: 42111							
Prep Date: 4/14/2017	Analysis Date: 4/14/2017	SeqNo: 1323040 Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qua	al						
Diesel Range Organics (DRO)	49 10 50.00	0 98.3 63.8 116							
Surr: DNOP	5.0 5.000	99.7 70 130							
Sample ID MB-31239 SampType: MBLK TestCode: EPA Method 8015M/D: Diesel Range Organics									
Client ID: PBS	Batch ID: 31239 RunNo: 42111								
Prep Date: 4/14/2017	Analysis Date: 4/14/2017	SeqNo: 1323041 Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qua	al						
Diesel Range Organics (DRO)	ND 10								
Motor Oil Range Organics (MRO)	ND 50								
Surr: DNOP	10 10.00	101 70 130							
Sample ID MB-31231	SampType: MBLK	TestCode: EPA Method 8015M/D: Diesel Range Organics							
Client ID: PBS	Batch ID: 31231	RunNo: 42111							
Prep Date: 4/13/2017	Analysis Date: 4/14/2017	SeqNo: 1323371 Units: %Rec							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qua	al						
Surr: DNOP	11 10.00	107 70 130							
Sample ID LCS-31231	SampType: LCS	TestCode: EPA Method 8015M/D: Diesel Range Organics							
Client ID: LCSS	Batch ID: 31231	RunNo: 42111							
Prep Date: 4/13/2017	Analysis Date: 4/14/2017	SeqNo: 1323398 Units: %Rec							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qua	al						
Surr: DNOP	5.0 5.000	99.7 70 130							

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- Holding times for preparation or analysis exceeded H
- Not Detected at the Reporting Limit ND
- R RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1704614

17-Apr-17

Client:

Blagg Engineering

Project:

SELLERS LS 5

Sample ID MB-31227	SampT	ype: ME	BLK	TestCode: EPA Method 8015D: Gasoline Range						
Client ID: PBS	Batch	1D: 31	227	R	tunNo: 4	2121				
Prep Date: 4/13/2017	Analysis D	ate: 4/	14/2017	S	eqNo: 1	323585	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	910		1000		91.3	54	150			

Sample ID LCS-31227	SampT	ype: LC	S	Test	tCode: El	PA Method	8015D: Gaso	oline Rang	е	
Client ID: LCSS	Batch	ID: 31	227	R	RunNo: 4	2121				
Prep Date: 4/13/2017	Analysis D	ate: 4/	14/2017	S	SeqNo: 1	323586	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	25	5.0	25.00	0	101	76.4	125			
Surr: BFB	1000		1000		100	54	150			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
 - d below qualititation mints
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1704614

17-Apr-17

Client:

Blagg Engineering

Project:

SELLERS LS 5

Sample ID MB-31227	SampT	уре: МЕ	BLK	Tes							
Client ID: PBS	Batch	h ID: 31:	227	F	RunNo: 4						
Prep Date: 4/13/2017	Analysis Date: 4/14/2017			8	SeqNo: 1	323630	Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	ND	0.025									
Toluene	ND	0.050									
Ethylbenzene	ND	0.050									
Xylenes, Total	ND	0.10									
Surr: 4-Bromofluorobenzene	1.1		1.000		112	66.6	132				
Sample ID LCS-31227	Sample ID LCS-31227 SampType: LCS TestCode: EPA Method 8021B: Volatiles										
Client ID: LCSS	Batch	h ID: 31	227	RunNo: 42121							

Sample ID LCS-31227	Sample ID LCS-31227 SampType: LCS					TestCode: EPA Method 8021B: Volatiles						
Client ID: LCSS	Batch ID: 31227				RunNo: 42121							
Prep Date: 4/13/2017	Date: 4/13/2017 Analysis Date: 4/14/2017			S	eqNo: 1							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	1.1	0.025	1.000	0	113	80	120					
Toluene	1.0	0.050	1.000	0	104	80	120					
Ethylbenzene	1.0	0.050	1.000	0	103	80	120					
Xylenes, Total	2.8	0.10	3.000	0	94.6	80	120					
Surr: 4-Bromofluorobenzene 1.2			1.000		116	66.6	132					

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
 - .5

Page 5 of 5

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

the law or the law of						-	Land Street		- Falls a - D	THE RESERVE AND ADDRESS OF THE PERSON NAMED IN	
Clie	nt Name:	BLAGG		Work O	rder Number:	1704	514			RcptN	lo: 1
Rece	eived By:	Lindsay Ma	angin	4/14/2017	7:15:00 AM			Junely	Happo		
	pleted By:	Lindsay Ma			7:55:14 AM			Specific	Wan		
		Littusay Mic	(4/14				Ond	mageo		
Revi	ewed By:	ω.	7	-1111	(/						
Cha	in of Cus	tody									
1. 0	Custody sea	ls intact on sa	mple bottles?			Yes		No		Not Present	,
2. 1	s Chain of C	Custody compl	lete?			Yes	~	No		Not Present	
3. F	3. How was the sample delivered?										
Log	ı In										
_		mpt made to	cool the samp	les?		Yes	~	No	. 1	NA	*
5. \	Were all san	nples received	d at a tempera	ture of >0° C t	o 6.0°C	Yes	V	No		NA ·	
6.	Sample(s) in proper container(s)?						v	No	1.		
7. 8	Sufficient sa	mple volume f	for indicated to	est(s)?		Yes	~	No	:		
				operly preserve	d?	Yes	V	No	i		
	9. Was preservative added to bottles?							No	v	NA	
10 \	/OA viale ha	ave zero head:	enaca?			Yes	:	No		No VOA Vials	/ .
		ample containe		roken?		Yes		No		THO VOY VIGIO	
11,	vveic any se	ample contain	ers received t	iokeii!		163		140	1	# of preserved bottles checked	
		vork match bo				Yes	~	No	1	for pH:	2 or >12 unless noted)
		pancies on ch				Vaa		No		Adjusted?	2 or >12 unless noted)
		at analyses w		n of Custody?		Yes		No	: :	•	
		ding times able				Yes		No	:	Checked by	y:
		customer for a									
Snec	rial Hand	ling (if app	licable)								
		11.		vith this order?		Yes		No		NA ·	,
10. 4		9	sciepaticies v	AUT THE OLDER	**	1 CO	entime:	NO	Name of the last o	INO.	
		Notified:	avante ille atendidistigation, i.i., de jape a	-Chil - Step Japid Shop Jab'al D. bad servasi judinas	Date:		.,	Dhara		In Domes	
!	By Wh Regard	Č.	AMERICAN SECUL DESERVATE SUPPLIES MEDICAL SECUL	CHARLES AND	Via: .	eMa	100-1127: 	Phone	Fax	In Person	
	-	nstructions:	· 1000年年本公司公司等300元代明200元日	SL S' distribilità di Silandonia sul Lorsa - destito di Sila	Matter History 1727 WHICH Springer - 400 S. H.	MARIN NOTENCHAR	Mary Calmar Co.	and one obstatement being the con-	CONTRACTACIONES	Hand op had it dem skeptelle daare bekende in het.	
17.	Additional re										
18	Cooler Info	rmation									
10.	Cooler No		Condition	Seal Intact	Seal No	Seal Da	ite	Signed B	Ву		
	1	1.8	Good	Yes							



