District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application True of ertiers
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1. Operator: <u>BP America Production Company</u> OGRID #: <u>778</u>
OIL CONS. DIV DIS I. 3
Address: 200 Energy Court, Farmington, NM 87401 Facility or well name: Elliott A LS 001A JUL 13 2017
API Number: 3004523383 OCD Permit Number:
U/L or Qtr/Qtr <u>E</u> Section <u>19</u> Township <u>31N</u> Range <u>11W</u> County: <u>San Juan</u>
Center of Proposed Design: Latitude <u>36.887815</u> Longitude <u>-108.03725</u> NAD: □1927 ⊠ 1983
Surface Owner: 🛛 Federal 🗌 State 🗌 Private 🗌 Tribal Trust or Indian Allotment
2. Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. 3. Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A Volume: 95 bbl Type of fluid: Produced water
Tank Construction material:
Secondary containment with leak detection 🗌 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
Visible sidewalls and liner Visible sidewalls only Other Single wall/Double bottom; no visible sidewalls
Liner type: Thicknessmil
4. Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

 s. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	, hospital,
 6. <u>Netting:</u> Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible) 	
 7. Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC 	
 8. <u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. <i>Please check a box if one or more of the following is requested, if not leave blank:</i> Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
9. <u>Siting Criteria (regarding permitting)</u> : 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acce material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
 Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	Yes No

\$

 Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No				
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site					
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No				
Temporary Pit Non-low chloride drilling fluid					
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	□ Yes □ No				
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No				
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No				
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No				
Permanent Pit or Multi-Well Fluid Management Pit					
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No				
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No				
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No				
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No				
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	cuments are NMAC 15.17.9 NMAC				
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC					
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:					

\$

4

12. Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Muisance or Hazardous Odors, including H ₂ S, Prevention Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Errosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
 Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	
15. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	rce material are Please refer to
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

۵

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	-			
- written confirmation or verification from the municipality; written approval obtained from the municipality	🗌 Yes 🗌 No			
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No			
Within an unstable area.				
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No			
Within a 100-year floodplain. - FEMA map	Yes No			
16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.				
17. Operator Application Certification:				
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli				
Name (Print): Title:				
Signature: Date:				
e-mail address: Telephone:				
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:	212017			
19.				
<u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.				
Closure Completion Date: 5/2/2017				
Closure Completion Date: 5/2/2017 Cosure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-lo	oop systems only)			

4

÷

Oil Conservation Division

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure repor- belief. I also certify that the closure complies with all applicable closure requirement	
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature:	Date: July 7, 2017
e-mail address: <u>steven.moskal@bp.com</u>	Telephone: (505) 326-9497

.

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Elliott LS A 001A API No. 3004523383 Unit Letter E, Section 19, T31N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number. **Notice was provided and is attached.**
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

BP BGT Closure Plan 04-01-2010

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

are as follows:

 BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.
 All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents

Constituents	Testing Method	Release Verification	Sample
Constituents	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.020
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.07
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<50
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

> Soil under the BGT was sampled for TPH, BTEX and chloride with all concentrations below the stated limits. The field report and laboratory reports are attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicates no release had occurred. Attached is a laboratory report and C-141.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicates no release had occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The location will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The location will be reclaimed when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The location will be reclaimed when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The location will be reclaimed when the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

BP BGT Closure Plan 04-01-2010

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Not	tification	and	Corrective	Action	
	(DFE	ATOD		Initi

	OPERATOR	Initial Report	Final Report
Name of Company: BP	Contact: Steve Moskal		
Address: 200 Energy Court, Farmington, NM 87401	Telephone No.: 505-326-9497		
Facility Name: Elliott LS A 001A	Facility Type: Natural gas well		
L			

Surface Owner: Federal

Mineral Owner: Federal

API No. 3004523383

LOCATION OF RELEASE

Unit Letter Section	Township	Range	Feet from the	North/South Line	Feet from the	East/West Line	County: San Juan
E 179	31N	11W	1,450	North	980	West	

Latitude 36.887815° Longitude -108.037563°

NATURE OF RELEASE

Type of Release: none	Volume of Release: unknown	Volume Re	ecovered: N/A
Source of Release: below grade tank - 95 bbl	Date and Hour of Occurrence:	Date and H	Iour of Discovery: none
	none		
Was Immediate Notice Given?	If YES, To Whom?		
🗌 Yes 🛛 No 🗌 Not Required	1		
By Whom?	Date and Hour		
Was a Watercourse Reached?	If YES, Volume Impacting the Wa	tercourse.	
🗌 Yes 🖾 No			
If a Watercourse was Impacted, Describe Fully.*			
in a wateroourse was impacted, beserve runy.			
Describe Cause of Problem and Remedial Action Taken.* Sampling of t		ing removal.	Soil analysis resulted for TPH,
BTEX and chlorides below BGT closure standards. Field reports and lal	poratory results are attached.		
	Tr' 111 . 1 ' 1	1	1.1
Describe Area Affected and Cleanup Action Taken.* No further action n	lecessary. Final laboratory analysis de	termined no re	emedial action is required.
I hereby certify that the information given above is true and complete to	the best of my knowledge and underst	and that pursu	ant to NMOCD rules and
regulations all operators are required to report and/or file certain release			
public health or the environment. The acceptance of a C-141 report by the			
should their operations have failed to adequately investigate and remedia			
or the environment. In addition, NMOCD acceptance of a C-141 report	does not relieve the operator of respon	sibility for co	mpliance with any other
federal, state, or local laws and/or regulations.			
10 200	OIL CONSER	VATION I	DIVISION
Signature: Alter Min			
	Approved by Environmental Speciali	et.	
Printed Name: Steve Moskal	Approved by Environmental Special	51.	
Title: Field Environmental Coordinator	Approval Date:	Expiration D	lote:
	Approval Date.	Expiration D	
E-mail Address: steven.moskal@bp.com	Conditions of Approval:		
			Attached
Date: July 7, 2017 Phone: 505-326-9497			

* Attach Additional Sheets If Necessary

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

April 25, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: ELLIOTT A LS 001A API #: 3004523383

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about April 27, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

Moskal, Steven

From:	Moskal, Steven
Sent:	Friday, April 28, 2017 7:55 AM
То:	Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us);
	l1thomas@blm.gov
Cc:	jeffcblagg@aol.com; blagg_njv@yahoo.com; Powell, Ross L (MBF SERVICES)
Subject:	Re: BP Pit Close Notification - ELLIOTT A LS 001A

This has been rescheduled for 8:30 this morning.

Thank you,

Steve Moskal Field Environmental Coordinator BP San Juan South Cell: (505) 330-9179

Sent from my mobile device

On Apr 27, 2017, at 7:50 AM, Moskal, Steven <<u>Steven.Moskal@bp.com</u>> wrote:

This activity has been delayed due to weather conditions. I will notify when it is rescheduled.

Thank you,

Steve Moskal Field Environmental Coordinator BP San Juan South Cell: (505) 330-9179

Sent from my mobile device

On Apr 25, 2017, at 5:23 PM, Moskal, Steven <<u>Steven.Moskal@bp.com</u>> wrote:

The BGT is scheduled to be removed on April 27, at 8:30 AM.

Thank you,

Steve Moskal BP Lower 48 – San Juan – Farmington Field Environmental Coordinator Office: (505) 326-9497 Cell: (505) 330-9179 <image003.jpg>

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

From: Buckley, Farrah (CH2M HILL)
Sent: Tuesday, April 25, 2017 12:52 PM
To: Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (<u>Vanessa.Fields@state.nm.us</u>)
Cc: jeffcblagg@aol.com; blagg_njv@yahoo.com; Moskal, Steven
Subject: RE: BP Pit Close Notification - ELLIOTT A LS 001A

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US;</u> <u>VANESSA.FIELDS@STATE.NM.US</u>

April 25, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ELLIOTT A LS 001A API 30-045-23383 (E) Section 19 – T31N – R11W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around April 27, 2017

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

(505) 326-9497

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

	DI ACC E			000 (500000
CLIENT: BP		NGINEERING, INC. BLOOMFIELD, NM 87	7413	API #: 3004523383
		05) 632-1199		TANK ID (if applicble):
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTHER	k	PAGE #: of
SITE INFORMATION	SITE NAME: ELLIO	TT A LS #1A		DATE STARTED: 04/28/17
QUAD/UNIT: E SEC: 19 TWP:	31N RNG: 11W PN	I: NM CNTY: SJ S	T: NM	DATE FINISHED:
1/4 -1/4/FOOTAGE: 1,450'N / 98	O'W SW/NW LEASE	TYPE: FEDERAL STATE / FEE	/ INDIAN	ENVIRONMENTAL
LEASE #: SF078095	PROD. FORMATION: DK	STRIKE CONTRACTOR: MBF - R. POW	/ELL	SPECIALIST(S): NJV
REFERENCE POINT	WELL HEAD (W.H.) GP	S COORD.: 36.88787 X	108.03725	GL ELEV.: 6,012'
1) 95 BGT (SW/DB)	GPS COORD.: 36	.887815 X 108.037563	DISTANCE/BEAF	RING FROM W.H.: 86.5', S86.5W
2)				
3)	GPS COORD.:		DISTANCE/BEAF	RING FROM W.H.:
4)				RING FROM W.H.:
SAMPLING DATA:				OVM READING
1) SAMPLE ID: 5PC - TB @ 5'			801	5B/8021B/300.0 (CI) NA
2) SAMPLE ID:				
3) SAMPLE ID:				
		SAMPLE TIME: LAB AN		
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND			
SOIL COLOR:MODE				DHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC
CONSISTENCY (NON COHESIVE SOILS):				
MOISTURE: DRY/SLIGHTLY MOIST/MOIST/W				
SAMPLE TYPE: GRAB		ANY AREAS DISPLAYING WETNESS: YE	ES NO EXPLAN	ATION
	second			
SITE OBSERVATION				
EQUIPMENT SET OVER RECLAIMED AREA:	YES NO EXPLANATION - 105 BE	BL SHALLOW LOW PROFILE ABOV	VE-GRADE TAN	IK TO BE SET ATOP BGT LOCATION.
OTHER: NMOCD OR BLM REPS. NOT P	RESENT TO WITNESS CONFIRM	ATION SAMPLING.		
SOIL IMPACT DIMENSION ESTIMATION	NA ft. X NA	ft. X NA ft. EX	CAVATION EST	IMATION (Cubic Yards) : NA
DEPTH TO GROUNDWATER:	EAREST WATER SOURCE: >1,00		,000' NMOC	D TPH CLOSURE STD: 100 ppm
SITE SKETCH	BGT Located : off on si	ite PLOT PLAN circle:	attached	CALIB. READ. = NA ppm RE =0.52
	STEEL			CALIB. READ. = <u>NA</u> ppm <u>RF = 0.52</u> CALIB. GAS = <u>NA</u> ppm
	CONTAINMENT RING			NA am/pm DATE: NA
PROD.				
TANK				MISCELL. NOTES
			W	
				EF #: P - 782 D: VHIXONEVB2
		W.H.		
BERM	(X)	AA *11.		ermit date(s): 06/14/10
				CD Appr. date(s): 04/08/16
PBGTL			Tan	k OVM = Organic Vapor Meter
T.B. ~5'	то			BGT Sidewalls Visible: Y /N
B.G.	SEPARATOR	Υ	S.P.D.	BGT Sidewalls Visible: Y / N
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION			WELL HEAD;	BGT Sidewalls Visible: Y / N
	OW-GRADE TANK LOCATION; SPD = SAMPLE	POINT DESIGNATION; R.W. = RETAINING WALL; I		agnetic declination: 10 ° E
NOTES: GOOGLE EARTH IMAG		ONSITE: 04/28/17		

Analytical Report
Lab Order 1705001

Date Reported: 5/2/2017

Hall Environmental Analysis Laboratory, Inc.

 CLIENT: Blagg Engineering
 Client Sample ID: 5PC - TB @ 5' (95)

 Project:
 Elliott A LS #1A
 Collection Date: 4/28/2017 8:45:00 AM

 Lab ID:
 1705001-001
 Matrix: MEOH (SOIL)
 Received Date: 4/29/2017 8:00:00 AM

 Applyage
 POL
 Ough
 Units
 DE
 Date Applyage

Analyses	Result	PQL Qua	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	LGT
Chloride	ND	30	mg/Kg	20	5/1/2017 11:16:36 AM	31503
EPA METHOD 8015M/D: DIESEL RANGE		S			Analyst	MAB
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	5/1/2017 9:31:29 AM	31495
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	5/1/2017 9:31:29 AM	31495
Surr: DNOP	105	70-130	%Rec	1	5/1/2017 9:31:29 AM	31495
EPA METHOD 8015D: GASOLINE RANG	E				Analyst	NSB
Gasoline Range Organics (GRO)	ND	4.0	mg/Kg	1	5/1/2017 9:45:16 AM	G42470
Surr: BFB	96.3	54-150	%Rec	1	5/1/2017 9:45:16 AM	G42470
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.020	mg/Kg	1	5/1/2017 9:45:16 AM	B42470
Toluene	ND	0.040	mg/Kg	1	5/1/2017 9:45:16 AM	B42470
Ethylbenzene	ND	0.040	mg/Kg	1	5/1/2017 9:45:16 AM	B42470
Xylenes, Total	ND	0.079	mg/Kg	1	5/1/2017 9:45:16 AM	B42470
Surr: 4-Bromofluorobenzene	113	66.6-132	%Rec	1	5/1/2017 9:45:16 AM	B42470

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method Blank
	D	Sample Diluted Due to Matrix	Е	Value above quantitation range
	Η	Holding times for preparation or analysis exceeded	J	Analyte detected below quantitation limits Page 1 of 5
	ND	Not Detected at the Reporting Limit	Р	Sample pH Not In Range
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit
	S	% Recovery outside of range due to dilution or matrix	W	Sample container temperature is out of limit as specified

	4/20/17	1/82									4/28/17	Date	EDD (Type)	O NELAP	Accreditation:	Standard	email of rax#:	Phone #:		Mailing Address:		Client:	Ch
necessary,	1749										08 45	Time	(pe)		on:	d vage.	XH:			dress:		BLAG	ain-o
samples su	Relinguished by:	Relinquished by									SOIL	Matrix		D Other				(505) 6	BLOON	P.O. BOX 87		G ENGR	f-Cu
all Environmy	Mustury 1 hotors	A m									5PC - TB @ 5 ' (95)	Sample Request ID				Level 4 (Full Validation)		(505) 632-1199	BLOOMFIELD, NM 87413	X 87		BLAGG ENGR. / BP AMERICA	Chain-of-Custody Record
contracted to other a	Received by:	A.									4 oz 1	Container Type and #	Sample Temperature:	On Ice	Sampler:		Project Manager		Project #:	E	Project Name:	Standard	Tum-Around Time:
ccredited laboratori	7.1	n. Walte									Cool	Preservative Type	erature 1	A Yes	NELSON VELEZ	NELSON VELEZ	Jer:			ELLIOTT A LS		Rush	fime:
es. This serves as notice	4/29/17 0800										100-	HEAL NO VTO 500	and the second		ELEZ ny	ELEZ				#1A		DAY	SAME
of this	Ref	CON									<		E	TM	84s (8	3021B)			1			
possib	VID: Reference #	conta										BTEX + MTB	3E +	TPH	(Ga	s only)		Te	490			
litty. A		ü									<	TPH 8015B	(GR	0/1	DRO	/ MR	D)		Tel. 505-345-3975	1901 Hawkins NE -			
iny sul	P - 787	BILL DIRECTLY TO BP & REFERENCE # WHE STEVE MOSKAL /		-								TPH (Meth			-				5-34	awki	-	>	I
b-cont	(ONEVB P - 787	ERENO			-							EDB (Meth	-	-					5-39	ns N	NMN	Z	HALI
racted	VB2	LY TO	-	+	\vdash							PAH (8310		-	OSIN	1S)		A	75	Ē	/.hal	F	-
data		BP U										RCRA 8 Me			_			naly	77	Albu	lenv	S	3
will be		APPLI			-							Anions (F,C			_		-	sis	X 5	anbr	rion	NALYSIS	<
olear		BILL DIRECTLY TO BP USING THE CO & REFERENCE # WHEN APPLICABLE: STEVE MOSKAL / VANCE HIX STEVE MOSKAL / VANCE HIX		_	-							8081 Pestic	-	s/a	808	2 PCB	s	Analysis Request	05-3	rqu	mer		R
ly nota		N APPLICABLE: VANCE HIXON		-	-	-						8260B (VO	-			_		uest	Fax 505-345-4107	Albuquerque, NM 87109	www.hallenvironmental.com	B	0
ited on		CTWI			-		-			_		8270 (Semi					_		107	M 87	com	0	
the a		BILL DIRECTLY TO BP USING THE CONTACT WITH CORRESPONDING VID & REFERENCE # WHEN APPLICABLE; STEVE MOSKAL / VANCE HIXON		_	-	-	-				<	Chloride (so	il - 3	00.0	/ wa	ater - 3	00.1			109		LABORATORY	ENVIRONMENTAL
nalytic		RRES	 _	+	-			_				Carl	1.									7	4
al rep		OND	_		-			_	_	-		Grab samp										R	
ort.		INGV			-			-		_		5 pt. compo			-	e						Y	
L		0			1							Air Bubbles	(Y o	rN)									

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

Client: Elliott A LS #1A **Project:**

Blagg Engineering

Sample ID MB-31503	SampType: mblk	TestCode: EPA Method	300.0: Anions	
Client ID: PBS	Batch ID: 31503	RunNo: 42466		
Prep Date: 5/1/2017	Analysis Date: 5/1/2017	SeqNo: 1335661	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Chloride	ND 1.5			
Sample ID LCS-31503	SampType: Ics	TestCode: EPA Method	300.0: Anions	
Client ID: LCSS	Batch ID: 31503	RunNo: 42466		
Prep Date: 5/1/2017	Analysis Date: 5/1/2017	SeqNo: 1335662	Units: mg/Kg	
Prep Date: 5/1/2017 Analyte	,	SeqNo: 1335662 SPK Ref Val %REC LowLimit	Units: mg/Kg HighLimit %RPD	RPDLimit Qual

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Sample Diluted Due to Matrix D
- Holding times for preparation or analysis exceeded Η
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank В
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Р Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

WO#: 1705001 02-May-17

Page 2 of 5

QC SUMMARY REPORT

Hall	Enviro	nmental	Analysis	Laborato	ry, Inc.

Client: Project:

Blagg Engineering Elliott A LS #1A

1705001-001AMS	SampT	ype: MS	3	Test	tCode: El	PA Method	8015M/D: Di	esel Rang	e Organics	
5PC - TB @ 5' (95)	Batch	ID: 31	495	R	RunNo: 4	2458				
5/1/2017	Analysis D	ate: 5/	1/2017	S	SeqNo: 1	335065	Units: mg/K	g		
	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
rganics (DRO)	48	9.7	48.73	0	98.6	51.6	130			
	4.5		4.873		93.1	70	130			
1705001-001AMSD	SampT	ype: MS	D	Test	tCode: El	PA Method	8015M/D: Die	esel Range	e Organics	
5PC - TB @ 5' (95)	Batch	ID: 31	495	R	RunNo: 4	2458				
5/1/2017	Analysis D	ate: 5/	1/2017	S	SeqNo: 1	335066	Units: mg/K	g		
	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
rganics (DRO)	48	9.7	48.36	0	98.4	51.6	130	0.955	20	
	4.6		4.836		95.7	70	130	0	0	
LCS-31495	SampT	ype: LC	S	Test	tCode: EF	PA Method	8015M/D: Die	esel Range	e Organics	
LCSS	Batch	ID: 31	495	R	RunNo: 42	2458				
5/1/2017	Analysis D	ate: 5/	1/2017	S	SeqNo: 1	335067	Units: mg/K	g		
	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
rganics (DRO)	47	10	50.00	0	93.8	63.8	116			
	4.6		5.000		91.8	70	130			
MB-31495	SampT	ype: ME	BLK	Test	tCode: EF	PA Method	8015M/D: Die	esel Range	organics	
MB-31495 PBS		ype: ME			tCode: EF		8015M/D: Die	esel Range	e Organics	
PBS		ID: 314	495	R		2458	8015M/D: Die Units: mg/K		organics	
PBS	Batch	ID: 314	495 1/2017	R	RunNo: 42 SeqNo: 13	2458 335069			organics	Qual
PBS	Batch Analysis D	ID: 314 ate: 5/	495 1/2017	R	RunNo: 42 SeqNo: 13	2458 335069	Units: mg/K	g		Qual
PBS 5/1/2017	Batch Analysis D Result	ID: 31 4 ate: 5 / PQL	495 1/2017	R	RunNo: 42 SeqNo: 13	2458 335069	Units: mg/K	g		Qual
	5PC - TB @ 5' (95) 5/1/2017 rganics (DRO) 1705001-001AMSE 5PC - TB @ 5' (95) 5/1/2017 rganics (DRO) LCS-31495 LCSS 5/1/2017	SPC - TB @ 5' (95) Batch 5/1/2017 Analysis D rganics (DRO) 48 4.5 4.5 1705001-001AMSD SampT 5PC - TB @ 5' (95) Batch 5/1/2017 Analysis D ganics (DRO) 48 4.6 4.6 CSS Batch 5/1/2017 Analysis D Result 1.6 CSS Batch 5/1/2017 Analysis D Result 1.6	5PC - TB @ 5' (95) Batch ID: 314 5/1/2017 Analysis Date: 5/ Result PQL rganics (DRO) 48 9.7 4.5 4.5 1705001-001AMSD SampType: MS 5PC - TB @ 5' (95) Batch ID: 314 5PC - TB @ 5' (95) Batch ID: 314 5/1/2017 Analysis Date: 5/ Result PQL rganics (DRO) 48 9.7 4.6 4.6 LCS-31495 SampType: LC LCSS Batch ID: 314 5/1/2017 Analysis Date: 5/ Result PQL rganics (DRO) 48 9.7 4.6 LCSS Batch ID: 314 5/1/2017 Analysis Date: 5/ Result PQL rganics (DRO) 47 10	5PC - TB @ 5' (95) Batch ID: 31495 5/1/2017 Analysis Date: 5/1/2017 Result PQL SPK value rganics (DRO) 48 9.7 48.73 4.5 4.873 4.5 4.873 1705001-001AMSD SampType: MSD 5PC - TB @ 5' (95) Batch ID: 31495 5/1/2017 5PC - TB @ 5' (95) Batch ID: 31495 5/1/2017 Ganics (DRO) 48 9.7 48.36 4.6 4.836 4.6 4.836 LCS-31495 SampType: LCS SampType: LCS Batch ID: 31495 5/1/2017 Analysis Date: 5/1/2017 5/1/2017 Result PQL SPK value rganics (DRO) 47 10 50.00	SPC - TB @ 5' (95) Batch ID: 31495 F 5/1/2017 Analysis Date: 5/1/2017 S Result PQL SPK value SPK Ref Val rganics (DRO) 48 9.7 48.73 0 4.5 4.873 0 4.5 4.873 1705001-001AMSD SampType: MSD Tes 5PC - TB @ 5' (95) Batch ID: 31495 F 5/1/2017 Analysis Date: 5/1/2017 S fganics (DRO) 48 9.7 48.36 0 4.6 4.836 0 4.6 4.836 LCS-31495 SampType: LCS Tes LCSS Batch ID: 31495 F 5/1/2017 Analysis Date: 5/1/2017 S LCSS Batch ID: 31495 F S 5/1/2017 Analysis Date: 5/1/2017 S ganics (DRO) 47 10 S S	SPC - TB @ 5' (95) Batch ID: 31495 RunNo: 42 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 13 Result PQL SPK value SPK Ref Val %REC rganics (DRO) 48 9.7 48.73 0 98.6 4.5 4.873 0 98.6 4.5 93.1 1705001-001AMSD SampType: MSD TestCode: Eff 5PC - TB @ 5' (95) Batch ID: 31495 RunNo: 42 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 13 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 14 ganics (DRO) 48 9.7 48.36 0 98.4 4.6 4.836 95.7 95.7 95.7 95.7 LCS-31495 SampType: LCS TestCode: Eff LCSS Batch ID: 31495 RunNo: 42 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 13	SPC - TB @ 5' (95) Batch ID: 31495 RunNo: 42458 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 1335065 Result PQL SPK value SPK Ref Val %REC LowLimit rganics (DRO) 48 9.7 48.73 0 98.6 51.6 4.5 4.873 0 98.6 51.6 4.5 4.873 93.1 70 TestCode: EPA Method 5PC - TB @ 5' (95) Batch ID: 31495 RunNo: 42458 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 1335066 Result PQL SPK value SPK Ref Val %REC LowLimit rganics (DRO) 48 9.7 48.36 95.7 70 LCS TestCode: EPA Method LCS TestCode: EPA Method 4.6 4.836 95.7 70 LCS TestCode: EPA Method LCS- 31495 SampType: LCS TestCode: EPA Method LCSS Batch ID: 31495 RunNo: 42458 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 1335067	SPC - TB @ 5' (95) Batch ID: 31495 RunNo: 42458 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 1335065 Units: mg/K rganics (DRO) 48 9.7 48.73 0 98.6 51.6 130 4.5 4.873 0 98.6 51.6 130 430 4.5 4.873 0 98.6 51.6 130 430 4.5 4.873 93.1 70 130 130 1705001-001AMSD SampType: MSD TestCode: EPA Method 8015M/D: Die 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 1335066 Units: mg/K 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 1335066 Units: mg/K ganics (DRO) 48 9.7 48.36 0 98.4 51.6 130 LCS-31495 SampType: LCS TestCode: EPA Method 8015M/D: Die LCS-31495 SampType: LCS TestCode: EPA Method 8015M/D: Die LCS-31495	SPC - TB @ 5' (95) Batch ID: 31495 RunNo: 42458 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 1335065 Units: mg/Kg ganics (DRO) 48 9.7 48.73 0 98.6 51.6 130 4.5 4.873 0 98.6 51.6 130 4.5 4.873 03.1 70 130 1705001-001AMSD SampType: MSD TestCode: EPA Method 8015M/D: Diesel Range 5PC - TB @ 5' (95) Batch ID: 31495 RunNo: 42458 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 1335066 Units: mg/Kg ganics (DRO) 48 9.7 48.36 0 98.4 51.6 130 0.955 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 1335066 Units: mg/Kg ganics (DRO) 48 9.7 48.36 0 98.4 51.6 130 0.955 4.6 4.836 95.7 <td>SPC - TB @ 5' (95) Batch ID: 31495 RunNo: 42458 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 1335065 Units: mg/Kg Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit rganics (DR0) 48 9.7 48.73 0 98.6 51.6 130 100</td>	SPC - TB @ 5' (95) Batch ID: 31495 RunNo: 42458 5/1/2017 Analysis Date: 5/1/2017 SeqNo: 1335065 Units: mg/Kg Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit rganics (DR0) 48 9.7 48.73 0 98.6 51.6 130 100

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

- Η Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- % Recovery outside of range due to dilution or matrix S
- В Analyte detected in the associated Method Blank
- Е Value above quantitation range
- J Analyte detected below quantitation limits
- Р Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified W

WO#: 1705001

02-May-17

Page 3 of 5

QC SUMMARY REPORT

Hall Environmental Analysis Labora	tory, Inc.
------------------------------------	------------

WO#: 1705001

02-May-17

Client: Project:	Blagg Eng Elliott A I										
Sample ID	RB	SampTy	pe: ME	BLK	Tes	tCode: El	PA Method	8015D: Gaso	oline Rang	e	
Client ID:	PBS	Batch	ID: G4	2470	F	RunNo: 4	2470				
Prep Date:		Analysis Da	ate: 5/	1/2017	S	SeqNo: 1	335533	Units: mg/k	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Rang Surr: BFB	e Organics (GRO)	ND 1000	5.0	1000		104	54	150			
Sample ID	2.5UG GRO LCS	SampTy	pe: LC	S	Tes	tCode: El	PA Method	8015D: Gase	oline Rang	e	
Client ID:	LCSS	Batch	ID: G4	2470	F	RunNo: 4	2470				
Prep Date:		Analysis Da	ate: 5/	1/2017	S	SeqNo: 1	335534	Units: mg/k	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Rang	e Organics (GRO)	25	5.0	25.00	0	98.0	76.4	125			
Surr: BFB		1100		1000		111	54	150			
Sample ID	1705001-001AMS	SampTy	pe: MS	6	Tes	tCode: El	PA Method	8015D: Gaso	oline Rang	e	
Client ID:	5PC - TB @ 5' (95)	Batch	ID: G4	2470	F	unNo: 4	2470				
Prep Date:		Analysis Da	ate: 5/	1/2017	S	SeqNo: 1	335535	Units: mg/k	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Rang	e Organics (GRO)	19	4.0	19.76	0	97.5	61.3	150			
Surr: BFB		890		790.5		112	54	150			
Sample ID	1705001-001AMSE	SampTy	pe: MS	D	Tes	tCode: El	PA Method	8015D: Gaso	oline Rang	e	
Client ID:	5PC - TB @ 5' (95)	Batch	ID: G4	2470	F	unNo: 4	2470				
Prep Date:		Analysis Da	ate: 5/	1/2017	S	eqNo: 1	335536	Units: mg/k	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
	e Organics (GRO)	18	4.0	19.76	0	92.4	61.3	150	5.44	20	
Surr: BFB		860		790.5		109	54	150	0	0	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 4 of 5

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering Project: Elliott A LS #1A

¢

Sample ID	RB	Samp	Гуре: МЕ	BLK	Tes	tCode: El	PA Method	8021B: Volat	tiles		
Client ID:	PBS	Batc	h ID: B4	2470	F	RunNo: 4	2470				
Prep Date:		Analysis [Date: 5/	1/2017	S	SeqNo: 1	335541	Units: mg/K	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		ND	0.025								
Toluene		ND	0.050								
Ethylbenzene		ND	0.050								
Xylenes, Total		ND	0.10								
,	ofluorobenzene	1.2		1.000		122	66.6	132			
Sample ID	100NG BTEX LCS	Samp	Type: LC	S	Tes	tCode: El	PA Method	8021B: Volat	tiles		
Client ID:	LCSS	Batc	h ID: B4	2470	F	unNo: 4	2470				
Prep Date:		Analysis [Date: 5/	1/2017	S	eqNo: 1	335542	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		0.93	0.025	1.000	0	93.0	80	120			
Toluene		0.95	0.050	1.000	0	95.1	80	120			
Ethylbenzene		0.95	0.050	1.000	0	95.4	80	120			
Vilenes, Total		2.9	0.10	3.000	0	97.0	80	120			
Surr: 4-Brom	ofluorobenzene	1.1		1.000		114	66.6	132			
Sample ID	1705001-001AMS	Samp	ype: MS	6	Tes	Code: El	PA Method	8021B: Volat	iles		
Client ID:	5PC - TB @ 5' (95)	Batc	n ID: B4	2470	R	unNo: 4	2470				
Prep Date:		Analysis D	oto: El	1/2017		eqNo: 1	335543	Units: mg/K	a		
		Allalysis L	ale. 3/	1/2017		cqito. It	000040	•	.9		
Analyte		Result	PQL		SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
										RPDLimit	Qual
Benzene		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit		RPDLimit	Qual
Benzene Toluene		Result 0.76	PQL 0.020	SPK value 0.7905	SPK Ref Val 0	%REC 96.2	LowLimit 61.5	HighLimit 138		RPDLimit	Qual
Benzene Toluene Ethylbenzene		Result 0.76 0.77	PQL 0.020 0.040	SPK value 0.7905 0.7905	SPK Ref Val 0 0	%REC 96.2 97.6	LowLimit 61.5 71.4	HighLimit 138 127		RPDLimit	Qual
Benzene Toluene Ethylbenzene Xylenes, Total	ofluorobenzene	Result 0.76 0.77 0.78	PQL 0.020 0.040 0.040	SPK value 0.7905 0.7905 0.7905	SPK Ref Val 0 0 0	%REC 96.2 97.6 98.8	LowLimit 61.5 71.4 70.9	HighLimit 138 127 132		RPDLimit	Qual
Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brorr	ofluorobenzene 1705001-001AMSD	Result 0.76 0.77 0.78 2.4 0.96	PQL 0.020 0.040 0.040	SPK value 0.7905 0.7905 0.7905 2.372 0.7905	SPK Ref Val 0 0 0	%REC 96.2 97.6 98.8 101 122	LowLimit 61.5 71.4 70.9 76.2 66.6	HighLimit 138 127 132 123	%RPD	RPDLimit	Qual
Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brom Sample ID		Result 0.76 0.77 0.78 2.4 0.96	PQL 0.020 0.040 0.040 0.079	SPK value 0.7905 0.7905 0.7905 2.372 0.7905	SPK Ref Val 0 0 0 0 Test	%REC 96.2 97.6 98.8 101 122	LowLimit 61.5 71.4 70.9 76.2 66.6	HighLimit 138 127 132 123 132	%RPD	RPDLimit	Qual
Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brom Sample ID	1705001-001AMSD	Result 0.76 0.77 0.78 2.4 0.96	PQL 0.020 0.040 0.040 0.079	SPK value 0.7905 0.7905 2.372 0.7905 5D 2470	SPK Ref Val 0 0 0 0 Test R	%REC 96.2 97.6 98.8 101 122	LowLimit 61.5 71.4 70.9 76.2 66.6 PA Method 2470	HighLimit 138 127 132 123 132	%RPD	RPDLimit	Qual
Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brorr Sample ID Client ID:	1705001-001AMSD	Result 0.76 0.77 0.78 2.4 0.96 SampT Batcl	PQL 0.020 0.040 0.040 0.079	SPK value 0.7905 0.7905 2.372 0.7905 5D 2470 1/2017	SPK Ref Val 0 0 0 0 Test R	%REC 96.2 97.6 98.8 101 122 Code: EF unNo: 42 seqNo: 13	LowLimit 61.5 71.4 70.9 76.2 66.6 PA Method 2470	HighLimit 138 127 132 123 132 8021B: Volat	%RPD	RPDLimit	Qual
Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brorr Sample ID Client ID: Prep Date: Analyte	1705001-001AMSD	Result 0.76 0.77 0.78 2.4 0.96 0 Samp ⁻¹ Batcl Analysis D	PQL 0.020 0.040 0.040 0.079 Type: MS Di ID: B4 Date: 5/	SPK value 0.7905 0.7905 2.372 0.7905 5D 2470 1/2017	SPK Ref Val 0 0 0 0 Test R S	%REC 96.2 97.6 98.8 101 122 Code: EF unNo: 42 seqNo: 13	LowLimit 61.5 71.4 70.9 76.2 66.6 PA Method 2470 335544	HighLimit 138 127 132 123 132 8021B: Volat Units: mg/K	%RPD illes		
Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Bron Sample ID Client ID: Prep Date: Analyte Benzene	1705001-001AMSD	Result 0.76 0.77 0.78 2.4 0.96 SampT Batcl Analysis D Result	PQL 0.020 0.040 0.040 0.079 Type: MS Type: MS Date: 5/ PQL	SPK value 0.7905 0.7905 2.372 0.7905 2.372 0.7905 2470 1/2017 SPK value	SPK Ref Val 0 0 0 Test R SPK Ref Val	%REC 96.2 97.6 98.8 101 122 Code: EF unNo: 4 ieqNo: 1 %REC	LowLimit 61.5 71.4 70.9 76.2 66.6 2470 335544 LowLimit	HighLimit 138 127 132 123 132 8021B: Volat Units: mg/K HighLimit	%RPD illes %RPD	RPDLimit	
Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brorr Sample ID Client ID: Prep Date: Analyte Benzene Toluene	1705001-001AMSD	Result 0.76 0.77 0.78 2.4 0.96 0 SampT Batcl Analysis D Result 0.74	PQL 0.020 0.040 0.040 0.079 Type: MS Type: MS Date: 5/ PQL 0.020	SPK value 0.7905 0.7905 2.372 0.7905 2.372 0.7905 5D 2470 1/2017 SPK value 0.7905	SPK Ref Val 0 0 0 Test R SPK Ref Val 0	%REC 96.2 97.6 98.8 101 122 Code: EF cunNo: 4 aeqNo: 1 %REC 94.1	LowLimit 61.5 71.4 70.9 76.2 66.6 PA Method 2470 335544 LowLimit 61.5	HighLimit 138 127 132 123 132 8021B: Volat Units: mg/K HighLimit 138	%RPD illes g %RPD 2.19	RPDLimit 20	
Benzene Toluene Ethylbenzene Xylenes, Total Surr: 4-Brorr Sample ID Client ID: Prep Date:	1705001-001AMSD	Result 0.76 0.77 0.78 2.4 0.96 0 SampT Batcl Analysis D Result 0.74 0.76	PQL 0.020 0.040 0.079 Type: MS Type: MS Date: 5/ PQL 0.020 0.040	SPK value 0.7905 0.7905 2.372 0.7905 2.372 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.72 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.79 3.	SPK Ref Val 0 0 0 0 Test R S SPK Ref Val 0 0	%REC 96.2 97.6 98.8 101 122 Code: EF cunNo: 4: ceqNo: 1: %REC 94.1 95.9	LowLimit 61.5 71.4 70.9 76.2 66.6 PA Method 2470 335544 LowLimit 61.5 71.4	HighLimit 138 127 132 123 132 8021B: Volat Units: mg/K HighLimit 138 127	%RPD illes g %RPD 2.19 1.74	RPDLimit 20 20	
Benzene foluene thylbenzene (ylenes, Total Surr: 4-Brom Sample ID Client ID: Prep Date: Analyte Benzene foluene thylbenzene (ylenes, Total	1705001-001AMSD	Result 0.76 0.77 0.78 2.4 0.96 0 SampT Batcl Analysis D Result 0.74 0.76 0.76	PQL 0.020 0.040 0.079 Type: MS n ID: B4 PQL 0.020 0.040 0.040	SPK value 0.7905 0.7905 2.372 0.7905 2470 1/2017 SPK value 0.7905 0.7905 0.7905 0.7905 0.7905	SPK Ref Val 0 0 0 Test SPK Ref Val 0 0 0	%REC 96.2 97.6 98.8 101 122 Code: EF JunNo: 42 SeqNo: 13 %REC 94.1 95.9 96.6	LowLimit 61.5 71.4 70.9 76.2 66.6 PA Method 2470 335544 LowLimit 61.5 71.4 70.9	HighLimit 138 127 132 123 132 8021B: Volat Units: mg/K HighLimit 138 127 132	%RPD tiles 5g %RPD 2.19 1.74 2.18	RPDLimit 20 20 20	

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Page 5 of 5

- P Sample pH Not In RangeRL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

1705001

WO#:

02-May-17

ANAL	ONMENTA Ysis Ratory	L.	TEL	Environmenta All : 505-345-397 /ebsite: www.h	4901 Haw buquerque, NN 5 FAX: 505-34	kins NE 4 87109 45-4107	Sam	ple Log-In Cl	neck List
Client Name:	BLAGG		Work	Order Numbe	r: 1705001			RcptNo:	1
Received By:	Andy Free	man	4/29/201	7 8:00:00 AM	n	a	h		
Completed By:	Andy Jans	son	5/1/2017	8:16:33 AM		-	in our		
Reviewed By:	ENM		05/1	/17		049	(Jacobian Contraction of the Co		
Chain of Cus	tody								
1. Custody sea	ls intact on sa	ample bottles?			Yes		No 🗆	Not Present	
2. Is Chain of C	ustody comp	lete?			Yes 🗹		No 🗌	Not Present	
3. How was the	sample deliv	vered?			Courier				
Log In					_		_	_	
4. Was an atte	mpt made to	cool the sample	es?		Yes 🗹		No 🗌		
5. Were all san	nples received	d at a temperati	ure of >0° C	to 6.0°C	Yes 🗹		No 🗌	NA 🗆	
6. Sample(s) in	n proper conta	ainer(s)?			Yes 🗹		No 🗌		
7. Sufficient sa	mple volume	for indicated tes	st(s)?		Yes 🗹		No 🗆		
8. Are samples	(except VOA	and ONG) proj	perly preserv	ed?	Yes 🗹		No 🗌	_	
9. Was preserv	ative added to	o bottles?			Yes		No 🗹	NA 🗌	
10.VOA vials ha	ave zero head	space?			Yes		No 🗌	No VOA Vials 🗹	
11. Were any sa	ample contain	ers received br	oken?		Yes		No 🗹	# of preserved bottles checked	
12. Does paperv (Note discret		ottle labels? ain of custody)			Yes 🗹		No 🗌	for pH:	>12 unless noted
13. Are matrices	correctly iden	ntified on Chain	of Custody?		Yes 🗹		No 🗌	Adjusted?	
14. Is it clear wh	at analyses w	ere requested?			Yes 🗹		No 🗌		
15. Were all hold (If no, notify		e to be met? authorization.)			Yes 🗹		No	Checked by:	
Special Hand	ling (if app	olicable)							
16. Was client n	otified of all di	iscrepancles wit	th this order?	,	Yes 🗌		No 🗆	NA 🗹	1
	Notified:			Date				-	
By Wh				Via:	eMail	_ Phone	Fax	In Person	
Client	Ing: Instructions:	Datavanya dalamata na mangangan data na manaka da			ning water a state of the state	A BAGHOLING AND AND A BAGHOLING AND		ante antenno free propins administration	
17. Additional re	,								
18. <u>Cooler Info</u>						1			
Cooler No			Seal Intact	Seal No	Seal Date	Sign	ed By		
D.	1.7	Good	res			1			

6



