OIL CONS. DIV DIST, 3

Form 3160-5 (June 2015)

RECEIVED

AUG 24 2017
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

AUG 2 2 2017

FORM APPROVED OMB No. 1004-0137 Expires: January 31, 2018

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELL Sarmington Field (If if it it is an a Management of Land Management)

SUBMIT IN TRIPLICATE - Other instructions on page 2				7. If Unit of CA/Agreement, Name and/or No. NMNM 135216A			
1. Type of Well	*			8. Well Name and No			
⊠Oil Well	Other		W Lybrook Unit 745	W Lybrook Unit 745H			
2. Name of Operator WPX Energy Production, LLC				9. API Well No. 30-045-35750			
3a. Address PO Box 640 Aztec, NM 87410		3b. Phone No. (inc. 505-333-1816			10. Field and Pool or Exploratory Area Lybrook Mancos W 11. Country or Parish, State San Juan, NM		
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description SHL: 1333' FSL & 2250' FEL, Sec 7, T23N, R8W BHL: 330' FSL & 434' FEL, Sec 17, T23N, R8W		eription)					
12	. CHECK THE APPROPR	LATE BOX(ES) TO INDICA	ATE NATURE OF	NOTICE, REPORT OR OTHE	ER DATA		
TYPE OF SUBMISSION			TYPE O	FACTION	ACTION		
☐Notice of Intent	Acidize	Deepen		☐ Production (Start/Resume)	☐ Water ShutOff		
	☐Alter Casing	☐ Hydraulic Fra	acturing	Reclamation	☐ Well Integrity		
Subsequent Report	☐ Casing Repair	☐ New Constr	uction	Recomplete	Other Final		
☐Final Abandonment Notice	☐ Change Plans	☐ Plug and Ab	andon	☐ Temporarily Abandon	Casing		
L Prinai Abandoninent Notice	Convert to Injection	on Plug Back		☐ Water Disposal			
e subsurface locations and measured and true filed within 30 days following completion of tices must be filed only after all requirements is ready for final inspection.) 14/17-MIRU i Test W/ Antelope Services: Pres	evertical depths of all pertinent mar the involved operations. If the ope s, including reclamation, have been stest High 2,000 Psi for 30	kers and zones. Attach the Bond under ration results in a multiple completion completed and the operator has dete	er which the work will be n or recompletion in a na nnined that the site	e perfonned or provide the Bond No. on filew interval, a Form 3160-4 must be filed o	le with BLM/BIA. Required subsequent reports : once testing has been completed. Final Abandon		
re subsurface locations and measured and true filed within 30 days following completion of tices must be filed only after all requirements is ready for final inspection.) 14/17-MIRU it Test W/ Antelope Services: Pres 15/17-Drilling ahead 6-1/8" later 16/17- Run Production Casing Lin 2000 Psi Test on Lines Flush Water Illowed by Displacement Totaling for Plug Down 8/16/2017 18:50hrs" or Out 50 Bbl Good Cement to Su 17/17-Run Tie Back Frac String , 1 tekside @ 2,000psi for 30 min, good center to Su 17/18- to Sun 18/18- to Sun 18/	s test High 2.000 Psi for 36 al. TD 6-1/8" lateral @ 15 al. TD 6-1/8" lateral @ 16 al. TD 6-1/8" lateral @ 17 al. TD 6-1/8" lateral @ 18 al. TD 6-1/8" lateral @ 19 al. TD 6-1/8" later	completed and the operator has determined by the complete	n, 7" Intermediate G set @ 14999', LG H 40 BBLS }, follow H Plug 1500 PSI & Best of Packer Seals	Casing, all tested good and recovered by Primary Cement @ 13.3 Bump up to 2450 PSI & Hold 5 r with Pump Truck, Good Test, Stated on Mandrel 35k & 30k on a serior serior interest and the serior of th	ecorded on chart 1 14928'. 1 14		
re subsurface locations and measured and true filed within 30 days following completion of trues must be filed only after all requirements is ready for final inspection.) [14/17-MIRU if Test W/ Antelope Services: Pres. [15/17-Drilling ahead 6-1/8" later. [16/17- Run Production Casing Lin 000 Psi Test on Lines Flush Water Illowed by Displacement Totaling for Plug Down 8/16/2017 18:50hrs. [17/17-Run Tie Back Frac String , 1 10 17/17-Run Tie Back Frac String , 1 10 18:50hrs.] [17/17-Run Tie Back Frac String , 1 10 18:50hrs.] [17/17-Run Tie Back Frac String , 1 18:50hrs.]	s test High 2.000 Psi for 30 al. TD 6-1/8" lateral @ 15 al. TD 6-1/8" lateral @ 16 al. TD 6-1/8" lateral @ 17 al. TD 6-1/8" lateral @ 18 al. TD 6-1/8" later	kers and zones. Attach the Bond underation results in a multiple completion completed and the operator has determined by the services of the s	n, 7" Intermediate G set @ 14999', LG H 40 BBLS }, follow H Plug 1500 PSI & Best of Packer Seals	Casing, all tested good and received by Primary Cement @ 13.3 Bump up to 2450 PSI & Hold 5 rewith Pump Truck, Good Test, Studed on Mandrel 35k & 30k on d 08/17/2017 03:00	## { 214 Bbls/885 sks ExtendaCem * min Floats Held got 1.5 Bbl Back on B ting out of Liner Hanger, W/ Pump t Seal assembly Pressure Test Tie Back		
re subsurface locations and measured and true filed within 30 days following completion of tices must be filed only after all requirements is ready for final inspection.) 14/17-MIRU it Test W/ Antelope Services: Pres 15/17-Drilling ahead 6-1/8" later 16/17- Run Production Casing Lin 2000 Psi Test on Lines Flush Water Illowed by Displacement Totaling for Plug Down 8/16/2017 18:50hrs" or Out 50 Bbl Good Cement to Su 17/17-Run Tie Back Frac String , 1 tekside @ 2,000psi for 30 min, good center to Su 17/18- to Sun 18/18- to Sun 18/	s test High 2.000 Psi for 30 al. TD 6-1/8" lateral @ 15 al. TD 6-1/8" lateral @ 16 al. TD 6-1/8" lateral @ 17 al. TD 6-1/8" lateral @ 18 al. TD 6-1/8" later	kers and zones. Attach the Bond underation results in a multiple completion completed and the operator has determined by the services of the s	n, 7" Intermediate G set @ 14999', LG H 40 BBLS }, follow H Plug 1500 PSI & Best of Packer Seals	Casing, all tested good and rewinterval, a Form 3160-4 must be filed of the service of the servi	ecorded on chart 19 14928'. 18 4 { 214 Bbls/885 sks ExtendaCem ® min Floats Held got 1.5 Bbl Back on B ting out of Liner Hanger, W/ Pump t Seal assembly Pressure Test Tie Back		
re subsurface locations and measured and true filed within 30 days following completion of tices must be filed only after all requirements is ready for final inspection.) 14/17-MIRU is 1-25/17-Drilling ahead 6-1/8" later. 15/17-Prilling ahead 6-1/8" later. 16/17- Run Production Casing Lin 2000 Psi Test on Lines Flush Water llowed by Displacement Totaling for Plug Down 8/16/2017 18:50hrs" or Out 50 Bbl Good Cement to Su 17/17-Run Tie Back Frac String, 1 ckside @ 2,000psi for 30 min, good ill report 4-1/2" test on completi	s test High 2.000 Psi for 30 al. TD 6-1/8" lateral @ 15 al. TD 6-1/8" lateral @ 16 al. TD 6-1/8" lateral @ 17 al. TD 6-1/8" lateral @ 18 al. TD 6-1/8" later	kers and zones. Attach the Bond underation results in a multiple completion completed and the operator has determined by the service of the s	or which the work will be nor recompletion in a nonnined that the site n, 7" Intermediate	Casing, all tested good and rewinterval, a Form 3160-4 must be filed of the service of the servi	ecorded on chart 19 14928'. 18 4 { 214 Bbls/885 sks ExtendaCem ® min Floats Held got 1.5 Bbl Back on B ting out of Liner Hanger, W/ Pump t Seal assembly Pressure Test Tie Back FOR RECORD		
e subsurface locations and measured and true filed within 30 days following completion of tices must be filed only after all requirements is ready for final inspection.) 14/17-MIRU i Test W/ Antelope Services: Pres. 15/17-Drilling ahead 6-1/8" later. 16/17- Run Production Casing Lin 200 Psi Test on Lines Flush Water lowed by Displacement Totaling Flug Down 8/16/2017 18:50hrs" c Out 50 Bbl Good Cement to Su 17/17-Run Tie Back Frac String , 1 ckside @ 2,000psi for 30 min, goo ill report 4-1/2" test on completi 4. I hereby certify that the foregoi accey Granillo	s test High 2.000 Psi for 30 al. TD 6-1/8" lateral @ 15 al. TD 6-1/8" later	kers and zones. Attach the Bond underation results in a multiple completion completed and the operator has determined by the service of the s	r which the work will be nor recompletion in a nonnined that the site n, 7" Intermediate G set @ 14999', LC 5# 40 BBLS }, follow the properties of Plug 1500 PSI & Fest of Packer Seals 5,570' MD TOL , Lare Well Rig Released the Permit Tech III the 8/22/17	Casing, all tested good and received by Primary Cement @ 13.3 Bump up to 2450 PSI & Hold 5 rwith Pump Truck, Good Test, Sided on Mandrel 35k & 30k on d 08/17/2017 03:00	ecorded on chart 19 14928'. 18 4 { 214 Bbls/885 sks ExtendaCem ® min Floats Held got 1.5 Bbl Back on Bitting out of Liner Hanger, W/ Pump to Seal assembly Pressure Test Tie Back FOR RECORD		
e subsurface locations and measured and true filed within 30 days following completion of tices must be filed only after all requirements is ready for final inspection.) 14/17-MIRU Test W/ Antelope Services: Pres. 15/17-Drilling ahead 6-1/8" later. 16/17- Run Production Casing Lin 200 Psi Test on Lines Flush Water lowed by Displacement Totaling Plug Down 8/16/2017 18:50hrs" c Out 50 Bbl Good Cement to Su 17/17-Run Tie Back Frac String , 1 ckside @ 2,000psi for 30 min, goo Ill report 4-1/2" test on completi 4. I hereby certify that the foregoi accey Granillo	s test High 2.000 Psi for 30 al. TD 6-1/8" lateral @ 15 al. TD 6-1/8" later	kers and zones. Attach the Bond underation results in a multiple completion completed and the operator has determined by the services of the s	r which the work will be nor recompletion in a nonnined that the site n, 7" Intermediate G set @ 14999', LC 5# 40 BBLS }, follow the properties of Plug 1500 PSI & Fest of Packer Seals 5,570' MD TOL , Lare Well Rig Released the Permit Tech III the 8/22/17	Casing, all tested good and received by Primary Cement @ 13.3 Bump up to 2450 PSI & Hold 5 rwith Pump Truck, Good Test, Sided on Mandrel 35k & 30k on d 08/17/2017 03:00	le with BLM/BIA. Required subsequent reports a corded on chart 2 14928'. 2# { 214 Bbls/885 sks ExtendaCem ® min Floats Held got 1.5 Bbl Back on Etting out of Liner Hanger, W/ Pump to Seal assembly Pressure Test Tie Back Took RECORD		

