Current Schematic

PI / UWI 3004511344		Surface Legal Location 020-032N-007W-H	Field Name MV	License		State/Province NEW MEXICO	200	Well Configuration Type Vertical	
ound E	levation (ft) 6,215.00	Original KB/RT Elevation (ft)	6,226.90 KB-Ground	Distance (ft)	11.90	B-Casing Flange Distance (ft)		KB-Tubing Hanger Distance (ft)	
			Vertical - Orig	ginal Hole,	7/24/2017	10:31:49 AM			
MD tKB)	Formation Tops		Vertical schematic (actual)						TVD (ftKB
11.8 43.6 53.5 5259.5 5259.5 5260.5 69.9 694.9 6,035.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1 6,640.1	NACIMIENTO 1.5 1.5 1.5 1.6 1.7 1.9 NACIMIENTO 1.9 NACIMIENTO 1.9 NACIMIENTO 1.9 NACIMIENTO 1.0 PICTURED	Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 11.9 ftKB; 43.5 ftKB Tubing Pup Joint; 2 3/8 in; 4.70 lb/ft; J -55; 43.5 ftKB; 53.6 ftKB Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 53.6 ftKB; 5,700.4 ftKB				ftKB; Adju 11.9' KB to KB; 260.6 Surface C 10/27/195. cement; C -2; Interme 11.9 ftKB; fto an 11.9'	Adjusted fixB to match to matc	sing Cement; 11.9-260.6; i; 162 sacks of regular bulk reulated to surface liate; 7 5/8 in; 7.025 in; Adjusted from a 13.46' KB KB to match production	
456.0 - 458.0 - 154.9 - 450.1 - 227.0 -	CHACRA CLIFF HOUSE		S. DIV DIST. 1	8		Intermo 3,458. regular of of N	1; 11/12/1 r cement f leat ceme	s.1 ftRB sing Cement; 1,695.0- 955; 150 sacks of followed by 50 sacks nt; TOC @ 1695' cy calculation	
274.9 - 460.0 - 521.0 -	MENEFEE POINT LOO		11/24/1955; Frac'd als of Slickwater and 58,000# of sand			Menef	ee; 5,242.	0-5,460.0; 11/23/1955]
525.9 - 589.9 - 607.9 - 700.5 -		with 40,000 ga Hydraulic Fracture; with 40,000 ga Seating Nipple (F J-55; 5,700.4	11/23/1955; Frac'd als of Slickwater and 57,500# of sand 11/22/1955; Frac'd als of Slickwater and 52,500# of sand 1; 2 3/8 in; 4.70 lb/ft; 1 ftKB; 5,701.2 ftKB 3 in; 4.70 lb/ft; J-55;			88	_ookout; 5	0-5,590.0; 11/22/1955	I
701.4 - 710.0 - 740.2 - 743.1 -		5,701.2	2 ftKB; 5,701.6 ftKB	M		PLUG 11/16/ 3; Prod ftKB; 5 PROD 4,155.0	1955 duction; 5 5,745.1 ftk DUCTION 0-5,745.1;	740.0-5,745.0; 1/2 in; 5.012 in; 11.9 (B CASING CEMENT; ; 11/16/1955; 150 cement; TOC @	