District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application Type of action: Below grade tank registration

Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1. Complete
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: Fields Com LS #5A
API Number: 3004522461 OCD Permit Number:
U/L or Qtr/Qtr F Section 28 Township 32N Range 11W County: San Juan
Center of Proposed Design: Latitude
Surface Owner: X Federal X State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC College Sterock
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK Company TANK Company
Volume: 45 bbl Type of fluid: Produced water
Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other <u>Single wall/ Double bottom; sidewalls visible</u>
Liner type: Thicknessmil
4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify							
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)							
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC							
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.							
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source						
General siting							
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA						
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No						
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No						
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No						
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No						
Below Grade Tanks							
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No						
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)							
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No							
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 								
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site								
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site								
Temporary Pit Non-low chloride drilling fluid								
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
 Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 								
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Permanent Pit or Multi-Well Fluid Management Pit								
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No							
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.								
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No							
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	NMAC							
Previously Approved Design (attach copy of design) API Number: or Permit Number:								
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC								
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:								
Treviously Approved Design (attach copy of design) Art indunioer or remit indunioer:								

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Closure Figure - based upon the appropriate requirements of Subsection C of 17.13.17.3 MMAC and 17.13.17.13 MMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Flaternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	uid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	□ Vac □ Na
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No							
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division								
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological								
Society; Topographic map	Yes No							
Within a 100-year floodplain FEMA map	☐ Yes ☐ No							
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC							
Operator Application Certification:								
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe	ef.							
Name (Print): Title:								
Signature: Date:								
e-mail address:								
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)								
OCD Representative Signature: Approval Date: 03	712017							
Title: Socialist OCD Permit Number:								
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 7/10/2017								
20.								
	op systems only)							

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments su	bmitted with this closure report is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all a	pplicable closure requirements and conditions specified in the approved closure plan.
Name (Print): <u>Erin Garifalos</u>	Title: Field Environmental Coordinator
Orin alril - Oax	
Signature: Vain garifalos	Date: September 18, 2017
orginature	Dutch September 10, 2017
e-mail address: erin.garifalos@bp.com	Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Fields Com LS #5A API No. 3004522461 Unit Letter F, Section 28, T32N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	45 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.027
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.110
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<48
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area
 - Sampling results indicate a release has not occurred. Attached is a laboratory report and field report.
- 10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

- 11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.
 - The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.
- 12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

- 13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover
 - The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

- 14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.
 - The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.
- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 BP did not meet the 60 closure completion requirement due to an error in internal tracking. Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action															
							ΓOR		Initia	al Report	\boxtimes	Final Report			
							Contact: Erin Garifalos								
Address: 200				M 87401			No.: 832-609-70								
Facility Nam	ne: Fields	Com LS #5A	A			Facility Typ	e: Natural gas v	well							
Surface Own	ner: Feder	al		Mineral C	wner: I	Federal			API No	. 30045224	161				
				LOCA	TION	OF RE	LEASE								
Unit Letter F	Section 28	Township 32N	Range 11W	Feet from the 1.765	North/ North	South Line	Feet from the 1.500	East/W West	est Line	County: Sa	an Juan	1			
	20	0211		tude 36.958	3.02.00	Longitue	de -107.997								
			Lati					101							
Type of Relea	ise: none	_		NAI	UKE	OF REL	Release: unknow	vn	Volume R	lecovered: N	J/A				
Source of Rel		v grade tank –	45 bbl				Iour of Occurrence			Hour of Dis		none			
						none									
Was Immedia	te Notice C		Yes 🗵	No Not Re	equired	If YES, To	Whom?								
By Whom?						Date and F									
Was a Waterc	course Reac		Yes 🗵	No		If YES, Volume Impacting the Watercourse.									
If a Watercour	rse was Im	pacted, Descri	be Fully.*												
							the BGT was don		g removal.	Soil analys	is resul	ted for			
Describe Area	Affected a	and Cleanup A	action Tak	en.* No action no	ecessary.	Final labora	atory analysis dete	ermined	no remedia	al action is r	equired	l.			
							knowledge and u								
							nd perform correc								
							arked as "Final Roon that pose a thro								
							e the operator of i								
federal, state,	or local lay	ws and/or regu	lations.					CERT		D.W.WOLO	2.7				
,	TIN OAT	11-0-2				OIL CONSERVATION DIVISION									
Signature:	ien gau	gaeos													
Printed Name	· Erin Gari	falos			1	Approved by	Environmental S _I	pecialist:							
Timed Name	, Erm Gari	14105													
Title: Field Er	nvironment	al Coordinato	r		1	Approval Dat	e:	Е	expiration I	Date:					
E-mail Addres	ss: erin.gar	ifalos@bp.cor	n		Conditions of Approval:										
Date: September 18, 2017 Phone: 832-609-7048															

^{*} Attach Additional Sheets If Necessary

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

June 23, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: FIELDS COM LS 005A

API#: 3004522461

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about June 29, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

Garifalos, Erin

From:

Buckley, Farrah (CH2M HILL)

Sent:

Friday, June 23, 2017 6:56 AM

To:

'Smith, Cory, EMNRD'; 'Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)'

Cc:

'jeffcblagg@aol.com'; 'blagg_njv@yahoo.com'; Moskal, Steven

Subject:

BP Pit Close Notification - FIELDS COM LS 005A

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

June 23, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

FIELDS COM LS 005A API 30-045-22461 (F) Section 28 – T32N – R11W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 45bbl BGT and a 21bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around June 29, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	BLAGG EI P.O. BOX 87, B	API #: 30045			
		5) 632-1199		(if applicble):	Α
FIELD REPORT:	(circle one): BGT CONFIRMATION /	RELEASE INVESTIGATION / OTHER	₹:	PAGE #: 1	of <u>1</u>
SITE INFORMATION		COM LS #5A		DATE STARTED: 0	7/05/17
QUAD/UNIT: F SEC: 28 TWP:	32N RNG: 11W PM:	NM CNTY: SJ S	ST: NM	DATE FINISHED:	
1/4-1/4/FOOTAGE: 1,765'N / 1,5	00'W SE/NW LEASE T	YPE: FEDERAL STATE / FEE	E / INDIAN	ENVIRONMENTAL	
LEASE #: NM010989	PROD. FORMATION: MV CO	STRIKE ONTRACTOR: MBF - R. POW	VELL	SPECIALIST(S):	NJV
REFERENCE POINT	: WELL HEAD (W.H.) GPS	COORD.: 36.95829 X	107.99739	GL ELEV.:	6,340'
1) 45 BGT (SW/DB)	GPS COORD.: 36.9	958093 X 107.997181	DISTANCE/BEA	RING FROM W.H.:89.5	', S49E
2)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
3)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # C	OR LAB USED: HALL			READING (ppm)
1) SAMPLE ID: 5PC - TB @ 5' (4	.5) - A SAMPLE DATE: 07/05	5/17 SAMPLETIME: 1410 LAB A	NALYSIS: 801	5B/8021B/300.0 (CI)	NA
2) SAMPLE ID:			NALYSIS:		
SAMPLE ID: SAMPLE ID:			NALYSIS:		
5) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB AI	NALYSIS:		
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND	SILT / SILTY CLAY / CLAY / GRAVEL / O	THER		
-	LOWISH ORANGE	PLASTICITY (CLAYS): NON PLASTIC / SLIC	GHTLY PLASTIC / C	OHESIVE / MEDIUM PLASTIC / I	HIGHLY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE SLIGHTL		DENSITY (COHESIVE CLAYS & SILTS	,)
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLYMOIST/MOIST/W		HC ODOR DETECTED: YES NO EXPL	ANATION -		
SAMPLE TYPE: GRAB (COMPOSITE) #		ANY AREAS DISPLAYING WETNESS: Y	ES NO EXPLAN	IATION -	
DISCOLORATION/STAINING OBSERVED: YES					
SITE OBSERVATION					
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:		ANATION:			
OTHER: NMOCD OR BLM NOT PRESENT		AMPLING.			
EXCAVATION DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA ft. EX	/CAV/ATION EST	IMATION (Cubic Yards) :	NA
	IEAREST WATER SOURCE: >1,000			D TPH CLOSURE STD:	100 ppm
SITE SKETCH	BGT Located : off on site				
	BOT Located. Oil / Oil site	PLOTPLAN circle.		CALIB. READ. = NA	ppm RF = 1.00
W.H. ⊕				CALIB. GAS = NA : NA am/pm DATE:	_ppm
	SEDADATOD 141	CODEN	N TIME		
		OODEN R.W.	l.,	MISCELL. No	JIE2
			_	O:	
		45 (A) PBGTL		EF#: P-825 ID: VHIXONEV	פס
	FENCE	T.B. ~ 5'		J#:	52
		B.G.			3/10/10
COMPRESSO	R		1 -		/08/16
			Tan	k OVM = Organic Vapo	r Meter
				BGT Sidewalls Visible:	
		Χ -	S.P.D.	BGT Sidewalls Visible:	/ / N
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION		ELOW; T.H. = TEST HOLE; ~ = APPROX.; W.H. =	WELL HEAD;	BGT Sidewalls Visible: \	
	.OW-GRADE TANK LOCATION; SPD = SAMPLE P E WALL; DW - DOUBLE WALL; SB - SINGLE BOT		NA-NOT M	lagnetic declination:	10°E
NOTES: GOOGLE EARTH IMAG		ONSITE: 07/05/17			

Analytical Report

Lab Order 1707166

Collection Date: 7/5/2017 2:10:00 PM

Date Reported: 7/10/2017

Hall Environmental Analysis Laboratory, Inc.

FIELDS COM LS 5A

CLIENT: Blagg Engineering Client Sample ID: 5PC-TB@5'(45)-A

Lab ID: 1707166-001 Matrix: MEOH (SOIL) Received Date: 7/6/2017 7:35:00 AM

Analyses	Result	PQL (Qual Unit	S DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst:	MRA
Chloride	ND	30	mg/l	(g 20	7/6/2017 11:52:41 AM	32655
EPA METHOD 8015M/D: DIESEL RANG	E ORGANICS	3			Analyst:	TOM
Diesel Range Organics (DRO)	ND	9.7	mg/ł	(g 1	7/6/2017 9:10:43 AM	32650
Motor Oil Range Organics (MRO)	ND	48	mg/ł	(g 1	7/6/2017 9:10:43 AM	32650
Surr: DNOP	111	70-130	%Re	c 1	7/6/2017 9:10:43 AM	32650
EPA METHOD 8015D: GASOLINE RANG	SE				Analyst:	NSB
Gasoline Range Organics (GRO)	ND	5.3	mg/ł	(g 1	7/6/2017 9:33:20 AM	32630
Surr: BFB	107	54-150	%Re	c 1	7/6/2017 9:33:20 AM	32630
EPA METHOD 8021B: VOLATILES					Analyst:	NSB
Benzene	ND	0.027	mg/k	(g 1	7/7/2017 3:17:24 PM	32652
Toluene	ND	0.053	mg/k	(g 1	7/7/2017 3:17:24 PM	32652
Ethylbenzene	ND	0.053	mg/k	(g 1	7/7/2017 3:17:24 PM	32652
Xylenes, Total	ND	0.11	mg/k	(g 1	7/7/2017 3:17:24 PM	32652
Surr: 4-Bromofluorobenzene	133	66.6-132	S %Re	c 1	7/7/2017 3:17:24 PM	32652

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

Project:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- Analyte detected below quantitation limits Page 1 of 6 J
- P Sample pH Not In Range
- Reporting Detection Limit RL
- Sample container temperature is out of limit as specified

C	hain-d	of-Cus	tody Record	Turn-Around	Ime:	SAME			-	н	AI	1	FI	NV	TE	20	PAR P	MEI	MT	AI	
Client:	BLAG	G ENGR.	/ BP AMERICA	Standard Project Name	☑ Rush _	DAY				A	N	AL	YS	SIS	S L	A		RA		*	
Mailing A	ddress:	P.O. BO	X 87	FIE	LDS COM L	S #5A		49)1 H	awki	ns N	IE -	Alb	uqu	erqu	Je, N	IM 8	37109)		
		BLOOM	FIELD, NM 87413	Project #:						5-34					4		410				
Phone #:		(505) 63	2-1199									A	naly	/sis	Red	ques	st				1/2
email or	Fax#:			Project Mana	ger:		-			1				4)		1		300.1)		-	
QA/QC Pa	The state of the s		Level 4 (Full Validation)		NELSON VE	ELEZ	80218)	(Aluo s	/ MRO)			(5)		PO4,SO	/ 8082 PCB's		. 6	water - 300			B .
Accredita	tion:			Sampler:	NELSON VE	ELEZ 97V	*	Ga	DRO	7	7	8270SIMS)		VO2,	808			/ W			sample N)
D NELA		☐ Other		On Ice:	XYes	□ No	#	TP	0	418	204	827	LA	OS	150		JA)	300.D /			
□ EDD (Type)			Sample Temp	erature: 4,3	THE RESERVE THE PARTY OF THE PA	4	BE +	GR	pou		ō	etal	N,	cide	(A)	Ϋ́	18.	12	e i	(Y c
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	=411°C HEAL No. 1707166	BTEX +- NATE	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or	RCRA 8 Metals	Anions (F,CI,NO ₅ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil	-	ge .	5 pt. composite Air Bubbles (Y or
7/5/17	1410	SOIL	5PC-TB@ 5"(45)-A	4 oz 1	Cool	-001	٧		٧									٧	1	1	V
7/5/17	1436	COIL	500 TO @ (1/21) D	108.1	Cool	-002	4		٧							7 7		4	#	+	4
													11	- 1					- <		
							1				1	1							+	+	
								A											1	+	
Date: 7/5/1-3	Time:	Ralinquishe	# 9Y: C	Received by:	1	Date Time	Rem	arks									ACT V	VITH CC	ORRESI	OND	ING VID
Date:	16co	Relinquishe	ed by:	Received by		7 (6 (1) 0735 Date Time	& REFERENCE # WHEN APPLICABLE; CONTACT: STEVE MOSKAL / VANCE HIXON VID: VHIXONEVB2 Reference # P - 825														

Hall Environmental Analysis Laboratory, Inc.

WO#:

1707166

10-Jul-17

Client:

Blagg Engineering

Project:

FIELDS COM LS 5A

Sample ID MB-32655

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 32655

RunNo: 44023

Prep Date: 7/6/2017

Analysis Date: 7/6/2017

SeqNo: 1389461

Units: mg/Kg

Analyte

Client ID:

Prep Date:

Result PQL ND 1.5

SampType: Ics

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD **RPDLimit** Qual

Chloride

Sample ID LCS-32655 LCSS

Batch ID: 32655

RunNo: 44023

TestCode: EPA Method 300.0: Anions

Units: mg/Kg

%RPD

Analyte

7/6/2017

Analysis Date: 7/6/2017

SeqNo: 1389462

SPK value SPK Ref Val %REC

HighLimit

RPDLimit

Chloride

Result PQL

15.00

93.3

14

Page 3 of 6

Qual

1.5

90

Oualifiers:

D

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix Holding times for preparation or analysis exceeded Η

Not Detected at the Reporting Limit ND Practical Quanitative Limit **PQL**

% Recovery outside of range due to dilution or matrix

В Analyte detected in the associated Method Blank

Value above quantitation range

Analyte detected below quantitation limits J

P Sample pH Not In Range

Reporting Detection Limit

Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#: 1707166

10-Jul-17

Client: Project:

Blagg Engineering FIELDS COM LS 5A

TestCode: EPA Method 8015M/D: Diesel Range Organics Sample ID MB-32650 SampType: MBLK Batch ID: 32650 Client ID: **PBS** RunNo: 44012 Prep Date: 7/6/2017 Analysis Date: 7/6/2017 SeqNo: 1387850 Units: mg/Kg SPK value SPK Ref Val %REC LowLimit HighLimit %RPD **RPDLimit** Analyte Result PQL Qual Diesel Range Organics (DRO) ND 10 Motor Oil Range Organics (MRO) ND 50 70 130 Surr: DNOP 10.00 104 10

Sample ID LCS-32650 TestCode: EPA Method 8015M/D: Diesel Range Organics SampType: LCS Client ID: LCSS Batch ID: 32650 RunNo: 44012 Units: mg/Kg Analysis Date: 7/6/2017 SegNo: 1387854 Prep Date: 7/6/2017 HighLimit Analyte Result PQL SPK value SPK Ref Val %REC LowLimit %RPD **RPDLimit** Qual Diesel Range Organics (DRO) 48 10 50.00 0 96.5 73.2 114 Surr: DNOP 5.0 5.000 101 70 130

Sample ID 1707166-001AMS SampType: MS TestCode: EPA Method 8015M/D: Diesel Range Organics Client ID: 5PC-TB@5'(45)-A Batch ID: 32650 RunNo: 44012 Prep Date: 7/6/2017 Analysis Date: 7/6/2017 SeqNo: 1388176 Units: mg/Kg Analyte Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD **RPDLimit** Qual Diesel Range Organics (DRO) 56 48.50 3.520 108 55.8 Surr: DNOP 5.1 70 4.850 105 130

Sample ID 1707166-001AMSD SampType: MSD TestCode: EPA Method 8015M/D: Diesel Range Organics 5PC-TB@5'(45)-A Batch ID: 32650 Client ID: RunNo: 44012 7/6/2017 Analysis Date: 7/6/2017 SeqNo: 1388177 Prep Date: Units: mg/Kg %RPD SPK value SPK Ref Val %REC HighLimit **RPDLimit** Qual Analyte Result PQL LowLimit

Diesel Range Organics (DRO) 51 10 49.75 3.520 94.8 55.8 122 10.1 20 Surr: DNOP 5.1 4.975 103 70 130 0 0

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 4 of 6

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1707166

10-Jul-17

Client:

Blagg Engineering

Project:

FIELDS COM LS 5A

Result

1100

PQL

SPK value SPK Ref Val

1000

Sample ID MB-32630	SampType: MBLK	TestCode: EPA Method 8015D: Gasoline	Range
Client ID: PBS	Batch ID: 32630	RunNo: 44020	
Prep Date: 7/5/2017	Analysis Date: 7/6/2017	SeqNo: 1388606 Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %F	RPD RPDLimit Qual
Gasoline Range Organics (GRO) Surr. BFB	ND 5.0 1100 1000	106 54 150	
Sample ID LCS-32630	SampType: LCS	TestCode: EPA Method 8015D: Gasoline	Range
Client ID: LCSS	Batch ID: 32630	RunNo: 44020	
Prep Date: 7/5/2017	Analysis Date: 7/6/2017	SeqNo: 1388607 Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %F	RPD RPDLimit Qual
Gasoline Range Organics (GRO)	23 5.0 25.00	0 90.2 76.4 125	
Sum: BFB	1200 1000	117 54 150	
Sample ID MB-32652	SampType: MBLK	TestCode: EPA Method 8015D: Gasoline	Range
Client ID: PBS	Batch ID: 32652	RunNo: 44055	
Prep Date: 7/6/2017	Analysis Date: 7/7/2017	SeqNo: 1390847 Units: %Rec	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %F	RPD RPDLimit Qual
Surr: BFB	990 1000	99.3 54 150	
Sample ID LCS-32652	SampType: LCS	TestCode: EPA Method 8015D: Gasoline	Range
Client ID: LCSS	Batch ID: 32652	RunNo: 44055	
Prep Date: 7/6/2017	Analysis Date: 7/7/2017	SeqNo: 1390848 Units: %Rec	

Qualifiers:

Analyte

Surr: BFB

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range

%REC

113

LowLimit

54

HighLimit

150

%RPD

RPDLimit

Page 5 of 6

- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#: 1

1707166 10-Jul-17

Client:

Blagg Engineering

Project:

FIELDS COM LS 5A

Sample ID MB-32652	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batch ID: 32652			F						
Prep Date: 7/6/2017	Analysis Date: 7/7/2017			SeqNo: 1390864			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.3		1.000		129	66.6	132			
Sample ID LCS-32652	SampTy	ampType: LCS TestCode: EPA Method 8021B: Volatiles								

Client ID: LCSS	Batch ID: 32652			R	RunNo: 4	4055				
Prep Date: 7/6/2017	Analysis D	ate: 7/	7/2017	S	SeqNo: 1	390865	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.025	1.000	0	106	80	120			
Toluene	1.1	0.050	1.000	0	106	80	120			
Ethylbenzene	1.1	0.050	1.000	0	107	80	120			
Xylenes, Total	3.3	0.10	3.000	0	110	80	120			
Surr: 4-Bromofluorobenzene	1.3		1.000		130	66.6	132			

Sample ID MB-32630	SampType:	MBLK	Tes	tCode: E	PA Method	8021B: Volat	iles		
Client ID: PBS	Batch ID:	32630	F	RunNo: 4	4055				
Prep Date: 7/5/2017	Analysis Date:	7/7/2017	S	SeqNo: 1	390879	Units: %Red	:		
Analyte	Result PC	L SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	1.3	1.000		126	66.6	132			

Sample ID LCS-32630	SampType: L	TestCode: EPA Method 8021B: Volatiles							
Client ID: LCSS	Batch ID: 3	2630	F	RunNo: 4	4055				
Prep Date: 7/5/2017	Analysis Date:	7/7/2017	8	SeqNo: 1	390880	Units: %Red	С		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	1.3	1 000		132	66.6	132			S

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 6 of 6

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

Sample Log-In Check List

BLAGG Work Order Number: 1707166 RcptNo: 1 Client Name: Received By: 7/6/2017 7:35:00 AM **Andy Jansson** Completed By: **Andy Jansson** 7/6/2017 7:44:20 AM Reviewed By: 7/6/17 Chain of Custody No 🗌 Not Present Yes 1. Custody seals intact on sample bottles? No 🗌 Not Present Yes 🗸 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In No 🗌 NA 🗔 Yes 🗸 4. Was an attempt made to cool the samples? No 🗌 NA 🔲 5. Were all samples received at a temperature of >0° C to 6.0°C Yes V No 🗆 Yes V 6. Sample(s) in proper container(s)? No 🗌 7. Sufficient sample volume for indicated test(s)? No 🗌 Yes 🗸 8. Are samples (except VOA and ONG) properly preserved? Yes No V NA 🗆 9. Was preservative added to bottles? Yes No 🗌 No VOA Vials 10. VOA vials have zero headspace? No V Yes 11. Were any sample containers received broken? # of preserved bottles checked Yes 🗸 No 🗌 for pH: 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) No 🗌 Adjusted? Yes 🗸 13. Are matrices correctly identified on Chain of Custody? No 🗌 Yes V 14. Is it clear what analyses were requested? 15. Were all holding times able to be met? Yes 🗸 No 🗌 Checked by: (If no, notify customer for authorization.) Special Handling (if applicable) Yes 16. Was client notified of all discrepancies with this order? No 🗌 NA V Person Notified: Date By Whom: Via: eMail Phone Fax In Person Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No Temp °C Condition Seal Intact Seal No Seal Date Signed By 4.1 Good Yes



