District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

-

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

<u>Pit, Below-Grade Tank, or</u> <u>Proposed Alternative Method Permit or Closure Plan Application</u>
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1. Operator: BP America Production Company OGRID #: 778 Address: 200 Energy Court, Farmington, NM 87401 Facility or well name: ATLANTIC A LS 005 API Number: 3004510280 U/L or Qtr/Qtr L Section 26 Township 31N Range 10W County: San Juan Center of Proposed Design: Latitude 36.867055 Longitude -107.857523 NAD83 Surface Owner: Federal State Private Tribal Trust or Indian Allotment OIL CONS. DIV DIST. 3
2. Pit: Subsection F, G or J of 19.15.17.11 NMAC Closure Report NOV 01 2017 Temporary: Drilling Workover Submitted after Corpey deadline Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Volume:bbl Dimensions: L x W x D
3. TANK B Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK B Volume: 21 bbl Type of fluid: Produced Water Tank Construction material: Steel
 4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
 5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify

Oil Conservation Division

6. <u>Netting</u> : Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8.	
Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank:	
Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept	ptable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	
<u>General siting</u>	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	□ Yes □ No
- 🗌 NM Office of the State Engineer - iWATERS database search; 🗌 USGS; 🗌 Data obtained from nearby wells	□ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.	Yes No
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	🗆 NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)	Yes No
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)	Yes No
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	
Within an unstable area. (Does not apply to below grade tanks)	Yes No
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain. (Does not apply to below grade tanks)	Yes No
- FEMA map	
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).	Yes No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.	Yes No
 NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Temporary I it using Low Chloride Drining Fluid (maximum emoride content 15,000 mg/mer)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole,	Yes No
 or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
 Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.	Yes No
NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	

1

.

,	
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number:	ouments are 9 NMAC 15.17.9 NMAC
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

12.							
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC							
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	documents are						
 Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment 							
 Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC 							
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC							
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC							
 Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC 							
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC							
 Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan 							
Oil Field Waste Stream Characterization							
Monitoring and Inspection Plan							
 Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 							
^{13.} <u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.							
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fl	uid Management Pit						
Proposed Closure Method: Waste Excavation and Removal							
 Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) 							
In-place Burial On-site Trench Burial							
Alternative Closure Method							
 closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 							
15. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.							
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA						
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA						
Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells							
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site							
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image							
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.							
- NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site							
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗋 Yes 🗌 No						
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site							
	□ Yes □ No						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance							

P

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. - FEMA map	Yes No
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure play a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC
Tr. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli Name (Print): Title: Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Isoure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: OCD State Approval Date: III Title: CONMENTAL OCD Permit Number: OCD Permit Number:	12017
19. <u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 8/21/2017	
 20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-log) If different from approved plan, please explain. 	oop systems only)
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude 36.867055 Longitude -107.857523	

Oil Conservation Division

Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print): Erin Garifalos

22.

Signature:

Title: Field Environmental Coordinator

erin garifalos

Date: October 30, 2017

e-mail address: erin.garifalos@bp.com

Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

ATLANTIC A LS 005

API No. 3004510280

Unit Letter L Section 26 T 31N R 10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

BP BGT Closure Plan 04-01-2010

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	<0.018
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.072
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<50
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

> Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

BP did not meet the 60 closure completion requirement due to an error in internal tracking. Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

BP BGT Closure Plan 04-01-2010

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised April 3, 2017

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

		OPERATOR		Initial Report		Final Report
Name of Company BP America Production Comp	any	Contact Erin Garifalos				
Address 200 Energy Court, Farmington, NM 87401		Telephone No. (832) 609-7048				
Facility Name ATLANTIC A LS 005		Facility Type: Natural Gas Well				
Surface Owner: Federal	Mineral Owne	r · Federal	4	PI No. 3004510280)	

				LOC	TION OF DE			
Unit Letter	Section	Township	Range	Feet from the	ATION OF RE	Feet from the	East/West Line	County
L	26	31N	10W	1,650	South	990	West	San Juan
			Latitud	e 36.867055	Longitude -1	07.857523	NAD83	

NATURE OF RELEASE

Type of Release:: none	Volume of Release: : unknown	Volume Re	ecovered:: N/A			
Source of Release: below grade tank - 21 bbl	Date and Hour of Occurrence: n/a	Date and H	lour of Discovery:			
Was Immediate Notice Given?	If YES, To Whom?					
By Whom?	Date and Hour					
Was a Watercourse Reached?	If YES, Volume Impacting the Wa	tercourse.				
If a Watercourse was Impacted, Describe Fully.*						
Sampling Soil analy	Describe Cause of Problem and Remedial Action Taken.* Sampling of the soil beneath the BGT was done during removal. Soil analysis resulted for Chlorides, BTEX, and TPH below BGT closure standards. Field reports and laboratory results are attached.					
Describe Area Affected and Cleanup Action Taken.* No action necessary. Final laboratory analysis determined no remedial action is required.						
I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.						
Signature: Printed Name: Erin Garifalos	OIL CONSER		DIVISION			
Printed Name: Erin Garifalos	Approved by Environmental Speciali	SU:				
Title: Field Environmental Coordinator	Approval Date:	Expiration D	ate:			
E-mail Address: erin.garifalos@bp.com	Conditions of Approval:		Attached			

Date: October 30, 2017 * Attach Additional Sheets If Necessary

Phone: (832) 609-7048

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

August 4, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: ATLANTIC A LS 005 API #: 3004510280

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about August 14, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

Garifalos, Erin

From:	Buckley, Farrah (CH2M HILL)
Sent:	Friday, August 04, 2017 6:48 AM
То:	'Smith, Cory, EMNRD'; 'Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)';
	'brandon.powell@state.nm.us'
Cc:	'jeffcblagg@aol.com'; 'blagg_njv@yahoo.com'; Moskal, Steven; Garifalos, Erin
Subject:	BP Pit Close Notification - ATLANTIC A LS 005

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

August 4, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ATLANTIC A LS 005 API 30-045-10280 (L) Section 26– T31N – R10W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around August 14, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator (505) 326-9497

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

2

	BLAGG EN		2	2004540	200
CLIENT: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413			API #: 3004510	
	(50		(if applicble): B		
FIELD REPORT:	(circle one): BGT CONFIRMATION /	RELEASE INVESTIGATION / OTI	HER:	PAGE #: of	f _1_
SITE INFORMATION				DATE STARTED: 08/1	7/17
QUAD/UNIT: L SEC: 26 TWP:				DATE FINISHED:	
1/4 -1/4/FOOTAGE: 1,650'S / 99 LEASE #: NM0606	D'W NW/SW LEASE T PROD. FORMATION: MV CC	STDIKE		ENVIRONMENTAL SPECIALIST(S):	В
REFERENCE POINT	WELL HEAD (W.H.) GPS	COORD.: 36.86683	X 107.85761	GL ELEV.: 6	,300'
1) 21 BGT (SW/DB)	GPS COORD.: 36.8	67055 X 107.857523	DISTANCE/BEAF	RING FROM W.H.: 82', N'	18E
2)	GPS COORD.:		DISTANCE/BEAF	RING FROM W.H.:	
3)					
4)			DISTANCE/BEAF	RING FROM W.H.:	OVM
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # O				READING (ppm)
1) SAMPLE ID: 21 BGT 5 - pt. (-				0.8
2) SAMPLE ID: 3) SAMPLE ID:					
4) SAMPLE ID:					
5) SAMPLE ID: SOIL DESCRIPTION	SAMPLE DATE:				
COHESION (ALL OTHERS): NON COHESIVE (SLIGHTL CONSISTENCY (NON COHESIVE SOILS): [LC MOISTURE: DRY /SLIGHTLY MOIST / MOIST / W SAMPLE TYPE: GRAB (COMPOSITE) # DISCOLORATION/STAINING OBSERVED: YES N SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: BGT SET UPON PVC LINER B	OSE FIRM DENSE / VERY DENSE T / SATURATED / SUPER SATURATED OF PTS. 5 0 EXPLANATION - IS: LOST INTEGRITY OF EQUIPMENT: D AND/OR OCCURRED : YES NO EXPLA YES NO EXPLANATION - ACKHOE USED TO COLLECT SAM	NATION:	XPLANATION	IATION	
EXCAVATION DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: >100' N	NA ft. X NA EAREST WATER SOURCE: >1,000'	ft. X <u>NA</u> ft. NEAREST SURFACE WATER:		IMATION (Cubic Yards) :	NA 00 ppm
SITE SKETCH	BGT Located : off on site BERM PBGTL T.B. ~ 6' B.G. PROD. TANK	E BERM FENCE		MISCELL. NOT O: EF #: P-674 D: VHIXONEVB2 J #: ermit date(s): 06/14 CD Appr. date(s): 04/08 k OVM = Organic Vapor Met ppm = parts per million BGT Sidewalls Visible: Y / M BGT Sidewalls Visible: Y / M	B/17/17 ES W10 B/16 Pr
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL			H. = WELL HEAD;	BGT Sidewalls Visible: Y / Magnetic declination: 10	
APPLICABLE OR NOT AVAILABLE; SW - SINGLE	WALL; DW - DOUBLE WALL; SB - SINGLE BOTT	OM; DB - DOUBLE BOTTOM.		agnetic declination: 10	<u> </u>
NOTES: GOOGLE EARTH IMAGE	ERT DATE: 3/15/2015.	ONSITE: 08/17/17	1		

revised: 11/26/13

BEI1005E-6.SKF

Analytical Report
Lab Order 1708B14
Date Reported: 8/21/2017

Hall Environmental Analysis Laboratory, Inc.

.

 CLIENT:
 Blagg Engineering
 Client Sample ID: 21 BGT 5-pt @ 6'

 Project:
 ATLANTIC A LS 5
 Collection Date: 8/17/2017 10:37:00 AM

 Lab ID:
 1708B14-001
 Matrix:
 SOIL
 Received Date: 8/18/2017 7:00:00 AM

 Analyses
 Result
 PQL
 Qual
 Units
 DF
 Date Analyzed
 Batch

 EPA METHOD 300.0: ANIONS
 Analyst:
 MRA

EPA METHOD 300.0: ANIONS					Analyst:	MRA
Chloride	ND	30	mg/Kg	20	8/18/2017 12:35:09 PM	33427
EPA METHOD 8015M/D: DIESEL RANGE	ORGANIC	S			Analyst:	TOM
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	8/18/2017 9:27:36 AM	33442
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	8/18/2017 9:27:36 AM	33442
Surr: DNOP	95.3	70-130	%Rec	1	8/18/2017 9:27:36 AM	33442
EPA METHOD 8015D: GASOLINE RANGE					Analyst:	NSB
Gasoline Range Organics (GRO)	ND	3.6	mg/Kg	1	8/18/2017 10:00:15 AM	33428
Surr: BFB	78.5	54-150	%Rec	1	8/18/2017 10:00:15 AM	33428
EPA METHOD 8021B: VOLATILES					Analyst:	NSB
Benzene	ND	0.018	mg/Kg	1	8/18/2017 10:00:15 AM	33428
Toluene	ND	0.036	mg/Kg	1	8/18/2017 10:00:15 AM	33428
Ethylbenzene	ND	0.036	mg/Kg	1	8/18/2017 10:00:15 AM	33428
Xylenes, Total	ND	0.072	mg/Kg	1	8/18/2017 10:00:15 AM	33428
Surr: 4-Bromofluorobenzene	106	66.6-132	%Rec	1	8/18/2017 10:00:15 AM	33428

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method Blank
D	Sample Diluted Due to Matrix	E	Value above quantitation range
Н	Holding times for preparation or analysis exceeded	J	Analyte detected below quantitation limits Page 1 of 5
ND	Not Detected at the Reporting Limit	Р	Sample pH Not In Range
PQL	Practical Quanitative Limit	RL	Reporting Detection Limit
S	% Recovery outside of range due to dilution or matrix	W	Sample container temperature is out of limit as specified
	ND	 D Sample Diluted Due to Matrix H Holding times for preparation or analysis exceeded ND Not Detected at the Reporting Limit PQL Practical Quanitative Limit 	DSample Diluted Due to MatrixEHHolding times for preparation or analysis exceededJNDNot Detected at the Reporting LimitPPQLPractical Quanitative LimitRL

X SI	Date: Time: Relinquished by:			11/2017 1037 SOIL 21 5-PE @ 6'	8	EDD (Type)	Accreditation	QA/QC Package: Standard D Level 4 (Full Validation)	email or Fax#:	Phone # (505) 320 - 1183		Mailing Address:	HVHENCA	Client 2 P A 4 4
All A L L La Received by:	Received by:			4 02 × 1 (000	Jog ((g/r) Container Type and # MccHlcd	Sample Temperature	Sampler: JEFF Bu On Ice: XYes	STEVE N	Project Manager:		Project #:	ATLANTIC A	Project Name:	Time
This serves as notice of this	Date Time			201	Preservative Type 17/07 B/4	e // .	Burger s INO	Moskac				5 s7 h	X Rush	SAME DAT
VID: VHXONEVSZ REF: P-674				×	BTEX + MT	-								
possibility. An			_		BTEX + MT						Tel.	490		
VID: REF: Vsub-contr				×	TPH 8015B TPH (Metho	-		RO / M	RO)		Tel. 505-345-3975	www.h 4901 Hawkins NE		
ontracte			-	-	EDB (Metho						345-	ww	A	H
VHIXONEVBZ P- 674					PAH's (831)	-		SIMS)				NE NE	NALYSIS	Ê
HIXONE P- 674					RCRA 8 Me					Analysis		- Alt	K	m
e dear					Anions (F,C	I,NC	D ₃ ,NO ₂	,PO ₄ ,S	04)	ysis	Fax	/iron	SI	Z
EVBZ 1					8081 Pestic	ides	8 / 8082	PCB's	6	Req	505-	ment		ļ
ted on					8260B (VOA	4)				Request	345	www.hallenvironmental.com	A	õ
Jrek the analy					8270 (Semi-		A)		·		Fax 505-345-4107	environmental.com Albuquerque. NM 87109	LABORATORY	ENVIRONMENTAL
alytica				X	CHLORID	E						109	RA	
al report.				 _									T	TN
5			 										R	À.
	-+-				Air Bubbles	(Y c	or N)		_				4	-

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering Project: ATLANTIC A LS 5

Sample ID MB-33427	SampType: mblk	TestCode: EPA Method	300.0: Anions	
Client ID: PBS	Batch ID: 33427	RunNo: 45054		
Prep Date: 8/17/2017	Analysis Date: 8/18/2017	SeqNo: 1426881	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Chloride	ND 1.5			
Sample ID LCS-33427	SampType: Ics	TestCode: EPA Method	300.0: Anions	
Sample ID LCS-33427 Client ID: LCSS	SampType: Ics Batch ID: 33427	TestCode: EPA Method RunNo: 45054	300.0: Anions	
	1 31		300.0: Anions Units: mg/Kg	
Client ID: LCSS	Batch ID: 33427 Analysis Date: 8/18/2017	RunNo: 45054		RPDLimit Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

WO#: 1708B14

21-Aug-17

Page 2 of 5

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

Client:Blagg EngineeringProject:ATLANTIC A LS 5

Sample ID LCS-33442	SampType: LCS	TestCode: EPA Method	8015M/D: Diesel Range	Organics
Client ID: LCSS	Batch ID: 33442	RunNo: 45040		
Prep Date: 8/18/2017	Analysis Date: 8/18/2017	SeqNo: 1426068	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD I	RPDLimit Qual
Diesel Range Organics (DRO)	47 10 50.00	0 93.6 73.2	114	
Surr: DNOP	4.4 5.000	87.4 70	130	
Sample ID MB-33442	SampType: MBLK	TestCode: EPA Method	8015M/D: Diesel Range (Organics
Client ID: PBS	Batch ID: 33442	RunNo: 45040		
Prep Date: 8/18/2017	Analysis Date: 8/18/2017	SeqNo: 1426069	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD I	RPDLimit Qual
Diesel Range Organics (DRO)	ND 10			
Motor Oil Range Organics (MRO)	ND 50			
Surr: DNOP	9.9 10.00	99.3 70	130	
Sample ID LCS-33429	SampType: LCS	TestCode: EPA Method	8015M/D: Diesel Range (Drganics
Client ID: LCSS	Batch ID: 33429	RunNo: 45041		
Client ID: LCSS Prep Date: 8/17/2017	Batch ID: 33429 Analysis Date: 8/18/2017	RunNo: 45041 SeqNo: 1426491	Units: %Rec	
	Analysis Date: 8/18/2017			RPDLimit Qual
Prep Date: 8/17/2017	Analysis Date: 8/18/2017	SeqNo: 1426491		RPDLimit Qual
Prep Date: 8/17/2017 Analyte	Analysis Date: 8/18/2017 Result PQL SPK value	SeqNo: 1426491 SPK Ref Val %REC LowLimit 95.0 70	HighLimit %RPD F	
Prep Date: 8/17/2017 Analyte Surr: DNOP	Analysis Date: 8/18/2017 Result PQL SPK value 4.8 5.000	SeqNo: 1426491 SPK Ref Val %REC LowLimit 95.0 70	HighLimit %RPD F 130	
Prep Date: 8/17/2017 Analyte Surr: DNOP Sample ID MB-33429	Analysis Date: 8/18/2017 Result PQL SPK value 4.8 5.000 SampType: MBLK	SeqNo: 1426491 SPK Ref Val %REC LowLimit 95.0 70 TestCode: EPA Method	HighLimit %RPD F 130	
Prep Date: 8/17/2017 Analyte Surr: DNOP Sample ID MB-33429 Client ID: PBS	Analysis Date: 8/18/2017 Result PQL SPK value 4.8 5.000 SampType: MBLK Batch ID: 33429 Analysis Date: 8/18/2017	SeqNo: 1426491 SPK Ref Val %REC LowLimit 95.0 70 TestCode: EPA Method RunNo: 45041	HighLimit %RPD F 130 8015M/D: Diesel Range C Units: %Rec	

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

1708B14

WO#:

Page 3 of 5

21-Aug-17

Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering Project: ATLANTIC A LS 5

8

Sample ID MB-33428	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Range	
Client ID: PBS	Batch ID: 33428	RunNo: 45051		
Prep Date: 8/17/2017	Analysis Date: 8/18/2017	SeqNo: 1427171	Units: mg/Kg	
Analyte	Result PQL SPK va	ue SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLin	nit Qual
Gasoline Range Organics (GRO)	ND 5.0			
Surr: BFB	820 10	00 82.2 54	150	
Sample ID LCS-33428	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Range	
Client ID: LCSS	Batch ID: 33428	RunNo: 45051		
Prep Date: 8/17/2017	Analysis Date: 8/18/2017	SeqNo: 1427173	Units: mg/Kg	
Analyte	Result PQL SPK val	ue SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLim	nit Qual
Gasoline Range Organics (GRO)	24 5.0 25.	0 0 94.3 76.4	125	
Surr: BFB	930 10	93.4 54	150	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 4 of 5

WO#: 1708B14

21-Aug-17

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

Client:Blagg EngineeringProject:ATLANTIC A LS 5

tCode: EPA Method 8021B: Volatiles
RunNo: 45051
SeqNo: 1427275 Units: mg/Kg
%REC. LowLimit HighLimit %RPD RPDLimit Qual
114 66.6 132
tCode: EPA Method 8021B: Volatiles
RunNo: 45051
SeqNo: 1427276 Units: mg/Kg
%REC LowLimit HighLimit %RPD RPDLimit Qual
%REC LowLimit HighLimit %RPD RPDLimit Qual
%REC LowLimit HighLimit %RPD RPDLimit Qual 104 80 120
%REC LowLimit HighLimit %RPD RPDLimit Qual 104 80 120 103 80 120

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

1708B14 21-Aug-17

WO#:

Page 5 of 5

ANALY	ONMENTAL SIS Atory	Hall Environmental Albu Albu TEL: 505-345-3975 Website: www.hal	4901 Hawkin guergue, NM 8 FAX: 505-345-	7109 S	am	ple Log-In Check List
Client Name:	BLAGG	Work Order Number:	1708B14			RcptNo: 1
Received By:	Anne Thome	8/18/2017 7:00:00 AM		Anne . Anne .	Am	~
Completed By:	Anne Thome	8/18/2017 7:40:07 AM		am	Am	
Reviewed By:	N 8/16/17					
Chain of Cust	ody					
1. Custody seals	s intact on sample bottles?		Yes	No		Not Present
2. Is Chain of Cu	ustody complete?		Yes 🗹	No		Not Present
3. How was the	sample delivered?		<u>Courier</u>			
Log In						
4. Was an atterr	npt made to cool the samples	?	Yes 🗹	No		NA 🗆
5. Were all same	oles received at a temperature	e of ≥0° C to 6.0°C	Yes 🗹	No		NA 🗀
6. Sample(s) in	proper container(s)?		Yes 🗹	No		
7. Sufficient sam	ple volume for indicated test(s)?	Yes 🗹	No		
8. Are samples (except VOA and ONG) prope	rly preserved?	Yes 🗹	No		
9. Was preserva	tive added to bottles?		Yes	No		NA 🗔
10. VOA vials hav	e zero headspace?		Yes	No		No VOA Viais 🗹
11. Were any san	nple containers received brok	en?	Yes	No		# of preserved
	ork match bottle labels? ancies on chain of custody)		Yes 🗹	No		bottles checked for pH: (<2 or >12 unless noted)
13. Are matrices of	correctly identified on Chain of	f Custody?	Yes 🗹	No		Adjusted?
14. Is it clear what	t analyses were requested?		Yes 🗹	No	_	
	ng times able to be met? ustomer for authorization.)		Yes 🗹	No		Checked by:
Special Handli	ng (if applicable)					
16, Was client not	ified of all discrepancies with	this order?	Yes	No		NA 🗹

Person Notified:	Date
By Whom:	Via: eMail Phone Fax In Person
Regarding:	
Client Instructions:	

17. Additional remarks:

4

18. Cooler Information

Cooler No	Temp °C	Condition	Seal Intact	Seal No	Seal Date	Signed By
1	1.3	Good	Yes			

Page 1 of 1



