District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

<u>Pit, Below-Grade Tank, or</u> <u>Proposed Alternative Method Permit or Closure Plan Application</u>

Type of action: Below grade tank registration

Santa Fe, NM 87505

Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: FLORANCE M 047A
0004500004
API Number: 3004522021 OCD Permit Number:
Center of Proposed Design: Latitude 36.836968 Longitude -107.801449 NAD83
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC BGT Closure left Submitted Pit: Subsection F, G or J of 19.15.17.11 NMAC BGT Closure left Submitted Temporary: Drilling Workover Workover left Submitted Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. TANK B Below-grade tank: Subsection I of 19.15.17.11 NMAC
Volume: 21bbl Type of fluid: Produced Water
Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other Single wall/ Double bottom; sidewalls not visible
Liner type: Thicknessmil
4.
Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)
Four foot height, four strands of barbed wire evenly spaced between one and four feet
Alternate. Please specify

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 No. Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doct attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 15.17.9 NMAC
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doct attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	15.17.9 NMAC

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	□ Vas□ Na
Within a 100-year floodplain.	Yes No
- FEMA map	163 110
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believes	ief.
Name (Print):	
Signature: Date:	
e-mail address: Date: Telephone:	
e-mail address:	s the closure report.
e-mail address: Telephone:	s the closure report.
e-mail address: Telephone:	the closure report.

22. Operator Closure Certification:	
	ted with this closure report is true, accurate and complete to the best of my knowledge and able closure requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Signature:Utin garifalos	Date: October 30, 2017
e-mail address: erin.garifalos@bp.com	Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

FLORANCE M 047A

API No. 3004522021

Unit Letter J Section 05 T 30N R 09W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.017
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.067
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<49
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The area will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled. The area will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled. The area will be reclaimed when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled. The area will be reclaimed when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled. The area will be reclaimed when the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

BP did not meet the 60 closure completion requirement due to an error in internal tracking. Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-141 Revised April 3, 2017 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

						OPERA	ГOR		Initia	al Report		Final Repor
Name of Co	mpany BP	America Produc	tion Compar	ny		Contact Erin (
		t, Farmington, N	M 87401				No. (832) 609-7048					
Facility Na	me FLORAN	CE M 047A				Facility Typ	e: Natural Gas Wel	II				
Surface Ow	ner: Federal	I		Mineral C)wner: F	Federal			API No	. 3004522021		
				LOCA	TION	OF RE	LEASE					
Unit Letter	Section	Township	Range	Feet from the	North/	South Line	Feet from the	East/V	Vest Line	County		1
J 05 30N 09W 1,505 South 1,820 East San J											Juan	
			Latitud	e 36.836968	Lo	ongitude1	07.801449	NAD	33			
				NAT	URE	OF REL	EASE					
Type of Rele	ase:: none)					Release:: unkno			Recovered::		
Source of Re	lease: belo	w grade ta	nk - 21 l	obl		Date and H	Iour of Occurrence	e:	Date and n/a	Hour of Disc	covery:	
Was Immedi	ate Notice (Yes	No Not Re	equired	If YES, To	Whom?					
By Whom?						Date and H	lour					
Was a Water	course Read		Yes 🗌	No		If YES, Vo	lume Impacting t	the Wate	ercourse.			
		pacted, Descri										
		em and Reme		Samı Soil a closu	analys	is resulte	beneath the d for Chlorid Field reports	les, B	TEX, ar	nd TPH b	elow	BGT
Describe Are	a Affected	and Cleanup A	Action Tak	No actio		essary. F n is requ	inal laborato ired.	ory ar	alysis d	determine	ed no)
regulations a public health should their or the enviro	Il operators or the environment. In a	are required to ronment. The lave failed to a	o report an acceptance adequately OCD accept	d/or file certain r e of a C-141 repo investigate and r	elease no ort by the emediate	otifications are NMOCD m e contaminati	knowledge and und perform correctarked as "Final Roon that pose a three the operator of the correction	etive acti eport" de eat to gr	ons for rele oes not reli ound water	eases which releve the operate, surface wat	may end ator of ter, hun	danger liability nan health
							OIL CON	SERV	ATION	DIVISIO	N	
Signature:	oun g	Willale	4			A 1.1	Ei	!-1'				
Signature:	Erin G	arifalos			-	Approved by	Environmental S	pecialist	:			
		onmenta		dinator		Approval Dat	e:	I	Expiration l	Date:		
E-mail Addre	ess: erin.	garifalos	@bp.	com	Conditions of Approval:							
Date: Octob				(832) 609-7048						Attached		
Attach Addi	tional Shee	ets If Necess	ary									

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

August 4, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: FLORANCE M 47A

API#: 3004522021

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about August 10, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

Garifalos, Erin

From:

Buckley, Farrah (CH2M HILL)

Sent:

Friday, August 04, 2017 6:40 AM

To:

'Smith, Cory, EMNRD'; 'Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)';

'brandon.powell@state.nm.us'

Cc:

'jeffcblagg@aol.com'; 'blagg_njv@yahoo.com'; Moskal, Steven; Garifalos, Erin

Subject:

BP Pit Close Notification - FLORANCE M 047A

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

August 4, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

FLORANCE M 47A API 30-045-22021 (J) Section 5– T30N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT and a 21bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around August 10, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator (505) 326-9497

Farrah Buckley
BGT Project Support
970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP		ENGINEERING, IN BLOOMFIELD, NN		API#: 3004522	
	(50	05) 632-1199		TANK ID (if applicble):	}
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / O	THER:	PAGE#: 1 c	of
SITE INFORMATION	: SITE NAME: FLORA	NCE M #47A		DATE STARTED: 08/2	21/17
QUAD/UNIT: J SEC: 5 TWP:	30N RNG: 9W PM	: NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4 - 1/4/FOOTAGE: 1,505'S / 1,8 LEASE #: SF078316		TYPE: FEDERAL STATE / STRIKE CONTRACTOR: BP - J. GO		ENVIRONMENTAL SPECIALIST(S):	JV
REFERENCE POINT		s coord.: 36.8370		CLEIEV: 6	205'
1) 21 BGT (SW/DB) - B	GPS COORD.: 36.			RING FROM W.H.:104', S7	
2)					
3)				RING FROM W.H.:	
,	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) #	OR LAB USED: HALL			OVM READING
1) SAMPLE ID: 5PC - TB @ 6' (2			LAB ANALYSIS: 801	15B/8021B/300.0 (CI)	(ppm)
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
3) SAMPLE ID: 4) SAMPLE ID:	SAMPLE DATE:		LAB ANALYSIS:		
5) SAMPLE ID:		SAMPLE TIME:			
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND	SILT / SILTY CLAY / CLAY / GRAVE	/ OTHER		
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLY MOIST/WOIST/WOIST/W SAMPLE TYPE: GRAB (COMPOSITE) # DISCOLORATION/STAINING OBSERVED: YES N	OOSE FIRM DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED OF PTS	HC ODOR DETECTED: YES NO ANY AREAS DISPLAYING WETNES	SILTS): SOFT / FIRM / EXPLANATION -	STIFF / VERY STIFF / HARD	HLY PLASTIC
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE					
EQUIPMENT SET OVER RECLAIMED AREA:		LANATION:			
OTHER: NMOCD OR BLM NOT PRESENT	TO WITNESS CONFIRMATION	SAMPLING.			
EXCAVATION DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA ft.	EXCAVATION EST	TIMATION (Cubic Yards) :	NA
DEPTH TO GROUNDWATER: >100' N	EAREST WATER SOURCE: >1,000)' NEAREST SURFACE WATER: _	<1,000' NMOC	CD TPH CLOSURE STD:1,0	00 ppm
SITE SKETCH	BGT Located: off on si	te PLOT PLAN circl	e: attached 0VM	CALIB. READ. = NA pp	m RF =1.00
		TO	N TIME	CALIB. GAS = NA PP : NA am/pm DATE: MISCELL. NO	NA NA
(21)-	В	W.H.	_	/O: EF #: P-837	
PBĞ T.B. ↑	TL	— FENCE		ID: VHIXONEVB2)
B.G	/ (J#:	
		BERM	Pe	ermit date(s): 06/0	3/10
				CD Appr. date(s): 05/0	1/17
	PROD. TANK		Tan	ppm = parts per million	
			В	BGT Sidewalls Visible: Y /	
			- S.P.D.	BGT Sidewalls Visible: Y /	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL				BGT Sidewalls Visible: Y /	
APPLICABLE OR NOT AVAILABLE; SW - SINGLI	WALL; DW - DOUBLE WALL; SB - SINGLE BO		M. Marine M. C. Marine M. M. Marine M.	lagnetic declination: 10	<u> </u>
NOTES: GOOGLE EARTH IMAGI	RY DATE: 10/5/2016.	ONSITE: 08/21/1	7		

Analytical Report

Lab Order 1708C10

Date Reported: 8/25/2017

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 6' (21)-B

Project: FLORANCE M #47A

Collection Date: 8/21/2017 12:55:00 PM

Lab ID: 1708C10-002

Matrix: SOIL

Received Date: 8/22/2017 7:00:00 AM

Analyses	Result	PQL Qu	ual Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst:	MRA
Chloride	ND	30	mg/Kg	20	8/22/2017 11:33:07 AM	33484
EPA METHOD 8015M/D: DIESEL RANG	E ORGANICS	6			Analyst:	TOM
Diesel Range Organics (DRO)	ND	9.8	mg/Kg	1	8/22/2017 11:45:58 AM	33482
Motor Oil Range Organics (MRO)	ND	49	mg/Kg	1	8/22/2017 11:45:58 AM	33482
Surr: DNOP	101	70-130	%Rec	1	8/22/2017 11:45:58 AM	33482
EPA METHOD 8015D: GASOLINE RAN	GE				Analyst:	NSB
Gasoline Range Organics (GRO)	ND	3.4	mg/Kg	1	8/22/2017 9:55:51 AM	33464
Surr: BFB	86.0	54-150	%Rec	1	8/22/2017 9:55:51 AM	33464
EPA METHOD 8021B: VOLATILES					Analyst:	NSB
Benzene	ND	0.017	mg/Kg	1	8/22/2017 9:55:51 AM	33464
Toluene	ND	0.034	mg/Kg	1	8/22/2017 9:55:51 AM	33464
Ethylbenzene	ND	0.034	mg/Kg	1	8/22/2017 9:55:51 AM	33464
Xylenes, Total	ND	0.067	mg/Kg	1	8/22/2017 9:55:51 AM	33464
Surr: 4-Bromofluorobenzene	122	66.6-132	%Rec	1	8/22/2017 9:55:51 AM	33464

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
 - V Sample container temperature is out of limit as specified

CI	nain-c	of-Cus	stody Record	Turn-Around	Time:	SAME				н	ΔI		FN	VT	RO	NI	ME	NT	TA I	Į	
Client:	BLAG	G ENGR	/ BP AMERICA	☐ Standard	Rush _	DAY)												ATO			
				Project Name						٧	vww	.hall	envir	onm	enta	l.cor	n				
Mailing A	ddress:	P.O. BO	X 87	FLC	DRANCE M	# 47A		49	01 H	awki	ns Ni	E - /	Albuq	uero	ue, l	NM 8	3710	9			
		BLOOM	FIELD, NM 87413	Project #:				Те	1. 50	5-34	5-39	75	Fax	505	-345	-410	7				
Phone #:		(505) 63	2-1199									An	alysi	s Re	que	st					
email or F	ax#:			Project Manag	ger:						Т	Т	1		T		300.1)		T	\top	
QA/QC Pa	_		Level 4 (Full Validation)		NELSON V	ELEZ	WB's (8021B)	+ MTBE + TPH (Gas only)	/ MRO)		5	(2)	PO4.SO	PCB's			water - 300			ø	
Accreditat	tion:			Sampler:	NELSON V	ELEZ ny	35	(Ga	SRO RO	1	F	<u>S</u>	0	3082			/ wa			sample	
□ NELAF	•	□ Other	**************************************	On lice	KYes -	E ANo.≛	1	TPH	1/0	418.	50	8270SIIMIS)	0	8/8		(A)	300.0 /			e sa	S
	уре)	T		Sample Temp	erature /	位于"是"等等	1	3E +	(GR	pod	pod	0	C.S.	cide	18	i-VC	- li		e	osit	3
Date	Time	Matrix	Sample Request ID	Container Type and # MINHET	Preservative Type	HEALING TO	BTEX +-N#F	BTEX + MT	TPH 8015B (GRO / DRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or	Anions (F.Cl. NO. NO. PO. SO.)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil -			5 pt. composite	Air Bubbles (Y or N)
8/4/1	1615	SOIL	570-10@ 6 (35)-A	4021	Cooi	1	4		-					-	-		J		<u> </u>	-	
1-1.7	78.3		6 (10)	402.		100	-			+	+	+	+	+	-	-		\vdash	+	-	\dashv
8/21/17	1255	SOIL	5PC-TB@ 6 '(21)-B	4 oz 1	Cool	702	٧		٧		-	+					٧		1	٧	
											+	1	+		F				#	1	
																			\pm	#	
											1	\pm							\pm	1	
		,								+	+	+	+	+	-				+	+	\dashv
											1	\dagger	+	T				\Box	\top	+	\neg
Date:	Time:	Relinquish	Mary	Received by:	I Wast	Date Time			ACT:	& REF	E MC	SKA	IEN AP	PLICA	BLE;		VITH C	CORRES	POND	ING	VID
Pate:	1832	Chr	mitted to Hall Environmental may be sul	4	accredited laboratorie	1 08/22/17	кет	eren	ce#	-	P - 83	37_	lata wil	i be cle	early no	otated	on the	analyti	ical re	oort.	

Hall Environmental Analysis Laboratory, Inc.

WO#:

1708C10

25-Aug-17

Qual

Client:

Blagg Engineering

Project:

FLORANCE M #47A

Sample ID MB-33484

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 33484

RunNo: 45131

Prep Date:

Analysis Date: 8/22/2017

Analyte

8/22/2017

SeqNo: 1429509

Units: mg/Kg

%RPD

HighLimit

Chloride

Result PQL ND 1.5

Sample ID LCS-33484

SampType: Ics

TestCode: EPA Method 300.0: Anions

LowLimit

90

Batch ID: 33484

RunNo: 45131

Prep Date: 8/22/2017

Client ID: LCSS

Analysis Date: 8/22/2017

SeqNo: 1429510

Units: mg/Kg

Analyte

SPK value SPK Ref Val %REC PQL 1.5

%RPD **RPDLimit** Qual

RPDLimit

15.00

HighLimit 110

Chloride

14

0

SPK value SPK Ref Val %REC LowLimit

92.9

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Practical Quanitative Limit PQL
- % Recovery outside of range due to dilution or matrix
- В Analyte detected in the associated Method Blank
- E Value above quantitation range
- Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Page 4 of 9

Hall Environmental Analysis Laboratory, Inc.

WO#:

1708C10

25-Aug-17

Client:

Blagg Engineering

Project:

FLORANCE M #47A

Sample ID LCS-33482	SampType:	LCS	Tes	tCode: El	PA Method	8015M/D: Di	esel Rang	e Organics		
Client ID: LCSS	Batch ID: 33482 RunNo: 45119									
Prep Date: 8/22/2017	Analysis Date:	8/22/2017	SeqNo: 1428873 Units: mg/Kg							
Analyte	Result PC	L SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Diesel Range Organics (DRO)	45	10 50.00	0	90.0	73.2	114				
Surr: DNOP	4.7	5.000		93.9	70	130				

Sample ID MB-33482	SampType: MBLK			TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: PBS	Batch ID: 33482			F	RunNo: 4	5119				
Prep Date: 8/22/2017	Analysis Date: 8/22/2017			SeqNo: 1428874			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	9.0		10.00		90.4	70	130			

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 5 of 9

Hall Environmental Analysis Laboratory, Inc.

WO#:

1708C10

25-Aug-17

Client:

Blagg Engineering

Project:

FLORANCE M #47A

Sample ID MB-33464

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

PBS

Batch ID: 33464

RunNo: 45126

Analyte

PQL

PQL

5.0

5.0

SPK value SPK Ref Val

SPK value SPK Ref Val

Prep Date: 8/21/2017

Analysis Date: 8/22/2017

SeqNo: 1429028

%REC LowLimit

Units: mg/Kg

150

HighLimit

Qual

Gasoline Range Organics (GRO)

Surr: BFB

ND 900

1000

89.8

54

%RPD **RPDLimit**

%RPD

Sample ID LCS-33464

LCSS

8/21/2017

SampType: LCS

Result

TestCode: EPA Method 8015D: Gasoline Range

RunNo: 45126

LowLimit

Prep Date:

Client ID:

Batch ID: 33464

Analysis Date: 8/22/2017

SeqNo: 1429029

%REC

Units: mg/Kg

RPDLimit

Qual

Analyte Gasoline Range Organics (GRO) Surr: BFB

24 980

Result

25.00 1000 97.3 98.4 76.4 54 125 150

HighLimit

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- Η Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- В Analyte detected in the associated Method Blank
- E Value above quantitation range
- Analyte detected below quantitation limits J
- P Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Page 6 of 9

Hall Environmental Analysis Laboratory, Inc.

WO#:

1708C10

25-Aug-17

Client:

Blagg Engineering

Project:

FLORANCE M #47A

Sample ID MB-33464	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batch ID: 33464			RunNo: 45126						
Prep Date: 8/21/2017	Analysis Date: 8/22/2017			SeqNo: 1429043			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.3		1.000		127	66.6	132			

Sample ID LCS-33464	SampType: LCS			TestCode: EPA Method 8021B: Volatiles						
Client ID: LCSS	Batch	n ID: 33	464	RunNo: 45126						
Prep Date: 8/21/2017	Analysis Date: 8/22/2017			SeqNo: 1429044			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.025	1.000	0	109	80	120			
Toluene	1.1	0.050	1.000	0	108	80	120			
Ethylbenzene	1.1	0.050	1.000	0	107	80	120			
Xylenes, Total	3.3	0.10	3.000	0	110	80	120			
Surr: 4-Bromofluorobenzene	1.3		1.000		131	66.6	132			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 7 of 9



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Cli	ent Name:	BLAGG		Work Order N	lumber:	1708C10)	RcptNo	o: 1
Rec	ceived By:	Anne T	horne	8/22/2017 7:00	MA 00:		Am. St. Am. St.		*
Cor	mpleted By:	Anne T	home	8/22/2017 7:14	:49 AM		Om Il		
Rev	riewed By:	DDS	8-22-17				0,714 277		
<u>Cha</u>	nin of Cus	stody							
1.	Custody sea	als intact or	n sample bottles?	•		Yes [No □	Not Present ✓	
2.	Is Chain of 0	Custody co	implete?			Yes 🗸	No 🗌	Not Present	
3.	How was the	e sample d	lelivered?			Courier			
Lo	g In		¥						
4.	Was an atte	empt made	to cool the same	oles?		Yes 🗸	No 🗆	NA 🗆	
5. Were all samples received at a temperature of >0° C to 6.0°C							No 🗆	NA 🗆	
6.	Sample(s) in	n proper co	ontainer(s)?			Yes 🗹	No 🗆		
7.	Sufficient sa	mple volur	me for indicated t	est(s)?		Yes 🗹	No 🗆		
8.	Are samples	(except V	OA and ONG) pr	operly preserved?		Yes 🗸	No 🗆		
9.	Was preserv	vative adde	ed to bottles?			Yes	No ✓	NA 🗆	
10.	VOA vials ha	ave zero he	eadspace?			Yes	No 🗆	No VOA Vials	
11.	Were any sa	ample cont	tainers received t	roken?		Yes	No ✓	# of preserved	
			bottle labels?			Yes 🗸	No 🗆	bottles checked for pH:	
			chain of custody				w- 🗆	(<2 Adjusted?	or >12 unless noted)
			identified on Chai	-		Yes 🗸	_	rajuotou	
			s were requested	7		Yes ₩		Checked by:	
		_	able to be met? for authorization.)			res 💌	NO L	Onound by.	
Spe	cial Hand	lling (if a	pplicable)						
			Il discrepancies v	vith this order?		Yes 🗌	No 🗆	NA 🗹	
	Persor	Notified:	The comments of the comments o		Date	MINISTER BASSAGE		•	7
	By Wh	om:	Authoration and authorities	CONTRACTOR	√ia: [eMail	Phone Fax	In Person	
	Regard	ding:							
	Client	Instructions	s:	TOTAL COLUMN ACTUAL ACT	MEZI JEZISOVE MISISHO	- CONTRACTOR - CON			
17.	Additional re	emarks:							
18.	Cooler Info	rmation							
	Cooler No			Seal Intact Seal I	No S	eal Date	Signed By	_	
	1	1.0	Good	Yes			***************************************		



