<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II

1000 Rio Brazos Road, Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Hobbs, NM 88240

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
of action: Relow grade tank registration

Santa Fe, NM 87505

Proposed Alternative Method Permit or Closure Plan Application									
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,									
or proposed alternative method									
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative reque	4								
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regular to comply with any other applicable governmental authority's rules, regular to comply with any other applicable governmental authority's rules, regular to comply with any other applicable governmental authority's rules, regular to comply with any other applicable governmental authority's rules, regular to comply with any other applicable governmental authority's rules, regular to comply with any other applicable governmental authority's rules, regular to comply with any other applicable governmental authority's rules, regular to comply with any other applicable governmental authority of the comply with any other applicable governmental authority of the comply with any other applicable governmental authority of the comply with any other applicable governmental authority of the comply with any other applicable governmental authority of the comply with any other applicable governmental authority of the comply with any other applicable governmental authority of the complex of the c	lations or ordinances.								
Operator: Di Vittorio di Vocado dell'o Stripari	DIV DIST. 3								
Address: 200 Energy Court, Farmington, NM 87401	1 2017								
Facility or well name: RIDDLE B 1 002									
API Number: 3004527461 OCD Permit Number:									
API Number: 3004527461 OCD Permit Number: U/L or Qtr/Qtr									
Center of Proposed Design: Latitude 36.881700 Longitude -107.773086 NAD83									
Surface Owner: Federal State Private Tribal Trust or Indian Allotment									
2. □ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: □ Drilling □ Workover □ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management □ Low Chloride Drilling Fluid □ yellow □ Lined □ Unlined □ Liner type: Thickness mil □ LLDPE □ HDPE □ PVC □ Other □ String-Reinforced □ String-Reinforced Unlined □ Volume: □ bbl □ Dimensions: □ x W									
Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A									
Volume: 45 bbl Type of fluid: Produced Water									
Tank Construction material: Steel									
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off									
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other Single wall/ Double bottom; sidewalls not visible									
Liner type: Thickness mil HDPE PVC Other									
Alternative Method:									
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for considerate	tion of approval.								
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	l, hospital,								

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)								
informing inspections (if netting of screening is not physically reasible)								
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC								
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.								
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.								
General siting								
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No							
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No							
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No							
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No							
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No							
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No							
Below Grade Tanks								
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)								
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No							
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image								
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300 feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Temporary Pit Non-low chloride drilling fluid										
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site										
Vithin 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image										
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site										
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Permanent Pit or Multi-Well Fluid Management Pit										
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No									
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:										
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC										
Previously Approved Design (attach copy of design) API Number: or Permit Number:	-									

Internations: Each of the following items must be attacked to the application. Please indicate, by a check mark in the box, that the documents are attacked.		
Proposed Closure: 19.15.17.13 NMAC Permanent Pit Below-grade Tank Multi-well Fluid Management Pit Market Permanent Pit Below-grade Tank Multi-well Fluid Management Pit Market Removal (Closed-loop systems only) Market Removal Closure Method (Only for temporary pits and closed-loop systems) Market Excavation and Removal Closure Method (Only for temporary pits and closed-loop systems) Market Excavation and Removal Closure Method (Only for temporary pits and closed-loop systems) Market Excavation and Removal Closure Method (Only for temporary pits and closed-loop systems) Market Excavation and Removal Closure Method (Only for temporary pits and closed-loop systems) Market Excavation and Removal Closure Method (Only for temporary pits and closed-loop systems) Market Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop systems) Market Method (Only for temporary pits and closed-loop s	Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.19 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fluid Management Pit Alternative Alternative Waste Excavation and Removal Waste Excavation and Removal Closed-loop systems only) Dro-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Tench Burial On-site Tench Burial On-site Tench Burial Alternative Closure Method Only for temporary pits and closed-loop systems In-place Burial On-site Tench Burial		
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation of Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation on Plan and Plan Reclamation of Subsection H of 19.15.17.13 NMAC Site Reclamation of Recla	Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial	luid Management Pit
Cosure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures' - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 25 feet below the bottom of the buried waste.		
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes \ No	closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes \ No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site		
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency.	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No Yes No No		
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site NA		
lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality □ Yes □ No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site □ Yes □ No	lake (measured from the ordinary high-water mark).	Yes No
at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No		☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes \sum No	at the time of initial application.	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes \sum No	Written confirmation or verification from the municipality: Written approval obtained from the municipality	☐ Yes ☐ No
☐ Yes ☐ No	Within 300 feet of a wetland.	
within incorporated municipal boundaries of within a defined municipal fresh water wen field covered under a municipal ordinance	Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	T									
	☐ Yes ☐ No									
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division - Yes										
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map □ Yes□ N										
Within a 100-year floodplain. FEMA map										
16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC										
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belong the complete to the complete to the best of my knowledge and belong the complete to the best of my knowledge and belong the complete to the complete to t										
Signature: Date:										
oignature										
e-mail address:										
e-mail address: Telephone:										
e-mail address: Telephone:	8 2017 g the closure report.									
e-mail address: Telephone:	8 2017 g the closure report.									
e-mail address: Telephone:	g the closure report.									

22. Operator Closure Certification:	
	nitted with this closure report is true, accurate and complete to the best of my knowledge and licable closure requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Signature: Utin garifialos	Date: November 17, 2017
e-mail address: erin.garifalos@bp.com	Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

RIDDLE B 1 002

API No. 3004527461

Unit Letter L Section 22 T 31N R 09W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	45 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.025
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.100
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<47
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

BP did not meet the 60 closure completion requirement due to an error in internal tracking. Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised April 3, 2017 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Final Report

☐ Initial Report

Release Notification and Corrective Action

OPERATOR

Name of Co				ту		Contact Erin Garifalos								
		t, Farmington, N	M 87401		_	Telephone No. (832) 609-7048								
Facility Nar	ne RIDDLE E	3 1 002				Facility Typ	e: Natural Gas We	II						
Surface Ow	ner : Federa			Mineral O	wner:	Federal			API No	.3004527461				
				LOCA	TIOI	N OF RE	LEASE							
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	200 200 200	West Line	County				
L	22	31N	09W	1,980	Sou	ıth	1,095	We	st	San Juan				
			Latitud	_e 36.881700	L	ongitude -1	07.773086	NAD	83					
						OF REL								
Type of Relea	ase:: none)					Release:: unkno			Recovered:: N/A				
Source of Re	lease: belo	w grade ta	nk - 45	obl		Date and H	lour of Occurrence	e:	Date and n/a	Hour of Discovery:				
Was Immedia	ate Notice (Yes	No Not Re	quired	If YES, To	Whom?							
By Whom?						Date and F	lour							
Was a Water	course Read		Yes	No		If YES, Vo	lume Impacting t	the Wate	ercourse.					
If a Watercou	rse was Im	pacted, Descr	ibe Fully.*											
Describe Cau	se of Proble	em and Reme	dial Action	Taken.*	olina d	of the soil	beneath the	BGT	was do	ne during removal.				
										nd TPH below BGT				
					-					ry results are attached.				
Describe Area	a Affected	and Cleanup A	Action Tak	en.* No action	n nec	ossary F	inal laborate	ory ar	nalveie n	determined no				
						n is requ		ory ar	iaiysis c	determined no				
				Torriodiai	aotio	ii io roqu	irou.							
										uant to NMOCD rules and				
										eases which may endanger eve the operator of liability				
										s, surface water, human health				
				tance of a C-141 i	report de	oes not reliev	e the operator of	responsi	ibility for co	ompliance with any other				
federal, state,	or local lav	ws and/or regu	nations.				OIL CONS	SERV	ATION	DIVISION				
0	Tin a	Willale	24				OIL COIN	OLICY	7111011	DIVISION				
Signature:	O	vrifale				Ammound have	Environmental C	1						
Printed Name	Erin G	arifalos				Approved by	Environmental S	pecialist						
Title: Field				dinator		Approval Dat	e:]	Expiration I	Date:				
E-mail Addre	ss: erin.	garifalos	@bp.	com		Conditions of	`Approval:		Attached					
Date: Novem	ber 17. 20	017	Phone	(832) 609-7048						Attached				
Date: November 17, 2017 Phone: (832) 609-7048 Attach Additional Sheets If Necessary														

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

September 18, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: RIDDLE B 1 002

API#: 3004527461

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about September 22, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From:

Buckley, Farrah (CH2M HILL)

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)

Cc:

jeffcblagg@aol.com; blagg_njv@yahoo.com; Garifalos, Erin

Subject: Date: BP Pit Close Notification - RIDDLE B 1 002 Monday, September 18, 2017 3:43:46 PM

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

September 18, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

RIDDLE B 1 002 API 30-045-27461 (L) Section 22– T31N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 45bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around September 22, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator – San Juan Cell: 832-609-7048

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

l`· RP	BLAGG ENGINEERING, INC.							
CLIENT:		LOOMFIELD, NM	187413	TANK ID	A			
	(50	5) 632-1199		(if applicble):	Α			
FIELD REPORT:	PAGE #: 1	of						
SITE INFORMATION	I: SITE NAME: RIDDLE	B1 #2		DATE STARTED: 09	9/21/17			
	0.111	NM CNTY: SJ	ST: NM	DATE FINISHED:				
1/4-1/4/FOOTAGE: 1,980'S / 1,0		YPE: FEDERAL STATE /						
111101001		STRIKE ONTRACTOR: BP - J. GO		ENVIRONMENTAL SPECIALIST(S):	NJV			
REFERENCE POINT	: WELL HEAD (W.H.) GPS	COORD.: 36.88190	0 X 107.77293	GL ELEV.:	6,271'			
1)45 BGT (SW/DB)	GPS COORD.: 36.8	381700 X 107.773086	DISTANCE/BEA	RING FROM W.H.: 91.5',	S38.5W			
2)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:				
3)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:				
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:				
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # C	OR LAB USED: HALL			OVM READING			
	(45) SAMPLE DATE: 09/21		I AR ANALYSIS: 80°	15B/8021B/300.0 (CI)	(ppm)			
	SAMPLE DATE:			, ,				
3) SAMPLE ID:			LAB ANALYSIS:					
	SAMPLE DATE:							
5) SAMPLE ID:	SAMPLE DATE:							
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND	SILT (SILTY CLAY) CLAY / GRAVE	L/OTHER					
	RATE BROWN	PLASTICITY (CLAYS): NON PLASTIC						
COHESION (ALL OTHERS): NON COHESIVE /SLIGHTL		DENSITY (COHESIVE CLAYS & S						
CONSISTENCY (NON COHESIVE SOILS): LO		HC ODOR DETECTED: YES NO	EXPLANATION -					
SAMPLE TYPE: GRAB (COMPOSITE) #		ANY AREAS DISPLAYING WETNES:	S: YES NO EXPLAN	NATION -				
DISCOLORATION/STAINING OBSERVED: YES								
SITE OBSERVATION	S: LOST INTEGRITY OF EQUIPMENT	YES NO EXPLANATION -						
APPARENT EVIDENCE OF A RELEASE OBSERVE	D AND/OR OCCURRED : YES NO EXPL	ANATION:						
EQUIPMENT SET OVER RECLAIMED AREA: OTHER: NMOCD OR BLM NOT PRESEN			ABOVE-GRADE TAI	NK TO BE SET ATOP BG	IT LOCATION.			
OTHER. NINOCO ON BLIM NOT FRESEN	TO WITHESS CONFIRMATION S	AMPLING.						
EXCAVATION DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA ft.	EXCAVATION EST	TIMATION (Cubic Yards) :	NA			
DEPTH TO GROUNDWATER: >100' N	EAREST WATER SOURCE: >1,000	NEAREST SURFACE WATER:	<1,000' NMOC	D TPH CLOSURE STD:	1,000 ppm			
SITE SKETCH	BGT Located: off on site	PLOT PLAN circl	e: attached 0VM	CALIB. READ. = NA	_ppm RF =1.00			
		1	▲ lovm	CALIB. GAS = NA	ppm 1(1 - 1.00			
		TO W.H. & PUMP JACK	N TIME		NA			
			· '\	MISCELL. NO	OTES			
			l		JILO			
	BERM		_	/O:				
	1 -	EF#: P-659 ID: VHIXONEV E	22					
	_	<u>ID: </u>	54					
	1 -		/02/10					
	1 -		/12/16					
10	Tar	nk OVM = Organic Vapor	Meter					
		D ppm = parts per million BGT Sidewalls Visible: Y /(N)						
				BGT Sidewalls Visible: Y				
NATES DOT DELONGO DE TANGES	ON DEDDESOION D. O. DELONIODADE D. D.		- S.P.D.	BGT Sidewalls Visible: Y				
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION T.B. = TANK BOTTOM: PBGTL = PREVIOUS BEL	ON DEPRESSION; B.G. = BELOW GRADE; B = BE .OW-GRADE TANK LOCATION; SPD = SAMPLE P		LILL NA MOT		10°E			
APPLICABLE OR NOT AVAILABLE; SW - SINGL	E WALL; DW - DOUBLE WALL; SB - SINGLE BOT	TOM; DB - DOUBLE BOTTOM.	10	iagnetic decimation.	10 L			
NOTES: GOOGLE EARTH IMAG	ERY DATE: 10/5/2016.	ONSITE: 09/11/1	7					

Analytical Report

Lab Order 1709C34

Date Reported: 9/27/2017

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC - TB @ 5' (45)

Project: Riddle B 1 #2

Collection Date: 9/21/2017 8:55:00 AM

Lab ID: 1709C34-001

Matrix: MEOH (SOIL) Received Date: 9/22/2017 7:40:00 AM

Analyses	Result	PQL Qua	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	MRA
Chloride	ND	30	mg/Kg	20	9/22/2017 11:20:01 AM	34018
EPA METHOD 8015M/D: DIESEL RANGE	ORGANICS	3			Analyst	TOM
Diesel Range Organics (DRO)	ND	9.3	mg/Kg	1	9/22/2017 10:17:22 AM	34015
Motor Oil Range Organics (MRO)	ND	47	mg/Kg	1	9/22/2017 10:17:22 AM	34015
Surr: DNOP	101	70-130	%Rec	1	9/22/2017 10:17:22 AM	34015
EPA METHOD 8015D: GASOLINE RANG	E				Analyst	NSB
Gasoline Range Organics (GRO)	ND	5.0	mg/Kg	1	9/22/2017 9:39:37 AM	33985
Surr: BFB	109	54-150	%Rec	1	9/22/2017 9:39:37 AM	33985
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.025	mg/Kg	1	9/22/2017 9:39:37 AM	33985
Toluene	ND	0.050	mg/Kg	1	9/22/2017 9:39:37 AM	33985
Ethylbenzene	ND	0.050	mg/Kg	1	9/22/2017 9:39:37 AM	33985
Xylenes, Total	ND	0.10	mg/Kg	1	9/22/2017 9:39:37 AM	33985
Surr: 4-Bromofluorobenzene	126	66.6-132	%Rec	1	9/22/2017 9:39:37 AM	33985

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Chain-of-Custody Record		SAME			HALL ENVIRONMENTAL											•						
Client:	Client: BLAGG ENGR. / BP AMERICA			☐ Standard	Rush _	DAY)			ANALYSIS LABORATORY													
		-		Project Name															111	JR	K T	
Mailing A	ddress:	P.O. BO	¥ 97	RIDDLE B 1 # 2			www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109															
				Project #:	HOULE D 3	. Tr &													9			
-			FIELD, NM 87413	Појесси.			Tel. 505-345-3975 Fax 505-345-4107															
Phone #:		(505) 63	32-1199				Analysis Request															
email or F				Project Manag	ger:				_					04)	S			300.1)			.	
QA/QC Pa	_		Level 4 (Full Validation)		NELSON V	ELEZ	(8021B)	only)	/ MRO)			(S		O4,S	PCB's						d)	
Accreditat	tion:			Sampler:	NELSON V	ELEZ ny	4s (8	(Gas	DRO,	급	귀	SIN		02,1	/ 8082			/ water			du	
□ NELAF		□ Other		On Ice			1	TPH (Gas	-	118.	4	270		N,EC	s / 8		(A)	0.00		1	Sal	2 Z
□ EDD (Гуре)			Sample Temp	erature: /	9108 82	1	+	GRC	od 4	od	or 8	tals	N'I	ide	A	-\0	il - 3(Ф	osite	(70
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No.	BTEX +-MTE	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0		Grab sample	5 pt. composite sample	Air Bubbles (Y or N)
9/21/17	5855	SOIL	5PC-TB@ 5 '(45)	4 oz 1	Cool	-001	٧		٧									٧			٧	
1-111	000																		\Box	\neg		_
.							-												\vdash	-		_
-											-				-	_			-	-	\dashv	_
								\vdash	_			_					_	\vdash	-	-		_
									_		_								\vdash	_	\Box	
-																				_		
																		\Box	\Box	\Box		
																			\Box	\neg	\neg	
													_							\dashv		
Date:	Time:	Relinquishe	ed by:	Received by:		Date Time	Ren	narks	:	BILL D	DIREC	TLY TO	O BP	USING	THE	CONT	ACT V	VITH C	ORRES	SPON	DING	VID
9/21/17	1851	91	hu I	CI Le	aut!	9/21/17/855				& REF												
Date:	Time:	Relinquishe	ed by:	Received by:		Date /Time/	C			ERIN VHI)				/ VA	INCE	HIX	ON					
Thiles	1921	Cu	La)als	Palenne	more	09122117	Ref	erend				559										
JUHL		samples sub	mitted to Hall Environmental may be sul	ocontracted to other	" Popular	2000	of this	possib	ility.					a will b	e clea	arly no	tated	on the	analyti	ical re	port.	

Hall Environmental Analysis Laboratory, Inc.

WO#:

1709C34 27-Sep-17

Client:

Blagg Engineering

Project:

Riddle B 1 #2

Sample ID MB-34018

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 34018

RunNo: 45820

TestCode: EPA Method 300.0: Anions

LowLimit

Prep Date: 9/22/2017

Analysis Date: 9/22/2017

POL

1.5

SeqNo: 1456581

Units: mg/Kg

RPDLimit

Qual

Analyte Chloride

Result ND

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD

Client ID: LCSS

Batch ID: 34018

SampType: Ics

RunNo: 45820

Prep Date:

Sample ID LCS-34018

9/22/2017

Analysis Date: 9/22/2017

SeqNo: 1456582

Units: mg/Kg

%RPD **RPDLimit**

Qual

Result

SPK value SPK Ref Val %REC

0

92.5

Analyte Chloride

PQL 1.5

90

HighLimit

14

15.00

110

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- Holding times for preparation or analysis exceeded H
- Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- Analyte detected below quantitation limits J
- Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified

Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1709C34

27-Sep-17

Client:

Blagg Engineering

Project:

Riddle B 1 #2

Sample ID LCS-34015	SampT	ype: LC	S	TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: LCSS	Batch	ID: 34	015	RunNo: 45805						
Prep Date: 9/22/2017	Analysis D	Analysis Date: 9/22/2017 SeqNo: 1455635 Units: mg/Kg								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	45	10	50.00	0	89.2	73.2	114			
Surr: DNOP	4.8		5.000		95.7	70	130			

Sample ID MB-34015	SampT	уре: МЕ	BLK	TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: PBS	Batch	1D: 34	015	F	RunNo: 4	5805				
Prep Date: 9/22/2017	Analysis D	ate: 9/	22/2017	8	SeqNo: 1	455636	Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	11		10.00		111	70	130			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1709C34

27-Sep-17

Client:

Blagg Engineering

Project:

Riddle B 1 #2

Sample ID MB-33985

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

PBS

Batch ID: 33985

PQL

5.0

RunNo: 45817

Prep Date:

9/21/2017

Analysis Date: 9/22/2017

SeqNo: 1457079 %REC

HighLimit

Units: mg/Kg

Qual

Analyte Gasoline Range Organics (GRO)

ND

1000

SPK value SPK Ref Val

110

%RPD

%RPD

RPDLimit

Surr: BFB

1100

Result

150

Sample ID LCS-33985

LCSS

9/21/2017

SampType: LCS

Batch ID: 33985

TestCode: EPA Method 8015D: Gasoline Range RunNo: 45817

LowLimit

SeqNo: 1457080

Units: mg/Kg

HighLimit

RPDLimit Qual

Client ID:

Prep Date:

54

150

SPK value SPK Ref Val %REC Analyte Result LowLimit Gasoline Range Organics (GRO) 5.0 25.00 111 Surr: BFB 1200 1000 120

Analysis Date: 9/22/2017

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit ND
- Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- В Analyte detected in the associated Method Blank
- Value above quantitation range
- J Analyte detected below quantitation limits
- Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified

Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1709C34

27-Sep-17

Client:

Blagg Engineering

Project:

Riddle B 1 #2

Sample ID MB-33985	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batch ID: 33985			RunNo: 45817						
Prep Date: 9/21/2017	Analysis D	Date: 9/	22/2017	8	SeqNo: 1	457105	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.2		1.000		125	66.6	132			

Sample ID LCS-33985	SampT	ype: LC	S	TestCode: EPA Method 8021B: Volatiles							
Client ID: LCSS	Batch	1D: 33	985	R	RunNo: 4						
Prep Date: 9/21/2017	Analysis D	ate: 9/	22/2017	SeqNo: 1457106 Un			Units: mg/K	Inits: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	1.1	0.025	1.000	0	112	80	120				
Toluene	1.1	0.050	1.000	0	109	80	120				
Ethylbenzene	1.1	0.050	1.000	0	113	80	120				
Xylenes, Total	3.4	0.10	3.000	0	114	80	120				
Surr: 4-Bromofluorobenzene	1.3		1.000		132	66.6	132			S	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name:	BLAGG	Work Order Number:	1709C34		RcptNo:	1
Received By: Completed By: Reviewed By:	Ashley Gallegos Ashley Gallegos	9/22/2017 7:40:00 AM 9/22/2017 7:50:57 AM 9/21 17		A		
Chain of Cus	tody					
1. Custody sea	als intact on sample bottles	?	Yes	No 🗆	Not Present	*
2. Is Chain of C	Custody complete?		Yes 🗹	No 🗆	Not Present	
3. How was the	e sample delivered?		Courier			
Log In						
4. Was an atte	empt made to cool the sam	ples?	Yes 🗹	No 🗌	NA 🗔	
5. Were all sar	mples received at a temper	rature of >0° C to 6.0°C	Yes 🗹	No 🗆	NA 🗆	
6. Sample(s) in	n proper container(s)?	*	Yes 🗹	No 🗌		
7. Sufficient sa	mple volume for indicated	test(s)?	Yes ✓	No 🗆		
8. Are samples	(except VOA and ONG) p	roperly preserved?	Yes 🗹	No 🗆		
9. Was preserv	vative added to bottles?		Yes	No 🗹	NA 🗆	
10.VOA vials ha	ave zero headspace?		Yes	No 🗆	No VOA Vials	
11. Were any sa	ample containers received	broken?	Yes	No 🗹	# of preserved	,
	work match bottle labels?		Yes 🗹	No 🗆	bottles checked for pH:	r >12 unless noted)
	pancies on chain of custod s correctly identified on Cha		Yes 🗸	No 🗆	Adjusted?	1 - 12 unioss notos,
	nat analyses were requeste		Yes 🗹	No 🗆	_	
15. Were all hold	ding times able to be met? customer for authorization.		Yes 🗸	No 🗆	Checked by:	
	lling (if applicable)					
16. Was client n	otified of all discrepancies	with this order?	Yes 🗌	No 🗆	NA 🗹	
By Wh		Date Via:	eMail [Phone Fax	☐ In Person	
17. Additional re	emarks:					
18. Cooler Info Cooler No	o Temp °C Condition 2.2 Good	Seal Intact Seal No S Yes	eal Date	Signed By		



