District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778 OIL CONS. DIV DIST. 3
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: ATLANTIC B LS 003A DEC 0 8 2017
020 00 4011
API Number: 3004522989 OCD Permit Number: U/L or Qtr/Qtr I Section 04 Township 30N Range 10W County: San Juan
Center of Proposed Design: Latitude 36.838258 Longitude -107.881955 NAD83
Surface Owner: 🔳 Federal 🗌 State 🔲 Private 🔲 Tribal Trust or Indian Allotment
Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: 21
4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
Submittal of all exception request is required. Exceptions must be submitted to the Santa Le Environmental Sureau office for consideration of approval.

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
☐ Screen ☐ Netting ☐ Other ☐ ☐ Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 15.17.9 NMAC
11.	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number:	
Treviously Approved Design (attach copy of design) Arrivation or remit indiffeet	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:	
18. A FI CON CONTRACTOR OF THE	
OCD Approval: Permit Application (including closure plan) Closure Plan (outy) OCD Conditions (see attachment)	- / -
OCD Representative Signature: Approval Date: 12/	20/17
Title: Entromental Sec. OCD Permit Number:	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 10/11/2017	
Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-lo If different from approved plan, please explain.	op systems only)
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please inc.	

22.	
Operator Closure Certification:	
	with this closure report is true, accurate and complete to the best of my knowledge and e closure requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Signature:Utin garifalos	Date: December 6, 2017
e-mail address: erin.garifalos@bp.com	Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

ATLANTIC B LS 003A

API No. 3004522989

Unit Letter I Section 04 T 30N R 10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.093
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	1.8
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	5300 -
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits except TPH. TPH will be addressed under the spill and release guidelines. The field report and laboratory

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has occurred. The release will be addressed under the spill and release guidelines. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has occurred. The release will be address under the spill and release guidelines. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

BP did not meet the 60 closure completion requirement due to an error in internal tracking. Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised April 3, 2017

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	catio	n and Co	orrective A	ction						
						OPERA'	ГOR		Initia	al Report		Final Report		
		America Product, Farmington, N		ny		Contact Erin								
Facility Nat			IVI 67401			Telephone No. (832) 609-7048 Facility Type: Natural Gas Well								
Surface Ow	ner : Federal	ĺ		Mineral C)wner:	Federal			API No	3004522989				
				LOCA	TIO	N OF RE	LEASE							
Unit Letter	Section	Township	Range	Feet from the		/South Line	Feet from the	East/We	st Line	County		1		
1	04	30N	10W	1,800	Soi	uth	825	East		5	san	Juan		
			Latitud	e 36.838258	L	ongitude1	07.881955	NAD83						
				NAT	URE	OF REL	EASE							
Type of Rele	ase:: none)					Release:: unkn			Recovered::				
Source of Re	lease: belo	w grade ta	nk - 21	bbl		n/a	Hour of Occurrence	n.		Hour of Dis	covery			
Was Immedi	ate Notice (Yes 🗸	No Not Re	equired	If YES, To	Whom?							
By Whom?			100	110 🚨 110111	rquired	Date and H	Hour							
Was a Water	course Read		Yes 🗸	l No		If YES, Vo	olume Impacting t	the Waterc	ourse.					
If a Watercon	irce was Im	pacted, Descr												
II a Watercoo	irse was iiii	pacieu, Deser	ibe I ully.											
Describe Co.	se of Proble	em and Reme	dial Action	Taken *										
Describe Cat	ise of Floor	em and Keme	ulai Actioi	Sampii			ath the BGT wa TPH below BG1							
				will be	addres	ssed followin	g the spill and re							
Describe Are	a Affected	and Cleanup A	Action Tak		are at	tached.								
Describe Are	a Affected a	and Cicanup 7	iction Tax	The rele			dressed follo							
				0		nal labora	atory analysi	s deter	mined	no rem	edial	action is		
I harahy cart	fy that the i	nformation ai	ven above	required is true and comp		he heet of my	knowledge and u	understand	that pure	suant to NM	OCD r	iles and		
regulations a	ll operators	are required to	o report an	d/or file certain re	elease r	notifications a	nd perform correc	ctive action	s for rele	eases which	may er	ndanger		
				e of a C-141 repo investigate and re										
		ddition, NMC ws and/or regu		tance of a C-141	report d	loes not reliev	e the operator of	responsibi	ity for co	ompliance w	vith any	other		
	-	^					OIL CON	SERVA	TION	DIVISIO	N			
· ·	rung	wiffalc	4											
						Approved by	Environmental S	pecialist:						
		arifalos												
Title: Field	Enviro	onmenta	d Coo	rdinator		Approval Dat	te:	Ex	piration l	Date:				
E-mail Addre	ess: erin.	garifalos	@bp.	com		Conditions of	Approval:			A4411				
Date: Decen				(832) 609-7048						Attached				
* Attach Addi			arv.											
				HNCS	17	354	320-1							
							16	-						

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

October 3, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: ATLANTIC B LS 003A

API#: 3004522989

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about October 6, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From:

Buckley, Farrah (CH2M HILL)

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)

Cc:

jeffcblagg@aol.com; blagg_njv@yahoo.com; Garifalos, Erin

Subject: Date: BP Pit Close Notification - ATLANTIC B LS 003A

Tuesday, October 03, 2017 1:55:47 PM

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

October 3, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ATLANTIC B LS 003A API 30-045-22989 (I) Section 4— T30N — R10W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around October 6, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator – San Juan Cell: 832-609-7048

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENTS BP		GINEERING, INC.		API#: 3004522	989
CLIENT:	,	OOMFIELD, NM 874 632-1199	113	TANK ID (if applicble):	
FIELD REPORT:	(circle one): BGT CONFIRMATION / RE	ELEASE INVESTIGATION / OTHER:		PAGE #: 1 o	f _1_
SITE INFORMATION		C B LS #3A		DATE STARTED: 10/0	6/17
QUAD/UNIT: SEC: 4 TWP:	30N RNG: 10W PM:	NM CNTY: SJ ST:	NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 1,800'S / 825		E: FEDERAL/STATE/FEE/I STRIKE TRACTOR: MBF-R.POWE		ENVIRONMENTAL SPECIALIST(S):	JV
REFERENCE POINT				GL ELEV.: 7	407'
1) 21 BGT (SW/DB) - B		3258 X 107.881955		RING FROM W.H.: 43.5', S	
2)				RING FROM W.H.:	
3)	GPS COORD.:		DISTANCE/BEAF	RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEAF	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR L	AB USED: HALL			OVM READING
1) SAMPLE ID: 5PC - TB @ 8' (2	1) - B SAMPLE DATE: 10/06/17	SAMPLETIME: 1415 LAB ANALY	sis: 801	5B/8021B/300.0 (CI)	1,428
2) SAMPLE ID:		SAMPLE TIME: LAB ANALY			
SAMPLE ID: SAMPLE ID:					
5) SAMPLE ID:		SAMPLE TIME: LAB ANALY			
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND SILT	/ SILTY CLAY / CLAY / GRAVEL OTHE	R BEDRO	CK (SANDSTONE)	
SOIL COLOR: MODE	RATE BROWN PL	ASTICITY (CLAYS): NON PLASTIC / SLIGHT	LY PLASTIC / CO	OHESIVE / MEDIUM PLASTIC / HIGH	LY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE (SLIGHTL' CONSISTENCY (NON COHESIVE SOILS): LC		ENSITY (COHESIVE CLAYS & SILTS): \$ CODOR DETECTED: YES NO EXPLANA			K
MOISTURE: DRY/SLIGHTLY MOIST/ MOIST/W		ODOR DETECTED. TEST NO EXPLANT	TION- DIS	COLORED GOILG/DEDIGO	
SAMPLE TYPE: GRAB (COMPOSITE) #	OF PTS. 5	IY AREAS DISPLAYING WETNESS: YES	NO EXPLAN	IATION -	
DISCOLORATION/STAINING OBSERVED: YES					
SITE OBSERVATION	S: LOST INTEGRITY OF EQUIPMENT: YE	S NO EXPLANATION - INSPECTION	OCAPBON	DEGREE ELBOW FITTING	
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:	YES NO EXPLANATION -	ATION: DISCOLURATION & HTDR	OCARBON	ODOR	
OTHER: NMOCD OR REPS. NOT PRESE	NT TO WITNESS CONFIRMATION SA	MPLING. SANDSTONE ENCOU	NTERED AT	8 FT. BELOW GRADE (SAM	/IPLED).
EXCAVATION DIMENSION ESTIMATION:	ft. X ft	t. X ft. EXCA	VATION EST	TIMATION (Cubic Yards) :	
DEPTH TO GROUNDWATER: >100'		NEAREST SURFACE WATER: >1,00	00' NMOC	D TPH CLOSURE STD: 5,0	00 ppm
SITE SKETCH	BGT Located: off on site	PLOT PLAN circle: att	ached OVM	CALIB. READ. = 100.0 ppr	m RF =1.00
			A .	CALIB. GAS = 100 ppi	111 1.00
	W.H. ⊕				0/06/17
	Ψ		ייי ו	MISCELL. NO	ES
	(21) - B		w	/O:	
	PBGTL T.B. ~ 6'		R	EF #: P-889	
	B.G.		V	ID: VHIXONEV11	
	(X X X)		P.	J#:	
	PR	OD.		ermit date(s): 08/29	
		NK	O	CD Appr. date(s): 09/12 OVM = Organic Vapor Met	/17 ter
	STEEL CONTAINMENT		ID	ppm = parts per million BGT Sidewalls Visible: Y /	
	RING	V 0		BGT Sidewalls Visible: Y /	
NOTES: DOT - DELON/ODADE TANK E.D EVON/ATI	ON DEDDECCION: D.O DELONICORADE, D DELON	X - S		BGT Sidewalls Visible: Y /	
	OW-GRADE TANK LOCATION; SPD = SAMPLE POINT	T DESIGNATION; R.W. = RETAINING WALL; NA-		lagnetic declination: 10	
	E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM		1	agnote acomaton. To	_
NOTES: GOOGLE EARTH IMAG	ERT DATE: 3/15/2015.	ONSITE: 10/06/17			

Analytical Report

Lab Order 1710437

Date Reported: 10/11/2017

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 8' (21)-B

Project: ATLANTIC B LS #3A

Collection Date: 10/6/2017 2:15:00 PM

Lab ID: 1710437-002

Matrix: SOIL

Received Date: 10/7/2017 10:35:00 AM

Analyses	Result	PQL (Qual	Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS						Analys	MRA
Chloride	ND	30		mg/Kg	20	10/9/2017 1:47:01 PM	34306
EPA METHOD 8015M/D: DIESEL RANGI	E ORGANICS	S				Analyst	:: TOM
Diesel Range Organics (DRO)	3600	99		mg/Kg	10	10/9/2017 11:14:51 AM	34298
Motor Oil Range Organics (MRO)	1700	500		mg/Kg	10	10/9/2017 11:14:51 AM	34298
Surr: DNOP	0	70-130	S	%Rec	10	10/9/2017 11:14:51 AM	34298
EPA METHOD 8015D: GASOLINE RANG	SE					Analyst	: NSB
Gasoline Range Organics (GRO)	310	19		mg/Kg	5	10/9/2017 12:22:08 PM	G46204
Surr: BFB	737	54-150	S	%Rec	5	10/9/2017 12:22:08 PM	G46204
EPA METHOD 8021B: VOLATILES						Analyst	: NSB
Benzene	ND	0.093		mg/Kg	5	10/9/2017 12:22:08 PM	B46204
Toluene	ND	0.19		mg/Kg	5	10/9/2017 12:22:08 PM	B46204
Ethylbenzene	0.81	0.19		mg/Kg	5	10/9/2017 12:22:08 PM	B46204
Xylenes, Total	1.8	0.37		mg/Kg	5	10/9/2017 12:22:08 PM	B46204
Surr: 4-Bromofluorobenzene	120	66.6-132		%Rec	5	10/9/2017 12:22:08 PM	B46204

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 2 of 6
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

C	hain-c	of-Cus	stody Record	Turn-Around	Time:	SAME					IAI			NIN/	TTE	20	BII	ME	NT		
Client:	BLAG	G ENGR.	/ BP AMERICA	☐ Standard	☑ Rush _	DAY)													ATC		
				Project Name							wwv										•
Mailing A	ddress:	P.O. BO	X 87	AT	LANTIC B L	S #3A		490	01 H									37109	9		
		BLOOM	FIELD, NM 87413	Project #:			1				15-39			ax !							
Phone #:		(505) 63	32-1199				FR	Tea	E.	941	11.0	А	naly	ysis	Rec	lues	t	TA VALCE	11 21		
email or F	ax#:			Project Manag	ger:									4				1	T	T	T
QA/QC Pa	_		Level 4 (Full Validation)		NELSON VI	ELEZ	B+5 (8021B)	only)	MRO)			15)		05,50	PCB's			er - 300.1)			a
Accredita	tion:			Sampler:	NELSON VI	ELEZ 977	18 (8)	TPH (Gas	DRO/	1)	F	SSIN		102	/ 8082			/ water		2	sample ()
□ NELAP		□ Other		The first state of the party of	M Yes	All and the second seco	1	TPH	-	418	504	8270SIMS)	S	03,1	se / se		(AC	300.0		1 5	r N
□ EDD (T)	/pe)	1		Sample Temp	erature- 🧷		1	BE +	(GR	pou	hod	5	eta	CI,N	icid	(A)	ni-V	oil - 3	-	ple	ج اق
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No.	BTEX +MF	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil -		Grab sample	S pt. composite se Air Bubbles (Y or N)
146/11	1315	SOIL	STE TO @ 5 (95) A	402. 1	Cool	asi	-1		4		-							4		4	H
																			\top	\top	+
10/6/17	1415	SOIL	5PC - TB @ 8 '(21) - B	4 oz 1	Cool	702	٧		٧									٧	1	Ţ	/
						-	-					_					_	-	+	+	+
							-			-	-	-			_		_	\vdash	+	+	+
											-	-			_				+	+	+
· · · · · · · · · · · · · · · · · · ·	-					 				\vdash			•			_			_	+	+
																		\Box	+	+	+
											\neg								\top	+	
																			\top	\top	
Date: 10/2/17	Time:	Refinquish	luy	Received by:	Jalt 1	Date Time		ONT/		& REI	EREN	CE#	WHEN	APP	LICAE	LE;		VITH C	ORRESE	PONDI	ING VID
Date:	Time:	Relinquish	ed by:	Received by:	1	Date Time	1	,	VID:	VHD	ONE	V	11	n	_	, ,,,,,,					
lolly	1844	1 m	utweet	Mus	up	10/7/17 1635		eren			P-8		-	700.7	-1		-1	41	-1.41 -7		
	if necessa	ity, samples s	submitted to Hall Environmental may be	supcontracted to other	accredited laboratorie	es. This serves as notice o	r this p	ossibil	πy. Ai	ny sub	-contra	acted (oata w	viii de (clearly	notat	ea on	trie and	aiyticai r	eport.	

Hall Environmental Analysis Laboratory, Inc.

WO#:

1710437

11-Oct-17

Client:

Blagg Engineering

Project:

ATLANTIC B LS #3A

Sample ID MB-34306

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Prep Date: 10/9/2017

Sample ID LCS-34306

LCSS

Batch ID: 34306

RunNo: 46208

SeqNo: 1472041

Units: mg/Kg

RPDLimit

Qual

Analyte

Result

Analysis Date: 10/9/2017

1.5

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD

Chloride

Client ID:

ND SampType: Ics

Batch ID: 34306

TestCode: EPA Method 300.0: Anions

RunNo: 46208

Prep Date:

10/9/2017

Analysis Date: 10/9/2017

PQL

SPK value SPK Ref Val %REC

SeqNo: 1472042

Units: mg/Kg

Qual

Result

%RPD

Analyte

LowLimit 90

110

14

0

Chloride

1.5

15.00

90.2

HighLimit

RPDLimit

Η

Qualifiers: Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix D

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit % Recovery outside of range due to dilution or matrix

Holding times for preparation or analysis exceeded

Analyte detected in the associated Method Blank

E Value above quantitation range

Analyte detected below quantitation limits

P Sample pH Not In Range

Reporting Detection Limit RL Sample container temperature is out of limit as specified Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1710437

11-Oct-17

Client:

Blagg Engineering

Project:

ATLANTIC B LS #3A

Sample ID LCS-34298	SampTy	pe: LC	S	Test	tCode: El	PA Method	8015M/D: Di	esel Rang	e Organics			
Client ID: LCSS	Batch	ID: 34 2	298	R	RunNo: 4	6197						
Prep Date: 10/9/2017	Analysis Da	ite: 10	0/9/2017	2017 SeqNo: 1470767 Units: mg/Kg								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range Organics (DRO)	46	10	50.00	0	91.3	73.2	114					
Surr: DNOP	4.2		5.000		83.3	70	130					

Sample ID MB-34298	SampType: MBLK			TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: PBS	Batch ID: 34298			RunNo: 46197						
Prep Date: 10/9/2017	Analysis Date: 10/9/2017			SeqNo: 1470768			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	9.8		10.00		98.1	70	130			

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 4 of 6

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1710437

11-Oct-17

Client:

Blagg Engineering

Project:

ATLANTIC B LS #3A

Sample ID RB

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID: PBS Batch ID: G46204

RunNo: 46204

%REC

PQL

5.0

Units: mg/Kg

150

HighLimit

Prep Date:

Surr: BFB

Prep Date:

Analysis Date: 10/9/2017

SeqNo: 1471397

RPDLimit

Qual

Analyte Gasoline Range Organics (GRO)

ND 930

Result

1000

SPK value SPK Ref Val

SPK value SPK Ref Val

93.3

54

%RPD

Sample ID 2.5UG GRO LCS

SampType: LCS

0

TestCode: EPA Method 8015D: Gasoline Range

Client ID: LCSS

RunNo: 46204

Batch ID: G46204 Analysis Date: 10/9/2017

PQL

SeqNo: 1471398

Units: mg/Kg

Analyte

Result 28

5.0 25.00

114 107

54

LowLimit

LowLimit

HighLimit %RPD 125

RPDLimit Qual

Gasoline Range Organics (GRO) Surr: BFB

1100

1000

%REC

76.4

150

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- Holding times for preparation or analysis exceeded H
- ND Not Detected at the Reporting Limit
- POL Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- Analyte detected below quantitation limits J
- P Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1710437 11-Oct-17

Client:

Blagg Engineering

Project:

ATLANTIC B LS #3A

SampType: MBLK TestCode: EPA Method 8021B: Volatiles Sample ID RB Batch ID: **B46204** RunNo: 46204 Client ID: PBS Units: mg/Kg Prep Date: Analysis Date: 10/9/2017 SeqNo: 1471413 Analyte Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD **RPDLimit** Qual Benzene ND 0.025 Toluene ND 0.050 ND 0.050 Ethylbenzene Xylenes, Total ND 0.10 Surr: 4-Bromofluorobenzene 0.97 1.000 97.4 66.6 132

Sample ID 100NG BTEX LC	Samp1	SampType: LCS			TestCode: EPA Method 8021B: Volatiles					
Client ID: LCSS	Batcl	Batch ID: B46204			RunNo: 46204					
Prep Date:	Analysis D	Analysis Date: 10/9/2017			SeqNo: 1471414			Units: mg/Kg		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.98	0.025	1.000	0	97.7	80	120			
Toluene	0.96	0.050	1.000	0	96.5	80	120			
Ethylbenzene	1.0	0.050	1.000	0	99.8	80	120			
Xylenes, Total	3.0	0.10	3.000	0	99.8	80	120			
Surr: 4-Bromofluorobenzene	1.0		1.000		103	66.6	132			

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- Holding times for preparation or analysis exceeded H
- ND Not Detected at the Reporting Limit
- **PQL** Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank B
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range

RL

Reporting Detection Limit Sample container temperature is out of limit as specified Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name:	BLAGG	Work Order Numb	er: 1710437		RcptNo: 1		
Received By:	Andy Freeman	10/7/2017 10:35:00	AM	andyl			
Completed By:	Anne Thome	10/9/2017 7:39:44 A	M	any I'm			
Reviewed By:	NL	10/9/17					
Chain of Cus	tody						
1. Custody sea	ils intact on sample bottle	s?	Yes	No 🗆	Not Present		
2. Is Chain of C	Custody complete?		Yes 🗹	No 🗌	Not Present		
3. How was the	e sample delivered?		Courier				
Log In							
4. Was an atte	empt made to cool the san	nples?	Yes 🗹	No 🗆	NA 🗆		
5. Were all san	nples received at a tempe	rature of >0° C to 6.0°C	Yes 🗹	No 🗆	NA 🗆		
6. Sample(s) in	n proper container(s)?		Yes 🗹	No 🗆			
7. Sufficient sa	mple volume for indicated	test(s)?	Yes 🗹	No 🗆			
8. Are samples	(except VOA and ONG)	properly preserved?	Yes 🗹	No 🗆			
Was preserv	rative added to bottles?		Yes	No 🗹	NA		
10.VOA vials ha	ave zero headspace?		Yes	No 🗆	No VOA Vials		
11. Were any sa	ample containers received	Yes	No 🗹				
12. Does paperw	vork match bottle labels?		Yes 🗹	No 🗔	# of preserved bottles checked for pH:		
	pancies on chain of custoo				(<2 o Adjusted?	r >12 unless noted)	
	correctly identified on Ch		Yes 🗹	No 🗆	Adjusted		
	at analyses were requeste ding times able to be met?		Yes ✓	No 🗆	Checked by:		
	customer for authorization		Tes 🖭	NO [
Special Hand	ling (if applicable)						
16. Was client no	otified of all discrepancies	with this order?	Yes	No 🗌	NA 🗹		
Person	Notified:	Date	STATE OF THE PARTY	MARINA MENDERS OF STREET STATES OF STREET]	
By Wh	om:	Via:	•	hone Fax	☐ In Person		
Regard	ling:		**************************************	COMMENSATION AND THE PARTY OF T	ACTION OF A PARTY AND ADDRESS OF THE PARTY.		
Client I	nstructions:	iki ki kanan amampa se 2,7 ga kilo da Mahahama ammo 2,7 ga pin da 25 da kalibah ban	erio di di 1940, del Zerio Militari di Malencamonio. Al		COLOR CONTRACTOR CONTR	2	
17. Additional re	emarks:						
18. Cooler Info	Temp °C Condition	Seal Intact Seal No	Seal Date	Signed By			
1	2.2 Good	Yes					



