District I 1625 N. French Dr., Hobbs, NM 88240 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

1/8/2018

Data

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

GAS	CA	PTI	IRE	PI	AN
UAD				1 1	

Date. 1/0/2010		
□ Original	Operator & OGRID No.:	Hilcorp Energy Company 372171
☐ Amended - Reason for Amendment:	,	
This Gas Capture Plan outlines actions to be new completion (new drill, recomplete to new		well/production facility flaring/venting for
Note: Form C-129 must be submitted and approved	prior to exceeding 60 days allowed by	Rule (Subsection A of 19.15.18.12 NMAC).
	•	

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Zachry 48	3004525608	G, 34, 29N, 10W	1980' FNL, 2145' FEL	255	Vented	

Gathering System and Pipeline Notification

This is a recompletion of a producing gas well. Gas production, sales and transportation infrastructure is already in place. The gas is dedicated to Hilcorp and will be connected to their gathering system located in San Juan County, New Mexico. Gas from these wells will be processed at Kutz Canyon Processing Plant located in Sec._13_, Twn._28N_, Rng._11W_, _San Juan__ County, New Mexico.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be routed to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Hilcorp's system at that time. Based on current information, it is Hilcorp's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessary the systems are necessary to the systems of the system and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis. MAN 09 2018

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

