

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1. Type of Well

☐ Oil Well

☒ Gas Well

☐ Other

2. Name of Operator

Hilcorp Energy Company

3a. Address

PO Box 4700, Farmington, NM 87499

3b. Phone No. (include area code)

505-599-3400

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Surface

Unit E (SWNW) 1485' FNL & 795' FWL, Sec. 24, T30N, R07W

5. Lease Serial No.

SF-079382

6. If Indian, Allottee or Tribe Name

7. If Unit of CA/Agreement, Name and/or No.

San Juan 30-6 Unit

8. Well Name and No.

San Juan 30-6 Unit POW 1

9. API Well No.

30-039-24530

10. Field and Pool or Exploratory Area

Basin CB : Fruitland Coal

11. Country or Parish, State

Rio Arriba

New Mexico

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☐ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☐ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☐ Well Integrity

☒ Other **MIT**

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof.

If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once Testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Hilcorp Energy Company requests permission to perform an MIT on the subject well per the attached procedure and wellbore schematic.

Notify NMOCD

24 hours

OIL CONS. DIV DIST. 3 prior to MIT

JAN 23 2018

BLM'S APPROVAL OR ACCEPTANCE OF THIS ACTION DOES NOT RELIEVE THE LESSEE AND OPERATOR FROM OBTAINING ANY OTHER AUTHORIZATION REQUIRED FOR OPERATIONS ON FEDERAL AND INDIAN LANDS

RECEIVED

JAN 19 2018

Farmington Field Office
Bureau of Land Management

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)

Etta Trujillo

Title **Operations/Regulatory Technician - Sr.**

Signature

Etta Trujillo

Date

1/17/2018

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

William Tambekou

Title **Petroleum Engineer**

Date

1/19/2018

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office **FFO**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instruction on page 2)

NMOCD

3

Hilcorp
SAN JUAN 30-6 UNIT 1 POW
Expense - MIT

Lat 36.80122 N

Long -107.52775 W

PROCEDURE

1. Hold pre-job safety meeting. Comply with all NMOCD, BLM, and HEC safety and environmental regulations.
2. Check casing, tubing, and bradenhead pressures and record them in WellView. If there is pressure on the BH, contact Operations Engineer.
3. Remove existing piping on casing valve. RU blow lines from casing valves and begin blowing down casing pressure.
4. Load casing with 2 % KCl water & corrosion inhibitor, as necessary. Perform MIT (Mechanical Integrity Test) above the bridge plug at 2,798' to 560 psig for 30 minutes on a 2 hour chart with 1000 lb. spring. If the test passes, SI the well. RD pump truck and MOL. If the test fails, contact the Operations Engineer.

Well Name: SAN JUAN 30-6 UNIT POW #1

API/LWH 3003924530	Surface Legal Location 024-030N-007W-E	Field Name BASIN (FRUITLAND COAL)	License No.	State/Province NEW MEXICO	Well Configuration Type
Ground Elevation (ft) 6,118.00	Original KB RT Elevation (ft) 6,130.00	KB-Ground Distance (ft) 12.00	KB-Casing Flange Distance (ft)	KB-Tubing Flange Distance (ft)	

Original Hole, 1/16/2018 1:09:17 PM

