State of New Mexico Energy, Minerals and Natural Resources Department

Susana Martinez Governor

Ken McQueen Cabinet Secretary

Matthias Sayer Deputy Cabinet Secretary Heather Riley, Division Director Oil Conservation Division



New Mexico Oil Conservation Division approval and conditions listed below are made in accordance with OCD Rule 19.15.7.11 and are in addition to the actions approved by BLM on the following <u>3160-4 or 3160-5</u> form.

Operator Signature Date: 1-16-18 Well information:

API WELL #	Well Name	Well #	Operator Name	Туре	Stat	County	Surf_Owner	UL	Sec	Twp	N/S	Rng W/E
30-039-29354- 00-00	SAN JUAN 28 6 UNIT		HILCORP ENERGY COMPANY	G		Rio Arriba	F	0	22	28	N	6 W

Application Type:

- P&A Drilling/Casing Change Location Change
- Recomplete/DHC (For hydraulic fracturing operations review EPA Underground injection control Guidance #84



Conditions of Approval:

- Notify OCD 24hrs prior to beginning operations.
- Mesaverde well density exemption must be approved prior to production of the Blanco Mesaverde.

Kithinic Parta

NMOCD Approved by Signature

2/5/18 Date

1220 South St. Francis Drive • Santa Fe, New Mexico 87505 Phone (505) 476-3441 • Fax (505) 476-3462 • www.emnrd.state.nm.us/ocd

Form 3160-5 (August 2007) DEPARTMENT OF THE INTE BUREAU OF LAND MANAGE	MENT WAN 2 9 701 Expires: July 31, 2010
	5. Lease Serial No. NMSF079193
SUNDRY NOTICES AND REPORTS Do not use this form for proposals to drill abandoned well. Use Form 3160-3 (APD) fo	or to re-enter an
SUBMIT IN TRIPLICATE - Other instructions	
1. Type of Well Oil Well X Gas Well Other	8. Well Name and No. San Juan 28-6 Unit 119E
2. Name of Operator Hilcorp Energy Company	9. API Well No. 30-039-29354
	ne No. (include area code) 10. Field and Pool or Exploratory Area
PO Box 4700, Farmington, NM 87499	505-599-3400 Blanco Mesaverde/Basin Dakota
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) Surface Unit O (SWSE) 155'FSL & 2615' FEL, Sec	. 22, T28N, R06W 11. Country or Parish, State Rio Arriba , New Mexico
12. CHECK THE APPROPRIATE BOX(ES) TO INI	DICATE NATURE OF NOTICE, REPORT OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION
Alter Casing Frame Alter Casing Frame Casing Repair New Casing Repair New Change Plans Plut Final Abandonment Notice Convert to Injection Plut I3. Describe Proposed or Completed Operation: Clearly state all pertinent details, inclue If the proposal is to deepen directionally or recomplete horizontally, give subsurface Attach the bond under which the work will be performed or provide the Bond No. following completion of the involved operations. If the operation results in a multi Testing has been completed. Final Abandonment Notices must be filed only after determined that the site is ready for final inspection.) Hilcorp Energy Company plans to recomplete the subject existing Dakota with the Mesaverde. Attached is the Mi application will be submitted and approved before the value ACTION DOPERATOR AUTHORIZ	e locations and measured and true vertical depths of all pertinent markers and zones. on file with BLM/BIA. Required subsequent reports must be filed within 30 days ple completion or recompletion in a new interval, a Form 3160-4 must be filed once all requirements, including reclamation, have been completed and the operator has ct well in the Mesaverde formation and downhole commingle the / C102, recomplete procedure & wellbore schematic. The DHC
	Farmington Field Office Bureau of Land Management
14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)	
Tammy Jones	Title Operations/Regulatory Technician - Sr.
Signature Tammy Juss	Date 1/16/2018
U THIS SPACE FOR FED	ERAL OR STATE OFFICE USE
	vould Office FFD
false, fictitious or fraudulent statements or representations as to any matter within its jur	sdiction CD M

(Instruction on page 2)

.

1

District I

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u>

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources **Oil Conservation Division** 1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT 3. Pool Name

1. API Numbe	<u>الم</u>	2.	Pool Code				3. P	ool Nar	ne				
30-039-29354 72319					BLANCO-MESAVERDE (PRORATED GAS)							AS)	
4. Property Code 5. Property Name 318710 SAN JUAN 28 6 UNIT					6. Well No. 119E								
				JAN 28 6 UNIT									
7. OGRID No	2171	8.	Operator Name	RP ENERGY C			9. E	levatior	י 6499				
	21/1			RF ENERGI C		IN 1			0499				
					1	0. Surfa	ce Locati	on					
UL - Lot	Section		Township	Range	Lot Idn	Fee	t From	N/SL	-	Feet From	E/W Line	Coun	
0		22	28N	06W			155		S	2615		E	rio arriba
L				11. Botton		Locatio	n'lf Diffor	ont Fi	rom Si	urfaco			
UL - Lot	Section		Township	Range	Lot		Feet From		N/S Li		om F/	WLine	County
			1011101										,
12. Dedicated	Acres 20.00 E/2	,	- I	13. Joint or In	fill		14. Cons	olidatio	n Code		15	. Order N	D.
NO ALL	OWABLE	WI		NED TO THIS C STANDARD U									O OR A NON-
						knowle minera this we interes	dge and beli I interest in ti II at this loca	ef, and he land tion pu	ormation that this includir rsuant to	o a contract with a	is true and c er owns a wo ttom hole lo owner of si	complete to prking inte cation(s) c uch a mine	rest or unleased or has a right to drill
-		- 1- 		· · · · · · · · · · · · · · · · · · ·		E-Sign Title: Date:	Ope		ny Jo s/Regul	nes latory Technicia	ı - Sr.	_	
		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					s made by m		Il locatio	VEYOR CERT on shown on this pl supervision, and th	at was plotte	ed from fie	ld notes of actual d correct to the best

and the second				
	Surveyed By:	Jason C. Edwards		
	Date of Survey:	6/15/2004		
	Certificate Number:	15269		

Form C-102 August 1, 2011

Permit 247239



HILCORP ENERGY COMPANY SAN JUAN 28-6 UNIT 119E MESA VERDE RECOMPLETION SUNDRY

	JOB PROCEDURES
1.	MIRU service rig and associated equipment; test BOP.
2 .	TOOH with 2 3/8" tubing set at 7,776'.
З.	Set a 4-1/2" cast iron bridge plug at +/- 6,050' to isolate the Dakota. Note: TOC at 2,950' by CBL.
4.	Load the hole and pressure test the casing to frac pressure.
5.	N/D BOP, N/U frac stack and test frac stack to frac pressure.
6.	Perforate and frac the Mesa Verde in two or three stages
7.	Isolate frac stages with a composite bridge plug.
8.	Nipple down frac stack, nipple up BOP and test.
9.	TIH with a mill and drill out top isolation plug and Mesa Verde frac plugs.
10.	Clean out to Dakota isolation plug and, when water and sand rates are acceptable, flow test the Mesa Verde.
11.	Drill out Dakota isolation plug and cleanout to PBTD of 7,804 '. TOOH.
12.	TIH and land production tubing. Get a commingled Dakota/Mesa Verde flow rate.

Hilcorp

HILCORP ENERGY COMPANY SAN JUAN 28-6 UNIT 119E MESA VERDE RECOMPLETION SUNDRY

۱.	likorp E	nergy Company	Current	Schematic - V	ersion 3		
Well N	lame:	SAN JUAN 28-6 UNIT #119	Fied Nata	License No.		Sata Pro/noe	Wei) Cardguration Type
3003929		022-028N-006W-C	BAS'N DAKOTA (PROR	ATED GAS)		NEW MEXICO	VERTIČAL
199.00		රාලාස KSRT වසයෙහා (බ) 6.514.00	15.0	10005-05666762477, 10	Kil-Canaly Fails	je Dillance (il) -Ci-Tubin) varða Dinauce (i)
		VERT	ICAL, Origina	al Hole, 1/12/20	018 10:21	54 AM	
MD (ftKB)	TVD (ftKB)			Vertical scheme	itic (actual)		· · ·
15.1	15.1					Contract of the local data and the	
15.7	15.7	Tubing Hanger; 7 1/16 in; 15.	0 ftKB; 15.6 ftKB		- 1 8 8		
1ā.1	15.1					X	
2 27	20.7	Fubing; 2 3/8 in; 4.70 lb/ft; J-55	156 fiKB 45 6		88 Ø	8	
33.5	23.5		10.0 mtb. 45.0	88 8 I II		3	
45.5	45.5					2 2	
48.2	48.2	Tubing Pup Joint; 2 3/8 in; 4.7					5.0-133.5; 3/9/2005;
69.9	639		ftKB; 70.0 ftKB			CEMENT WITH 5	D SX CIRCULATING 1 BBL
132.5	192.5				2 W W	TO SURFACE	FACE; 9 5/8 in; 9.00 in; 15.0
132.5	132.5	Rubia - A AM	1 FF. 74 8 81-4-1			ftKB; 133.5 ftKB	_,
155.2	135.1	Fubing; 2 3/8 in; 4.70 lb/ft;	J-55; 70.0 ftKB; 823.4 ftKB				15.0-2,810.0; 3/18/2005;
823.5 2,578.1	823.4 2.577.7	OJO ALAMO (final)		👸 🕴 📅			47 SX CIRCULATING 43
2,534.9	2,57.5	-KIRTLAND (final)				DOLS TO SURFAI	<u>~</u>
2,813.0	2.809.6						
2813.5	2812.9						
2,953.1	2,949.7						
3,157.1	3,135.7	-FRUITLAND (final)	···· · · · · · · · · · · · · · · · · ·		× *	FIRST STAGE: 2,0	110.0-3,591.4; 3/18/2005;
3,314.0	2,313.5	-PICTURED CLIFFS (final)-			× *	CEMENT WITH 1	13 SX CIRCULATING
2,546.3	3,545.7			38 88 H			
3.547.2	2,645.7			※ 綴	88 SA		
3,590.5	3,590.0					2 CASING INTE	RMEDIATE; 7 in; 6.46 in;
5.591.5	12310				1000	15.0 ftKB; 3,591.4	
3,523.0	3,622.5	[Tubing (YELLOW); 2 3/8 in	4 7016/11-551		88293		
4,237,1	4,288.3		(B; 7,741.4 ftKB		I 💥——		
4,885.2	4,885.2	-CUFFHOUSE (final)	· · · · · · · · · · · · · · · · · · ·				
4,965.2	4,954.3						
4,973.1	4,574,1					SINGLE: 2.950.0-7	801 7: 3/22/2005:
5,143.1 5,518.0	5,129.1 5,518.9	—MENEFEE (final)——— —POINT LOOKOUT (final)——				CEMENT WITH 2	3 SX TOC DETERMINED
6,027.9	6,025.5					BY CBL	
6,723.1	6,721.6	MANCOS (final) GALLUP (final)		~~~~	× mm		
7,221.5	7,319.8						· · · · ·
7,221.4	7,229.7				N N		
7,458.9	7,455.1				. ————————————————————————————————————		
7,524.1	7,532.4	-GRANEROS (final)		<u>````</u>	×——		
7,578.2	7,571.4	- DAKOTA (final) Tubing Pup Joint; 2 3/8 in	4 70 6/1: 1-55				·
7,576.1	7,574,4	7,741.4 10	(B; 7,743.6 ftKB)		500 500 B	DEPE OVPOTA 7	576.0-7.785.0; 4/8/2005
7,741.5	7,739.7	Tubing (YELLOW); 2 3/8 in:	4.70 lb/ft; J-55; (B; 7,774.6 ftKB	<u> </u>	8%	TERF DARUTA: /	JIV.V-1,100.0, 4/0/2005
7,743.8	7,742.0	Profile Nipple; 2 3/8 in; 7,774		289 - 11	1881		
7,774.6	7,772.8		ftKB		9999 (F		
7,775.6	7,773.8	Expendable Check w/ Mule			88		
7,778.2	7,774,4	1,115.5 T	0B; 7,776.4 ftKB		188		
7,735.1	7,782.5			- XX			
7,790.0	7,788.2	Fill/Junk; 7,790.0-7,801.7; De			7 X		
7,799.9	7,798.0	L	to 6/18/2015		- 185		DUCTION (LONG STR.); 4
7,800.9	7,739.0 7,700.0						7.7.804.0; 3/23/2005
7,811.8	7,200.0		DRTD- 7 404 A				.1-1,004.0, 3/23/2005
الەنم،	5,223						
7,804.1 www.pe	7,822.8 loton.co		[PBTD; 7.804.0]	Page 1/1			Report Printed: 1/12/