District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

OIL CONS. DIV DIST. 3

Form C-144
Revised April 3, 2017
For temporary pits, below grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.
For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application							
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request							
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.							
Operator: BP America Production Company OGRID #: 778							
Operator: BP America Production Company Address: 200 Energy Court, Farmington, NM 87401							
Facility or well name: NAVAJO ALLOTTED GC A 001							
API Number: 3004513252 OCD Permit Number:							
U/L or Qtr/Qtr B Section 25 Township 28N Range 09W County: San Juan							
Center of Proposed Design: Latitude 36.63760 Longitude -107.73698 NAD83							
Surface Owner: 🔳 Federal 🗌 State 🔲 Private 🔲 Tribal Trust or Indian Allotment							
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: □ Drilling □ Workover □ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management □ Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined □ Liner type: Thicknessmil □ LLDPE □ HDPE □ PVC □ Other □ String-Reinforced Liner Seams: □ Welded □ Factory □ Other Volume:bbl Dimensions: L x Wx D							
Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A							
4. Alternative Method:							
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.							
s. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital.							



Four foot height, four strands of barbed wire evenly spaced between one and four feet

institution or church)

Alternate. Please specify

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)							
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC							
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.							
9. <u>Siting Criteria (regarding permitting)</u> : 19.15.17.10 NMAC <i>Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate are provided below.</i> Siting criteria does not apply to drying pads or above-grade tanks.	ptable source						
General siting							
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No						
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells							
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No						
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No						
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No						
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No						
Below Grade Tanks							
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)							
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No						
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image							
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Temporary Pit Non-low chloride drilling fluid							
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No						
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No						
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Permanent Pit or Multi-Well Fluid Management Pit							
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No						
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site							
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC							
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:							

Permainent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Lak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are					
Proposed Closure: 19.15.17.13 NMAC						
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F. Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit					
14.						
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC						
15,						
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Fig. 19.15.17.10 NMAC for guidance.						
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA					
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA					
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA					
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image						
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No					
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No					
Within 300 feet of a wetland.						
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance						

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No							
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No							
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No							
Within a 100-year floodplain FEMA map								
· ·								
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC							
17. Operator Application Certification:								
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.							
Name (Print): Title:								
Signature: Date:								
e-mail address: Telephone:								
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: OCD Permit Number:	7106101							
19.								
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.								
Closure Completion Date: 12/15/2017								
Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-lo If different from approved plan, please explain.	op systems only)							
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please incomark in the box, that the documents are attached.	dicate by a check							

Operator Closure Certification:	
	tted with this closure report is true, accurate and complete to the best of my knowledge and cable closure requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Signature:Utin garifalos	Date: February 7, 2018
e-mail address: erin.garifalos@bp.com	Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

NAVAJO ALLOTTED GC

API No. 3004513252

Unit Letter B Section 25 T 28N R 09W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

ı

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

	m 1 36 1 1	D 1 XX 100 .1	G 1
Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.020
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.079
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<47
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I ¹
1625 N. French Dr., Hobbs, NM 88240
District III
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141 Revised April 3, 2017

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

				Sa	ma re	, INIVI 0/J	103						
			Rele	ase Notific	ation	and Co	orrective A	ction	1				
						OPERATOR						Final Re	eport
				tion Company			n Garifalos	7040					
		y Court, Fa JO ALLOT		n, NM 87401			No.(832) 609- De: Natural Ga		ıll				\dashv
Surface Ow			TED G	Mineral O			- Hatarar Gt	20 110		.300451	3250)	=
Surface Ow	ner. reu	erai					ELGE		Allino	.000401	0202		
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	Fast/	West Line	County			
В	25	28N	09W		Sou	_	1,700	Eas		S	an	Jua	an
<u> </u>	20	2014											
			Latitud	e 36.63760	Lo	ongitude	07.73698	NAD	83				
				NAT	URE	OF REL							
Type of Rele	ase:: none	9					Release: unknown			Recovered: : Hour of Dis			
		w grade ta	nk - 95 k	obl		n/a			n/a	11041 01 1515	overy.		
Was Immedia	ate Notice (Yes 🗸	No Not Re	auired	If YES, To	Whom?						
By Whom?					quire	Date and H	Iour						_
Was a Water	course Rea			27		If YES, Vo	olume Impacting t	the Wat	ercourse.				
			Yes 🗸										
If a Watercou	irse was Im	pacted, Descr	ibe Fully.*										
Describe Cau	ise of Probl	em and Reme	dial Action	Taken.*	ling o	of the soil	honooth the	PCT	was do	no durin	a ron	noval	
					_		beneath the d for Chloric				_		
					-		Field reports						ed.
Describe Are	a Affected	and Cleanup A	Action Tak	en.*						-			
		r		No action		-	inal laborate	ory a	nalysis c	determin	ed no)	
				remedial	actio	n is requ	ired.						
Thombo cont	C. 41-41-	: f		:. t d	-+- +- +1	a bast a Consu	Imazzila dan and w	do.noto	u d th at m	went to NIM	OCD	laa an d	_
				is true and compled/or file certain re									
public health	or the envi	ronment. The	acceptanc	e of a C-141 repo	rt by the	NMOCD m	arked as "Final R	eport" o	loes not reli	eve the oper	ator of	liability	h.
				investigate and retance of a C-141 i									n
		ws and/or regu											_
	14in a	ATTER D.	.)				OIL CON	SERV	ATION	DIVISIO	N		
Signature:	oun g	willard	14										
Signature: Printed Name: Erin Garifalos					1	Approved by Environmental Specialist:							
				rdin atau									$\overline{}$
		onmenta			1	Approval Dat	e:		Expiration I	Date:			
E-mail Addre	ess: erin.	garifalos	@bp.c	com		Conditions of	Approval:			Attached			
Date: February 7, 2018 Phone: (832) 609-7048						Attaclied							

^{*} Attach Additional Sheets If Necessary

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

December 8, 2017

Federal Indian Minerals Office Attn: Christine Bitsoi 6251 College Blvd, Suite B Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: NAVAJO ALLOTTED GAS COM A 001 API #: 3004513252

Dear Mrs. Bitsoi,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about December 13, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time.

Sincerely,

Erin Garifalos

Field Environmental Coordinator – San Juan Cell: 832-609-7048

Garifalos, Erin

From:

Buckley, Farrah (CH2M HILL)

Sent:

Friday, December 08, 2017 11:14 AM

To:

'Smith, Cory, EMNRD'; 'Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)'

Cc:

'jeffcblagg@aol.com'; 'blagg_njv@yahoo.com'; Garifalos, Erin

Subject:

BP Pit Close Notification - NAVAJO ALLOTTED GAS COM A 001

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

December 8, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

NAVAJO ALLOTTED GAS COM A 001 API 30-045-13252 (B) Section 25 – T28N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around December 12, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator – San Juan

Cell: 832-609-7048

Farrah Buckley
BGT Project Support
970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413									
	(50	5) 632-1199		TANK ID (if applicble):	Α					
FIELD REPORT:	(circle one): BGT CONFIRMATION /	RELEASE INVESTIGATION	N / OTHER:	PAGE #: 1	of					
SITE INFORMATION	I: SITE NAME: NAVAJO	ALLOTTED (GC A #1	DATE STARTED: 1	2/12/17					
QUAD/UNIT: B SEC: 25 TWP:	28N RNG: 9W PM:	NM CNTY:	SJ ST: NM	DATE FINISHED:						
1/4 - 1/4/FOOTAGE: 990'N / 1,70 LEASE #: 14-20-602-780		YPE: FEDERAL/ST/ STRIK ONTRACTOR: BP-J	Œ	ENVIRONMENTAL SPECIALIST(S):	NJV					
REFERENCE POINT				GL ELEV.:	E OEE'					
	GPS COORD.: 36									
2)		1007007 1071700		EARING FROM W.H.:						
	GPS COORD.:									
4)	GPS COORD.:		DISTANCE/BE	EARING FROM W.H.:						
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # O	R LAB USED:	ALI		OVM READING					
	(95) SAMPLE DATE: 12/12			015B/8021B/300.0 (CI)	(ppm) NA					
2) SAMPLE ID:										
3) SAMPLE ID:										
SAMPLE ID: SAMPLE ID:	SAMPLE DATE:									
SOIL DESCRIPTION	CONTROL CAND CHAY CAND		SBAVEL / OTHER							
COHESION (ALL OTHERS): NON COHESIVE SLIGHTL CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLY MOIST/W SAMPLE TYPE: GRAB COMPOSITE : DISCOLORATION/STAINING OBSERVED: YES	OOSE FIRM DENSE / VERY DENSE JET / SATURATED / SUPER SATURATED # OF PTS	HC ODOR DETECTED: YES	NO EXPLANATION -	/ STIFF / VERY STIFF / HARD						
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: NMOCD OR BLM REPS. NOT P	ED AND/OR OCCURRED : YES NO EXPL YES NO EXPLANATION - 105 BBL	ANATION:SHALLOW LOW PRO		ANK TO BE SET ATOP BO	GT LOCATION.					
EXCAVATION DIMENSION ESTIMATION	:NA ft. XNA	ft. X NA ft	. EXCAVATION ES	STIMATION (Cubic Yards) :	NA					
DEPTH TO GROUNDWATER: <100' N	NEAREST WATER SOURCE: >1,000'	NEAREST SURFACE WA	ATER: <1,000' NMC	OCD TPH CLOSURE STD:	100 ppm					
SITE SKETCH	BGT Located: off on site	PLOT PLAN	circle: attached 0V	M CALIB. READ. = NA	ppm RF =1.00					
			↑ OV	M CALIB. GAS = NA	ppm					
			NI	ME: NA am/pm DATE:	NA					
				MISCELL. N	OTES					
	FENCE			WO:						
STEEL CONTAINMENT	FENCE BERM		W.H. ⊕	REF #: P-813						
RING				VID: VHIXONEV	B2					
				PJ#:						
\ \		SEPARATOR		-	/14/10					
PROD.	PROTI		T	ank OVM = Organic Vapo	3/03/17 r Meter					
TANK	PBGTL T.B. ~ 6'			ppm = parts per million BGT Sidewalls Visible:						
	B.G.			BGT Sidewalls Visible:						
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATI	ON DEPRESSION: B.G. = RELOW GRADE: R = RE	FLOW: TH = TEST HOLE: ~ = APE	X - S.P.D.	BGT Sidewalls Visible: \	Y / N					
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	LOW-GRADE TANK LOCATION; SPD = SAMPLE P	OINT DESIGNATION; R.W. = RETA		Magnetic declination:	10° E					
APPLICABLE OR NOT AVAILABLE; SW-SINGL NOTES: GOOGLE EARTH IMAG	E WALL; DW - DOUBLE WALL; SB - SINGLE BOTH ERY DATE: 10/5/2016.	TOM; DB - DOUBLE BOTTOM. ONSITE: 12	2/12/17							

Analytical Report

Lab Order 1712717

Date Reported: 12/15/2017

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (95)

Project: NAVAJO ALLOTTED GC A 1

Collection Date: 12/12/2017 1:55:00 PM

Lab ID: 1712717-001

Matrix: SOIL

Received Date: 12/13/2017 7:00:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed Batch	
EPA METHOD 300.0: ANIONS					Analyst: MRA	
Chloride	ND	30	mg/Kg	20	12/13/2017 11:52:55 AM 35482	
EPA METHOD 8015D MOD: GASOLINE I	RANGE				Analyst: AG	
Gasoline Range Organics (GRO)	ND	3.9	mg/Kg	1	12/13/2017 12:38:25 PM R4774	5
Surr: BFB	103	70-130	%Rec	1	12/13/2017 12:38:25 PM R4774	5
EPA METHOD 8015M/D: DIESEL RANGE	ORGANICS	;			Analyst: TOM	
Diesel Range Organics (DRO)	ND	9.5	mg/Kg	1	12/13/2017 9:47:11 AM 35476	
Motor Oil Range Organics (MRO)	ND	47	mg/Kg	1	12/13/2017 9:47:11 AM 35476	
Surr: DNOP	103	70-130	%Rec	1	12/13/2017 9:47:11 AM 35476	
EPA METHOD 8260B: VOLATILES SHOP	RT LIST				Analyst: AG	
Benzene	ND	0.020	mg/Kg	1	12/13/2017 12:38:25 PM S4774	5
Toluene	ND	0.039	mg/Kg	1	12/13/2017 12:38:25 PM S4774	5
Ethylbenzene	ND	0.039	mg/Kg	1	12/13/2017 12:38:25 PM S4774	5
Xylenes, Total	ND	0.079	mg/Kg	1	12/13/2017 12:38:25 PM S4774	5
Surr: 4-Bromofluorobenzene	101	70-130	%Rec	1	12/13/2017 12:38:25 PM S4774	5
Surr: Toluene-d8	93.7	70-130	%Rec	1	12/13/2017 12:38:25 PM S4774	5

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
 - W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1712717

15-Dec-17

Client:

Blagg Engineering

Project:

NAVAJO ALLOTTED GC A 1

Sample ID MB-35482

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 35482

RunNo: 47741

Prep Date: 12/13/2017

SeqNo: 1528089

Units: mg/Kg

Analyte

Analysis Date: 12/13/2017

SampType: Ics

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD **RPDLimit** Qual

Chloride

Result PQL ND 1.5

TestCode: EPA Method 300.0: Anions RunNo: 47741

LCSS

Sample ID LCS-35482

Batch ID: 35482

Units: mg/Kg

Client ID:

Prep Date: 12/13/2017

Analysis Date: 12/13/2017

SeqNo: 1528090

RPDLimit

Analyte

PQL

15.00

SPK value SPK Ref Val %REC

0

93.1

%RPD

Qual

Chloride

14

1.5

90

LowLimit

HighLimit 110

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Practical Quanitative Limit **PQL**

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

Value above quantitation range

J Analyte detected below quantitation limits

Sample pH Not In Range

Reporting Detection Limit

Sample container temperature is out of limit as specified

Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1712717

15-Dec-17

Client:

Blagg Engineering

Project:

NAVAJO ALLOTTED GC A 1

Sample ID LCS-35476	SampType	e: LCS	Tes	TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: LCSS	Batch ID	Batch ID: 35476 Ru				47737				
Prep Date: 12/13/2017	Analysis Date	alysis Date: 12/13/2017 SeqNo: 1526304 Units: mg/Kg								
Analyte	Result P	QL SPK va	ue SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Diesel Range Organics (DRO)	46	10 50	00 0	91.4	73.2	114				
Surr: DNOP	4.5	5.0	00	89.2	70	130				
Sample ID MB-35476 SampType: MBLK TestCode: EPA Method 8015M/D: Diesel Range Organics										
Client ID: DRS	Ratch ID	35476		RunNo: 47	7737					

Cample ID IIID-33470	Campriye. MDER									
Client ID: PBS	Batch I	176	R	RunNo: 47737						
Prep Date: 12/13/2017	Analysis Dat	te: 12	2/13/2017	S	SeqNo: 1526305 Units: mg/Kg					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	9.6		10.00		96.0	70	130			

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
 - te detected below quantitation inints
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1712717

15-Dec-17

Client:

Blagg Engineering

Project:

NAVAJO ALLOTTED GC A 1

Commission of	Camal	BAT	DI IK	Too	T 10 1 TT 10 1 TT 10 TT										
Sample ID rb	SampType: MBLK				TestCode: EPA Method 8260B: Volatiles Short List										
Client ID: PBS	Batcl	h ID: S4	7745	RunNo: 47745											
Prep Date:	Analysis D	Analysis Date: 12/13/2017 SeqNo: 1526481 Units: mg/K					g								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	ND	0.025													
Toluene	ND	0.050													
Ethylbenzene	ND	0.050													
Xylenes, Total	ND	0.10													
Surr: 1,2-Dichloroethane-d4	0		0.5000		0	70	130			S					
Surr: 4-Bromofluorobenzene	0.50		0.5000		99.9	70	130								
Surr: Dibromofluoromethane	0		0.5000		0	70	130			S					
Surr: Toluene-d8	0.50		0.5000		100	70	130								

Sample ID 100ng btex lcs	100ng btex lcs SampType: LCS					PA Method	8260B: Vola	tiles Short	List						
Client ID: LCSS	ent ID: LCSS Batch ID: S47745					RunNo: 47745									
Prep Date:	Analysis D	ate: 12	2/13/2017	5	SeqNo: 1	527038	Units: mg/k	(g							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	1.0	0.025	1.000	0	105	70	130								
Toluene	1.0	0.050	1.000	0	100	70	130								
Ethylbenzene	0.99	0.050	1.000	0	98.9	70	130								
Xylenes, Total	3.0	0.10	3.000	0	101	70	130								
Surr: 4-Bromofluorobenzene	0.44		0.5000		88.8	70	130								
Surr: Toluene-d8	0.50		0.5000		99.1	70	130								

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1712717

15-Dec-17

Client:

Blagg Engineering

Project:

NAVAJO ALLOTTED GC A 1

Sample ID rb SampType: MBLK TestCode: EPA Method 8015D Mod: Gasoline Range Client ID: PBS Batch ID: R47745 RunNo: 47745 Prep Date: Analysis Date: 12/13/2017 SeqNo: 1526492 Units: mg/Kg Analyte Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD **RPDLimit** Qual 5.0 Gasoline Range Organics (GRO) ND Surr: BFB 500 500.0 101 70 130

Sample ID 2.5ug gro lcs	SampT	ype: LC	S	Test	tCode: El	PA Method	8015D Mod:	Gasoline	Range				
Client ID: LCSS	Batch	ID: R4	7745	R	tunNo: 4	7745							
Prep Date:	Analysis Date: 12/13/2017			S	eqNo: 1	527037	Units: mg/Kg						
Analyte	Result	esult PQL SPK value SPK R		SPK Ref Val	%REC LowLimit		HighLimit	%RPD	RPDLimit	Qual			
Gasoline Range Organics (GRO)	23	5.0	25.00	0	90.5	70	130						
Surr: BFB	480		500.0		95.8	70	130						

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
 - Sample pH Not In Range
- RL Reporting Detection Limit

P

W Sample container temperature is out of limit as specified

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name:	BLAGG	Work Order Number:	17127	17			RcptN	lo: 1		
Received By:	Anne Thorne	12/13/2017 7:00:00 AM			ann ,	H-				
Completed By:	Anne Thorne	12/13/2017 7:30:52 AM			anne	A.	_			
Reviewed By:	DDS	12/13/17	7							
Chain of Cus	stody									
1. Custody sea	als intact on sample	bottles?	Yes		No		Not Present			
2. Is Chain of C	Custody complete?		Yes	\checkmark	No		Not Present			
3. How was the	e sample delivered?	,	Cour	ier					*	
Log In										
4. Was an atte	empt made to cool th	ne samples?	Yes	\checkmark	No		NA [
.5. Were all sar	mples received at a t	temperature of >0° C to 6.0°C	Yes	✓ .	No		NA 🗆]		
6. Sample(s) ii	n proper container(s)?	Yes	\checkmark	No					
7. Sufficient sa	imple volume for ind	icated test(s)?	Yes	2	No					,
8. Are samples	(except VOA and C	NG) properly preserved?	Yes	✓	No			,		
9. Was present	vative added to bottle	es?	Yes		No	✓	NA C] .		. :
10.VOA vials ha	ave zero headspace	?	Yes		No		No VOA Vials	2	٠.	
11. Were any sa	ample containers rec	ceived broken?	Yes		No	✓ -	# of preserved			
, ,	work match bottle lat pancies on chain of		Yes	V	No		bottles checked for pH:	2 or >12	unless	noted)
13. Are matrices	correctly identified	on Chain of Custody?	Yes	\checkmark	No	□	Adjusted?			
14. Is it clear wh	at analyses were re	quested?		Y	No					*
	ding times able to be		Yes	✓	No	□	Checked by	<u> </u>		
(ii no, notily	customer for author	ization.)								
Special Hand	lling (if applicat	ble)								,
16. Was client n	otified of all discrepa	ancies with this order?	Yes		No		NA 🛂			
Person	n Notified:	Date	la mand constitute de la cons	i tu bi bi bi bi boh/milal bi ni bi banar	Con Anni Alla Anni A	ASSAULT				
By Wh	nom:	Via:] eMa	il Pho	ne 🗌	Fax [In Person			
Regard	ding:									
Client	Instructions:						and the second s			
17. Additional re	emarks:									
18. Cooler Info				. 1 -		. 1				
Cooler No	o Temp °C Cor		eal Da	te Si	gned B	У				
		mana an anna perte de se es este de se esta de la santida de la completa de la completa de la completa de la c	h.e tereten							

Chain-of-Custody Record Client: BLAEG / BP AMER) A Mailing Address:			Turn-Around						_							1					
			☐ Standard Project Name	HALL ENVIRONMENTAL ANALYSIS LABORATORY												r					
			NAVATO ALCOTTED &C A #					www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109													
				Project #:							5-345-				505-						
Phone :	#: (5	65)	320-3489	1				M.		. 000	010		Anal								
email or Fax#:			Project Mana	ger:	1/		=	only)	8	T	Т		04)	40						Γ	
QA/QC Package: □ Level 4 (Full Validation)			V	ECTON	VEGEZ	-	s- (8021)	TPH (Gas o	30 / MI		SIMS)		PO4,S	PCB's					TE		
Accreditation □ NELAP □ Other			Sampler: NELSON VELEZ PV On Ice: X Yes No.					+ TPH	(GRO / DRO / MRO)	18.1)	8270 8		03,NO2	s / 8082		(A)			COMPOST	or N)	
□ EDD (Type)			Sample Temp	perature:	10				<u>G</u>	4 bo	0 0	etals	N,	cide	(A)	i-V0	3		0	2	
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	17.12	一种性性的原理性的一种,所以1500mm。	BTEX **	+	TPH 8015B	TPH (Method 418.1)	PAH's (8310 or 8270	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE		5 74.0	Bubbl
12/12/17	1355	SOIL	SPC-TBC 5'(95)	402-1	COOL		7001	V		1								$\sqrt{}$		V	
																					L
										•										\perp	L
										_		\perp	_								\perp
										_		\perp	_								_
										_	\perp	+	_	_	_			Ш		_	\perp
									\vdash	\dashv	+	+	+	\vdash	-	_		\sqcup	\vdash	+	+
				-					\vdash	-	-	+	+	-	\vdash	-		H	\vdash	+	╀
									\vdash	+	_	_	-	\vdash	\vdash			\vdash		+	+
Date:	Time:	Relinquish	Men f	Received by:	Wat	12 Date	Time 7 /433	i	narks	: B	P	ده ده	tac	T:	ER	I AN	GP	RIT H	FALC PX61	1/2/	Щ.
Date:	1921	Relinquish	vo has	Received by)	Date 12//3	0700												FALC IX 61		
1	f necessary,	samples sub	mitted to Hall Environmental may be sub-	contracted to other a	ccredited laboratori	es. This sen	es as notice of this	possi	bility. A	lny sub	b-contra	cted da	ta will b	e clea	rly not	ated o	n the a	analytic	al report	L	



