OIL CONS. DIV DIST. 3

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

JAN 31 2018

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or								
Proposed Alternative Method Permit or Closure Plan Application								
Type of action:  Below grade tank registration  Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method  Modification to an existing permit/or registration  Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,								
or proposed alternative method								
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request								
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.								
Operator: BP America Production Company  OGRID #: 778								
Address: 200 Energy Court, Farmington, NM 87401								
Facility or well name: GCU 336								
API Number: 3004525470         OCD Permit Number:								
Center of Proposed Design: Latitude 36.65234 Longitude -108.0577 NAD83								
Surface Owner: 🔳 Federal 🗌 State 🗌 Private 🗀 Tribal Trust or Indian Allotment								
2.								
Pit: Subsection F, G or J of 19.15.17.11 NMAC								
Temporary: Drilling Workover								
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no								
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other								
☐ String-Reinforced								
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D								
Below-grade tank: Subsection I of 19.15.17.11 NMAC   TANK D								
Alternative Method:  Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.								
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Alternate. Please specify								

7 9								
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)								
Screen Netting Other								
☐ Monthly inspections (If netting or screening is not physically feasible)								
7.								
Signs: Subsection C of 19.15.17.11 NMAC								
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers								
☐ Signed in compliance with 19.15.16.8 NMAC								
Variances and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.								
Please check a box if one or more of the following is requested, if not leave blank:								
<ul> <li>□ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.</li> <li>□ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.</li> </ul>								
Exception(s). Requests must be submitted to the Santa Pe Environmental Buleau office for consideration of approval.								
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source							
General siting								
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes☐ No☐ NA							
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No							
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No							
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No							
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No							
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No							
Below Grade Tanks								
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured								
from the ordinary high-water mark).	Yes No							
- Topographic map; Visual inspection (certification) of the proposed site								
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)								
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole,								
or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No							
application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image								
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock								
watering purposes, or 300 feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							

4									
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Temporary Pit Non-low chloride drilling fluid									
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site									
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image									
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Permanent Pit or Multi-Well Fluid Management Pit									
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No								
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.  Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number:	NMAC 15.17.9 NMAC								
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC									
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:									

T T	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.  Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan	documents are
<ul> <li>□ Emergency Response Plan</li> <li>□ Oil Field Waste Stream Characterization</li> <li>□ Monitoring and Inspection Plan</li> <li>□ Erosion Control Plan</li> <li>□ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC</li> </ul>	
Proposed Closure: 19.15.17.13 NMAC  Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.  Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative  Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	rce material are Please refer to
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

Y w	
adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	□ Vaa□ Na
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
1 Diff i map	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 NMAC  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 5.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:	
18.  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
OCD Representative Signature: Approval Date: 2/1/2	9/18
Title: Livinon mental Spec. OCD Permit Number:	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date: 12/5/2017	
Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-local If different from approved plan, please explain.	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please into mark in the box, that the documents are attached.  Proof of Closure Notice (surface owner and division)  Proof of Deed Notice (required for on-site closure for private land only)  Plot Plan (for on-site closures and temporary pits)  Confirmation Sampling Analytical Results (if applicable)  Waste Material Sampling Analytical Results (required for on-site closure)  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique	licate, by a check

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments subn	nitted with this closure report is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all app	plicable closure requirements and conditions specified in the approved closure plan.
F : 0 - 11-1	
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Orin altil Dal	
erin garifalos	D   January 26, 2019
Signature:	Date: January 26, 2018
e-mail address: erin.garifalos@bp.com	Telephone: (832) 609-7048

# BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

**GCU 336** 

API No. 3004525470

Unit Letter A Section 24 T 28N R 12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

#### General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

#### Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

#### Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

# All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

### The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

### All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows:

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	<0.021
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.086
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<46
Chlorides	US EPA Method 300.0 or 4500B	620	64

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate detectable chloride concentration but is below regulatory standards. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate detectable chloride concentration but is below regulatory standards. Attached is a laboratory report and field report. The location has been reclaimed as the well has been plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location was reclaimed as the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled. The location was reclaimed as the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled. The location was reclaimed as the well has been plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

The area has been backfilled. The location was reclaimed as the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled. The location was reclaimed as the well has been plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

### State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141 Revised April 3, 2017

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

			Rele	ease Notifi	catioi	n and Co	orrective A	ction						
						OPERA'	ГOR		Initia	al Report		Final Repor		
Name of Co	ompany BF	<sup>2</sup> America	Produc	tion Compan	ıy		n Garifalos							
Address 20	0 Energy	Court, Fa		on, NM 8740	1	Telephone No. (832) 609-7048								
Facility Na	me GCU 3	336				Facility Typ	e: Natural Ga	as Wel						
Surface Ow	ner: Fed	eral		Mineral (	Owner:	Federal			API No	.300452	5470			
				LOC	ATIO	N OF RE	LEASE							
Unit Letter	Section	Township	Range	Feet from the	_	South Line	Feet from the	East/W	est Line	County				
Α	24	28N		1,035	Nor	th	1,110	Eas	t	S	San	Juan		
			Latitud	36.65234	L	ongitude1	08.0577	NAD8	3					
	_			NAT	ΓURE	OF REL	EASE							
Type of Rele	ase:: none	)					Release:: unkno			Recovered::				
Source of Re	lease: belo	w grade ta	nk -21	bbl		Date and F	Hour of Occurrence		Date and	Hour of Dis	covery:			
Was Immedi		Given?				If YES, To	Whom?		17 CL					
			Yes 🗸	No Not R	equired									
By Whom?						Date and I								
Was a Water	course Read		Yes 🗸	No		If YES, Vo	olume Impacting t	the Water	course.					
If a Watercon	irce was Im	pacted, Descr	he Fully ?	k										
				Soil	analys	sis resulte	beneath the d for Chlorid Field reports	des, B7	EX, ar	nd TPH b	elow	BGT		
Describe Are	a Affected	and Cleanup A	Action Tak	No actio		essary. F on is requ	inal laborato	ory an	alysis c	determin	ed no	)		
regulations a public health should their of or the environment	Il operators or the envi- operations h nment. In a	are required to ronment. The lave failed to a	o report ar acceptance adequately OCD accep	nd/or file certain to be of a C-141 report investigate and in	release n ort by the remediate	otifications as e NMOCD m e contaminati	knowledge and u nd perform correc arked as "Final R on that pose a thre e the operator of	etive action eport" do eat to gro	ons for rele es not reli ound water	eases which eve the oper , surface wa	may en ator of ter, hur	danger liability nan health		
	10.1	need a					OIL CON	SERVA	ATION	DIVISIO	N			
Signature:	run g	orifalo	14				D .							
Printed Name	Erin G	arifalos				Approved by	Environmental S	pecialist:						
		onmenta		rdinator		Approval Dat	e:	Е	xpiration l	Date:				
E-mail Addre	ess: erin.	garifalos	@bp.	com		Conditions of Approval:  Attached								
Date: Janua	ary 26, 2	018	Phone:	(832) 609-70	048					Attached				
Attach Addi	tional Shee	ets If Necess	ary											

# bp



BP America Production Company 200 Energy Court Farmington, NM 87401

November 27, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

#### VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: GALLEGOS CANYON UNIT 336

API #: 3004525470

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about November 30, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From:

Buckley, Farrah (CH2M HILL)

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)

Cc:

jeffcblagg@aol.com; blagg\_njv@yahoo.com; Garifalos, Erin; Beebe, Sabre; Moskal, Steven

Subject: Date: BP Pit Close Notification - GCU 336 Monday, November 27, 2017 8:55:59 AM

**BP America Production Company** 

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

#### SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

November 27, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 336 API 30-045-25470 (A) Section 24 – T28N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around November 30, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator – San Juan Cell: 832-609-7048

## Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

BP		ENGINEERING		API#: 3004525470
CLIENT:		BLOOMFIELD, 505) 632-1199	NM 87413	TANK ID (if applicble):
FIELD REPORT:	(circle one): BGT CONFIRMATION	ON / RELEASE INVESTIGATION	N / OTHER:	PAGE #: 1 of 1
SITE INFORMATION	I: SITE NAME: GCU	# 336		DATE STARTED: 11/30/17
QUAD/UNIT: A SEC: 24 TWP:	28N RNG: 12W	PM: NM CNTY:	SJ ST: NM	DATE FINISHED:
1/4 - 1/4/FOOTAGE: 1,035'N / 1,1 LEASE #: SF078904	10'E NE/NE LEA	SE TYPE: FEDERAL ST.	<b>/</b> F	ENVIRONMENTAL SPECIALIST(S): NJV
REFERENCE POINT		GPS COORD.: 36.6		
1) 21 BGT (SW/DB)		36.65234 X 108.057		GL ELEV.: 5,660'  RING FROM W.H.: 78', N24.5E
2)				
3)	GPS COORD.:		Blackbern bleen werech stall met betreen be-	RING FROM W.H.:
	GPS COORD.:		DISTANCE/BEA	OVM
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S	·		FDIO024DI200 0 (CI)
1) SAMPLE ID: <b>5PC - TB @ 6'</b> 2) SAMPLE ID:	• • • • • • • • • • • • • • • • • • • •			5B/8021B/300.0 (CI) NA
3) SAMPLE ID:				
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:	
5) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:	
SOIL DESCRIPTION  SOIL COLOR: DARK YEL  COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY  CONSISTENCY (NON COHESIVE SOILS): LC  MOISTURE: DRY SLIGHTLY MOIST MOIST / WI  SAMPLE TYPE: GRAB COMPOSITE - #  DISCOLORATION/STAINING OBSERVED: YES N	LOWSH ORANGE Y COHESIVE / COHESIVE / HIGHLY COHESIVE / DENSE / VERY DEN ET / SATURATED / SUPER SATURATE FOR PTS.  5	PLASTICITY (CLAYS): NON F DENSITY (COHESIVE CLA SE HC ODOR DETECTED: YES	PLASTIC / SLIGHTLY PLASTIC / C AYS & SILTS): SOFT / FIRM / S NO EXPLANATION -	OHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC STIFF / VERY STIFF / HARD  NATION -
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:	D AND/OR OCCURRED : YES NO EXPLANATION -	EXPLANATION:		
OTHER: GAS WELL PLUGGED & ABAND	ONED (P&A). NMOCD OR B	LM NOT PRESENT TO WIT	NESS CONFIRM ATION	SAMPLING.
EXCAVATION DIMENSION ESTIMATION:	NA ft. XNA	<b>A</b> ft. X <b>NA</b> ft	t. EXCAVATION ES	TIMATION (Cubic Yards) : NA
DEPTH TO GROUNDWATER: >100' N	EAREST WATER SOURCE: >1,0	000' NEAREST SURFACE W	ATER: <1,000' NMOO	CD TPH CLOSURE STD: ppm
SITE SKETCH	BGT Located: off on	site PLOT PLAN	circle: attached OM	CALIB. READ. = NA ppm RE = 1.00
	FENCE	PBGTL		CALIB. GAS = NA ppm ATE: NA
	(xxx)	T.B. ~ 6' B.G.		MISCELL. NOTES
	BERM →			o: 4300877507
			I =	FE #: X7-006X4-E:25470
			1 -	io: 190040007672
			-	L#: 745277
			_	ermit date(s): 06/03/10 CD Appr. date(s): 03/11/13
			Tai	nk OVM = Organic Vapor Meter
	P&A			
<u> </u>	MARKER			BGT Sidewalls Visible: Y / N
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO		R = RELOWATH - TEST HOLE ADD	X - S.P.D.	BGT Sidewalls Visible: Y / N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGLE	OW-GRADE TANK LOCATION; SPD = SAMP	PLE POINT DESIGNATION; R.W. = RET.	TOM AN LIMIT OF	lagnetic declination: 10° E
NOTES: GOOGLE EARTH IMAGE	ERY DATE: 3/15/2015.	ONSITE: 11	/30/17	

#### **Analytical Report**

#### Lab Order 1712005

Date Reported: 12/5/2017

#### Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Client Sample ID: 5PC-TB @ 6' (21)

Project: GCU 336

**Collection Date:** 11/30/2017 8:25:00 AM

Lab ID: 1712005-001

Matrix: SOIL

Received Date: 12/1/2017 7:08:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	MRA
Chloride	64	30	mg/Kg	20	12/1/2017 12:13:23 PM	35263
EPA METHOD 8015M/D: DIESEL RANG	E ORGANICS				Analyst	TOM
Diesel Range Organics (DRO)	ND	9.2	mg/Kg	1	12/1/2017 10:41:24 AM	35260
Motor Oil Range Organics (MRO)	ND	46	mg/Kg	1	12/1/2017 10:41:24 AM	35260
Surr: DNOP	104	70-130	%Rec	1	12/1/2017 10:41:24 AM	35260
EPA METHOD 8015D: GASOLINE RAN	GE				Analyst	NSB
Gasoline Range Organics (GRO)	ND	4.3	mg/Kg	1	12/1/2017 2:05:21 PM	G47476
Surr: BFB	91.5	15-316	%Rec	1	12/1/2017 2:05:21 PM	G47476
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.021	mg/Kg	1	12/1/2017 2:05:21 PM	B47476
Toluene	ND	0.043	mg/Kg	1	12/1/2017 2:05:21 PM	B47476
Ethylbenzene	ND	0.043	mg/Kg	1	12/1/2017 2:05:21 PM	B47476
Xylenes, Total	ND	0.086	mg/Kg	1	12/1/2017 2:05:21 PM	B47476
Surr: 4-Bromofluorobenzene	86.1	80-120	%Rec	1	12/1/2017 2:05:21 PM	B47476

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

CI	hain-c	f-Cus	tody Record	Turn-Around T	ime:	SAME				44	\LL		MIN	/TE	20	D.I.B.	4=	RIT	- A I	**
Client: BLAGG ENGR. / BP AMERICA		/ BP AMERICA	☐ Standard	Rush _	DAY			_		IAL									_	
				Project Name:							vw.ha									
Mailing Ad	ddress:	P.O. BOX	X 87		GCU # 33	16		490	)1 Ha	wkins								9		
		BLOOM	FIELD, NM 87413	Project #:						-345-						-410				
Phone #:		(505) 63	2-1199				70						-		lues					4 (8)
email or F	ax#:		4	Project Manag	jer:	*****				Т							_			T
QA/QC Pad	_		Level 4 (Full Validation)		NELSON V	ELEZ	218)	(kluc	MRO)				74,SO <sub>4</sub>	8082 PCB's			r - 300.1)			
Accreditat			Level 4 (I uli validation)	Sampler:	NELSON V	ELEZ ny	(80	Gas	10		SIMS		)2,P(	082			water			sample
□ NELAP		□ Other		Onice		(iiii)No	FMB's (8021B)	PH (	/ DR	18.1	270		3,N(	8/8		F	0.0			San
□ EDD (T	ype)			Sample Temp	Hardie 3:4 -		H	+ +	GRO.	od 5	or 8	tals	J,NO	ide	8	9	8		0	Y or
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALING T	BTEX ←MFB	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO / MRO)	TPH (Method 418.1) EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO3,NO2,PO4,SO4)	8081 Pesticides /	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /		Grab sample	5 pt. composite sa Air Bubbles (Y or N)
11/30/17	08 25	SOIL	5PC-TB@ 6 (ZI)	4 oz 1	Cool	107	٧		٧								٧			V
																			$\forall$	
																		$\neg$		
																			1	
									$\top$	$\top$							$\neg$	$\top$	+	
									$\top$									_	$\dagger$	_
									$\dashv$	+								_	+	+
									+	+								$\dashv$	+	
							П		$\top$									$\dashv$	+	+
									$\dashv$	+						$\vdash$			+	+
Date:	Time:	Relinquishe	d by: My VI	Received by:	100	Date Time - 11/30/1/1/10	Rem	arks:	-	ILLING I					BE FC	RWAI	RDED	FROM	BP. I	NOT,
Date: 130/17	Time:	Relinquishe		Received by:		Date Time							•							

If necessary, samples submitted to Hall Environmental may be subcontracted to other accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report.

## Hall Environmental Analysis Laboratory, Inc.

WO#:

1712005

05-Dec-17

Client:

Blagg Engineering

Project:

GCU 336

Sample ID MB-35263

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 35263

RunNo: 47471

Prep Date:

12/1/2017

SeqNo: 1516483

Units: mg/Kg

**RPDLimit** 

Qual

Analyte

Analysis Date: 12/1/2017

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD

Chloride

PQL

1.5

TestCode: EPA Method 300.0: Anions

Client ID:

Prep Date:

Sample ID LCS-35263 LCSS

SampType: Ics

ND

Result

Batch ID: 35263

RunNo: 47471

Units: mg/Kg

Analyte

12/1/2017

Analysis Date: 12/1/2017

SPK value SPK Ref Val %REC

92.7

LowLimit

HighLimit

Qual

**PQL** 1.5

110

%RPD

Chloride

14

15.00

SeqNo: 1516484

90

**RPDLimit** 

Result

Qualifiers:

Value exceeds Maximum Contaminant Level. D Sample Diluted Due to Matrix Holding times for preparation or analysis exceeded

H Not Detected at the Reporting Limit **PQL** 

Practical Quanitative Limit % Recovery outside of range due to dilution or matrix

E

Analyte detected in the associated Method Blank Value above quantitation range

J Analyte detected below quantitation limits Sample pH Not In Range

RL Reporting Detection Limit Sample container temperature is out of limit as specified Page 2 of 5

# Hall Environmental Analysis Laboratory, Inc.

ND

50

10.00

WO#: 17

1712005 05-Dec-17

Client:

Blagg Engineering

Project:

Motor Oil Range Organics (MRO)

Surr: DNOP

GCU 336

Sample ID LCS-35260	SampType: LCS	TestCode: EPA Method 8015M/D: Diesel Range Organics					
Client ID: LCSS	Batch ID: 35260	RunNo: 47457					
Prep Date: 12/1/2017	Analysis Date: 12/1/2017	SeqNo: 1515167	Units: mg/Kg				
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual				
Diesel Range Organics (DRO)	45 10 50.00	0 89.8 73.2	114				
Surr: DNOP	3.8 5.000	75.8 70	130				
Sample ID MB-35260	SampType: MBLK	TestCode: EPA Method	I 8015M/D: Diesel Range Organics				
Client ID: PBS	Batch ID: 35260	RunNo: 47457					
Prep Date: 12/1/2017	Analysis Date: 12/1/2017	SeqNo: 1515168	Units: mg/Kg				
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual				
Diesel Range Organics (DRO)	ND 10						

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank

70

130

- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

on limits Page 3 of 5

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1712005

05-Dec-17

Client:

Blagg Engineering

Project:

GCU 336

Sample ID RB	SampT	ype: ME	BLK	Tes	tCode: El	PA Method	8015D: Gaso	line Rang	е	
Client ID: PBS	Batch	ID: G4	7476	F	RunNo: 4	7476				
Prep Date:	Analysis D	ate: 12	2/1/2017	S	SeqNo: 1	516064	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	880		1000		88.5	15	316			

TestCode: EPA Method 8015D: Gasoline Range Sample ID 2.5UG GRO LCS SampType: LCS Client ID: LCSS Batch ID: **G47476** RunNo: 47476 Prep Date: Analysis Date: 12/1/2017 SeqNo: 1516065 Units: mg/Kg Analyte Result SPK value SPK Ref Val %REC LowLimit HighLimit %RPD **RPDLimit** Qual Gasoline Range Organics (GRO) 25 5.0 25.00 0 75.9 131 99.8 Surr: BFB 1000 1000 104 15 316

#### Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

Page 4 of 5

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1712005

05-Dec-17

Client:

Blagg Engineering

Project:

GCU 336

Sample ID RB	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batch ID: <b>B47476</b>			RunNo: 47476						
Prep Date:	Analysis Date: 12/1/2017			SeqNo: <b>1516095</b>			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.85		1.000		84.6	80	120			

Sample ID 100NG BTEX LC	S Samp	SampType: LCS			TestCode: EPA Method 8021B: Volatiles					
Client ID: LCSS	Batc	h ID: <b>B4</b>	7476	RunNo: 47476						
Prep Date:	Analysis [	Date: 12	2/1/2017	SeqNo: 1516096			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.93	0.025	1.000	0	92.6	77.3	128			
Toluene	0.93	0.050	1.000	0	92.7	79.2	125			
Ethylbenzene	0.92	0.050	1.000	0	92.3	80.7	127			
Xylenes, Total	2.8	0.10	3.000	0	94.1	81.6	129			
Surr: 4-Bromofluorobenzene	0.87		1.000		86.6	80	120			

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Page 5 of 5

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107

# Sample Log-In Check List

Website: www.hallenvironmental.com Client Name: BLAGG Work Order Number: 1712005 RcptNo: 1 12/1/2017 7:08:00 AM ame Sham Received By: **Anne Thome** anne Sham 12/1/2017 8:02:54 AM Completed By: **Anne Thorne** 12/01/17 Reviewed By: Chain of Custody Yes No 🗆 Not Present 1. Custody seals intact on sample bottles? No 🗌 Yes 🗹 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In Yes 🗸 No 🗌 NA 🗌 4. Was an attempt made to cool the samples? NA 🗌 5. Were all samples received at a temperature of >0° C to 6.0°C Yes 🗸 No 🗌 No 🗌 6. Sample(s) in proper container(s)? Yes 🗸 Yes V 7. Sufficient sample volume for indicated test(s)? 8. Are samples (except VOA and ONG) properly preserved? Yes V No 🗌 No 🗸 NA 🗌 Yes 🗆 9. Was preservative added to bottles? Yes No 🗌 No VOA Vials 10. VOA vials have zero headspace? No V 11. Were any sample containers received broken?. # of preserved bottles checked No 🗌 for pH: 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No 🗌 13. Are matrices correctly identified on Chain of Custody? Yes 🗹 No 🗌 14. Is it clear what analyses were requested? Checked by: Yes 🗸 No 🗌 15. Were all holding times able to be met? (If no, notify customer for authorization.) Special Handling (if applicable) Yes 16. Was client notified of all discrepancies with this order? No 🗌 NA 🗹 Person Notified: Date By Whom: eMail Phone Fax In Person Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No Temp °C Condition Seal Intact Seal No Seal Date 2.1 Good

**GALLEGOS CANYON UNIT 336** 



