State of New Mexico Energy, Minerals and Natural Resources Department

Susana Martinez Governor

Ken McQueen Cabinet Secretary

Matthias Sayer Deputy Cabinet Secretary Heather Riley, Division Director Oil Conservation Division



New Mexico Oil Conservation Division approval and conditions listed below are made in accordance with OCD Rule 19.15.7.11 and are in addition to the actions approved by BLM on the following <u>3160-4 or 3160-5</u> form.

Operator Signature Date: 2/1/18 Well information:

API WELL #	Well Name	Well #	Operator Name	Туре	Stat	County	Surf_Owner	UL	Sec	Twp	N/S	Rng W/E
30-039-27784- 00-00	SAN JUAN 29 5 UNIT		HILCORP ENERGY COMPANY	G		Rio Arriba	F	J	8	29	N	5 W

Application Type:

on Type.		
P&A	Drilling/Casing Change	Location Change

Recomplete/DHC (For hydraulic fracturing operations review EPA Underground injection control Guidance #84; Submit Gas Capture Plan form prior to spudding or initiating recompletion operations)



Conditions of Approval:

- Notify NMOCD 24hrs prior to beginning operations.
- Monitor intermediate casing during completion to ensure no communication.
- Perform a Braden head test within 6 months of the completion.

Seand T

NMOCD Approved by Signature

<u>2/19/18</u> Date

•			7	
Form 3160-5 (August 2007)	UNITED STATES DEPARTMENT OF THE INTE BUREAU OF LAND MANAGE		OMB Expires	1 APPROVED No. 1004-0137 5: July 31, 2010
			5. Lease Serial No.	MSF078305
	NDRY NOTICES AND REPORTS		6. If Indian, Allottee or Tribe	
	se this form for proposals to dril d well. Use Form 3160-3 (APD) fo			
	UBMIT IN TRIPLICATE - Other instruction		7. If Unit of CA/Agreement, 1	Name and/or No.
1. Type of Well				
Oil Well	X Gas Well Other			an 29-5 Unit 21B
2. Name of Operator	Hilcorp Energy Company		9. API Well No. 30-	039-27784
Ba. Address		one No. (include area code) 505-599-3400	10. Field and Pool or Explora	tory Area PC/Blanco Mesaverde
PO Box 4700, Farming 4. Location of Well (Footage, Sec., T.,		505-599-3400	11. Country or Parish, State	PC/Dialico Mesaverde
	NWSE) 2010'FSL & 2325' FEL, Se	ec. 8, T29N, R05W	Rio Arriba	, New Mexico
	THE APPROPRIATE BOX(ES) TO IN			IER DATA
TYPE OF SUBMISSION		TYPE OF A	CTION	
X Notice of Intent		epen	Production (Start/Resume) Reclamation	Water Shut-Off Well Integrity
Subsequent Report		w Construction X		Other
	Change Plans Plu	ig and Abandon	Temporarily Abandon	
Final Abandonment Notice	Convert to Injection Plu peration: Clearly state all pertinent details, inclu	ig Back	Water Disposal	-
the existing Mesaverde	ny plans to recomplete the subjo with the Pictured Cliffs. Attach ill be submitted and approved b	ed is the PC C102, r	ecomplete procedure a	-
	ACTIO OPERA AUTHO	APPROVAL OR ACCEP N DOES NOT RELIEVE TOR FROM OBTAININ ORIZATION REQUIRED DERAL AND INDIAN LA	THE LESSEE AND G ANY OTHER FOR OPERATIONS FEE NDS	CEIVED 0 1 2013 gton Field Office Land Management
14. I hereby certify that the foregoing is	s true and correct. Name (Printed/Typed)			
Tammy Jones		Title Operations/	Regulatory Technician -	Sr.
Signature 10mmA	Jonas	Date 2/1/2	INIR	
	THIS SPACE FOR FEE		FICE USE	
Approved by	Tambekou	Title	Indeum Engincer	Date 2/2/2018
that the applicant holds legal or equitable entitle the applicant to conduct operatio		would Office	FFO	
	43 U.S.C. Section 1212, make it a crime for any or representations as to any matter within its ju		ly to make to any department or a	gency of the United States any
Instruction on page 2)		NMOC	D PV	

6

District I

4

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

Phone:(505) 476-3470 Pax.(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-039-27784	2. Pool Code 77440	
		GOBERNADOR PICTURED CLIFFS (GAS)
4. Property Code	5. Property Name	6. Well No.
318837	SAN JUAN 29 5 UNIT	021B
7. OGRID No.	8. Operator Name	9. Elevation
372171	HILCORP ENERGY COMPANY	6605

UL - Lot Section Township Range Lot Idn Feet From N/S Line Feet From EW Line County J 8 29N 05W 2010 S 2325 E RIO ARRIBA		.				10.	Surface Locati	on -				•
J 8 29N 05W 2010 S 2325 E RIO ARRIBA	ſ	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
		J	8	29N	05W		2010	S	2325	E	-	RIO ARRIBA

 11. Bottom Hole Location If Different From Surface									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
			_						-
12. Dedicated Acres 320.00 E/2		13. Joint or Infill		14. Consolidatio	n Code		15. Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

		'. '.
 	-	
-	(<u>₹</u>)	
 	1	

	OPERATOR CERTIFICATION
knowledge ar mineral intere this well at th	fy that the information contained herein is true and complete to the best of my nd belief, and that this organization either owns a working interest or unleased est in the land including the proposed bottom hole location(s) or has a right to dril, is location pursuant to a contract with an owner of such a mineral or working a voluntary pooling agreement or a compulsory pooling order heretofore entered n.
E-Signed By:	Tammy Jones
E-Signed By: Title:	<i>Tammy Jones</i> Operations/Regulatory Technician - Sr.

surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By:Jason C. EdwardsDate of Survey:10/7/2004Certificate Number:15269

Form C-102 August 1, 2011

Permit 247828

Hilcorp

HILCORP ENERGY COMPANY SAN JUAN 29-5 UNIT 21B PICTURED CLIFFS RECOMPLETION SUNDRY

	JOB PROCEDURES
1.	MIRU service rig and associated equipment; test BOP.
2.	TOOH with 2 3/8" tubing set at 5,768'.
3.	Set a 4-1/2" cast iron bridge plug at +/- 3,800' to isolate the Mesa Verde. Note: TOC at 3,180' by CBL.
4.	Load the hole and pressure test the casing to frac pressure.
5.	N/D BOP, N/U frac stack and test frac stack to frac pressure.
6.	Perforate and frac the Pictured Cliffs in a single stage (Top Perforation @ 3,563'; Bottom Perforation @ 3,645').
7.	Isolate frac stages with a composite bridge plug.
8.	Nipple down frac stack, nipple up BOP and test.
9.	TIH with a mill and drill out top Pictured Cliffs isolation plug.
10.	Clean out to Mesa Verde isolation plug and, when water and sand rates are acceptable, flow test the Pictured Cliffs.
11.	Drill out Mesa Verde isolation plug and cleanout to PBTD of 6,102'. TOOH.
12.	TIH and land production tubing. Get a commingled Mesa Verde/Pictured Cliffs flow rate.



HILCORP ENERGY COMPANY SAN JUAN 29-5 UNIT 21B PICTURED CLIFFS RECOMPLETION SUNDRY

		nergy campany	urrent Schematic - Vers	ion 3	
Well N		SAN JUAN 29-5 UNIT #21B Surtice Legis Location 008-029N-005/V-J MV	B Ucerse No.	State Province NEW MEXICO	Well Conliguration Type Vertice1
around Eleve 6,605.00		Original KBRT Elevation (#) 6.618.00			
					7
-			riginal Hole, 1/31/2018	9.39.20 AM	
MD (ftKB)	TVD (ftKB)		Vertical schematic (a	actual)	
	13.2				
121				Surface Casing C	Cement; 13.0-245.0]
18.4	18.4			5/30/2005	n; 9.00 in; 13.0 ftKB; 245.0
255.1	245.1			fiKB	
1,498.0	1,497.9	NACIMIENTO (final)		intermediate Cas 8/5/2005	ing Cement, 13.0-3,874.0
2,732.9	2,732.5	OJO ALAMO (final)		×	
2,905.8	2,905.4	KIR5,766.	<u>0 ftKB</u>		
2,163.1	3,179.7				
8,252.1	3,251.7	-FRUITLAND (final)		×**	·
3,557.1	3,558.6	PICTURED CLIFFS (final)		× ×	
3,829.4	3,828.9				
5,850.4	3,629.8				
3,537.9	3,857.4				
2,872.7	3,872.2				
3,874.0	3,873.5			2; Intermediate; 7 TURBOLIZERS; 3	in; 6.46 in; 13.3 ftKB; 6
1,5313	3,584.3				
4574.1	4,573.5	CHACRA/OTERRO (final)		Production Casin 6/7/2005; TOC Fo	ng Cement, 3, 180.0-6, 105.0; und @ 3, 160' with CBL Run
5,522.9	5,582.0			on 06/15/2005	
5,441.9	5,441.7				
5,473.1	5,459.3				
5,751.0	5,750.1	POINT LOOKOUT (final)	1 9 	Perforated: 5.442	0-5.843.0: 6/20/2005
5,756.1	5,755.2		385		
5,757.1	5,755.1	Profile Nipple; 2 3/8 in; 5.766.0 ftKB; 5	767.0 ЯКВ ХХ ТГ		
5,753.0	a, rao. 1 5,787.1	Mule Shoe Guide; 2 3/8 in; 5,767.0 5,768.	O FIKB	80 87	
5,5-2.8	5,641.9				
6,102.0	6,101.1			3 Production: 4 1	2.0-6,105.0; 6/8/2005 /2 in; 4.05 in; 13.0 ftKB;
6,103.0	6,102.0			<u>6,105.0 ftKB</u>	@ 5223', 5210' & 5202'.;
6,105.0	8,104.0			Cement: 6.105.0-6	6,108.0: 6/8/2005
6,137.9	6,137.0			×	
8,138.1	6,137.1				

- ----

-