Districts 1 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

The Delow Grade Tailing Or	or	Tank,	Grade	Below-	Pit.
----------------------------	----	-------	-------	--------	------

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the nvironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: AL ELLIOTT D 001A
API Number: 3004522338 OCD Permit Number:
API Number: 3004522338 OCD Permit Number: U/L or Qtr/Qtr F Section 12 Township 29N Range 09W County: San Juan
Center of Proposed Design: Latitude 36.74190 Longitude -107.73363 NAD83
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: ☐ Drilling ☐ Workover ☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined Liner type: Thickness mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other ☐ String-Reinforced Liner Seams: ☐ Welded ☐ Factory ☐ Other Volume:
3. TANK A
Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: 45
4.
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

Alternate. Please specify

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
8.	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: □ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. □ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
0	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).	☐ Yes ☐ No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within, 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Temporary Pit Non-low chloride drilling fluid										
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No									
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site										
Permanent Pit or Multi-Well Fluid Management Pit										
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image										
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site										
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site										
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC										
Previously Approved Design (attach copy of design) API Number: or Permit Number:										
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doct attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.19 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	15.17.9 NMAC									
Previously Approved Design (attach copy of design) API Number: or Permit Number:										

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	Tuid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	
Within a 100-year floodplain.	☐ Yes ☐ No
- FEMA map	L les L No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 2	3106/2018
19.	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
Closure Completion Date: 12/18/2017	
Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-lo If different from approved plan, please explain.	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please incommark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits)	dicate, by a check

	Itted with this closure report is true, accurate and complete to the best of my knowledge and icable closure requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Signature:UTIN gwifalos	Date: February 9, 2018
e-mail address: erin.garifalos@bp.com	Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

AL ELLIOTT D 001A

API No. 3004522338

Unit Letter F Section 12 T 29N R 09W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	45 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.017
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.068
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<48
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-141 Revised April 3, 2017

Release Notification and Corrective Action												
				OPERA'			Initia	al Report		Final Report		
		America			Garifalos	7040						
Facility Nar	ne AL EL	LIOTT D 0	rmingto 01A	n, NM 87401			No. (832) 609- le: Natural Ga		ell			
Surface Ow				Mineral C						.300452	2338	}
Surface 5 H	ner . i cut	orai		-			FASE			1000102		
Unit Letter	Section	Township	Range	Feet from the		Orth/South Line Feet from the East/West Line County						
F	12	29N		1,710	Nor							Juan
Latitude 36.74190 Longitude -107.73363 NAD83												
				NAT	URE	OF RELI	EASE					
Type of Rele	ase:: none)					Release:: unkno			Recovered::		
Source of Re	lease: belo	w grade ta	nk - 45	bbl		n/a	lour of Occurrence	e:	n/a	Hour of Dis	covery:	
Was Immedia	ate Notice (Yes 🗸	No Not Re	equired	If YES, To	Whom?					
By Whom?						Date and H						
Was a Water	course Read		Yes 🗸	No		If YES, Vo	lume Impacting t	the Wat	ercourse.			
If a Watercou	irse was Im	pacted, Descr	ibe Fully.*									
Describe Con	CD h1	em and Reme	dial Astica	Tolon *								
Describe Cat	se of Proble	em and Reme	iiai Actioi	Sam	_		beneath the				_	
							d for Chlorid					
Describe Ass	- A CC4-1	1.01	-4' T-1-		ile Sta	iliualus. F	ield reports	anu i	aborato	ry results	sale	allacrieu.
Describe Are	a Affected	and Cleanup A	Action Tak	No actio	n nec	essary. F	inal laborate	ory ar	nalysis d	determin	ed no	
				remedia	l actio	n is requ	ired.					
71 1	C 1 . 1 .		1	1	1	1	1 1 1 1	1 .	1.1	20.00	OCD	11
regulations a	1 operators	are required to	report an	is true and comp d/or file certain re	elease no	otifications ar	nd perform correct	tive act	ions for rele	eases which	may en	danger
				e of a C-141 repo								
or the environ	nment. In a	ddition, NMC	CD accep	tance of a C-141								
federal, state,	or local lav	ws and/or regu	lations.				OIL CON	SERV	ATION	DIVISIO	N	
l	run a	wishalo	4									
Signature:	0	orifalo				Approved by	Environmental S	pecialis	t:			
Printed Name	Erin G	arifalos										
Title: Field	Enviro	onmenta	l Coo	rdinator	1	Approval Dat	e:		Expiration 1	Date:		
E-mail Addre	ss: erin.	garifalos	@bp.	com		Conditions of	Approval:			Attached		
Date: Febru				(832) 609-70	048							
Attach Addit	ional Shee	ets If Necess	ary									

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

December 8, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: A L ELLIOTT D 001A

API#: 3004522338

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about December 13, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From:

Buckley, Farrah (CH2M HILL)

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa, Fields@state.nm.us)

Cc:

jeffcblagg@aol.com; blagg_njv@yahoo.com; Garifalos, Erin

Subject: Date: BP Pit Close Notification - AL ELLIOTT D 001A Friday, December 08, 2017 11:16:56 AM

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

December 8, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

AL ELLIOTT D 001A API 30-045-22338 (F) Section 12 – T29N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT and a 45bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around December 13, 2017

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator - San Juan

Cell: 832-609-7048

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

, CLIENT: BP	P.O. BOX 87, E	ENGINEERING, IN BLOOMFIELD, NI		API #: 300452	_
	(5)	05) 632-1199		(if applicble):	A
FIELD REPORT:	(circle one): BGT CONFIRMATION	7 RELEASE INVESTIGATION /	OTHER:	PAGE #: 1	of
SITE INFORMATION	I: SITE NAME: A.L. E	LLIOTT D #1A		DATE STARTED: 12	/14/17
QUAD/UNIT: F SEC: 12 TWP:	29N RNG: 9W PN	: NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 1,710'N / 1,5	590'W SE/NW LEASE PROD. FORMATION: MV/DK	TYPE: FEDERAL STATE STRIKE		ENVIRONMENTAL SPECIALIST(S):	NJV
REFERENCE POINT		s coord.: 36.741		GL ELEV.:	E 004'
	GPS COORD.: 3				
2)		0,74100 X 107,70000		ARING FROM W.H.:	
3)					
	GPS COORD.:			ARING FROM W.H.:	
	CHAIN OF CUSTODY RECORD(S) #	OPTABLISED: LIAIT		THE PROPERTY.	OVM READING
SAMPLING DATA: 1) SAMPLE ID: 5PC - TB @ 5' (4')				15B/8021B/300 0 (CI)	(ppm)
1) SAMPLE ID:				130/002 10/300.0 (CI)	INA
3) SAMPLE ID:					
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
5) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLY MOIST MOIST / W. SAMPLE TYPE: GRAB COMPOSITE + DISCOLORATION/STAINING OBSERVED: YES M	DOSE (FIRM) DENSE / VERY DENSE JET / SATURATED / SUPER SATURATED # OF PTS		EXPLANATION -		
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: NMOCD OR BLM REPS. NOT PI	LOST INTEGRITY OF EQUIPMENT OF EQUIPMENT OF EXPLANATION -	PLANATION:			
EXCAVATION DIMENSION ESTIMATION	NA ft X NA	ft. X NA ft.	EXCAVATION ES	TIMATION (Cubic Yards) :	NA
DEPTH TO GROUNDWATER: >100'	NEAREST WATER SOURCE: >1,00	0' NEAREST SURFACE WATER	:<1,000' NMO	CD TPH CLOSURE STD:1	,000 ppm
SITE SKETCH	BGT Located: off on s	ite PLOT PLAN cir	rcle: attached OVIV	I CALIB. READ. = NA	_ppm RF =1.00
T.B.	GTL WOODEN R.W.		N	MISCELL. NO	ppm NA
	TO THE PARTY OF TH		_	VO:	
			1 -	REF#: P-792 ID: VHIXONEVE	22
		FENCE	_	<u>/ID: </u>	02
			_		14/10
W.H.	PROD.				07/17
\oplus	TANK	ERM	Tai	nk OVM = Organic Vapor	Meter
	ы	=1 MT(ppm = parts per million BGT Sidewalls Visible: Y	
		,	X - S.P.D.	BGT Sidewalls Visible: Y	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	ON DEPRESSION: R.G. = RELOW GRADE: R.=			BGT Sidewalls Visible: Y	/ N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	OW-GRADE TANK LOCATION; SPD = SAMPLE	POINT DESIGNATION; R.W. = RETAINING		/lagnetic declination:	10°E
APPLICABLE OR NOT AVAILABLE; SW-SINGLINOTES: GOOGLE EARTH IMAG		OTTOM; DB - DOUBLE BOTTOM. ONSITE: 12/14	/17		

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering Client Sample ID: 5PC-TB @ 5' (45)-A

 Project:
 A.L. ELLIOTT D 1A
 Collection Date: 12/14/2017 1:00:00 PM

 Lab ID:
 1712908-001
 Matrix: SOIL
 Received Date: 12/15/2017 7:30:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analys	st: MRA
Chloride	ND	30	mg/Kg	20	12/15/2017 10:55:06	AM 35535
EPA METHOD 8015M/D: DIESEL RAN	GE ORGANICS				Analys	st: TOM
Diesel Range Organics (DRO)	ND	9.7	mg/Kg	1	12/15/2017 11:43:19	AM 35531
Motor Oil Range Organics (MRO)	ND	48	mg/Kg	1	12/15/2017 11:43:19	AM 35531
Surr: DNOP	92.8	70-130	%Rec	1	12/15/2017 11:43:19	AM 35531
EPA METHOD 8015D: GASOLINE RA	NGE				Analys	st: NSB
Gasoline Range Organics (GRO)	ND	3.4	mg/Kg	1	12/15/2017 11:22:34 /	AM 35517
Surr: BFB	91.4	15-316	%Rec	1	12/15/2017 11:22:34	AM 35517
EPA METHOD 8021B: VOLATILES					Analys	t: NSB
Benzene	ND	0.017	mg/Kg	1	12/15/2017 11:22:34 A	AM 35517
Toluene	ND	0.034	mg/Kg	1	12/15/2017 11:22:34 A	AM 35517
Ethylbenzene	ND	0.034	mg/Kg	1	12/15/2017 11:22:34 /	AM 35517
Xylenes, Total	ND	0.068	mg/Kg	1	12/15/2017 11:22:34 A	AM 35517
Surr: 4-Bromofluorobenzene	110	80-120	%Rec	1	12/15/2017 11:22:34 /	AM 35517

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

CI	nain-c	of-Cus	stody Record	Turn-Around	Time:	SAME				н	ALL	=	NV	TE	20	MI	ME		FAI		
Client:	BLAG	G ENGR.	/ BP AMERICA	☐ Standard	☑ Rush _	DAY)					NAI										
				Project Name	Project Name:						ww.h									-	
Mailing Ad	ddress:	P.O. BO	X 87	A.I	. ELLIOTT	D #1A		49	01 H	awkir								9			
	BLOOMFIELD, NM 87413			Project #:						5-345			-	-		-410					
Phone #:	Phone #: (505) 632-1199							Ha.	ď			Anal	ysis	Red	ques	t			TEXT		
email or F	ax#:			Project Manag	јег:		2 3										\Box	\Box	\neg		
QA/QC Pad Standa			Level 4 (Full Validation)		NELSON V	ELEZ	₩ (8021B)	+ MTBE + TPH (Gas only)	MRO)		(S)		PO4,50	PCB's			ter - 300.1)			9	
Accreditat	ion:			Sampler:	NELSON V	ELEZ	18 80	(Gas	80	न	OSIN		102	808			/ wat			ldmi	
□ NELAP		□ Other		On Ice:		TINO TY	I	F	0/0	418	827	S	03,0	se /		(AC	0000			te s	Z
□ EDD (T	ype)	1			erature: //2		1	# #	(GR	90	0 0	etal	C,N	icide	(A))-i	- 3 - 1		e	osi	٤
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX ←MH	BTEX + MT	TPH 8015B (GRO / DRO	TPH (Method 418.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 / water		Grab sample	5 pt. composite sample	Air Bubbles (Y or N)
12/14/17	1300	SOIL	5PC-TB@ 5' (45)-A	4 oz 1	Cool	701	٧		٧								٧			٧	
																			\dashv		
			A 400/100							\top											\neg
										_	+								7		
											+	-		-					\dashv	\neg	\neg
					-					-	+	-							1	\dashv	\dashv
				-						+	+								-	\dashv	\dashv
									\vdash	+	+-			_			\vdash		-	\dashv	
										_	+	-		\vdash	-		\vdash	\vdash	-	\dashv	-
		-				-				-	+	-		\vdash			\vdash		-	\dashv	-
Date:	Time:	Relinquish	ed by:	Received by:		Date Time	Rem	arks	-	BILL DII	RECTLY	OBP	USING	THE	CONT	ACT V	VITH (CORRE	SPON	DING	VID
12/14/17	1421	90	lul_	1 rus	Val.	14 1421		ONT	ACT:	& REFE	RENCE #	WHE	N APP	LICA	BLE;						
Date:	Time:	Relinquish	ed by:	Received by:	the	Date Time /2//5//7	Ref		VID: ce#	VHIXO	NEVB - 792										
1:11	If necess	1 00	submitted to Hall Environmental may be	subcontracted to other	accredited laboratorie	es. This serves as notice of	this p	ossibil	ity. Ar	ny sub-co	ontracted	data	vill be	clearl	y notat	ted on	the ar	nalytica	repor	rt.	

Hall Environmental Analysis Laboratory, Inc.

WO#:

1712908

18-Dec-17

Client:

Blagg Engineering

Project:

A.L. ELLIOTT D 1A

Sample ID MB-35535

SampType: mblk

PQL

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Prep Date: 12/15/2017

Batch ID: 35535

RunNo: 47816

Units: mg/Kg

Qual

Analyte Chloride

Analysis Date: 12/15/2017

SeqNo: 1531039

HighLimit

%RPD **RPDLimit**

Result ND

Sample ID LCS-35535

SampType: Ics

TestCode: EPA Method 300.0: Anions RunNo: 47816

Client ID: LCSS Batch ID: 35535

Units: mg/Kg

Prep Date: 12/15/2017

Analysis Date: 12/15/2017

SeqNo: 1531040

%RPD

Analyte

SPK value SPK Ref Val %REC 15.00

92.4

RPDLimit

Qual

14

0

HighLimit 110

Chloride

1.5

PQL

SPK value SPK Ref Val %REC LowLimit

90

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix D

Η Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Sample pH Not In Range

RL Reporting Detection Limit

Sample container temperature is out of limit as specified

Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1712908

18-Dec-17

Client:

Blagg Engineering

Project:

A.L. ELLIOTT D 1A

Sample ID LCS-35531	SampType: LCS			TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: LCSS	Batch	ID: 35	531	R	tunNo: 4	7811				
Prep Date: 12/15/2017	Analysis Da	te: 12	2/15/2017	S	eqNo: 1	529467	Units: mg/F	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	46	10	50.00	0	91.4	73.2	114			
Surr: DNOP	4.6		5.000		91.2	70	130			

Sample ID MB-35531	SampType: MBLK			TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: PBS	Batch	ID: 35	531	R	RunNo: 4	7811				
Prep Date: 12/15/2017	Analysis D	ate: 12	2/15/2017	S	SeqNo: 1	529468	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	9.9		10.00		99.1	70	130			

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

The state of the s

Page 3 of 5

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1712908

18-Dec-17

Client: Project: Blagg Engineering A.L. ELLIOTT D 1A

Sample ID MB-35517

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

PBS

Batch ID: 35517

PQL

RunNo: 47817

Prep Date:

12/14/2017

Analysis Date: 12/15/2017

960

SeqNo: 1530380

Analyte

Result

Units: mg/Kg

SPK value SPK Ref Val %REC

HighLimit %RPD

Qual

Gasoline Range Organics (GRO) Surr: BFB

1000

96.2

316

RPDLimit

Sample ID LCS-35517

Prep Date: 12/14/2017

SampType: LCS

0

TestCode: EPA Method 8015D: Gasoline Range

Client ID: LCSS

Batch ID: 35517

RunNo: 47817

%REC

SeqNo: 1530381

LowLimit

LowLimit

15

Units: mg/Kg

HighLimit

Qual

Gasoline Range Organics (GRO) Surr: BFB

Result 27 970

Analysis Date: 12/15/2017 5.0

25.00 1000

SPK value SPK Ref Val

107 96.9 75.9 15

131 316

%RPD **RPDLimit**

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix Holding times for preparation or analysis exceeded H Not Detected at the Reporting Limit ND

Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank В

Value above quantitation range

Analyte detected below quantitation limits

P Sample pH Not In Range Reporting Detection Limit

Sample container temperature is out of limit as specified

Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1712908

18-Dec-17

Client: Project:

Blagg Engineering
A.L. ELLIOTT D 1A

TestCode: EPA Method 8021B: Volatiles Sample ID MB-35517 SampType: MBLK Client ID: **PBS** Batch ID: 35517 RunNo: 47817 Analysis Date: 12/15/2017 SeqNo: 1530395 Units: mg/Kg Prep Date: 12/14/2017 SPK value SPK Ref Val %REC LowLimit Analyte Result PQL HighLimit %RPD **RPDLimit** Qual Benzene 0.025 Toluene ND 0.050 ND 0.050 Ethylbenzene Xylenes, Total ND 0.10 Surr: 4-Bromofluorobenzene 1.000 114 120 1.1

Sample ID LCS-35517	SampType: LCS			TestCode: EPA Method 8021B: Volatiles						
Client ID: LCSS	Batch ID: 35517			RunNo: 47817						
Prep Date: 12/14/2017	Analysis D	ate: 12	2/15/2017	S	SeqNo: 1	530396	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.95	0.025	1.000	0	94.8	77.3	128			
Toluene	0.97	0.050	1.000	0	96.6	79.2	125			
Ethylbenzene	0.97	0.050	1.000	0	97.0	80.7	127			
Xylenes, Total	3.0	0.10	3.000	0	98.5	81.6	129			
Surr: 4-Bromofluorobenzene	1.1		1.000		110	80	120			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawktns NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

Albuquerque, NM 87109 Sample Log-In Check List

Client Name:	BLAGG	Work Order Number:	1712908		RcptNo:	1
Received By:	Anne Thorne	12/15/2017 7:30:00 AM		anne Il-	~	
Completed By:	Anne Thorne	12/15/2017 8:13:09 AM		Aone Sh Aone Sh	_	
Reviewed By:						
						*
Chain of Cus	<u>tody</u>					
	ls intact on samp		Yes	No 🗆	Not Present	
	Custody complete		Yes 🗹	No 🗆	Not Present	
3. How was the	sample delivere	d?	Courier			
Log In	1	*				
4. Was an atte	mpt made to coo	ol the samples?	Yes 🗹	No 🗆	NA 🗆	
5. Were all sam	nples received at	a temperature of >0° C to 6.0°C	Yes 🗹	No 🗆	NA 🗆	
6. Sample(s) in	n proper containe	r(s)?	Yes 🗹	No 🗆		
7 Sufficient sar	mple volume for	indicated test(s)?	Yes ✓	No 🗔		
	* .	d ONG) properly preserved?	Yes 🗹	No 🗆		
	ative added to be		Yes 🗌	No 🗹	NÁ 🗆	
					' ' ' · · · · · · · · · · · · · · · · ·	
10.VOA vials ha			Yes 🗌	No 🗆	No VOA Vials	
11. Were any sa	imple containers	received broken?	Yes -	· No ☑	# of preserved	
12. Does paperw	ork match bottle	labels?	Yes 🗹	No 🗆	bottles checked for pH:	
	pancies on chain		, , ,		(<2 0	r >12 unless noted)
		ed on Chain of Custody?	Yes 🗹	No 🗆	Adjusted? _	
14. Is it clear who			Yes 🗹	· No L	Checked by:	
15. Were all hold (If no, notify of	ling times able to customer for auth	·	Yes ⊻	No 📙	Criecked by.	
Special Handi	ling (if applic	able)				
16. Was client no	otified of all discre	epancies with this order?	Yes	No 🗆	NA 🗹	
Person	Notified:	Date	in the same and th]
By Who	om:	Via:	eMail [Phone Fax	☐ In Person	
Regard	- Contractor					
Client I	nstructions:					
17. Additional re	marks:					
18. Cooler Infor						
Cooler No			eal Date	Signed By		
[1	1.0 Go	ood Yes		<u> </u>]	



