District II
811 S. First St., Artesia, NM 88240
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

## <u>Pit, Below-Grade Tank, or</u> Proposed Alternative Method Permit or Closure Plan Application

Type of action:  Below grade tank registration  Permit of a pit or proposed alternati  Closure of a pit, below-grade tank, of a modification to an existing permit of a pit, below-grade tank, of modification to an existing permit of a pit or proposed alternation.	or proposed alternative representation	
Instructions: Please submit one application (Form C-144) per	r individual pit, below-grad	de tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability sl environment. Nor does approval relieve the operator of its responsibility to comply with		
I.	any other applicable govern	
Operator: BP America Production Company	OGRID #: 778	OIL CONS. DIV DIST. 3
Address: 200 Energy Court, Farmington, NM 87401		
Facility or well name: BOLACK 002		FEB 2 0 2018
API Number: 3004523257 OCD P	ermit Number:	
U/L or Qtr/Qtr G Section 19 Township 28N  Center of Proposed Design: Latitude 36.64713 Longi	Range 08W Co	ounty: San Juan
Center of Proposed Design: Latitude 36.64713 Longi	tude -107.71897	NAD83
Surface Owner: Federal State Private Tribal Trust or Indian Allotme		
Temporary: Drilling Workover  Permanent Emergency Cavitation P&A Multi-Well Fluid Mana Lined Unlined Liner type: Thickness mil LLDPE F  String-Reinforced  Liner Seams: Welded Factory Other Vo	HDPE PVC Other	
Below-grade tank: Subsection I of 19.15.17.11 NMAC  TANK	A	
Volume: 95 bbl Type of fluid: Produced Water		
Tank Construction material: Steel		
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inc	th lift and automatic overflo	ow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ■ Other Single wa	all/ Double bottom; side	ewalls not visible
Liner type: Thicknessmil		
4.  Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the	e Santa Fe Environmental	Bureau office for consideration of approval.
5.		
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, tempor	rary pits, and below-grade	tanks)
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporal Chain link, six feet in height, two strands of barbed wire at top (Required if loc institution or church)		,
☐ Chain link, six feet in height, two strands of barbed wire at top (Required if loc	rated within 1000 feet of a p	,

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other	
☐ Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC  12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
<u>Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.</u> NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300 feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natural Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.  Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number:  or Permit Number:	NMAC 15.17.9 NMAC
II. Multi Wall Fluid Management Dit Cheeldist. Subsection D of 10 15 17 0 NMAC	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Previously Approved Design (attach copy of design) API Number:  or Permit Number:	.15.17.9 NMAC

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.  Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Climatological Factors Assessment  Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan  Emergency Response Plan  Oil Field Waste Stream Characterization  Monitoring and Inspection Plan  Erosion Control Plan  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.  Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fallernative  Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geology; Topographic map	
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the square plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached to the square plan of Subsection Constructions: Each of the following items must be attached.	
Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate required Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure st Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	ements of 19.15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowl	edge and belief.
Name (Print): Title:	
Signature: Date:	
e-mail address:	
18.  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see atta	achment)
OCD Representative Signature: Approval Date	e: 212612018
Title: Environmental pacifist OCD Permit Number:	, ,
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC	
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. It section of the form until an approved closure plan has been obtained and the closure activities have been completed.	Please do not complete this
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. It section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date: 12/2	Please do not complete this
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. It section of the form until an approved closure plan has been obtained and the closure activities have been completed.	Please do not complete this 21/2017
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. It section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date: 12/2  20.  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal	21/2017  al (Closed-loop systems only)

Operator Closure Certification:	
	ed with this closure report is true, accurate and complete to the best of my knowledge and able closure requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Signature:Utin garifalos	Date: February 14, 2018
e-mail address: erin.garifalos@bp.com	Telephone: (832) 609-7048

# BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

# BELOW-GRADE TANK CLOSURE PLAN

#### **BOLACK 002**

API No. 3004523257

Unit Letter G Section 19 T 28N R 08W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

#### General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

#### Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

#### Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

# All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

#### The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

#### All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.016
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.063
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<47
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District 1 1625 N. French Dr., Hobbs, NM 88240
District II 811 S. First St., Artesia, NM 88210
District III 1000 Rio Brazos Road, Aztec, NM 87410
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

#### State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

**OPERATOR** 

Form C-141 Revised April 3, 2017 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Final Report

**Initial Report** 

# Release Notification and Corrective Action

				tion Compan			n Garifalos			
Address 20	0 Energy	Court, Fa	rmingto	n, NM 87401			No. (832) 609-			
Facility Nar	ne BOLA	CK 002				Facility Typ	e: Natural Ga	as We	ell	
Surface Ow	ner: Fede	eral		Mineral C	)wner	: Federal			API No	.3004523257
				LOCA	ATIO	N OF RE	LEASE			
Unit Letter	Section	Township	Range	Feet from the	North	n/South Line	Feet from the	East/\	West Line	County
G	19	28N	W80	2,430	No	rth	1,650	Eas	st	San Juan
			Latitud	<sub>e</sub> 36.64713	L	ongitude1	07.71897	NAD	83	
				NAT		OF REL				
Type of Rele	ase:: none	)					Release:: unkno	own	Volume F	Recovered:: N/A
Source of Re	lease: belo	w grade ta	nk - 95	obl		Date and In/a	Iour of Occurrence	e:	Date and n/a	Hour of Discovery:
Was Immedia	ate Notice (		Yes 🗸	No Not Re	equired	If YES, To	Whom?			
By Whom?			105	110 🗖 110110	equired	Date and H	Jour			
Was a Water	course Read	ched?					olume Impacting t	he Wate	ercourse.	
			Yes ✓	No						
If a Watercou	rse was Im	pacted, Descri	be Fully.*							
Describe Cau	se of Proble	em and Remed	dial Action	<sup>1 Taken.*</sup> Samı	olina	of the soil	beneath the	BGT	was do	ne during removal.
					_					nd TPH below BGT
					-					ry results are attached.
Describe Are	a Affected	and Cleanup A	ction Tak	en.*						
				No actio		-		ory ar	nalysis c	determined no
				remedia	l action	on is requ	ired.			
										uant to NMOCD rules and
										eases which may endanger eve the operator of liability
										, surface water, human health
or the environ	nment. In a	ddition, NMO	CD accep							ompliance with any other
tederal, state,	or local lav	ws and/or regu	lations.				OIL COM	CEDV	ATION	DIVISION
0	Tim a	17:0-0-	1				OIL CONS	SEK V	ATION	DIVISION
Signature:	non g	vigialo								
Signature:	Erin C	orifolos				Approved by	Environmental Sp	pecialis	t:	
Title: Field	Enviro	onmenta	I Cooi	dinator		Approval Dat	e:	]	Expiration I	Date:
E-mail Addre	ss: erin.	garifalos	@bp.o	com		Conditions of	Approval:			Attached
Date: Febru	ary 14, 2	2018	Phone:	(832) 609-70	)48					Attached
* Attach Addit										

# bp



BP America Production Company 200 Energy Court Farmington, NM 87401

December 14, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

#### VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: BOLACK 002

API#: 3004523257

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about December 19, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

#### Garifalos, Erin

From:

Buckley, Farrah (CH2M HILL)

Sent:

Thursday, December 14, 2017 9:11 AM

To:

'Smith, Cory, EMNRD'; 'Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)'

Cc:

'ieffcblagg@aol.com'; 'blagg niv@yahoo.com'; Garifalos, Erin

Subject:

BP Pit Close Notification - BOLACK 002

#### **BP America Production Company**

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

#### SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

December 14, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

BOLACK 002 API 30-045-23257 (G) Section 19 – T28N – R08W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around December 19, 2017.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator – San Juan Cell: 832-609-7048

Farrah Buckley
BGT Project Support
970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	P.O. BOX 87, B	NGINEERING, IN LOOMFIELD, NN 05) 632-1199		API #: 300452 TANK ID (if applicble):	23257 A
FIELD REPORT:	(circle one): BGT CONFIRMATION /		OTHER:	_	
SITE INFORMATION QUAD/UNIT: <b>G</b> SEC: <b>19</b> TWP:  1/4 -1/4/FOOTAGE: <b>2,430'N / 1,6</b>	28N RNG: 8W PM:	NM CNTY: SJ	ST: NM / FEE / INDIAN	DATE STARTED: 12 DATE FINISHED: ENVIRONMENTAL	2/19/17
LEASE #: NM03549  REFERENCE POINT	PROD. FORMATION: MV/DK CO	OTOUCE	ONZALES	SPECIALIST(S):	NJV 5.838'
1) 95 BGT (SW/DB) 2) 3)	GPS COORD.: 36,	5.64713 X 107.71897	DISTANCE/BEAI  DISTANCE/BEAI  DISTANCE/BEAI	RRING FROM W.H.: 91', S	310.5W
SAMPLING DATA:  1) SAMPLE ID:	SAMPLE DATE:  SAMPLE DATE:	SAMPLE TIME: 1330 SAMPLE TIME: SAMPLE TIME: SAMPLE TIME:	LAB ANALYSIS: LAB ANALYSIS: LAB ANALYSIS: LAB ANALYSIS:	15B/8021B/300.0 (CI)	OVM READING (ppm) NA
SOIL DESCRIPTION  SOIL COLOR: DARK YEL  COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY  CONSISTENCY (NON COHESIVE SOILS): LO  MOISTURE: DRY / SLIGHTLY MOIST MOIST WE  SAMPLE TYPE: GRAB COMPOSITE #  DISCOLORATION/STAINING OBSERVED: YES N	LOWISH ORANGE  Y COHESIVE / COHESIVE / HIGHLY COHESIVE  DOSE [FIRM] DENSE / VERY DENSE  JET / SATURATED / SUPER SATURATED  # OF PTS. 5	PLASTICITY (CLAY) / CLAY / GRAVE PLASTICITY (CLAYS): NON PLASTIC DENSITY (COHESIVE CLAYS &: HC ODOR DETECTED: YES NO ANY AREAS DISPLAYING WETNES	C/SLIGHTLY PLASTIC/CO SILTS): SOFT/FIRM/S	STIFF / VERY STIFF / HARD	GHLY PLASTIC
SITE OBSERVATION  APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:  OTHER: NMOCD OR BLM REPS. NOT PR	LOST INTEGRITY OF EQUIPMENT: ED AND/OR OCCURRED: YES NO EXPL YES NO EXPLANATION - 105 BBL	ANATION: L SHALLOW LOW PROFILE A	ABOVE-GRADE TAI	NK TO BE SET ATOP BG	LOCATION.
	E NA ft. X NA  IEAREST WATER SOURCE: >1,000'	ft. X <u>NA</u> ft.  NEAREST SURFACE WATER:	1 0001	TIMATION (Cubic Yards) : CD TPH CLOSURE STD:	NA ,000 ppm
SITE SKETCH	BGT Located : off for site	PLOT PLAN circ	A	CALIB. GAS = NA	ppm RF=1.00 ppm NA
PROD. TANK  FENCE -  NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO	DN DEPRESSION; B.G. = BELOW GRADE; B = BE		RI VI P. OX Tan ID A	VO:  DEF #: P-852  ID: VHIXONEVE  J #:  ermit date(s): 06/  CD Appr. date(s): 03/  OVM = Organic Vapor I  ppm = parts per millior	32 14/10 03/17 Weter
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELO	OW-GRADE TANK LOCATION; SPD = SAMPLE PO E WALL; DW - DOUBLE WALL; SB - SINGLE BOTT	OINT DESIGNATION; R.W. = RETAINING	WALL; NA - NOT M	flagnetic declination: 1	0°E

#### **Analytical Report**

#### Lab Order 1712B61

Date Reported: 12/21/2017

### Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (95)

Project: BOLACK 2

Collection Date: 12/19/2017 1:30:00 PM

Lab ID: 1712B61-001

Matrix: SOIL

Received Date: 12/20/2017 6:30:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed Batc	h
EPA METHOD 300.0: ANIONS					Analyst: CJS	
Chloride	ND	30	mg/Kg	20	12/20/2017 1:00:24 PM 3562	6
EPA METHOD 8015M/D: DIESEL RANGE	ORGANICS				Analyst: TOM	1
Diesel Range Organics (DRO)	ND	9.5	mg/Kg	1	12/20/2017 11:35:25 AM 3562	2
Motor Oil Range Organics (MRO)	ND	47	mg/Kg	1	12/20/2017 11:35:25 AM 3562	2
Surr: DNOP	104	70-130	%Rec	1	12/20/2017 11:35:25 AM 3562:	2
EPA METHOD 8015D: GASOLINE RANG	E				Analyst: NSB	
Gasoline Range Organics (GRO)	ND	3.2	mg/Kg	1	12/20/2017 11:04:32 AM G479	14
Surr: BFB	94.7	15-316	%Rec	1	12/20/2017 11:04:32 AM G479	14
EPA METHOD 8021B: VOLATILES					Analyst: NSB	
Benzene	ND	0.016	mg/Kg	1	12/20/2017 11:04:32 AM B479	14
Toluene	ND	0.032	mg/Kg	1	12/20/2017 11:04:32 AM B479	14
Ethylbenzene	ND	0.032	mg/Kg	1	12/20/2017 11:04:32 AM B479	14
Xylenes, Total	ND	0.063	mg/Kg	1	12/20/2017 11:04:32 AM B479	14
Surr: 4-Bromofluorobenzene	114	80-120	%Rec	1	12/20/2017 11:04:32 AM B479	14

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

CI	hain-c	of-Cus	stody Record	Turn-Around T	Time:	SAME				H	IA		FI	NV	TE	20	N.	VE	NT	AT.
Client:	BLAG	G ENGR.	/ BP AMERICA	Standard Project Name:	☑ Rush _	DAY				A		AL	YS	319	S L	A	30	RA		RY
Mailing Ad	ddress:	P.O. BO	X 87	1	BOLACK #	2		49	01 H	awk	ins N	VE -	Alb	uqu	erqu	ue, N	IM 8	7109	)	
M		BLOOM	FIELD, NM 87413	Project #:			1				45-39				505-					
Phone #:		(505) 63	2-1199	1.			200	76.	W.	W.	Say.	А	inal	/sis	Red	ques	t			MAN.
email or F	ax#:			Project Manag	ger:									•				(1	T	
QA/QC Pad  Standa	_		Level 4 (Full Validation)		NELSON VI	LEZ	₩ (8021B)	only)	(MRO)			(S)		PO4,50,	PCB's			ter - 300.1)		0
Accreditat		□ Other		Sampler:	NELSON VI	LEZ No	8) <b>s,am</b>	+ MTBE + TPH (Gas only)	/ DRO /	18.1)	504.1)	270SIN		3,NO2,	5 / 8082		A)	0.0 / water		sample
□ EDD (T	ype)				erature 2 144	Berns (L. II.)	I	E+1	GRO	od 4	od 5	918	tals	J'NC	cide	F	-\0	1-30	_	osite
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALAG Filzsij	BTEX +-MTB	BTEX + MTB	TPH 8015B (GRO / DRO	TPH (Method 418.1)	EDB (Method	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO3,NO2,PO4,SO4)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /	Grab cample	5 pt. composite
12/19/17	1330	SOIL	5PC-TB@ 5 (95)	4 oz 1	Cool	701	٧		٧									٧		٧
Date: 12/19/17 Date: 12/19/17	Time: 1532 Time: \\\$50	Relinquish	lulj	Received by:	In m	Date Time  2 to 10 1333  Clate' Time  12/20//1  20/30	Rei	feren	ACT: VID:	& REI	FEREN N GAI KONE P - 8	RIFAI EVB2 852	LOS	VA	NCE	HIXO	ON			ONDING '

### Hall Environmental Analysis Laboratory, Inc.

WO#:

1712B61

21-Dec-17

Client:

Blagg Engineering

Project:

**BOLACK 2** 

Sample ID MB-35626

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 35626

RunNo: 47918

HighLimit

Prep Date:

12/20/2017

Analysis Date: 12/20/2017

SeqNo: 1535014

Units: mg/Kg

%RPD

%RPD

Qual

Analyte Chloride

Result **PQL** ND

SPK value SPK Ref Val %REC LowLimit 1.5

TestCode: EPA Method 300.0: Anlons

**RPDLimit** 

Sample ID LCS-35626 Client ID:

LCSS

SampType: Ics Batch ID: 35626

RunNo: 47918

Prep Date: 12/20/2017

14

0

Units: mg/Kg

Analyte

Analysis Date: 12/20/2017

SeqNo: 1535015

**RPDLimit** 

Qual

SPK value SPK Ref Val **PQL** 

90

HighLimit

Chloride

Result

15.00 1.5

%REC 90.2

LowLimit

110

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- Н Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- В Analyte detected in the associated Method Blank
- Е Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- Reporting Detection Limit RL
- Sample container temperature is out of limit as specified

Page 2 of 5

## Hall Environmental Analysis Laboratory, Inc.

WO#:

1712B61

21-Dec-17

Client:

Blagg Engineering

Project:

**BOLACK 2** 

Sample ID LCS-35622	Samp	ype: LC	s	Tes	tCode: El	PA Method	8015M/D: Di	esel Rang	e Organics	
Client ID: LCSS	Batc	n ID: 35	622	F	RunNo: 4	7873				
Prep Date: 12/20/2017	Analysis [	Date: 12	2/20/2017	8	SeqNo: 1	534671	Units: mg/F	<b>(</b> g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	46	10	50.00	0	91.8	73.2	114			
Surr: DNOP	4.7		5.000		93.8	70	130			
Sample ID MB-35622	SampT	ype: ME	BLK	Tes	tCode: EF	A Method	8015M/D: Di	esel Rang	e Organics	
Sample ID MB-35622 Client ID: PBS	•	ype: <b>ME</b> n ID: <b>35</b>			tCode: Ef		8015M/D: DI	esel Rang	e Organics	
·	•	n ID: 35	622	F		7873	8015M/D: DI	J	e Organics	
Client ID: PBS	Batcl	n ID: 35	622 2/20/2017	F	RunNo: 47	7873		J	e Organics RPDLimit	Qual
Client ID: PBS Prep Date: 12/20/2017 Analyte	Batcl Analysis D	n ID: 35 Pate: 12	622 2/20/2017	F	RunNo: 47 SeqNo: 18	7873 534672	Units: mg/F	(g	•	Qual
Client ID: PBS Prep Date: 12/20/2017	Batci Analysis D Result	n ID: <b>35</b> Pate: <b>1</b> 2	622 2/20/2017	F	RunNo: 47 SeqNo: 18	7873 534672	Units: mg/F	(g	•	Qual

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Page 3 of 5

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

## Hall Environmental Analysis Laboratory, Inc.

WO#: 1712B61

21-Dec-17

Client:

Blagg Engineering

Project: BOL	ACK 2						
Sample ID RB	SampType: MBLK	TestCode: EPA Method 8015D: Gasoline Range					
Client ID: PBS	Batch ID: G47914	RunNo: 47914					
Prep Date:	Analysis Date: 12/20/2017	SeqNo: 1535211 Units: mg/Kg					
Analyte	Result PQL SPK value	e SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual					
Gasoline Range Organics (GRC	) ND 5.0						
Surr: BFB	970 1000	96.7 15 316					
Sample ID 2.5UG GRO LCS SampType: LCS TestCode: EPA Method 8015D: Gasoline Range							
Client ID: LCSS	Batch ID: G47914	RunNo: 47914					
Prep Date:	Analysis Date: 12/20/2017	SeqNo: <b>1535212</b> Units: <b>mg/Kg</b>					
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual					
Gasoline Range Organics (GRO	) 24 5.0 25.00	0 94.1 75.9 131					
Surr: BFB	1100 1000	111 15 316					
Sample ID MB-35606 SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range							
Client ID: PBS	Batch ID: 35606	RunNo: 47914					
Prep Date: 12/19/2017	Analysis Date: 12/20/2017	SeqNo: 1535215 Units: %Rec					
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual					
Surr: BFB	860 1000	85.8 15 316					
Sample ID LCS-35606	mple ID LCS-35606 SampType: LCS TestCode: EPA Method 8015D: Gasoline Range						
Client ID: LCSS	Batch ID: 35606	RunNo: 47914					
Prep Date: 12/19/2017	Analysis Date: 12/20/2017	SeqNo: <b>1535216</b> Units: <b>%Rec</b>					
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual					
Surr: BFB	1100 1000	105 15 316					

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- В Analyte detected in the associated Method Blank
- Value above quantitation range
- J Analyte detected below quantitation limits
- Page 4 of 5

- P Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified

#### Hall Environmental Analysis Laboratory, Inc.

WO#:

1712B61

21-Dec-17

Client: Project: Blagg Engineering

Sample ID RB

**BOLACK 2** 

Campic ID	ND
Client ID:	PBS

SampType: MBLK

PQL

0.025

TestCode: EPA Method 8021B: Volatiles

Batch ID: **B47914** 

Result

ND

1.1

RunNo: 47914

Prep Date: Analysis Date: 12/20/2017

SeqNo: 1535274

SPK value SPK Ref Val %REC LowLimit

Units: mg/Kg

%RPD

%RPD

%RPD

**RPDLimit** 

HighLimit

**RPDLimit** 

Qual

Qual

Analyte						
Benzene						
Toluene						
Ethylbenzene						

Xylenes, Total Surr: 4-Bromofluorobenzene

0.050 ND ND 0.050 ND 0.10

1.000

112

120 20

Sample ID 100NG BTEX LCS SampType: LCS TestCode: EPA Method 8021B: Volatiles

Client ID: LCSS

Batch ID: **B47914** 

RunNo: 47914

Units: mg/Kg

Prep Date:

Analysis Date: 12/20/2017

SeqNo: 1535275

Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit
Benzene	0.89	0.025	1.000	0	89.0	77.3	128
Toluene	0.91	0.050	1.000	0	90.8	79.2	125
Ethylbenzene	0.90	0.050	1.000	0	89.7	80.7	127
Xylenes, Total	2.8	0.10	3.000	0	91.7	81.6	129
Surr: 4-Bromofluorobenzene	1.1		1.000		114	80	120

Sample ID MB-35606 Client ID:

SampType: MBLK Batch ID: 35606

TestCode: EPA Method 8021B: Volatiles

RunNo: 47914

LowLimit

80

Prep Date: Analyte

12/19/2017

Analysis Date: 12/20/2017

SeqNo: 1535278 %REC

Units: %Rec HighLimit

120

**RPDLimit** Qual

Sample ID LCS-35606

Surr: 4-Bromofluorobenzene

SampType: LCS

101

TestCode: EPA Method 8021B: Volatiles

Client ID:

LCSS

Batch ID: 35606

PQL

RunNo: 47914

Analyte

Prep Date: 12/19/2017

Analysis Date: 12/20/2017

SeqNo: 1535279

SPK Ref Val

Units: %Rec

%RPD

**RPDLimit** Qual

Surr: 4-Bromofluorobenzene

1.2

Result

Result

1.0

1.000

SPK value

SPK value SPK Ref Val

1.000

%REC 118

LowLimit

80

HighLimit

120

# Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- В Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits

Page 5 of 5

- P Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

# Sample Log-In Check List

Clie	ent Name:	BLAGG		Work	Order Numi	per: 1712	B61		RcptNo	x: 1
Rece	eived By:	Anne Thor	ne	12/20/20	17 6:30:00	AM		anne M	-	
Com	pleted By:	Anne Thor	ne	12/20/20	17 6:52:22	AM		anne H		
Revi	iewed By:	DIDS		12/2	11/0			Cana Sic		
Cha	in of Cus	tody								
1. 0	Custody sea	ls intact on sa	mple bottles?	,		Yes		No 🗆	Not Present	
2. 1	s Chain of C	custody comp	lete?			Yes	<b>V</b>	No 🗆	Not Present	
3. ł	How was the	sample deliv	ered?			Cour	rier			
Log	ı In									*
74		mpt made to	cool the samp	oles?		Yes	<b>V</b>	No 🗌	NA 🗆	
5. 1	Were all san	nples received	d at a tempera	ture of >0° C	to 6.0°C	Yes	<b>V</b>	No 🗆	· NA	
6,	Sample(s) in	proper conta	iner(s)?			Yes	V	No 🗆		
.7. 8	Sufficient sar	mple volume	for indicated to	est(s)?		Yes	V	No 🗌		٠
				operly preserv	ed?	Yes	V	No 🗆		• •
9. V	Nas preserv	ative added to	bottles?			Yes	<u> </u>	No 🗹	NA 🗆	•
10 1	OA dala ha								No VOA Vials ✓	
		ve zero head		enkan?		Yes		No □ No ☑	No VOA VIAIS	
. 11.1	vvere any sa	imple contain	ers received b			res	. ,	NO E	# of preserved	
12.0	Does paperw	ork match bo	ttle labels?	_		Yes	<b>V</b>	No 🗆	bottles checked for pH:	
	* 1.		ain of custody						(<2 Adjusted?	or >12 unless noted)
				n of Custody?		Yes	V	No L	Adjusted	
127 1272		at analyses w ling times able	ere requested			Yes	<b>V</b>	No 🗆	Checked by:	
			authorization.)				-			
								•		
Spec	cial Hand	ling (if app	licable)							
16. V	Vas client no	otified of all di	screpancies v	vith this order?		Yes		No 🗆	NA 🗹	_
	Person	Notified:	RALIANT MANAGEMENT OF THE PROPERTY OF THE PROP		Date	-	head and an artist of the	-0036364Hard ratherthin ASS Broken Alberta Andreit		
	By Who	om:			Via:	eMa	ail [	Phone Fax	In Person	
	Regard		Name of the Party			68.000.000.000.000	LES CONTRACTOR OF THE PARTY OF	MOD statement with the consist you		
[		nstructions:		_						
17.	Additional re	marks:								
18.	Cooler Info									
	Cooler No	Temp °C	Condition	Seal Intact Yes	Seal No	Seal Da	ate	Signed By	-	
	Ľ	11.7	2000	100						



