District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

1

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

<u>Pit, Below-Grade Tank, or</u> Proposed Alternative Method Permit or Closure Plan Application
rioposed Alternative Method remit of Closure I fair Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Deperator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: DRYDEN 001E
API Number: 3004525566 OCD Permit Number: U/L or Qtr/Qtr I Section 28 Township 28N Range 08W County: San Juan
Center of Proposed Design: Latitude 36.63004 Longitude -107.67938 NAD83
Surface Owner: E Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC FEB 2 7 2018
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. TANK B Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK B Volume: 45 bbl Type of fluid: Produced Water Tank Construction material: Steel
 <u>Alternative Method</u>: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
 5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify

Oil Conservation Division

8 . Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
 7. Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC 	
 8. <u>Variances and Exceptions</u>: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. <i>Please check a box if one or more of the following is requested, if not leave blank:</i> Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
9. <u>Siting Criteria (regarding permitting)</u> : 19.15.17.10 NMAC <i>Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate active acti</i>	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	Yes No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No

.

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No						
Temporary Pit Non-low chloride drilling fluid							
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	🗋 Yes 🗌 No						
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.							
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image							
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 							
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						
Permanent Pit or Multi-Well Fluid Management Pit							
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa							
 lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No						
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of							
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No						
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗍 No						
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	o NMAC 15.17.9 NMAC						
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.10 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC							
Previously Approved Design (attach copy of design) API Number: or Permit Number:							

,

12. <u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial	luid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	
Form C-144 Oil Conservation Division Page 4 o	f 6

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality								
	🗌 Yes 🗌 No							
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No							
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological								
Society; Topographic map	🗌 Yes 🗌 No							
Within a 100-year floodplain. - FEMA map	🗌 Yes 🗌 No							
16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.								
17. Operator Application Certification:								
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ief.							
Name (Print): Title:								
Signature: Date:								
e-mail address: Telephone:								
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 222								
Title: L-nuironmental periatist OCD Permit Number:	810GB							
Title: <u>-nvironmental periatist</u> OCD Permit Number:	81066							
Title: _nuironmental periatist OCD Permit Number:	the closure report.							
Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not	the closure report.							
Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this							

Oil Conservation Division

Operator Closure Certification:

22.

Signature:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print): Erin Garifalos

Title: Field Environmental Coordinator

erin garibalas

Date: February 23, 2018

e-mail address: erin.garifalos@bp.com

Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

DRYDEN 001E

API No. 3004525566

Unit Letter I Section 28 T 28N R 08W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

BP BGT Closure Plan 04-01-2010

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	45 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.020
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.080
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	122
Chlorides	US EPA Method 300.0 or 4500B	620	110

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits except TPH and chloride. The release will be addressed following the spill and release guidelines. The field report and laboratory reports are attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has occurred. The release will be addressed following the spill and release guidelines. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has occurred. The release will be addressed following the spill and release guidelines. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area will is within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area will is within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area will is within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area will is within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area will is within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

BP BGT Closure Plan 04-01-2010

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised April 3, 2017

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Sultu I e, I thi 07505						
Release	Notification	and	Corrective Action			

						OPERA			Initia	al Report		Final Report
Name of Company BP America Production Company							n Garifalos					
Address 200 Energy Court, Farmington, NM 87401 Facility Name DRYDEN 001E							No. (832) 609-					
Facility Nat	neDRYD	EN 001E				Facility Typ	e: Natural Ga	as we				
Surface Ow	Surface Owner: Federal Mineral Owner								API No	.300452	5566	5
				LOCA	TIO	N OF REI	LEASE					
Unit Letter	Section	Township	Range	Feet from the	North	South Line	Feet from the	East/V	West Line	County		1
1	28	28N	08W	1,905	Sou	uth	580	Eas	st	5	an	Juan
		1	Latitud	e 36.63004	L	ongitude1	07.67938	NAD	83			
				NAT	URE	OF REL						
Type of Rele	ase:: none)					Release: : unkno			Recovered: : Hour of Disc		
Source of Re	Source of Release: below grade tank - 45 bbl					n/a	iour of Occurrence		n/a	fiour of Disc	lovery.	
Was Immedia	ate Notice (Yes 🗸	No 🗌 Not Re	equired	If YES, To	Whom?					
By Whom?						Date and H	lour					
Was a Water	course Read		Yes 🗸	No		If YES, Vo	olume Impacting t	the Wate	ercourse.			
		pacted, Descri										
		em and Remed		for Chl The re and lal	orides, lease w	BTEX, and vill be addres v results are	ath the BGT wa TPH below BG ^T ssed following th attached.	r closui ne spill	re standar and releas	ds, except se guideline	TPH ar s. Fiel	nd chloride.
							atory analysi	0				
regulations al public health should their o or the environ	Il operators or the envir operations h nment. In a	are required to ronment. The nave failed to a	o report an acceptance adequately OCD accept	d/or file certain r e of a C-141 repo investigate and r	elease n ort by the emediate	otifications and NMOCD m e contaminati	knowledge and u nd perform correc arked as "Final R on that pose a thr e the operator of	eport" d eport" d eat to gr	ions for rele loes not reli round water	eases which i ieve the oper r, surface wa	may en ator of ter, hur	danger liability nan health
		1					OIL CON	SERV	ATION	DIVISIO	N	
l	Tun 9	Wilfald	es-					1	A			
						Approved by	Environmental S	pecialis)	
Printed Name	Erin G	Garifalos							a	Xy		
Title: Field	d Envir	onmenta	al Coor	dinator		Approval Dat	e: 21281	DOIN	Expiration 1	Date:		
E-mail Addre	ess: erin.	garifalos	@bp.o	com		Conditions of	Approval:			Attached		
Date: Febru				(832) 609-70)48	-						
* Attach Addi	tional Shee	ets If Necess	ary			NN	F 1805	59:	326	39		

bp



BP America Production Company 200 Energy Court Farmington, NM 87401

December 19, 2017

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: DRYDEN 001E API #: 3004525566

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about December 26, 2017. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From:	Buckley, Farrah (CH2M HILL)
To:	Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa, Fields@state.nm.us)
Cc:	jeffcblagg@aol.com; blagg_njv@yahoo.com; Garifalos, Erin
Subject:	RE: BP Pit Close Notification - DRYDEN 001E
Date:	Friday, December 22, 2017 9:03:14 AM

The work on this site is scheduled for Tuesday, December 26th at 12:30pm.

Thanks.

Farrah

From: Buckley, Farrah (CH2M HILL)
Sent: Tuesday, December 19, 2017 3:56 PM
To: 'Smith, Cory, EMNRD'; 'Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)'
Cc: 'jeffcblagg@aol.com'; 'blagg_njv@yahoo.com'; Garifalos, Erin
Subject: BP Pit Close Notification - DRYDEN 001E

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US;</u> <u>VANESSA.FIELDS@STATE.NM.US</u>

December 19, 2017

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

DRYDEN 001E API 30-045-25566 (I) Section 28 – T28N – R08W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close two 45bbl BGTs that will no longer be operational at

this well site. We anticipate this work to start on or around December 26, 2017. Should you have any questions, please feel free to contact BP at our Farmington office. Sincerely,

Erin Garifalos

Field Environmental Coordinator – San Juan Cell: 832-609-7048

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP		ENGINEERING, INC BLOOMFIELD, NM 8		API #: 300452	5566
		05) 632-1199		TANK ID (if applicble):	}
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTHE	ER:	PAGE #:1 c	of <u>1</u>
SITE INFORMATION	SITE NAME: DRYDE	EN #1E		DATE STARTED: 12/2	26/17
QUAD/UNIT: SEC: 28 TWP:			ST: NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 1,905'S / 58(LEASE #: NM012200		TYPE: FEDERAL STATE / FE STRIKE CONTRACTOR: BP - J. GONZ		ENVIRONMENTAL SPECIALIST(S):	JV
REFERENCE POINT	WELL HEAD (W.H.) GP	S COORD.: 36.63032)	K 107.67936	GL ELEV.:	5,829'
1) 45 BGT (SW/DB) - B	GPS COORD.: 3	6.63004 X 107.67938	DISTANCE/BEA	RING FROM W.H.: 111', S	6.5W
2)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
3)	GPS COORD .:		DISTANCE/BEA	RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEAI	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) #	OR LAB USED: HALL			OVM READING (ppm)
1) SAMPLE ID: 5PC - TB @ 6' (4	5) - B SAMPLE DATE:12/2	6/17 SAMPLE TIME: 1325 LAB	ANALYSIS: 801	15B/8021B/300.0 (CI)	0.0
2) SAMPLE ID:					_
3) SAMPLE ID: 4) SAMPLE ID:					
		SAMPLE TIME: LAB			
SOIL DESCRIPTION			OTHER		
	ODERATE BROWN	_ PLASTICITY (CLAYS): NON PLASTIC / SI		OHESIVE / MEDIUM PLASTIC / HIGI	HIY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTL					LITEADIO
CONSISTENCY (NON COHESIVE SOILS):		HC ODOR DETECTED: YES NO EXP	PLANATION -		
MOISTURE: DRY / SLIGHTLY MOIST / MOIST / W SAMPLE TYPE: GRAB (COMPOSITE +					
DISCOLORATION/STAINING OBSERVED: YES		ANY AREAS DISPLAYING WETNESS:			
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE	LOST INTEGRITY OF EQUIPMEN	T: YES / NO EXPLANATION - POSSI	BLY NEAR INSP		r
EQUIPMENT SET OVER RECLAIMED AREA: OTHER: <u>NMOCD OR BLM REPS. NOT PF</u> (<0.5 cubic yards).	YES NO EXPLANATION - RESENT TO WITNESS CONFIRM	ATION SAMPLING. DISCOLORE	ED SOILS AT 45E	3 VERY MINOR IN QUANTI	ry
EXCAVATION DIMENSION ESTIMATION:	NA ft. X NA	ft. Xft. E	EXCAVATION EST	TIMATION (Cubic Yards) :	NA
DEPTH TO GROUNDWATER: <a>	EAREST WATER SOURCE: >1,00	0' NEAREST SURFACE WATER:	1,000' NMOC	CD TPH CLOSURE STD: 10	00 ppm
SITE SKETCH	BGT Located : off / on si	ite PLOT PLAN circle:	attached OVM	CALIB. READ. = 100.0 pr	om RF = 1.00
					om
	то				2/26/17
	/ W.H.			MISCELL. NO	TES
	~		14	10:	
	BERM			EF #: P-907	
	PRO	n		ID: VHIXONEVB2	,
				J#:	
	(45)-B			ermit date(s): 06/1	4/10
	PBGTL T.B. ~ 6'	- FENCE		CD Appr. date(s): 12/0	7/17
	B.G.		Tan	NK OVM = Organic Vapor Me	eter
				BGT Sidewalls Visible: Y /	N
		Χ.	- S.P.D.	BGT Sidewalls Visible: Y /	N
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO	DN DEPRESSION; B.G. = BELOW GRADE; B =		= WELL HEAD;	BGT Sidewalls Visible: Y /	
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGLE	OW-GRADE TANK LOCATION; SPD = SAMPLE E WALL; DW - DOUBLE WALL; SB - SINGLE BC	. POINT DESIGNATION; R.W. = RETAINING WAL DTTOM; DB - DOUBLE BOTTOM.		lagnetic declination: 10)°E
NOTES: GOOGLE EARTH IMAGE	ERY DATE: 10/5/2016.	ONSITE: 12/26/17			
revised: 11/26/13				BEI10	005E-6.SKF

Ana	alytic	al	Rep	ort
Lab	Orde	r 17	12E	50

Date Reported: 12/29/2017

Hall Environmental Analysis Laboratory, Inc.

.

Lab ID: 1	1712E50-002	Matrix:	MEOH (SOIL)	Received	d Date: 12/27/2017 7:30:00 AM	
Project: D	Dryden 1E			Collection	Date: 12/26/2017 1:25:00 PM	
CLIENT: B	Blagg Engineering			Client Sam	ple ID: 5PC-TB@ 6' (45)-B	

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analy	st: MRA
Chloride	110	30	mg/Kg	20	12/27/2017 12:17:41	PM 35727
EPA METHOD 8015M/D: DIESEL RA	NGE ORGANICS				Analy	st: TOM
Diesel Range Organics (DRO)	49	9.6	mg/Kg	1	12/27/2017 1:35:51 P	M 35726
Motor Oil Range Organics (MRO)	73	48	mg/Kg	1	12/27/2017 1:35:51 P	M 35726
Surr: DNOP	106	70-130	%Rec	1	12/27/2017 1:35:51 P	M 35726
EPA METHOD 8015D: GASOLINE RA	ANGE				Analys	st: NSB
Gasoline Range Organics (GRO)	ND	4.0	mg/Kg	1	12/27/2017 11:03:07	AM 35687
Surr: BFB	78.8	15-316	%Rec	1	12/27/2017 11:03:07	AM 35687
EPA METHOD 8021B: VOLATILES					Analys	st: NSB
Benzene	ND	0.020	mg/Kg	1	12/27/2017 11:03:07	AM 35687
Toluene	ND	0.040	mg/Kg	1	12/27/2017 11:03:07	AM 35687
Ethylbenzene	ND	0.040	mg/Kg	1	12/27/2017 11:03:07	AM 35687
Xylenes, Total	ND	0.080	mg/Kg	1	12/27/2017 11:03:07	AM 35687
Surr: 4-Bromofluorobenzene	92.4	80-120	%Rec	1	12/27/2017 11:03:07	AM 35687

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method Blank
	D	Sample Diluted Due to Matrix	Е	Value above quantitation range
	Н	Holding times for preparation or analysis exceeded	J	Analyte detected below quantitation limits Page 2 of 6
	ND	Not Detected at the Reporting Limit	Р	Sample pH Not In Range
	PQL	Practical Quanitative Limit	RL	Reporting Detection Limit
	S	% Recovery outside of range due to dilution or matrix	W	Sample container temperature is out of limit as specified

12/24/17	12/26/17	Date:								12/26/17	17 107 171		Date	EDD (Type)	O NELAP	Accreditation:	 ✓ Standard 	OA/OC Package:	email or Fax#:	Phone #:		Mailing Address:		Client:	C
1819	luno	Time:								1325	1620		Time	Type)	U	tion:	ard	ickage:	Fax#:			ddress:		BLAG	hain-c
Refinquistied by:	A	Relinquished								SOIL	JUIC		Matrix		Other					(505) 632-1199	BLOOM	P.O. BOX 87		G ENGR.	of-Cus
rulan arihamithad to Liall Endocompanial may be a	Mr. VI-	ad/hv/								SPC - TB @ 6' (45)-B	1 (a) (2 a) a c	-	Sample Request ID				Level 4 (Full Validation)			32-1199	BLOOMFIELD, NM 87413	X 87		BLAGG ENGR. / BP AMERICA	Chain-of-Custody Record
Received by: Spl (Im	Received by:				-				4 oz 1	4 02. 2		Container Type and #	Sample Temperature 🗵 🚊	On lee	Sampler:			Project Manager:		Project #:		Project Name:	Standard	Turn-Around Time:
arredited laboratoria	lig									Cool	600		Preservative Type	enature 3.3	X Yes	NELSON VELEZ	NELSON VELEZ		ler:			DRYDEN #	1	Rush	îme;
IIIIe 9730	L4	Date Time								- 002	001		HEAL No.		ALG DIP	ELEZ	ELEZ					# 1E		DAY	SAME
Reference		Remarks:								<	4	•	BTEX + MTD		HAD	÷ (8	021B)							
VID: Reference #	CONTACT:										 4	+	BTEX + MTB			-	-		_		Tel	490			_
		-								<	\$	-	TPH 8015B (-	MRC	D)	_		Tel. 505-345-3975	4901 Hawkins NE -			-
P - 907	& REFERENCE # WHEN APPLICABLE; ERIN GARIFALOS / VANCE HIXON		_	_					 -		 +	-	TPH (Meth						_		-34	wkin	\$		I
P - 907	GARI		_				 				 ╉	-+	EDB (Meth		-	-	101		_		5-39	IN SU	www	Z	
bad read rise	E#W		-				 				 +	-	PAH (8310	1		DSIN	AS)			Ar	75		.hall	5	
ta will	HEN/		_						 		 +	-	RCRA 8 Me	-					_	nalys	T	Albu	env	S	
	VAN		_	_			 				+	-	Anions (F,C		-			_)	sis F	X 5	Ique	iron	SIS	3
party n	CE H		_				 				+	-	8081 Pestic	-	s/8	808	2 PCE	3's	_	Analysis Request	05-3	rque	men		R
otated	IXON		_	_			 	-			+	-	8260B (VO	-						lest	Fax 505-345-4107	Albuquerque, NM 87109	www.hallenvironmental.com	LABORATORY	ENVTRONMENTAL
on the	_										 +	-	8270 (Semi		-				_		1107	N 87	om	0:	Z
			\dashv					-		<	 1	-	Chloride (sol	I - 30	0.0	/ wat	ter - 3	00.1	L)			109		S	11
VHIXONEVB2 P - 907 Anv sub-contracted data will be clearly notated on the analytical report		22222	-		_		 				 +	+	Carl												T
Phone			_	-					 		 +	-	Grab samp				-		_					R	
										<	1	-	5 pt. comp	osite	e sa	mp	e							≺'	

Client: Blagg Engineering Project: Dryden 1E

.

Sample ID MB-35727	SampType: mblk	TestCode: EPA Method		
Client ID: PBS	Batch ID: 35727	RunNo: 48035		
Prep Date: 12/27/2017	Analysis Date: 12/27/2017	SeqNo: 1540826	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Chloride	ND 1.5			
Sample ID LCS-35727	SampType: Ics	TestCode: EPA Method	300.0: Anions	
Sample ID LCS-35727 Client ID: LCSS	SampType: Ics Batch ID: 35727	TestCode: EPA Method RunNo: 48035	300.0: Anions	
	1 31		300.0: Anions Units: mg/Kg	
Client ID: LCSS	Batch ID: 35727 Analysis Date: 12/27/2017	RunNo: 48035		RPDLimit Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 3 of 6

WO#: 1712E50 29-Dec-17

Client:Blagg EngineeringProject:Dryden 1E

Sample ID LCS-35726	SampTy	ype: LC	S	TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: LCSS	Batch	ID: 35	726	R	RunNo: 48027					
Prep Date: 12/27/2017	Analysis Date: 12/27/2017			S	SeqNo: 1	539266	Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	48	10	50.00	0	95.6	73.2	114			
Surr: DNOP	4.7		5.000		93.4	70	130			
Sample ID MB-35726	SampTy	pe: ME	BLK	lest	tCode: El	PA Method	8015M/D: Die	esel Range	e Organics	
Client ID: PBS		Batch ID: 35726 RunNo: 48027								
	Batch	ID: 35	726	R	anNo: 4	8027				
Prep Date: 12/27/2017	Batch Analysis Da		726 2/27/2017		RunNo: 48 SeqNo: 1		Units: mg/K	g		
Prep Date: 12/27/2017 Analyte			2/27/2017				Units: mg/K HighLimit	g %RPD	RPDLimit	Qual
	Analysis Da	ate: 12	2/27/2017	S	SeqNo: 1	539267	5	0	RPDLimit	Qual
Analyte	Analysis Da Result	ate: 12 PQL	2/27/2017	S	SeqNo: 1	539267	5	0	RPDLimit	Qual
Analyte Diesel Range Organics (DRO)	Analysis Da Result ND	ate: 12 PQL 10	2/27/2017	S	SeqNo: 1	539267	5	0	RPDLimit	Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 4 of 6

WO#: 1712E50 29-Dec-17

Client: Blagg Engineering Project: Dryden 1E

Sample ID MB-35687	SampType: M	BLK	Tes	TestCode: EPA Method 8015D: Gasoline Range					
Client ID: PBS	Batch ID: 35	5687	F	RunNo: 48031					
Prep Date: 12/22/2017	Analysis Date: 1	SeqNo: 1539740			Units: mg/Kg				
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND 5.0								
Surr: BFB	830	1000		83.5	15	316			
Sample ID LCS-35687	SampType: LC	cs	Tes	tCode: EF	PA Method	8015D: Gaso	line Rang	е	
	Batch ID: 35687 RunNo: 48031								
Client ID: LCSS	Batch ID: 35	5687	R	RunNo: 48	8031				
Client ID: LCSS Prep Date: 12/22/2017	Batch ID: 35 Analysis Date: 1			RunNo: 48 SeqNo: 1		Units: mg/K	g		
		2/27/2017				Units: mg/K HighLimit	g %RPD	RPDLimit	Qual
Prep Date: 12/22/2017	Analysis Date: 1	2/27/2017 SPK value	S	SeqNo: 1	539741	0		RPDLimit	Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 5 of 6

WO#: 1712E50 29-Dec-17

Client: Blagg Engineering Project: Dryden 1E

4

Sample ID MB-35687	Samp1	Type: ME	BLK	Tes	tCode: E						
Client ID: PBS	Batcl	h ID: 35	687	RunNo: 48031							
Prep Date: 12/22/2017	Analysis D	Date: 12	2/27/2017	S	SeqNo: 1	539781	Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	ND	0.025									
Toluene	ND	0.050									
Ethylbenzene	ND	0.050									
Xylenes, Total	ND	0.10									
Surr: 4-Bromofluorobenzene	0.96		1.000		96.5	80	120				
Sample ID LCS-35687	SampT	ype: LC	s	Tes	tCode: E	PA Method	8021B: Volat	tiles			
Client ID: LCSS	Batch	h ID: 35	687	F	RunNo: 4	8031					
Prep Date: 12/22/2017	Analysis D	Date: 12	2/27/2017	S	SeqNo: 1	539782	Units: mg/K	g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	0.93	0.025	1.000	0	93.0	77.3	128				
Toluene	0.95	0.050	1.000	0	94.9	79.2	125				
Ethylbenzene	0.94	0.050	1.000	0	94.3	80.7	127				
Xylenes, Total	2.9	0.10	3.000	0	95.9	81.6	129				
Surr: 4-Bromofluorobenzene	0.97		1.000		97.3	80	120				

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

WO#: 1712E50 29-Dec-17

Page 6 of 6

HALL ENVIRONMENTAL ANALYSIS LABORATORY	Hall Environmental A Albuq TEL: 505-345-3975 F Website: www.hall	4901 Hawkins N uerque, NM 8710 FAX: 505-345-410	^E Sam	Sample Log-In Check List					
Client Name: BLAGG	Work Order Number:	1712E50		RcptNo:	1				
Received By: Sophia Campuzano Completed By: Sophia Campuzano Reviewed By: Image: Completed By:	12/27/2017 7:30:00 AM 12/27/2017 8:45:09 AM パイレフ		Sophie Co-p	-					
 <u>Chain of Custody</u> 1. Custody seals intact on sample bottles? 2. Is Chain of Custody complete? 3. How was the sample delivered? 		Yes 🗋 Yes 🗹 Courier	No 🗌 No 🗌	Not Present 🗹					
 Log In 4. Was an attempt made to cool the samples 	?	Yes 🗹	No 🗌						
5. Were all samples received at a temperatur	e of >0° C to 6.0°C	Yes 🗹	No 🗌						
6. Sample(s) in proper container(s)?		Yes 🗹	No 🗌						
7. Sufficient sample volume for indicated test 8. Are samples (except VOA and ONG) prope		Yes 🗹	No 🗌						
9. Was preservative added to bottles?		Yes	No 🗹	NA 🗌					
10.VOA vials have zero headspace? 11. Were any sample containers received brok	ken?	Yes 🗌	No 🗌	No VOA Viais					
 12. Does paperwork match bottle labels? (Note discrepancies on chain of custody) 13. Are matrices correctly identified on Chain of 14. Is it clear what analyses were requested? 	of Custody?	Yes 🗹 Yes 🗹	No 🗌 No 🗌 No 🗌	# of preserved bottles checked for pH: (<2 o Adjusted?	r >12 unless noted)				
15. Were all holding times able to be met? (If no, notify customer for authorization.)		Yes 🗹	No 🗌	Checked by:					
Special Handling (if applicable)		_	_	_					
16. Was client notified of all discrepancies with Person Notified: By Whom: Regarding: Client Instructions:	this order? Date: Via:	Yes 🗌	No 🗌	NA 🗹					
17. Additional remarks:	· <u>· · · · · · · · · · · · · · · · · · </u>				ſ				
18. <u>Cooler Information</u> Cooler No Temp ^o C Condition S 1 3.3 Good Ye		eal Date S	igned By						

Page 1 of 1



