NMOCD

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division

1220 South St. Francis Dr. Santa Fe, NM 87505 MAR 1 6 2018

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Proposed Alternative Method Permit or Closure Plan Application Type of action: Below grade tank registration Permit of a pit or proposed alternative method
Type of action: Below grade tank registration
Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: PRITCHARD 008
API Number: 3004524686 OCD Permit Number: U/L or Qtr/Qtr P Section 04 Township 29N Range 08W County: San Juan
Center of Proposed Design: Latitude 36.74913 Longitude -107.67378 NAD83
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: ☐ Drilling ☐ Workover ☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other ☐ String-Reinforced Liner Seams: ☐ Welded ☐ Factory ☐ Other Volume:
3. ■ Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK B
Volume: 95bbl Type of fluid: Produced Water
Tank Construction material: Steel
□ Secondary containment with leak detection □ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off □ Visible sidewalls and liner □ Visible sidewalls only ■ Other Single wall/ Double bottom; sidewalls not visible □ Liner type: Thickness mil □ HDPE □ PVC □ Other
4,
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
Alternative Method:
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 5.



Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
☐ Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	otable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300 feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number: or Permit Number:	NMAC
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

12.	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F. Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P. 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
k	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure problem of the property of the following items must be attached to the closure problem of the property of the following items must be attached to the closure problem of the property of the following items must be attached to the closure problem of the property of the property of the following items must be attached to the closure problem of the property of the proper	.11 NMAC .15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) COCD Conditions (see attachment) OCD Representative Signature: Approval Date: OCD Permit Number:	29/18
OCD Representative Signature: Approval Date: 3/	
OCD Representative Signature: Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	t complete this

•

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submi	itted with this closure report is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all appl	icable closure requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
van garifialos	
Signature:	Date: February 7, 2018
e-mail address: erin.garifalos@bp.com	Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

PRITCHARD 008

API No. 3004524686

Unit Letter P Section 04 T 29N R 08W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	<0.019
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.075
TPH	US EPA Method SW-846 418.1 or <u>8015</u> extended	100	<48
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled a 105 bbl shallow low low profile tank has been set atop the BGT location. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled a 105 bbl shallow low low profile tank has been set atop the BGT location. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled a 105 bbl shallow low low profile tank has been set atop the BGT location. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled a 105 bbl shallow low low profile tank has been set atop the BGT location. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled a 105 bbl shallow low low profile tank has been set atop the BGT location. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II*
811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised April 3, 2017

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	eation	and Co	orrective A	ction								
						OPERA'	ГOR		Initia	al Report		Final Report				
				tion Company			Garifalos	7040								
		CHARD 00		on, NM 87401			No. (832) 609- De : Natural Ga		II							
Surface Ow	ner: Fede	eral		Mineral C)wner:	Federal			API No	.300452	4686	3				
		0141		•		OF RE	FASE			000 102	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/V	Vest Line	County						
Р	04	29N	08W	800	Sou	ıth	800	0-11								
			Latitud	le 36.74913	Lo	ngitude -1	07.67378	NAD8	33							
						OF REL										
Type of Rele	ase:: none)			CKE	Volume of	Release:: unkno			Recovered::						
Source of Re	lease: belo	w grade ta	nk - 95	bbl		Date and H	Iour of Occurrenc		Date and n/a	Hour of Dis	covery:	:				
Was Immedi		Given?				If YES, To	Whom?									
By Whom?			res 🗸	No Not Re	equirea	Date and H	Iour									
Was a Water	course Read						olume Impacting t	he Wate	rcourse.							
			Yes 🗸													
If a Waterco	irse was Im	pacted, Descri	ibe Fully.	¢												
D " 0	CD 11	1.5		TD 1												
Describe Cau	ise of Proble	em and Remed	dial Action	Samp	oling c	of the soil	beneath the	BGT	was do	ne durin	g ren	noval.				
					-		d for Chlorid	-								
					re sta	ndards. F	Field reports	and la	aborato	ry results	are	attached.				
Describe Are	a Affected	and Cleanup A	Action Tak	No actio	n nec	essary. F	inal laborate	ory an	alysis o	determin	ed no	0				
				remedial	actio	n is requ	ired.									
							knowledge and und perform correct									
public health	or the envir	ronment. The	acceptance	e of a C-141 repo	ort by the	NMOCD m	arked as "Final Roon that pose a three	eport" de	oes not reli	eve the oper	ator of	liability				
or the enviro	nment. In a	ddition, NMO	CD accep				e the operator of i									
		ws and/or regu					OIL CONS	SERV	ATION	DIVISIO	N					
1	run a	wishalo	4				0120 00111			21,1010						
Signature:	0	U				Approved by	Environmental S ₁	pecialist								
Signature:	Erin G	arifalos														
		onmenta		rdinator		Approval Dat	e:	E	Expiration 1	Date:						
E-mail Addre	ess: erin.	garifalos	@bp.	com		Conditions of										
Date: Febru				(832) 609-70			T.F.			Attached						
* Attach Addi				(302) 003-70	7-10											



BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

January 12, 2018

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: PRITCHARD 008

API#: 3004524686

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 16, 2018. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From:

Buckley, Farrah (CH2M HILL)

To: Cc: Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa, Fields@state.nm.us) jeffcblagg@aol.com;blagg_njv@yahoo.com; Garifalos, Erin Gonzales, Jody J

Subject: Date: RE: BP Pit Close Notification - PRITCHARD 008 Monday, January 15, 2018 5:09:05 PM

The BGT's on this location will be closed tomorrow, January 16th at 1pm.

Thanks.

Farrah

From: Buckley, Farrah (CH2M HILL) Sent: Friday, January 12, 2018 2:50 PM

To: 'Smith, Cory, EMNRD'; 'Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)'

Cc: 'jeffcblagg@aol.com'; 'blagg_njv@yahoo.com'; Garifalos, Erin

Subject: BP Pit Close Notification - PRITCHARD 008

BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

January 12, 2018

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

PRITCHARD 008 API 30-045-24686 (P) Section 4 – T29N – R08W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to a 95bbl and a 21bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around January 16, 2018.

Should you have any questions, please feel free to contact BP at our Durango office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator – San Juan Cell: 832-609-7048

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

l RD				ADI# 30045	24686
CLIENT:	P.O. BOX 87		NM 87413	, u ,	
4 *		(505) 632-1199		(if applicble):	R
FIELD REPORT:	(circle one): BGT CONFIRMA	TION / RELEASE INVESTIGATION	/ OTHER:	PAGE #: 1	of1
SITE INFORMATION	: SITE NAME PRI	TCHARD #8		DATE STARTED: 0'	1/16/18
			J ST: NM		
07070107		STRIKE		SPECIALIST(S):	NJV
REFERENCE POINT	: WELL HEAD (W.H	.) GPS COORD.: 36.74	932 X 107.67395	GL ELEV.:	6,322'
1) 95 BGT (SW/DB) - B					S31E
2)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
3)					
4)					
					OVM
				15D/9021D/300 0 /CI\	(ppm)
				130/80210/300.0 (CI)	INA
5) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
SOIL DESCRIPTION	SOIL TYPE: SAND SILTYS	AND SILT SILTY CLAY CLAY / GR	AVEL OTHER CALICE	IF (MOTTLED OLIVE GR	AYMHITE)
			_		
			NO EXPLANATION -		
		ANY AREAS DISPLAYING WET	NESS: YES NO EXPLA	NATION -	
		DMENT: VEG NO EVDI ANATIONI			
OTHER: NMOCD OR BLM REPS. NOT PI	RESENT TO WITNESS CON	FIRMATION SAMPLING.			
EXCAVATION DIMENSION ESTIMATION	NA # X	NA + X NA +	FYCAVATION FS	TIMATION (Cubic Yards):	NΔ
				,	4 000
					посо ррпп
SITE SKETCH	BGT Located . Oil / Oil	PLOTPLAN	A OVIV		ppm RF =1.00
	↑ то				_''
	W.H.		N TIME	: NA am/pm DATE:	NA
			' [MISCELL. NO	OTES
			V	VO:	
	BERM	(XXX)	R	EF#: P-915	
		FENCE	V	ID: VHIXONEVI	B2
l //			P	J#:	
BERM —	FEN	(93)-D	P	ermit date(s): 06	/14/10
		PBGTL T.B. ~ 5'	_	CD Appr. date(s): 12	/27/17
l N	PROD	B.G.	Tai	nk OVM = Organic Vapor	r Meter
l	TANK				
l			Y S DD	BGT Sidewalls Visible: Y	/ / N
NOTES: BGT = BFLOW-GRADE TANK: F.D. = FXCAVATIO	Code ords BST CONFRINATION RELEASE MYSTIGATION / OTHER DATE STARTED DAT				
FIELD REPORT: Circle one BOT COMPRIANTON RELASE MESTIGATION / OTHER Circle one BOT COMPRIANTON RELASE MESTIGATION / OTHER CIRCLE INFORMATION: SITE INFORMATION: DEPTITION OF THE INFORMATION: SITE INFORMATION: DEPTITION OF THE INFORMATION: DEPTITION OF THE INFORMATION: SITE INFORMATION: DEPTITION OF THE INFORMATION: SITE INFORMATION: DEPTITION OF THE INFORMATION OF TH					
				and a domination.	
NOTES: GOOGLE EARTH IMAG	ERY DATE: 10/5/2016.	ONSITE: 01/1	6/18		

Analytical Report

Lab Order 1801818

Date Reported: 1/19/2018

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (95)-B

Project: PRITCHARD 8

Collection Date: 1/16/2018 1:05:00 PM

Lab ID: 1801818-002

Matrix: SOIL

Received Date: 1/17/2018 7:10:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	MRA
Chloride	ND	30	mg/Kg	20	1/17/2018 11:26:59 AM	36067
EPA METHOD 8015M/D: DIESEL RANG	E ORGANICS				Analyst	TOM
Diesel Range Organics (DRO)	ND	9.6	mg/Kg	1	1/17/2018 10:42:23 AM	36064
Motor Oil Range Organics (MRO)	ND	48	mg/Kg	1	1/17/2018 10:42:23 AM	36064
Surr: DNOP	93.1	70-130	%Rec	1	1/17/2018 10:42:23 AM	36064
EPA METHOD 8015D: GASOLINE RAN	GE				Analyst	NSB
Gasoline Range Organics (GRO)	ND	3.8	mg/Kg	1	1/17/2018 10:06:24 AM	G48506
Surr: BFB	81.7	15-316	%Rec	1	1/17/2018 10:06:24 AM	G48506
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.019	mg/Kg	1	1/17/2018 10:06:24 AM	B48506
Toluene	ND	0.038	mg/Kg	1	1/17/2018 10:06:24 AM	B48506
Ethylbenzene	ND	0.038	mg/Kg	1	1/17/2018 10:06:24 AM	B48506
Xylenes, Total	ND	0.075	mg/Kg	1	1/17/2018 10:06:24 AM	B48506
Surr: 4-Bromofluorobenzene	89.5	80-120	%Rec	1	1/17/2018 10:06:24 AM	B48506

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- Analyte detected below quantitation limits Page 2 of 6 I
- P Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Client:			stody Record	Turn-Around T	ime: Rush	SAME	L		_									ME			
				Project Name:														RA	LI	JR	T
Mailing Ad	ddress:	P.O. BO	X 87		PRITCHARD	#8		49	01 H		www							n 37109	3		
		BLOOM	FIELD, NM 87413	Project #:		·.	1)5-3 ⁴							-410		,		
Phone #:		(505) 63	2-1199													ques					
email or F	ax#:			Project Manag	jer:									~				7			П
QA/QC Pad Standa	_		Level 4 (Full Validation)		ERIN GARI	FALOS	(8021B)	(Aluo	/ MRO}	:		. (SI		04,504	PCB's			er - 300.1)			a)
Accreditat	ion:			Sampler:	NELSON VI	LEZ)8) 	(Gas	RO/	1)	1	SIIV		102,6	3082			/ wat		1	mpl
□ NELAP)	□ Other		On Ice:	Xi Yeş 🔻	ENG - VV	HABI	+ TPH (Gas	0/0	418.	504.	827(O3,N	s/s		(A)	00.00			e Sa
□ EDD (T	ype)				rature 246	10:14	1	3E +	(GR	por	pou	or (etal	CI,N	icide	8	i-VC	oil-3	- 1	ole	osit
Date	Time	Matrix	Sample Request ID	Container Type and # Modify 15	Preservative Type	HEAL NO	BTEX +-MF	BTEX + MTBE	TPH 80158 (GRO / DRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 / water		Grab sample	5 pt. composite sample
1/16/10	1320	SOIL	EDC TR 6 / (31) A	1 on 1	Cool	TO THE PART WHEN THE PART WAS A PART OF THE PART OF TH	4		4									4	\dashv		4
	10		(95)-8	205															7		\neg
1/16/18	1305	SOIL	5PC-TB@ 5 / (38)-48	4 oz 1	Cool	702	٧		٧									٧			٧
*.																					
Date:	1431	Relinquish	luly	Received by:	ihet	Date Time		ont/	ACT:	& REI	FEREN	ICE#	WHE	N APP	LICA	BLE;		WITH C	ORRE	SPON	DING
Date:	1849	Relinquish	Lit- Vall	Received by:	-70	Date Time		eren	ce#	VHI	P-9	915	_	arill bo	clearly	v note	lad on	the on	ahtica	I rano	

Hall Environmental Analysis Laboratory, Inc.

WO#:

1801818 19-Jan-18

Client:

Blagg Engineering

Project:

PRITCHARD 8

Sample ID MB-36067

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 36067

RunNo: 48508

Prep Date:

1/17/2018

Analysis Date: 1/17/2018

PQL

1.5

SeqNo: 1560534

Units: mg/Kg HighLimit

RPDLimit

Qual

Analyte Chloride

TestCode: EPA Method 300.0: Anions

SPK value SPK Ref Val %REC LowLimit

%RPD

Client ID:

Sample ID LCS-36067 LCSS

SampType: Ics

Batch ID: 36067

RunNo: 48508

Prep Date:

1/17/2018

Analysis Date: 1/17/2018

SeqNo: 1560535

Units: mg/Kg

%RPD

Qual

98.2

HighLimit

RPDLimit

Chloride

Result

ND

PQL SPK value SPK Ref Val %REC Analyte 15 1.5 15.00

LowLimit 110

Oualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- Holding times for preparation or analysis exceeded H
- ND Not Detected at the Reporting Limit
- Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1801818

19-Jan-18

Client:

Blagg Engineering

Project:

PRITCHARD 8

Sample ID LCS-36064	SampTy	pe: LC	S	Test	Code: E	PA Method	8015M/D: Di	esel Rang	e Organics			
Client ID: LCSS	Batch	Batch ID: 36064 RunNo: 48503										
Prep Date: 1/17/2018	Analysis Da	ate: 1/	17/2018	SeqNo: 1559350 Units: mg/Kg								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range Organics (DRO)	44	10	50.00	0	88.6	70	130					
Surr: DNOP	4.2		5.000		84.5	70	130					

Sample ID MB-36064	SampType: MBLK			TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: PBS	Batch	1D: 36	064	F	RunNo: 4	8503				
Prep Date: 1/17/2018	Analysis D	ate: 1/	17/2018	S	SeqNo: 1	559351	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	9.0		10.00		89.8	70	130			

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1801818

19-Jan-18

Client: Project: Blagg Engineering

PRITCHARD 8

Sample ID RB

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

15

Client ID: **PBS**

Batch ID: G48506

RunNo: 48506

LowLimit

Prep Date:

Analysis Date: 1/17/2018

SeqNo: 1559852

Units: mg/Kg

Analyte

Result PQL ND 5.0

HighLimit

RPDLimit

RPDLimit

Qual

Gasoline Range Organics (GRO) Surr: BFB

860

1000

SPK value SPK Ref Val %REC

86.3

316

Qual

Sample ID 2.5UG GRO LCS

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

%RPD

%RPD

Client ID: LCSS

Batch ID: G48506

5.0

RunNo: 48506

HighLimit

Prep Date:

Analysis Date: 1/17/2018

SeqNo: 1559853

Units: mg/Kg

Analyte Gasoline Range Organics (GRO) Result PQL

SPK value SPK Ref Val %REC 0 98.6 LowLimit 75.9

131 316

Surr: BFB

25 910 25.00 1000

91.1

15

Oualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix
- Holding times for preparation or analysis exceeded H
- ND Not Detected at the Reporting Limit **PQL** Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1801818

19-Jan-18

Client: Project:

Blagg Engineering PRITCHARD 8

Sample ID RB	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batch ID: B48506			RunNo: 48506						
Prep Date:	Analysis D	ate: 1/	17/2018	S	SeqNo: 1	559858	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.94		1.000		94.4	80	120			

Sample ID 100NG BTEX LC	Samp	SampType: LCS			TestCode: EPA Method 8021B: Volatiles							
Client ID: LCSS	Bato	Batch ID: B48506			RunNo: 48506							
Prep Date:	Analysis I	Date: 1/	17/2018 SeqNo: 1559859 Unit				Units: mg/k	nits: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	0.92	0.025	1.000	0	91.6	77.3	128					
Toluene	0.93	0.050	1.000	0	92.6	79.2	125					
Ethylbenzene	0.92	0.050	1.000	0	92.3	80.7	127					
Xylenes, Total	2.8	0.10	3.000	0	94.1	81.6	129					
Surr: 4-Bromofluorobenzene	0.92		1.000		91.9	80	120					

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- Page 6 of 6

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name:	BLAGG	Work Order Num	nber: 1801818		RcptNo:	1
Received By:	Anne Thorne	1/17/2018 7:10:00	АМ	Anne Sh	_	
Completed By:	Anne Thorne	1/17/2018 7:23:16	AM	Down M.		
Reviewed By:	th /2/2000			Cime Ji		
Chain of Cus	stody				*	
	Custody complete?		Yes 🗹	No 🗆	Not Present	
2. How was the	e sample delivered?		Courier			
Log In						
the second secon	mpt made to cool the sar	mples?	Yes 🗹	No 🗆	NA 🗆	
4. Were all sam	iples received at a tempe	erature of >0° C to 6.0°C	Yes 🗹	No 🗆	NA 🗆	
5. Sample(s) in	proper container(s)?		Yes 🗸	No 🗌		
6. Sufficient sar	nple volume for indicated	test(s)?	Yes 🗹	No 🗌		
7. Are samples	(except VOA and ONG)	properly preserved?	Yes 🗹	No 🗀		
	ative added to bottles?		Yes	No 🗹	NA 🗆	
9. VOA vials ha	ve zero headspace?		Yes	No 🗌	No VOA Vials	
10. Were any sa	mple containers received	broken?	Yes	No 🗹	# of preserved	
44 -					bottles checked	
	ork match bottle labels? ancies on chain of custo	dv)	Yes 🗹	No 🗔	for pH: (<2 or	>12 unless noted)
	correctly identified on Ch		Yes 🗸	No 🗆	Adjusted?	
	at analyses were request		Yes 🗹	No 🗆		
	ing times able to be met		Yes 🗹	No 🗆	Checked by:	
	ling (if applicable)	,				
	otified of all discrepancie	s with this order?	Yes	No 🗆	NA 🗹	
Person	Notified:	Date		PANEL		
By Wh	om:	Via:	eMail P	none Fax	☐ In Person	
Regard	ling:	MILLIAN STOP CONTROL TO BE SUBSTITUTED IN STREET	NAME AND ADDRESS OF THE PROPERTY OF THE PROPER			
Client I	nstructions:					
16. Additional re	marks:					
17. Cooler Info				-		
Cooler No			Seal Date	Signed By		¥
<u>[]</u>	1.4 Good	Yes				



