District I

1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application NMOCD
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration MAR 2 2 2018 DISTRICT
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: JONES LS 002
API Number: 3004507651 OCD Permit Number:
U/L or Qtr/Qtr L Section 35 Township 29N Range 08W County: San Juan
Center of Proposed Design: Latitude 36.68010 Longitude -107.65175 NAD83
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined Liner type: Thickness mil □ LLDPE □ PVC □ Other □ String-Reinforced Volume:
Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A
4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify



Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
☐ Screen ☐ Netting ☐ Other	
☐ Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8,	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance of the compliance of the complian	ntable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	state source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	☐ Yes ☐ No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 No Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 5.17.9 NMAC
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number: or Permit Number:	15.17.9 NMAC

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Flank Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P. 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	□ Vas□ Na
Within a 100-year floodplain FEMA map	Yes No
· · · · · · · · · · · · · · · · · · ·	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
OCD Representative Signature: Approval Date:	
Title: OCD Permit Number:	
Title. OCD Termit Number.	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 1/24/2018	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	t complete this

Operator Closure Certification:	
	itted with this closure report is true, accurate and complete to the best of my knowledge and licable closure requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Signature:Utin garifalos	Date: March 20, 2018
e-mail address: erin.garifalos@bp.com	Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

JONES LS 002

API No. 3004507651

Unit Letter L Section 35 T 29N R 08W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.022
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.057
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<47
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141** is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled and a 105 BBL shallow low profile above-grade tank set atop BGT location. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised April 3, 2017 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

			Rele	ease Notific	cation	and Co	rrective A	ction	1							
						OPERA'			Initi	al Report		Final Report				
				tion Compan	_		Garifalos	7040								
Facility Na	neJONE:	S LS 002	rmingio	on, NM 87401		Telephone No. (832) 609-7048 Facility Type: Natural Gas Well										
Surface Ow				Mineral (Federal				.300450	7651					
Surface O W	ner, r eur	ciai					EACE		711111	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	7001					
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/	West Line	County						
L	35	29N		1,800	Sou		920 West County San J									
	Latitude 36.68010 Longitude -107.65175 NAD83															
						OF REL										
Type of Rele	ase:: none)					Release:: unkn			Recovered::						
Source of Re	lease: belo	w grade ta	nk - 95	bbl		Date and H	Iour of Occurrence	ce:	Date and n/a	Hour of Disc	covery:					
Was Immedi	ate Notice (Yes 🗸	No Not R	equired	If YES, To	Whom?									
By Whom?					-	Date and H	Iour									
Was a Water	course Read		Yes 🗸	No		If YES, Vo	lume Impacting t	the Wat	ercourse.							
If a Watercon	ırse was Im	pacted, Descri														
		parted, 2 com														
Describe Cau	se of Proble	em and Remed	dial Action	n Taken.*				D.0.7								
							beneath the d for Chloric				_					
							Field reports									
Describe Are	a Affected a	and Cleanup A	Action Tak	en.*												
		1		No actio		_	inal laborate	ory a	nalysis (determin	ed no					
				remedia	actio	n is requ	irea.									
I hereby certi	fy that the i	information gi	ven above	is true and comp	lete to th	ne best of my	knowledge and u	ındersta	nd that purs	suant to NMO	OCD ru	iles and				
regulations a	l operators	are required to	report an	d/or file certain r	elease ne	otifications ar	nd perform correct	ctive act	tions for rel	eases which	may en	danger				
							arked as "Final R on that pose a thr									
		ddition, NMO ws and/or regu		tance of a C-141	report de	oes not reliev	e the operator of	respons	ibility for c	ompliance w	rith any	other				
							OIL CON	SERV	ATION	DIVISIO	N					
Signature:	run a	Wilsalo	4													
Signature:						Approved by	Environmental S	pecialis	t:							
		onmenta				Approval Dat	e:		Expiration	Date:						
E-mail Addre	es: erin.	garifalos	@bp.	com		Conditions of	Approval:			Attached						
Date: Marc	n 20, 201	18	Phone:	(832) 609-70	048					- Ittuoriou						
* Attach Addi	tional Shee	ets If Necess	ary													

bp



380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

January 16, 2018

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: JONES LS 002

API#: 3004507651

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 19, 2018. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From:

Buckley, Farrah (CH2M HILL)

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa, Fields@state.nm.us)

Cc:

jeffcblagg@aol.com; blagg_njv@yahoo.com; Garifalos, Erin

Subject: Date: BP Pit Close Notification - JONES LS 002 Tuesday, January 16, 2018 3:42:09 PM

> BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

January 16, 2018

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

JONES LS 002 API 30-045-07651 (L) Section 35 – T29N – R08W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to a 95bbl and a 45bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around January 19, 2018.

Should you have any questions, please feel free to contact BP at our Durango office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator – San Juan Cell: 832-609-7048

Farrah Buckley

BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	P.O. BOX 87, BLC	GINEERING, INC. DOMFIELD, NM 8' 632-1199	7413	API #: 30045 TANK ID (if applicble):	507651 A					
FIELD REPORT:	(circle one): BGT CONFIRMATION / RE		₹:	PAGE #: 1	of1					
SITE INFORMATION	J: SITE NAME: JONES LS	5 # 2		DATE STARTED: 0	1/22/18					
QUAD/UNIT: L SEC: 35 TWP:	29N RNG: 8W PM: 1	NM CNTY: SJ S	ST: NM	DATE FINISHED:						
1/4-1/4/FOOTAGE: 1,800'S / 92		FEDERAL STATE / FEE	E / INDIAN	ENVIRONMENTAL	NI D.					
LEASE #: SF079938	PROD. FORMATION: MV CONT	RACTOR: BP - J. GONZ	ALES	SPECIALIST(S):	NJV					
REFERENCE POINT	WELL HEAD (W.H.) GPS CO	ORD.: 36.68032 X	107.65163	GL ELEV.:	6,256'					
1) 95 BGT (SW/DB) - A	GPS COORD.: 36.68	010 X 107.65175	DISTANCE/BEAI	RING FROM W.H.: 92'	, S21W					
2)	GPS COORD.: DISTA									
3)	GPS COORD.:		DISTANCE/BEAR	RING FROM W.H.:						
4)	GPS COORD.:		DISTANCE/BEAF	RING FROM W.H.:						
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LA	B USED: HALL			OVM READING (ppm)					
1) SAMPLE ID: 5PC - TB @ 5' (9	•			5B/8021B/300.0 (CI)	NA					
2) SAMPLE ID:										
SAMPLE ID: SAMPLE ID:										
5) SAMPLE ID:	SAMPLE DATE:									
SOIL DESCRIPTION	SOIL TYPE: SAND / SILTY SAND / SILT /	SILTY CLAY / CLAY / GRAVEL TO	THER BEDRO	CK (SANDSTONE)						
SOIL COLOR: PALE TO DARK		STICITY (CLAYS): NON PLASTIC / SLIC			HIGHLY PLASTIC					
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY		ISITY (COHESIVE CLAYS & SILTS								
CONSISTENCY (NON COHESIVE SOILS): LC		DOOR DETECTED: YES NO EXPL	ANATION -							
MOISTURE: DRY/SLIGHTLYMOIST/MOIST/W SAMPLE TYPE: GRAB/COMPOSITE-#		AREAS DISPLAYING WETNESS: Y	TO THO EVELAN	IATION						
DISCOLORATION/STAINING OBSERVED: YES		AREAS DISPLATING WETNESS. T	ES [NO] EXPLAN	MATION -						
SITE OBSERVATION		NO EXPLANATION -								
APPARENT EVIDENCE OF A RELEASE OBSERVE	ED AND/OR OCCURRED : YES NO EXPLANAT	10N:								
EQUIPMENT SET OVER RECLAIMED AREA: OTHER: NMOCD OR BLM REPS. NOT PR	YES NO EXPLANATION - 105 BBL SH	ALLOW LOW PROFILE ABOY	VE-GRADE TAN	NK TO BE SET ATOP BO	GT LOCATION.					
SANDSTONE BETWEEN 1 FT 5 FT. I		SAMPLING. BGI INSTALL	ED BY EXCAV	ATING INTO SHALLOW	BEDROCK					
EXCAVATION DIMENSION ESTIMATION:		X NA ft. EX	CAVATION EST	IMATION (Cubic Yards) :	NA					
DEPTH TO GROUNDWATER: >100' N	IEAREST WATER SOURCE: >1,000' N	EAREST SURFACE WATER: >1	,000' NMOC	D TPH CLOSURE STD:	5,000 ppm					
SITE SKETCH	BGT Located: off on site	PLOT PLAN circle:	attached	CALIB. READ. = NA	ppm RF =1.00					
	\oplus		♦ OVM	CALIB. GAS = NA	ppm					
	W.H.		TIME	: NA am/pm DATE:	NA					
				MISCELL. N	OTES					
			l w	/O:	0.20					
			_	EF#: P-914						
	FENCE			D: VHIXONEV	B2					
(95	0.4	0.0	P	J#:						
PBC	GTL SELVIOL	OR	Pe	ermit date(s): 06	6/14/10					
T.B. B.	$G.$ $(x \hat{x} \hat{x})$			CD Appr. date(s): 12	2/27/17					
	BERM BERM		Tan ID	ppm = parts per milli	ion					
			Α	BGT Sidewalls Visible:	Y /(N)					
		Χ -	S.P.D.	BGT Sidewalls Visible:						
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION		T.H. = TEST HOLE; ~= APPROX.; W.H. =	WELL HEAD;	BGT Sidewalls Visible:						
	.OW-GRADE TANK LOCATION; SPD = SAMPLE POINT I E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; I		NA-NOT M	lagnetic declination:	10°E					
NOTES: GOOGLE EARTH IMAGI		ONSITE: 01/22/17								

Analytical Report

Lab Order 1801A36

Date Reported: 1/24/2018

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (95)-A

Project: JONES LS 2

Collection Date: 1/22/2018 2:25:00 PM

Lab ID: 1801A36-001

Matrix: SOIL

Received Date: 1/23/2018 6:55:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	MRA
Chloride	ND	30	mg/Kg	20	1/23/2018 12:42:24 PM	36154
EPA METHOD 8015M/D: DIESEL RANG	GE ORGANICS				Analyst	TOM
Diesel Range Organics (DRO)	ND	9.5	mg/Kg	1	1/23/2018 10:20:44 AM	36142
Motor Oil Range Organics (MRO)	ND	47	mg/Kg	1	1/23/2018 10:20:44 AM	36142
Surr: DNOP	96.6	70-130	%Rec	1	1/23/2018 10:20:44 AM	36142
EPA METHOD 8015D: GASOLINE RAN	IGE				Analyst	NSB
Gasoline Range Organics (GRO)	ND	4.3	mg/Kg	1	1/23/2018 9:47:10 AM	36131
Surr: BFB	83.7	15-316	%Rec	1	1/23/2018 9:47:10 AM	36131
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.022	mg/Kg	1	1/23/2018 9:47:10 AM	36131
Toluene	ND	0.043	mg/Kg	1	1/23/2018 9:47:10 AM	36131
Ethylbenzene	ND	0.043	mg/Kg	1	1/23/2018 9:47:10 AM	36131
Xylenes, Total	ND	0.087	mg/Kg	1	1/23/2018 9:47:10 AM	36131
Surr: 4-Bromofluorobenzene	91.8	80-120	%Rec	1	1/23/2018 9:47:10 AM	36131

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 6
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

CI	hain-c	f-Cus	tody Record	Turn-Around	Time:	SAME				1	IA			NV	/TE	20	MI	ME	RET	ГА		,
Client:	BLAG	G ENGR.	/ BP AMERICA	☐ Standard	Rush _	DAY												R				#
				Project Name																		
/lailing A	ddress:	P.O. BO	X 87	1	JONES LS # 2			www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109														
		BLOOM	FIELD, NM 87413	Project #:		A BASALAN .	1			5-34							410					
hone #:		(505) 63	2-1199	1				3.70	di.				TEN L	ysis	Red	ques	st		de a	1	15	
mail or f	Fax#:			Project Manag	ger:									(4)				300.1)				
A/QC Pa	_		Level 4 (Full Validation)		ERIN GARI	FALOS	TMB's (8021B)	s only)	/ MRO)			(S)		PO ₄ , SO	PCB's			1			Ф	
ccredita	tion:			Sampler:	NELSON VI	LEZ] %	(Ga	080	F	F	OSIN		VO2,	8082			/ wa			sample	
NELAF		□ Other		THE RESIDENCE OF THE PARTY OF T	ignas —	THE PERSON CONTRACTOR OF STREET	#	TPH	1/0	418	504	827	S	03,1	/ se		(AC	300.0			te sa	Or N
EDD (Type)	1		Sample Temp	erature 2/42	usaker (+)	1	BE +	(GR	poq	pou	Oor	etal	CI,N	icide	(A)	ni-V	oll-		ple	posit	S (Y
Date	Time	Matrix	Sample Request ID	Container Type and # Meoff Krf	Preservative Type	HEAL NO	BTEX + MTBE	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides /	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 / water		Grab sample	5 pt. composite	Air Bubbles (Y or N)
1/22/18	1425	SOIL	5PC-TB@ 5 / (95)-A	4 oz 1	Cool	7001	٧		٧									٧			٧	
1/22/10	1510	SOIL	SPG TD @ 1.5 (45) D	102-1	Cool	602	V		4									v			·/	
	-		- Allina																			_
							\vdash															
												_							\dashv			
																			\dashv		_	
ate:	Time:	Relinquish	adyby:	Received by:		Date Time	Ren	narks	:	BILL	DIREC	TLY TO	O BP I	JSING	THE	CONT	ACT V	VITH C	ORRE	SPON	DING	VID
1/22/18	1645	91	les of	amito	ask 1/2	22/18 1645	1	ONT		& REI							AD.					
ate:	Time:	Relinquishe	ed by:	Received by:		Date Time	1 "	ONTA		VHI				/ VA	ANCE	niX	UN					
nla	1904	11.1		123/18 Reference # P-914																		

Hall Environmental Analysis Laboratory, Inc.

WO#:

1801A36

24-Jan-18

Client:

Blagg Engineering

Project:

JONES LS 2

Sample ID MB-36154

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 36154

RunNo: 48638

Prep Date: 1/23/2018

Analysis Date: 1/23/2018

SeqNo: 1565154

Units: mg/Kg

Analyte

SPK value SPK Ref Val %REC LowLimit

HighLimit

RPDLimit

Qual

Chloride

ND

1.5

TestCode: EPA Method 300.0: Anions

SampType: Ics Batch ID: 36154

RunNo: 48638

Units: mg/Kg

Client ID: Prep Date: 1/23/2018

LCSS

Analysis Date: 1/23/2018

SeqNo: 1565155

LowLimit

%RPD

Analyte

Result

92.5

90

0

SPK value SPK Ref Val %REC

Chloride

Sample ID LCS-36154

RPDLimit

Qual

14

1.5

PQL

15.00

HighLimit

110

Page 3 of 6

Qualifiers:

H

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix D
- ND Not Detected at the Reporting Limit PQL Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix

Holding times for preparation or analysis exceeded

- Value above quantitation range J Analyte detected below quantitation limits
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Analyte detected in the associated Method Blank

P Sample pH Not In Range

Hall Environmental Analysis Laboratory, Inc.

WO#:

1801A36

24-Jan-18

Client:

Blagg Engineering

Project:

JONES LS 2

Sample ID LCS-36142	SampType: LCS TestCode: EPA Method 8015M/D: Diesel Range Organics											
Client ID: LCSS	Batch ID: 36142 RunNo: 48617											
Prep Date: 1/23/2018	Analysis D	Analysis Date: 1/23/2018 SeqNo: 1563800 Units: mg/Kg										
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range Organics (DRO)	50	10	50.00	0	99.7	70	130					
Surr: DNOP	4.5		5.000		90.6	70	130					

Sample ID MB-36142	SampT	ype: ME	BLK	TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: PBS	Batch ID: 36142			F	RunNo: 4	8617				
Prep Date: 1/23/2018	Analysis D	ate: 1/	23/2018	S	SeqNo: 1	563801	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	9.4		10.00		93.6	70	130			

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1801A36

24-Jan-18

Client:

Blagg Engineering

Project:

JONES LS 2

Sample ID	MB-36131
Client ID:	DRS

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Batch ID: 36131

PQL

5.0

RunNo: 48626

Prep Date: 1/22/2018

Analysis Date: 1/23/2018

SeqNo: 1564548 Units: mg/Kg

15

LowLimit

%RPD

Qual

Analyte Gasoline Range Organics (GRO) Surr: BFB

Result ND 820

930

1000

25.00

1000

SPK value SPK Ref Val

81.5

%REC

316

HighLimit

RPDLimit

Sample ID LCS-36131

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

Client ID: LCSS Prep Date:

Surr: BFB

Batch ID: 36131

RunNo: 48626 SeqNo: 1564549

Units: mg/Kg

Gasoline Range Organics (GRO)

1/22/2018

Analysis Date: 1/23/2018 **PQL** SPK value SPK Ref Val Result

%REC LowLimit HighLimit

RPDLimit Qual

%RPD 107 92.9 15 316

Oualifiers:

- Value exceeds Maximum Contaminant Level.
- Sample Diluted Due to Matrix
- Η Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- E Value above quantitation range
- Analyte detected below quantitation limits
- P Sample pH Not In Range
- Reporting Detection Limit
- Sample container temperature is out of limit as specified

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1801A36

24-Jan-18

Client:

Blagg Engineering

Project:

JONES LS 2

Sample ID MB-36131	SampT	ype: ME	BLK	Tes						
Client ID: PBS	Batch	ID: 36	131	F	RunNo: 4	8626				
Prep Date: 1/22/2018	Analysis D	ate: 1/	23/2018	S	564562	Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.90		1.000		89.7	80	120			

Sample ID LCS-36131	Sampl	ype: LC	s	Tes	TestCode: EPA Method 8021B: Volatiles						
Client ID: LCSS	Batcl	Batch ID: 36131 RunNo: 48626									
Prep Date: 1/22/2018	Analysis D	ate: 1/	23/2018	S	SeqNo: 1	564563	Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	0.99	0.025	1.000	0	98.5	77.3	128				
Toluene	0.99	0.050	1.000	0	99.0	79.2	125				
Ethylbenzene	0.99	0.050	1.000	0	98.6	80.7	127				
Xylenes, Total	3.0	0.10	3.000	0	99.9	81.6	129				
Surr: 4-Bromofluorobenzene	0.90		1.000		90.4	80	120				

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits

Page 6 of 6

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL; 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	per: 180	1A36			RcptNo: 1		
Received By: Anne Thorne	1/23/2018 6:55:00 /	AM		ann.	A.	_	
Completed By: Anne Thorne	AM		Am.	_			
Reviewed By: 11 /23/18							
Chain of Custody							
1. Is Chain of Custody complete?		Yes	\checkmark	No		Not Present	
2. How was the sample delivered?		Cou	<u>rier</u>				
Log In							*
3. Was an attempt made to cool the sample	es?	Yes	V	No [NA 🗌	
4. Were all samples received at a temperat	ure of >0° C to 6.0°C	Yes	\checkmark	No [NA 🗆	
5. Sample(s) in proper container(s)?		Yes	V	No [
6. Sufficient sample volume for indicated te	st(s)?	Yes	V	No [
7. Are samples (except VOA and ONG) pro	Yes	\checkmark	No [
8. Was preservative added to bottles?		Yes		No 5		NA 🗆	
9. VOA vials have zero headspace?		Yes		No [No VOA Vials	
10. Were any sample containers received br	Yes		No 8	V	# of preserved		
				_	_	bottles checked	
11. Does paperwork match bottle labels? (Note discrepancies on chain of custody)		Yes	\checkmark	No L	۱ ا	for pH: (<2 o	>12 unless noted)
12. Are matrices correctly identified on Chair		Yes	V	No [Adjusted?	,
13, Is it clear what analyses were requested?		Yes	V	No [
14. Were all holding times able to be met?		Yes	\checkmark	No []	Checked by:	
(If no, notify customer for authorization.)							
Special Handling (if applicable)			_		_	_	
15. Was client notified of all discrepancies w	ith this order?	Yes		No [NA 🗹	7
Person Notified:	Date		AL-ABOTTANIA ANDREAS AND ANDREAS AND ANDREAS AND ANDREAS AND AND ANDREAS ANDREAS AND ANDREAS ANDREAS AND ANDREAS A		easer .		
By Whom:	Via:	_ eMa	ail 🔲 i	Phone 🔲 I	Fax	In Person	
Regarding:		Data Still And St. 1864 St. 1845 States and		OCHURA CHICKRANICA			
Client Instructions:							
16. Additional remarks:	e)						
17. Cooler Information							
Cooler No Temp C Condition		Seal Da	ite	Signed By	/		
1 1.4 Good	Yes						



