Form 3160-5 (August 2007)	UNITED STATES DEPARTMENT OF THE INTI BUREAU OF LAND MANAGE		FORM APPROVED			
	SUNDRY NOTICES AND REPORTS o not use this form for proposals to dril andoned well. Use Form 3160-3 (APD) f	I or to re-enter anand				
	7. If Unit of CA/Agreement, Name and/or No.					
1. Type of Well	SUBMIT IN TRIPLICATE - Other instruction		San Juan 29-5 Unit			
Oil Well	X Gas Well Other		8. Well Name and No. San Juan 29-5 Unit 17B 9. API Well No.			
2. Name of Operator	Hilcorp Energy Company		30-039-29742			
3a. Address PO Box 4700, F	armington, NM 87499	one No. (include area code) 505-599-3400	5-599-3400 Gobenador PC / Blanco Mesaverde			
	ge, Sec., T.,R.,M., or Survey Description) Unit H (SENE) 2110'FNL & 310' FEL, Se	c. 05, T29N, R05W	11. Country or Parish, State Rio Arriba , New Mexico			
	CHECK THE APPROPRIATE BOX(ES) TO IN					
TYPE OF SUBMIS	SSION	TYPE OF A				
X Notice of Intent Subsequent Report	Alter Casing Fr Casing Repair No		Production (Start/Resume) Water Shut-Off Reclamation Well Integrity Recomplete Other			
Final Abandonment		ug and Abandon	Temporarily Abandon			
the existing Me		ed is the PC C102, re	d Cliffs formation and downhole commingle complete procedure & wellbore schematic. eds.			
SEE ATTA FOR CONIL OF APPR	MAR 3.0 2018	ACTI OPEI AUTI	S APPROVAL OR ACCEPTANCE OF THIS ON DOES NOT RELIEVE THE LESSEE AND RATOR FROM OBTAINING ANY OTHER HORIZATION REQUIRED FOR OPERATIONS TEDERAL AND INDIAN LANDS			
Etta Trujillo		Title Operations/Regulatory Technician - Sr.				
	- f	,				
Signature	high	Date 3-23-18				
	THIS SPACE FOR FEE	ERAL OR STATE OF	FICE USE			
Approved by <u><u><u></u></u> <u>Conditions of approval, if an</u></u>	m Tambekou y, are attached. Approval of this notice does not warrant of	Title K	Holeum Engineer Date 3/29/2018			
that the applicant holds legal entitle the applicant to condu	or equitable title to those rights in the subject lease which act operations thereon.	n would Office	FFO			
false, fictitious or fraudulent	and Title 43 U.S.C. Section 1212, make it a crime for an statements or representations as to any matter within its ju		ly to make to any department or agency of the United States any			
(Instruction on page 2)		NMOCDA				

District I

æ....

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505

Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	3. Pool Name
30-039-29742	77440	GOBERNADOR PICTURED CLIFFS (GAS)
4. Property Code	5. Property Name	6. Well No.
318837	SAN JUAN 29 5 UNIT	017B
7. OGRID No.	8. Operator Name	9. Elevation
372171	HILCORP ENERGY COMPANY	6631

10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
<u> </u>	5	29N	05W		2110	N	310	E	RIO ARRIBA

			11. Botto	om Hole Locat	tion if Different	From Surfac	e		•
UL - Lot	Section	Township	Range	Lot Idn	. Feet From	N/S Line	Feet From	E/W Line	County
12. Dedicated 32	Acres 21.24 E/2	I	13. Joint or	infill	14. Consolida	ition Code	I	15. Order No	<u></u>).

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

		+
 		11 11
		1, 1
 	f L	h ng l

OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Etta Trujillo

Title: Operations/Regulatory Tech Sr.

Date: 3/23/2018

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By:	Jason C. Edwards
Date of Survey:	12/26/2005 (revised date)
Certificate Number:	15269

Form C-102 August 1, 2011

Permit 250237



ا. بو سن

HILCORP ENERGY COMPANY SAN JUAN 29-5 UNIT 17B PICTURED CLIFFS RECOMPLETION SUNDRY

· · · · ·	JOB PROCEDURES
1.	MIRU service rig and associated equipment; test BOP.
2.	TOOH with 2 3/8" tubing set at 5,812'.
3.	Set a 4-1/2" cast iron bridge plug at +/- 3,800' to isolate the Mesa Verde. (Note: Production TOC at 3,266' by CBL.)
4.	Load the hole and pressure test the casing to frac pressure.
5.	N/D BOP, N/U frac stack and test frac stack to frac pressure.
6.	Perforate and frac the Pictured Cliffs in a single stage (Top Perforation @ 3,595'; Bottom Perforation @ 3,674').
7.	Isolate frac stage with a composite bridge plug.
8.	Nipple down frac stack, nipple up BOP and test.
9 .	TIH with a mill and drill out top Pictured Cliffs isolation plug.
10.	Clean out to Mesa Verde isolation plug and, when water and sand rates are acceptable, flow test the Pictured Cliffs.
11.	Drill out Mesa Verde isolation plug and cleanout to PBTD of 6,116'. TOOH.
1 2 .	TIH and land production tubing. Get a commingled Mesa Verde/Pictured Cliffs flow rate.



.

HILCORP ENERGY COMPANY SAN JUAN 29-5 UNIT 17B PICTURED CLIFFS RECOMPLETION SUNDRY

		nengy Company SAN JUAN 29-5 UNIT #17E		nt Schematic - \	ersion 3		
30039297		Surface Legal Location 005-029N-005W-H	Field Name MV	License No.		Size Province NEW MEXICO	Wet Contguration Type Vertical
around Eleva		Original V3RT Elevation (1)	-	General Distance (R)	KB-Catalog Florig		ng Hanger Olistance (1)
6,631.00		6,647.00		16.00	<u></u>		
		Ve	rtical, Origiu	nal Hole, 3/19/20	18 4:29:51	PM	
MD (ftKB)	TVD (ftKB)			Vertical schem	atic (actual)		
59							ament; 16.0-244.3; 7/18/2006; HLUMBERGER & PUMP 5
15_1			والمحتر أرغم فالمحتم وأعادهما بأراق والمحتم		282 28280	BBLS FRESH WA	TER AHEAD. PRESSURE
Z4.0						WATER/DYE THE	LAST 10 BBLS. CEMENT
198.2]					S G CEMENT W/3% CaCL2.
199.5						PPG. PUNE 50 B	BL SLURRY @ 3.0 BPM, S/D. SPLACE W/16.4 BBLS FRESH
243.4						WATER, FCP 81 F	PSI. BUMP PLUG W/268 PSIG.
244.4							320. CHECKED FLOATS. BLS. 15 BBLS CEMENT TO
255.9					62900000 80	' SURFACE. JSA W	SCHLUMBERGER . RIG
1,175.9		-NACIMIENTO (final)			· 🕅 💳	1; Surface; 8 5/8 b	n; 9.00 in; 16.0 ftKB; RUN 6
2,536.1		OJO ALAMO (final)					', H-40, 32.3 PPF CASING 244', FLOAT COLLAR @ 198',
2,711.0		KIR Tubing; 2 3/8 in; 4.70 lb/	n: J-65; 6.0 fike			CENTRALIZERS	@ 234', 154', 111', 67'. SET TOP
3,011.2		FRU	5,810.1 ftKE			LEVEL. TEST CA	IGE 2" BELOW GROUND _ SING TO 1000 PSI ON
3,255.1						7/19/06.; 244.3 ft	(8 53,688.3; 7/23/2006; PJSM
3,448.2		PICTURED CLIFFS (final)				R/U CEMENT HEA	D& LINES. TEST LINES TO
3,542.5 3,843.2		1					20 BBLS GEL WATER. BL CLASS G CEMENT W/3%
3,585,5							3.3.0 LB/88L CEMNET @ 11.7 88L SLURRY @ 4.0 8PM
3.888.5				2 X 1		FOLLOWED BY 2	30 SKS 50/50 POZ/CLASS G.
2,901.9						D24. 0.15% D65.	.2%D45.2% S-001, 5 LB/SK 3 LB.BBL CEMINET @ 13.5
4,185.0		NAVAJO CITY (final)	_				BLS SLURRY. S/D. DROP E W/166 BBLS FRESH WATER-
4,574.0						@ 4 BPM. CAUGH	IT CEMENT AFTER 1 BBLS
4,637.9		OTERO 2 (final)			<u> </u>	PLUG WITH 1811	160 PSI @ 2 BPM. BUMP PSIG, PLUG DOWN @ 2030
4,819.9					<u>81</u>		LOATS, 1 BBL BLED BACK.
5,022.0		-CLIFFHOUSETRANSITION	final)		- Million - Mill	W/SCHLUMBERG	ER . RIG DOWN
5,233.9				n 💥			ILOAD OUT CEMENT HEAD.
5,271.0				<u>- 506</u> (v	824		15, 20.0 PPF, STC CASING, FS 3843'.3 CENTRALIZERS @
1,271.0					<u> </u>	1.3886', 3842', 3756	r, 3669', 3582', 3496', 281', 163'_
5,280.8					(1)	2811'.2769' LAND	S @ 2983', 2940, 2897', 2854, 7" MANDREL IN SPEED
5,356.0					\$8 6- 1	HEAD. TEST CAS	ING TO 1800 PIS ON 7/24/06.:_
5,534.8		POINT LOOKOUT (final)			188-1 186-1	PERF-LEWIS; 4,	374.0-4,820.0; 8/15/2006
8,557.2						7/26/2006; PJSM	Cement: 3.266.0-6, 138.0; & CEMENT W/265 SX 50/60
5,710.0		1					9 % D20,1 % D4628 D2425 % D167, .15 % D65, 1
5,810.0		Profile Nipple; 2 3/8 in; 5.81			189. 1	% D800, 3.5 # /SX	PS@ 13 PPG 67 BBL PLUG
5,811.0		Mule Shoe; 2 3/8 in; 5.811.1 ft	ftKE KB: 5 811 5 ftKE		48 <u>84</u> 780 /	PERF - CLIFF HO	RS & R/D SCHLUMBERGER
5,811.4		<u></u>				5.234.0-5.657.0;8	V15/2006 OKOUT / MENEFEE LOWER;
5,954.1 6,092.2						5,710.0-5,954.0;8	
6,092.2 6,118.1						Coment Phone 44	6.0-6.138.0; 7/26/2006
6,131.9					\$X	Genear - 09, 0, 11	0.0-0,100.0,1120/2004
6,134.8					8 8	3: Production: 4 1/	2 in; 4.05 in; 16.0 ftKB; RAN
6,136.2	ĺ				i kali kali kali kali kali kali kali kal	+4 JTS 10.5 # J	55 STC 4-1/2" CSG SET @
6,138.1					×	6138'; 6, 138.0 ftKi	
6,143.9							
6,635.9							
www.pe							

•