District .

1625 N French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

NMOCD

Form C-144 Revised April 3, 2017

Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company Address: 200 Energy Court, Farmington, NM 87401 Facility or well name: ELLIOTT GC T 001
API Number: 3004520297 OCD Permit Number: U/L or Otr/Otr B Section 26 Township 30N Range 09W County: San Juan
Center of Proposed Design: Latitude 36.78717 Longitude -107.74673 NAD83 Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Drilling Workover Drilling Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Volume: bbl Dimensions: L x W x D Dimension
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: 21 bbl Type of fluid: Produced Water Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off ☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other ☐ Single wall/ Double bottom; sidewalls not visible ☐ Liner type: Thicknessmil ☐ HDPE ☐ PVC ☐ Other
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet

22

Alternate. Please specify

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
☐ Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300 feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland. -y US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 15.17.9 NMAC
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: *Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Falternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. -3 Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believes	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: OCD Permit Number:	12018
19.	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
■ Closure Completion Date: 3/7/2018	
Closure Completion Date: 3/7/2018	
20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-loc If different from approved plan, please explain.	op systems only)

Operator Closure Certification:	
	d with this closure report is true, accurate and complete to the best of my knowledge and ble closure requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Signature:UTIN gWifalos	Date: May 3, 2018
e-mail address: erin.garifalos@bp.com	Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

ELLIOTT GC T 001

API No. 3004520297

Unit Letter B Section 26 T 30N R 09W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.025
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	<0.098
TPH	US EPA Method SW-846 418.1 or <u>8015</u> extended	100	<46
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. Impacted soils were discovered during the confirmation sampling. The source of the release was undetermined, but most likely from the 21 bgt. Two (2) subsequent grab samples were collected at 5 (soil) & 6.5 (bedrock) feet (ft.) below grade showing high TPH. The release will be addressed following spill and release guidelines The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has occurred and will be addressed following the spill and release guidelines. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has occurred and will be addressed following the spill and release guidelines. Attached is a laboratory report and field report. The location has been reclaimed as the well has been plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The gas well has been plugged and abandoned, BGT location's surface condition is clear.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The gas well has been plugged and abandoned, BGT location's surface condition is clear.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The gas well has been plugged and abandoned, BGT location's surface condition is clear.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The gas well has been plugged and abandoned, BGT location's surface condition is clear.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The gas well has been plugged and abandoned, BGT location's surface condition is clear.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised April 3, 2017 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

			Rele	ease Notific	eation	and Co	orrective A	ction	1			
						OPERA	ГOR		Initia	al Report		Final Report
				tion Company			n Garifalos			*		
				n, NM 87401			No. (832) 609-					
Facility Nar	ne ELLIO	TTGCT	001			Facility Typ	e: Natural Ga	as We	ell			
Surface Ow	ner: Fede	eral		Mineral C)wner:	Federal			API No	.300452	0297	,
				LOCA	TION	OF RE	LEASE					
Unit Letter	Section	Township	Range	Feet from the	North/	South Line	Feet from the	East/\	West Line	County		
В	26	30N	09W	790	Nor	th	1,615	Eas	st	S	an	Juan
			Latitud	_e 36.78717	Lo	ongitude1	07.74673	NAD	83			
				NAT	URE	OF REL	EASE					
Type of Rele	ase:: none)					Release:: unkno			Recovered::		
Source of Re	lease: belo	w grade ta	nk - 21	bbl		n/a	Hour of Occurrenc	e:	n/a	Hour of Disc	covery:	
Was Immedia		Given?				If YES, To	Whom?					
			Yes ✓	No Not Re	equired							
By Whom? Was a Water	course Reac	hed?				Date and H	lour olume Impacting t	he Wate	ercourse			
was a water	course reac		Yes 🗸	No		11 125, 70	rume impacting t	iic wan	orcourse.			
If a Watercou	irse was Im	pacted, Descri	ibe Fully.*									
Describe Cau	se of Proble	em and Remed	dial Action	Impacted undetern 6.5 (bed	d soils we nined, but rock) feet	ere discovered t most likely fro (ft.) below gra	d for chloride, TPH a during the confirmati m the 21 bgt. Two (de showing high TPI	ion samp (2) subse H. The re	oling. The so equent grab selease will be	urce of the rel samples were	ease wa	d at 5 (soil) &
Describe Are	Affected	and Cleanup A	Action Tak		guidelines	The field repo	ort and laboratory re	ports are	e attached.			
				Final lab			is attached.					
regulations all public health should their of or the environ	l operators or the envir operations h nment. In a	are required to ronment. The ave failed to a	acceptance acceptance adequately CD accep	d/or file certain re e of a C-141 repo investigate and re	elease no ort by the emediate	otifications as NMOCD m contaminati	knowledge and und perform correct arked as "Final Re on that pose a three the operator of r	tive act eport" d eat to gr	ions for rele loes not reli round water	eases which a eve the oper s, surface was	may end ator of l ter, hun	danger liability nan health
							OIL CONS	SERV	ATION	DIVISIO	N	
Signature:	run g	arifalo	4									
Printed Name	Erin G	arifalos				Approved by	Environmental Sp	pecialis	t:			
Title: Field	Enviro	onmenta	I Coo	rdinator	I	Approval Dat	e:]	Expiration I	Date:		
E-mail Addre	ss: erin.	garifalos	@bp.	com		Conditions of	Approval:			Attached		
Date: May				(832) 609-70)48							
Attach Addit	ional Shee	ets If Necessa	arv									



380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

March 2, 2018

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank

Well Name: ELLIOTT GAS COM T 001

API#: 3004520297

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about March 5, 2018. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From:

Buckley, Farrah (CH2M HILL)

To:

Smith, Corv. EMNRD; Fields, Vanessa, EMNRD (Vanessa, Fields@state.nm.us)

Cc:

jeffcblagg@aol.com; blagg_njv@yahoo.com; Garifalos, Erin; Beebe, Sabre; Moskal, Steven

Subject:

BP Pit Close Notification - ELLIOTT GAS COM T 001

Date:

Friday, March 02, 2018 8:25:25 AM

BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

March 2, 2018

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ELLIOTT GAS COM T 001 API 30-045-20297 (B) Section 26 – T30N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around March 5, 2018.

Should you have any questions, please feel free to contact BP at our Durango office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator – San Juan Cell: 832-609-7048

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	BLAGG ENGINE P.O. BOX 87, BLOOM	IFIELD, NM 87413	API #: 3004520297 TANK ID (if applicble): A
	(505) 632		(if applicble):
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE	INVESTIGATION / OTHER:	PAGE #: of
SITE INFORMATION	: SITE NAME: ELLIOTT GC	T #1	DATE STARTED: 03/05/18
QUAD/UNIT: B SEC: 26 TWP:	30N RNG: 9W PM: NM	CNTY: SJ ST: NM	DATE FINISHED:
1/4 - 1/4/FOOTAGE: 790'N / 1,615 LEASE #: SF078139		DERAL STATE / FEE / INDIAN KELLEY O.F.S. OR: BP - S. BEEBE	ENVIRONMENTAL SPECIALIST(S): NJV
REFERENCE POINT			_
21 BGT (SW/DB)	WELL HEAD (W.H.) GPS COORD.: 36.78717	36.78730 X 107.7468	001 040 ==
1) ZI DOI (SYVIDD)			
2)	GPS COORD:	San	EARING FROM W.H.:
3)	GPS COORD:		EARING FROM W.H.:
4)	GPS COORD.:		EARING FROM W.H.:
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB USEI		READING (ppm)
	(21) SAMPLE DATE: 03/05/18 SAM SAMPLE DATE: SAM		015B/8021B/300.0 (CI) 0.7
SAMPLE ID: 3) SAMPLE ID:		IPLE TIME: LAB ANALYSIS: IPLE TIME: LAB ANALYSIS:	
4) SAMPLE ID:		IPLE TIME: LAB ANALYSIS:	
5) SAMPLE ID:	SAMPLE DATE:SAM	IPLE TIME: LAB ANALYSIS:	
SOIL COLOR: DUS COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LO MOISTURE: DRY SLIGHTLY MOIST MOIST / WE SAMPLE TYPE: GRAB COMPOSITE . #	COHESIVE / COHESIVE / [HIGHLY COHESIVE] DENSITY (OSE / FIRM / DENSE / [VERY DENSE] HC ODOR DE TT / SATURATED / SUPER SATURATED SOILS A	(CLAYS): NON PLASTIC SLIGHTLY PLASTIC COHESIVE CLAYS & SILTS): SOFT FIRM DETECTED: YES NO EXPLANATION - VE BOVE SANDSTONE. 6 DISPLAYING WETNESS: YES NO EXPL	COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC STIFF / VERY STIFF / HARD ERY SLIGHT FROM DISCOLORED ANATION -
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: GAS WELL PLUGGED & ABAND BEDROCK AT 6 FT. BELOW GRADE, VI EXCAVATION DIMENSION ESTIMATION:	ONED (P&A). NMOCD OR BLM REPS. NO ERY HARD, SLIGHTLY FRIABLE, COMPETE NA ft. X NA ft. X	OISCOLORED SOILS & APPARENT FOR THE PRESENT TO WITNESS CONFIRMENT. NA ft. EXCAVATION E	
			M CALIB. READ. = 100.0 ppm RF = 1.00
MA	BERM PBGTL T.B. ~ 6' FEN(x x x)	N T	MCALIB. GAS = 100 ppm ME: 8:50 ampm DATE: 03/05/18 MISCELL. NOTES PO: 4300903070 AFE#: X7-006YF-E:REST SIO #: 190040007672 GL #: 745277 Permit date(s): 06/08/10 OCD Appr. date(s): 01/17/18 ank OVM = Organic Vapor Meter ID ppm = parts per million
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELO	B.G. N DEPRESSION; B.G. = BELOWGRADE; B = BELOW, T.H. = TI DWGRADE TANK LOCATION; SPD = SAMPLE POINT DESIGN. WALL; DW-DOUBLE WALL; SB-SINGLE BOTTOM; DB-DOUBLE WALL; SB-SINGLE	ATION; R.W. = RETAINING WALL; NA - NOT	A BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N Magnetic declination: 10° E

Analytical Report

Lab Order 1803215

Date Reported: 3/7/2018

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Project:

ELLIOTT GC T 1

Client Sample ID: 5PC-TB @ 6.5' (21)

Collection Date: 3/5/2018 8:20:00 AM

Lab ID: 1803215-001 Matrix: SOIL Received Date: 3/6/2018 6:55:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	CJS
Chloride	ND	30	mg/Kg	20	3/6/2018 5:27:01 PM	36854
EPA METHOD 8015D MOD: GASOL	INE RANGE				Analyst	AG
Gasoline Range Organics (GRO)	ND	4.0	mg/Kg	1	3/6/2018 10:14:12 AM	G49570
Surr: BFB	125	70-130	%Rec	1	3/6/2018 10:14:12 AM	G49570
EPA METHOD 8015M/D: DIESEL RA	NGE ORGANICS	;			Analyst	TOM
Diesel Range Organics (DRO)	ND	9.8	mg/Kg	1	3/6/2018 10:03:09 AM	36850
Motor Oil Range Organics (MRO)	ND	49	mg/Kg	1	3/6/2018 10:03:09 AM	36850
Surr: DNOP	91.0	70-130	%Rec	1	3/6/2018 10:03:09 AM	36850
EPA METHOD 8260B: VOLATILES	SHORT LIST				Analyst	AG
Benzene	ND	0.020	mg/Kg	1	3/6/2018 10:14:12 AM	R49570
Toluene	ND	0.040	mg/Kg	1	3/6/2018 10:14:12 AM	R49570
Ethylbenzene	ND	0.040	mg/Kg	1	3/6/2018 10:14:12 AM	R49570
Xylenes, Total	ND	0.079	mg/Kg	1	3/6/2018 10:14:12 AM	R49570
Surr: 4-Bromofluorobenzene	116	70-130	%Rec	1	3/6/2018 10:14:12 AM	R49570
Surr: Toluene-d8	91.5	70-130	%Rec	1	3/6/2018 10:14:12 AM	R49570

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- Ε Value above quantitation range
- Analyte detected below quantitation limits Page 1 of 4
- Sample pH Not In Range
- Reporting Detection Limit RL
- Sample container temperature is out of limit as specified

Chai	in-o	f-Cus	tody Record	Turn-Around 7	îme:	SAI	ME					AL			MV	ft E	20	nt s	va e	:N7	FA	, H ·	
Cilent: B	BLAGO	S ENGR.	/ BP AMERICA	☐ Standard	Rush _	DA	•													AT(
				Project Name:														.com		~		P B	
Mailing Addre	ss:	P.O. BO	X 87	EI	LUOTT GC	T #1			49	01 H								 1M 8		9			
		BLOOM	FIELD, NM 87413	Project #:)5-34					•		-410					
Phone #:		(505) 63	2-1199	1													ques						
email or Fax#:				Project Manag	jer.										4)				1)				
QA/QC Package Standard	8 :		Level 4 (Full Validation)		SABRE BEE	BE		WB's (8021B)	(Ajuo	/ MRO)			(S)		204,50	PCB's			er - 300.1)			a	
Accreditation:				Sampler:	NELSON VI	ELEZ	n_{Y}	1 (8)	+ TPH (Gas	RO/	ਜ਼	(1:	OSIN		1021	808			/water			臣	
□ NELAP		□ Other		office and	Yes ex		200	1	TPH	0/0	418	504	827	s	Oal	/ Se		8	0.00			S	N (
□ EDD (Type)	<u>) </u>			Same en	efatere sebak T			ŧ		(GR	poq	hod	Oor	etal	D, N	icid	র	길	- Jo		읦	90si	يغ
Date Ti	me	Matrix	Sample Request ID	Container Type and # Mealt t	Preservative Type			BTEX +•M	BTEX + MTBE	TPH 80158 (GRO / DRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 M	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	Chloride (soll - 300.0 /		Grab sample	5 pt. composite sample	Air Bubbles (Y or N)
3/5/18 09	82O	SOIL	5PC - TB @ 6.5'(21)	4 oz 1	Cool		701	<		٧									٧			٧	
																					П	П	
																				П			
						}	•																
	Ì																			П			
												-	·				:						
																	·						
			•																				
							•															П	
Dete: Time 3/5/18	» «	Relinquish	hil	Received by: Musti	abela	3/5/18	Time /500	Rem	arks	•			FORM				BE FC	RWA	RDED	FROM	BP.	IF MO	L .
Date: Time):	Relinquish	ed by:	Received by:) 63	Date /U/8	Time																
19 11 X 1100	190esser	ry samples a	with WWW Lex ubmitted to Hall Environmental may be s	subcontracted to other	accredited laboratoric		ves as notice of	filts p	ldisso	ity. A	пу виб	-contr	acted	data v	vii) be	clearly	y notal	ed on	the er	ratytica	ıl repo	n.	

OC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1803215

07-Mar-18

Client:

Blagg Engineering

Project:

Client ID:

Client ID:

Sur: DNOP

ELLIOTT GC T 1

Sample ID LCS-36850

SampType: LCS

LCSS

Batch ID: 36850

RunNo: 49575

3/6/2018

130

130

Prep Date:

Analysis Date: 3/6/2018 **PQL**

10

10

SeqNo: 1602665

LowLimit

LowLimit

LowLimit

70

70

Units: mg/Kg HighLimit

TestCode: EPA Method 8015M/D: Diesel Range Organics

Analyte Diesel Range Organics (DRO)

47 4.2

Result

SPK value SPK Ref Val %REC 94.7 83.8

%RPD **RPDLimit** Qual

Surr: DNOP

Sample ID MB-36850 PBS

SampType: MBLK Batch ID: 36850

TestCode: EPA Method 8015M/D: Diesel Range Organics RunNo: 49575

Analyte

Prep Date: 3/6/2018 Result

Analysis Date: 3/6/2018 SPK value SPK Ref Val %REC

50.00

5.000

SeqNo: 1602666

Units: mg/Kg HighLimit

%RPD **RPDLimit**

Qual

Diesel Range Organics (DRO) Motor Oil Range Organics (MRO) ND ND 8.9

50 10.00

88.9

70

Sample ID LCS-36842

Prep Date: 3/5/2018

SampType: LCS

RunNo: 49575

TestCode: EPA Method 8015M/D: Diesel Range Organics

130

Client ID: LCSS

Batch ID: 36842 Analysis Date: 3/6/2018

PQL

Units: %Rec

130

Analyte

Result

SPK value SPK Ref Val

5.000

SeqNo: 1602834 %REC 83.0

HighLimit

%RPD **RPDLimit**

Qual

Surr. DNOP

Sample ID MB-36842

SampType: MBLK

TestCode: EPA Method 8015M/D: Diesel Range Organics

Client ID: PBS

Batch ID: 36842

RunNo: 49575

Units: %Rec

Analyte

Prep Date: 3/5/2018 Analysis Date: 3/6/2018 PQL

SeqNo: 1602835

HighLimit

%RPD

RPDLimit Qual

Surr: DNOP

10

Result

4.1

10.00

SPK value SPK Ref Val

%REC 101

70

LowLimit

130

Oualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix

Holding times for preparation or analysis exceeded Н

Not Detected at the Reporting Limit

Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

В Analyte detected in the associated Method Blank

Value above quantitation range Ε

J Analyte detected below quantitation limits Page 2 of 4

Sample pH Not In Range

RL Reporting Detection Limit

Sample container temperature is out of limit as specified

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1803215

07-Mar-18

Client:

Blagg Engineering

Project:

ELLIOTT GC T 1

Sample iD 100ng lcs	SampType: LCS4 TestCode: EPA Method 8260B: Volatiles Short List									
Client ID: BatchQC	Batc	h ID: R4	9570	RunNo: 49570						
Prep Date:	Analysis [Date: 3/	6/2018	8	SeqNo: 1	602691	Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.94	0.025	1.000	0	93.9	80	120			
Toluene	0.92	0.050	1.000	0	92.1	80	120			
Ethylbenzene	0.90	0.050	1.000	0	90.4	80	120			
Xylenes, Total	2.8	0.10	3.000	0	92.3	80	120			
Surr: 4-Bromofluorobenzene	0.44		0.5000		88.4	70	130			
Surr: Toluene-d8	0.47		0.5000		94.5	70	130	•		

Sample ID rb	SampType: MBLK Batch ID: R49570 Analysis Date: 3/6/2018			TestCode: EPA Method 8260B: Volatiles Short List						
Client ID: PBS				RunNo: 49570						
Prep Date:				SeqNo: 1602695			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.56		0.5000		111	70	130			
Surr: Toluene-d8	0.48		0.5000		96.9	70	130			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Page 3 of 4

QE SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1803215

07-Mar-18

Client:

Blagg Engineering

Project:

ELLIOTT GC T 1

Sample ID 2.5ug gro Ics

SampType: LCS

TestCode: EPA Method 8015D Mod: Gasoline Range

LowLimit

70

70

Client ID: LCSS

Batch ID: G49570

5.0

RunNo: 49570

Prep Date:

Units: mg/Kg

Analysis Date: 3/6/2018

SeqNo: 1602671

110

108

%REC

Analyte Gasoline Range Organics (GRO) Result **PQL** 28

SPK value SPK Ref Val 25.00

HighLimit

130

130

RPDLimit

Qual

Sur: BFB

540

500.0

TestCode: EPA Method 8015D Mod: Gasoline Range

%RPD

Sample ID rb Client ID: PBS

SampType: MBLK Batch ID: G49570

PQL

5.0

RunNo: 49570

HighLimit

Prep Date:

SeqNo: 1602672

Units: mg/Kg

Analyte

Analysis Date: 3/6/2018

SPK value SPK Ref Val %REC LowLimit %RPD

RPDLimit Qual

Page 4 of 4

Gasoline Range Organics (GRO) Surr: BFB

ND 600

Result

500.0

120

70

130

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix D

Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

PQL Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

В Analyte detected in the associated Method Blank

Ε Value above quantitation range

Analyte detected below quantitation limits

Sample pH Not In Range

RLReporting Detection Limit

Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

Albuquerque, NM 87109 Sample Log-In Check List

Client Name:	BLAGG	Work Order Num	ber: 1803215		RcptNo:	1
Received By:	Anne Thome	3/8/2018 6:55:00 A	M	Am In	- .	
Completed By:	Completed By: Anne Thome 3/8/2018 7:04:21 Al			an Il		
· Reviewed By:	I M0	3/4/18				-
Chain of Cus	stody					
1. Is Chain of C	ustody complete?		Yes 🗹	No 🗆	Not Present	
2. How was the	sample delivered?		Courter			
Log In	• • •		٠			
3. Was an attempt made to cool the samples?			Yes 🗹	No 🗆	NA 🗆	
4. Were all same	ples received at a temper	ature of >0° C to 6.0°C	Yes 🗹	No 🗆	NA 🗆	
5. Sample(s) in	proper container(s)?		Yes 🗹	No 🗆		
6. Sufficient sam	ple volume for Indicated	test(s)?	Yes 🗹	No 🗆	•	
7. Are samples (except VOA and ONG) properly preserved?			Yes 🗹	No 🗆		
8. Was preserva	itive added to bottles?		Yes 🗆	No 🗹	na 🗆	
9. VOA vials hav	e zero headspace?		Yes 🗌	No 🗆	No VOA Vials 🗹	
10. Were any sar	mple containers received	broken?	Yes 🗆	No ☑ ˌ	# of preserved	
				_	bottles checked	
• •	ork match bottle labels? ancles on chain of custod		Yes ☑	No □	for pH:	>12 unless noted)
•	correctly identified on Cha	•	Yes 🗹	No 🗆	Adjusted?	- 12 4
	t analyses were requeste	-	Yes 🗹	No 🗆		
14. Were all holdi	ng times able to be met? ustomer for authorization.		Yes 🗹	Nó 🗆	Checked by:	<u> </u>
Special Handi	ling (If applicable)					
15. Was client no	otified of all discrepancies	with this order?	Yes 🗌	No 🗆	NA 🗹	
Person	Notified:	Date				
By Who	om:	Via:	eMail P	hone Fax	n Person	
Regard	ing:					•
Client in	nstructions:					
16. Additional res	marks:					
17. Cooler Infor		s iki zwakuwa policy okuza modula inti	i 1822 Sighilladar (1842)	arayang masi wil		
Cooler No	Temp°C Condition	Seal Intact Seal No	Seal Date	Signed By		
<u> </u>	11.0 GGGG	1168	L_			
		·				

ELLIOTT GC T #1



