This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator Hilcor	p Energ	y Company		Lease	e Name SAN	JUAN 28-7 UN	IT	Well No96
Location of Wel	l: Unit L	etter G	Sec	08	Twp027N	Rge	007W API	# 30-039-07129
	Name of Reservoir or Pool				Type of Prod		Method of Prod	Prod Medium
Upper Completion	PC			Gas	Gas			Tubing
Lower Completion	MV			Gas	Gas		ial Lift	Tubing
				Pre-Flow S	Shut-In Pressu	ıre Data		
Upper	Hour, Date, Shut-In				of Time Shut-In	· · · · · · · · · · · · · · · · · · ·	ss. PSIG	Stabilized?(Yes or No)
Completion	5/18/2018			96 hours		ĺ	198	Yes
Lower	Hour, Date, Shut-In			Length	of Time Shut-In	SI Pres	s. PSIG	Stabilized?(Yes or No)
Completion	5/18/2018			178	hours .		162	Yes
Commenced at: 5/22/2018			DREG			ing (Upper or Lower): UPPER		
Time (date/time)		Lapsed Time Since*		PRESSURE Upper zone Lower zone		Prod Zone Temperature		Remarks
5/23/2018 12:1	1 PM	36		112	112 165			
5/24/2018 12:00	5/24/2018 12:00 PM		60		166	79		NMOCD
5/25/2018 10:4	5/25/2018 10:47 AM 82			95	166	76		JUN 0 4 2018
Production rate	during t	est					D	ISTRICT III
Oil:	BPOD Based on:			Bbls. InHrs.		Grav.		GOR
Gas		MCFPD;	Test thru	ı (Orifice or N	1eter)			
,				Mid-Test S	Shut-In Pressu	ıre Data		
Upper Completion	Hour, Da	te, Shut-In			Length of Time Shut-In		ss. PSIG	Stabilized?(Yes or No)
Lower Completion	Hour, Date, Shut-In			Length	of Time Shut-In	SI Pres	ss. PSIG	Stabilized?(Yes or No)

(Continue on reverse side)

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Commenced at:			Zone Producing (Upper or Lower)						
Time	Lapsed Time Since*	PRESSURE		Prod Zone					
(date/time)		Upper zone	Lower zone	Temperature	е	Remarks			
							i		
					_				
					ļ				
	d.								
Production rate during		Bbls In	Hrs		Grav	GOR			
Gas	NICFPD; Test tr	iru (Orifice or ivi	leter)						
Remarks:									
I hereby certify that th	e information herein c	ontained is true	and complete	to the best of	f my knowled	dge.			
Approved: // -)	NE	20 18	Operat	tor: HEC					
	onservation Division		By:	By: Lawrence Lucero					
ву:	m		Title:	Title: Multi-Skilled Operator					
To Donu	ty Oil & Gas Insp	ector,							
Title: Depu	District #3		_ Date: _	Date: Monday, June 4, 2018					

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production
- while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3