Diekri + I	
1625 N. French Dr., Hobbs, NM 88240	F
District II	•
1301 W. Grand Avenue, Artesia, NM 88210	
District III	1
1000 Rio Brazos Road, Aztec, NM 87410	1
District IV	
1220 S. St. Francis Dr., Santa Fe, NM 87505	
2009 Pink 16 PM 1 1	1

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

# Dit Closed I can System Palary Grade Tonk or

Proposed Alternative Method Permit or Closure Plan Application
Type of action:  Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method  Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method  Modification to an existing permit  Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances
Operator: Elm Ridge Exploration OGRID #: 149052
Address: P.O. Box 156; Bloomfield, NM 87413
Facility or well name: <u>Lybrook Federal 4</u>
API Number: <u>3003924894</u> OCD Permit Number:
U/L or Qtr/Qtr H Section 24 Township 24N Range 7W County: Rio Arriba
Center of Proposed Design: Latitude 36.180091 Longitude -107.313150 NAD: □1927 ☑ 1983
Surface Owner:  ☐ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
2.  Pit: Subsection F or G of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.  Closed-loop System: Subsection H of 19.15.17.11 NMAC
Type of Operation: P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent)
Type of Operation:  P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent)  Drying Pad Above Ground Steel Tanks Haul-off Bins Other
intent)  Drying Pad Above Ground Steel Tanks Haul-off Bins Other
intent)
intent)  Drying Pad
Drying Pad



Form C-144

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)				
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,			
Four foot height, four strands of barbed wire evenly spaced between one and four feet				
✓ Alternate. Please specify 4' tall hogwire fencing with pipe railing				
7. <b>Netting:</b> Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)				
☐ Screen ☐ Netting ☐ Othersolid/cone top				
☐ Monthly inspections (If netting or screening is not physically feasible)				
8. Signs: Subsection C of 19.15.17.11 NMAC				
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers				
⊠ Signed in compliance with 19.15.3.103 NMAC				
9.				
Administrative Approvals and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.				
Please check a box if one or more of the following is requested, if not leave blank:  Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau of the Santa Fe En	office for			
consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.				
10.				
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system.				
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  The attached iWATERS database search shows a nearby well approximately 6.5 miles north-east of the Lybrook Federal 4 well site with a depth to groundwater of 80 feet. The water well is at an elevation of approximately 312 feet lower in elevation than the well site, indicating that the depth to groundwater from the bottom of the BGT at this site is greater than 50 feet.	☐ Yes ⊠ No			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).0.	☐ Yes ⊠ No			
The nearest watercourse 1,022.7 ft. north-west per attached topographic map. These findings are reflected by the attached visual inspection sheet.				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  The attached aerial photograph and visual inspection sheet indicate that none of the above locations are within 1000 feet of the well site.	☐ Yes ☒ No ☐ NA			
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to permanent pits)	☐ Yes ☐ No ☑ NA			
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. iWATERS database search indicates that no well is within 1000 feet of the well site. A visual inspection was also performed. The attached results of the visual inspection reflect that no water wells were visible within 1000 feet.	☐ Yes ☑ No			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	☐ Yes ⊠ No			
The site is not within incorporated municipal boundaries, indicated by the attached topographic map and visual inspection sheet.	163 🖾 140			
Within 500 feet of a wetland.  The USFWS data file, WetlandsData.kmz, dated July 2, 2008 was opened using Google Earth. No wetlands were noted.  The visual inspection sheet indicates these findings.	☐ Yes ⊠ No			
Within the area overlying a subsurface mine.  The NM EMNRD web map was reviewed and attached, the well is not in an area overlying a subsurface mine	☐ Yes ⊠ No			
Within an unstable area.  Attached topographic map and visual inspection indicates that the site is not in an unstable area	☐ Yes ⊠ No			
Within a 100-year floodplain.  Attached FEMA flood map indicates the site to be outside of a 100 year floodplain	☐ Yes ⊠ No			

II. L
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC
and 19.15.17.13 NMAC
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:
12.
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are
attached.  Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API Number:
Previously Approved Operating and Maintenance Plan API Number: (Applies only to closed-loop system that use
above ground steel tanks or haul-off bins and propose to implement waste removal for closure)
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC   Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.   Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC   Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC   Climatological Factors Assessment   Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC   Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Quality Control/Quality Assurance Construction and Installation Plan   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC   Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan   Golf Field Waste Stream Characterization   Monitoring and Inspection Plan   Erosion Control Plan   Erosion Control Plan   Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Proposed Closure: 19.15.17.13 NMAC
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative
Proposed Closure Method: Waste Excavation and Removal
Waste Removal (Closed-loop systems only)
☐ On-site Closure Method (Only for temporary pits and closed-loop systems) ☐ In-place Burial ☐ On-site Trench Burial
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

Page 3 of 5

Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.I Instructions: Please indentify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if facilities are required.					
Disposal Facility Name: Disposal Facility Permit Number:					
Disposal Facility Name: Disposal Facility Permit Number:					
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will not be used for future service and operations?  Yes (If yes, please provide the information below)  No					
Required for impacted areas which will not be used for future service and operations:  Soil Backfill and Cover Design Specifications based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC					
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC  Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.					
Ground water is less than 50 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA				
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA				
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No				
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No				
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No				
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No				
Within a 100-year floodplain FEMA map	Yes No				
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)  Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC					

Operator Application Certification:  I hereby certify that the information submitted with this application is true.	te, accurate and complete to the best of my knowledge and belief.					
Name (Print): Ms. Amy Mackey, Title:	Administrative Manager					
Signature: Au Call	Date: 3/10/09					
e-mail address: amackey1@elmridge.net	Telephone: 505-632-3476 ext 201					
OCD Approval: Permit Application (including closure plan)	osure Plan (only) OCD Conditions (see attachment)					
OCD Representative Signature:	Approval Date:					
Title: OCD Permit Number:						
Instructions: Operators are required to obtain an approved closure plan. The closure report is required to be submitted to the division within 60 d	Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.					
	Closure Completion Date:					
22. Closure Method: Waste Excavation and Removal On-Site Closure Method If different from approved plan, please explain.	Alternative Closure Method   Waste Removal (Closed-loop systems only)					
	Disposal Facility Permit Number:ed on or in areas that <i>will not</i> be used for future service and operations?  No					
Re-vegetation Application Rates and Seeding Technique						
	losure)  Longitude NAD:   1983					
25. Operator Closure Certification:						
	closure report is true, accurate and complete to the best of my knowledge and requirements and conditions specified in the approved closure plan.					
Name (Print): Title:						
Signature: Date:						
e-mail address: Telephone:						

Telephone: \_

#### New Mexico Office of the State Engineer **Point of Diversion Summary**

Back

(quarters are 1=NW 2=NE 3=SW 4=SE) (quarters are biggest to smallest)

POD Number

Tws Rng Sec q q q

Zone X Y

SJ 00681

25N 06W 21 4 1 4

Driller Licence:

Driller Name: E.C. BARRY

Source:

Drill Start Date:

Drill Finish Date: 05/04/1977

Log File Date:

Pump Type: WINDMI

PCW Received Date: Pipe Discharge Size: Estimated Yield:

Casing Size: Depth Well:

Depth Water: 80

### New Mexico Office of the State Engineer **POD Reports and Downloads**

Township: 24N

Range: 07W

Sections: 24

NAD27 X:

Y:

Zone:

Search Radius:

County:

Basin:

Number:

Suffix:

Owner Name: (First)

(Last)

Non-Domestic

Domestic • All

Clear Form iWATERS Menu

Help

AVERAGE DEPTH OF WATER REPORT 11/25/2008


Bsn Tws Rng Sec Zone

Y Wells

(Depth Water in Feet)


No Records found, try again






## Elm Ridge Exploration Mine Map


Mines, Mills & Quarries Commodity Groups **Aggregate & Stone Mines Coal Mines Industrial Minerals Mines Industrial Minerals Mills Metal Mines and Mill Concentrate Potash Mines & Refineries** Smelters & Refinery Ops. **Uranium Mines Uranium Mills** Mines, Mills & Quarries Status **Active Mining Active Mining, Active Reclamation** Permanent Closure, Active Reclamation Permanent Closure, Reclaimed Awaiting Bond Release **Temporary Suspension** 











From wellhead to any continuous flowing or significant water course.

From below-grade tanks to any permanent residence, school, church, hospital, etc. NH

Elm Ridge Site Inventory Sheet

۰	Date: 8-20-08 Initials: No Time: Started: 1:55AM Ended: 2:10DM
•	Well Name & Number: LYBROOK FED. 004
•	API#: 3003924894
•	Lease #: <i>NM</i> - 83502
•	Quarter/Quarter: H Section: 24 Township: 24N Range: 7W
•	Lat: N36° 18.0091' Long: W107° 31, 3150' GPS Point ID: Lbf 4
•	Pit Tank #1: Manufacturer:
•	Serial #: NA DOM: NA Size NA bbl
	o If N/A – Dimensions: Diameter 10' Height 4'
•	Material: Steel Galvanized Fiberglass
•	Tank Configuration: Double Wall Single Wall (Buried × or Exposed)
•	Visible Walls: Y N_ <u>'</u> Leak Detection: Y N_ <u>'</u>
•	Contents: Produced Water Condensate Recycled Oil
•	Tank Top Covering: Solid/Cone-topx Netting (Solid_x Fiber)
•	Secondary Containment: Yes X No
•	Fencing around berm: Yes No
	o Fence Type: Cattle Panel Field Fence Barbwire
•	Pit Tank #2: Manufacturer:
•	Pit Tank #2: Manufacturer:
•	Serial #:
•	Serial #: DOM: Sizebbl  o
•	Serial #:
•	Serial #: DOM: Sizebbl  o If N/A - Dimensions: Diameter
•	Serial #:

## BELOW GRADE TANK (BGT) CLOSURE PLAN

#### SITE NAME:

Lybrook Federal 4
Unit Letter H, Section 24, Township 24N, Range 7W
Rio Arriba County, New Mexico
Latitude 36.180091 Longitude -107.313150

#### SUBMITTED TO:

MR. WAYNE PRICE
NEW MEXICO OIL CONSERVATION DIVISION
1220 SOUTH ST. FRANCIS DRIVE
SANTA FE, NEW MEXICO 87505
(505) 476-3490

#### SUBMITTED BY:

Ms. AMY MACKEY
ELM RIDGE EXPLORATION
PO BOX 156
BLOOMFIELD, NEW MEXICO 87413
(505) 632-3476

**MARCH 2009** 

# BELOW GRADE TANK (BGT) CLOSURE PLAN ELM RIDGE EXPLORATION LYBROOK FEDERAL 4 RIO ARRIBA COUNTY, NEW MEXICO

#### **TABLE OF CONTENTS**

INTRODUCTION	1
SCOPE OF CLOSURE ACTIVITIES	1
REPORTING	3

#### Introduction

Elm Ridge Exploration would like to submit a closure plan for the below grade tank (BGT) at the Lybrook Federal 4 well site located in the SE ¼ NE ¼ of Section 24, Township 24N, Range 07W, Rio Arriba County, New Mexico. This closure plan has been prepared in conformance with the closure requirements of 19.15.17.13 NMAC.

#### SCOPE OF CLOSURE ACTIVITIES

The purpose of this closure plan is to provide the details of activities involved in the closure of the BGT at the Lybrook Federal 4 well site. The following scope of closure activities has been designed to meet this objective:

- 1) Elm Ridge Exploration, or a contractor acting on behalf of Elm Ridge Exploration, will close all of the BGTs currently in service within the five (5) years allotted. Elm Ridge Exploration does not operate any BGTs which would qualify to be upgraded or retrofitted; as such they will be closing all their current BGTs and replacing them with above ground storage tanks.
- 2) Elm Ridge Exploration will close BGTs deemed to be an imminent danger to fresh water, public health, or the environment by an earlier date that the division requires as specified in Subsection A of 19.15.17.13 NMAC.
- 3) Elm Ridge Exploration will close any BGT which demonstrates a compromise of integrity before the five (5) years allotted by the division per Paragraph (6) of Subsection I of 19.15.17.11 NMAC.
- 4) Elm Ridge Exploration will close any BGT within 60 days of cessation of the BGTs operation per Subsection A of 19.15.17.13 NMAC.
- 5) No less than 72 hours and no greater than one (1) week prior to BGT removal Elm Ridge Exploration or a contractor acting on behalf of Elm Ridge Exploration will provide written notification to the appropriate division district office as well as a schedule of on-site activities, as in accordance with 19.15.17.13 Subsection J Paragraph (2) NMAC. Written notification will include the name of the well operator, the well's API number, the well's name and number, and the well's unit letter, section, township and range.
- 6) No less than 24 hours and no greater than one (1) week prior to beginning BGT closure activities Elm Ridge Exploration or a contractor acting on behalf of Elm Ridge Exploration will provide written notification to the appropriate surface owner, as in accordance with 19.15.17.13 Subsection J Paragraph (1) NMAC. Elm Ridge Exploration, or a contractor acting on behalf of Elm Ridge Exploration, will notify the surface owner by certified mail, return receipt requested, that the operator plans to close a below-grade tank. The return receipt will be used to ensure that the surface owner has received written notification no less than 24 hours and no greater than one (1) week prior to the beginning of BGT closure activities. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records is sufficient to demonstrate compliance with this requirement. Closure activities that will take place on tribal land will have notifications sent by certified mail, return

receipt requested, to the appropriate tribal office. Elm Ridge Exploration, or a contractor acting on behalf of Elm Ridge Exploration, will notify the Bureau of Land Management (BLM) of closure activates for wells located on federal land per a Sundry Notice, as in accordance with 19.15.17.13 Subsection J Paragraph (1) NMAC. All notices will be sent in such a way that the surface owner received notice at least 24 hours prior to the beginning of closure activities.

11 .

- 7) Elm Ridge Exploration or a contractor acting on behalf of Elm Ridge Exploration will remove all liquids, and/or sludge, if applicable, prior to closure. Material will be disposed of at Envirotech's Landfarm #2, Permit # NM-01-0011, TNT Environmental Inc. Landfarm, Permit # NM-01-0008, Industrial Ecosystems Inc. (IEI) Landfarm, permit # NM-01-0010B or Basin Disposal, Permit # NM-01-0005, depending on the consistence of the material removed, as in accordance with 19.15.17.13 Subsection E Paragraph (1) NMAC.
- 8) Elm Ridge Exploration or a contractor acting on behalf of Elm Ridge Exploration will remove all on-site equipment associated with this BGT that is no longer required for some other purpose, as in accordance with 19.15.17.13 Subsection E Paragraphs (3) NMAC.
- 9) If applicable, any liners or leak detection systems removed from a BGT closure will be cleaned off and disposed of at San Juan County Regional Landfill in accordance with Subparagraph (m) of Paragraph (1) of Subsection D of 19.15.9.712 NMAC.
- 10) Elm Ridge Exploration or a contractor acting on behalf of Elm Ridge Exploration will obtain prior approval from the OCD to dispose, recycle, reuse or reclaim the BGT. Elm Ridge Exploration or a contractor acting on behalf of Elm Ridge Exploration will provide the OCD with documentation concerning the final disposition of the BGT with the closure report.
- 11) Once the BGT is removed a five (5) point composite sample will be collected from directly below the tank or below the leak detection system if present. Grab samples will be collected from any areas that are wet, discolored, or showing other evidence of a release. All samples being collected will be analyzed for benzene and total BTEX via USEPA Method 8021B, TPH via USEPA Method 418.1, and chlorides via USEPA 300.1, as in accordance with 19.15.17.13 Subsection E Paragraph (4) NMAC.
- 12) Depending on soil sample results the area will be either backfilled or the area will be excavated.
  - a. If soil samples do not exceed the regulatory standards of 0.2 mg/kg benzene, 50 mg/kg BTEX, 100 mg/kg TPH, and 250 mg/kg or background concentration of chlorides, as in accordance with 19.15.17.13 Subsection E Paragraph (4) NMAC.
    - i. Elm Ridge Exploration or a contractor acting on behalf of Elm Ridge Exploration shall submit a Form C-141 with the laboratory results so that the division may review the results to determine if additional delineation is required in accordance with Paragraph (5) of Subsection E of 19.15.17.13 NMAC.
    - ii. Elm Ridge Exploration or a contractor acting on behalf of Elm Ridge Exploration will backfill the excavation or impacted area with non-waste containing, earthen material, in accordance with 19.15.17.13

Subsection E Paragraph (6) NMAC. A soil cover shall be installed for all backfilled excavations consisting of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater in accordance with Subsections H of 19.15.17.13 NMAC. The operator shall construct the soil cover to the site's existing grade and prevent ponding of water and erosion of the cover material.

- iii. All areas of the well site that are no longer utilized on a day to day basis for the production of oil and/or gas, Elm Ridge Exploration or a contractor acting on behalf of Elm Ridge Exploration will substantially restore, re-contour and re-vegetate the areas, in accordance with 19.15.17.13 Subsections G and I NMAC. The operator shall notify the division when it has been re-seeded and when it has achieved successful re-vegetation. For re-vegetation methods, please see attached re-vegetation plan.
- b. If soil samples exceed the regulatory standards stated above.
  - i. Elm Ridge Exploration will submit a Release Notification by Form C-141 with the appropriate analytical laboratory results to the appropriate division district office, in accordance with 19.15.17.13 Subsection E Paragraph (4) NMAC.
  - ii. In accordance with Paragraph (5) of Subsection E of 19.15.17.13 NMAC, once the operator or the OCD has determined that a release has occurred, Elm Ridge Exploration or a contractor acting on behalf of Elm Ridge Exploration will comply with rule 19.15.3.116 NMAC and 19.15.1.19 NMAC as appropriate.

#### REPORTING

Elm Ridge Exploration will submit a closure report within 60 days following the BGT closure and will consist of a form C-144 with all supporting data, and a form C-141 with all supporting data. The supporting data will include proof of closure notice to the surface owner and the OCD, confirmation sampling analytical results, a site diagram, soil backfilling and cover installation, and re-vegetation rates, re-seeding techniques and site reclamation photo documentation if applicable, along with all other information related to the onsite activities.

We appreciate the opportunity to be of service. If you have any questions or require further information, please do not hesitate to contact our office at (505) 632-3476 Ext. 201.

Respectfully Submitted:

Elm Ridge Exploration

Amy Mackey

Elm Ridge Exploration

#### **Elm Ridge Exploration**

1.6

#### **Re-Seeding Techniques and Seed Mixture Ratios**

These applied practices by Elm Ridge Exploration will at a minimum comply with the New Mexico Oil Conservation Divisions rule 19.15.17.13, Subsection I NMAC. Elm Ridge Exploration has adopted these re-seeding application techniques, ratios and mixtures as their standard operating procedures.

- 1. The first growing season after closure of a below grade tank or pit, all areas of the well site not utilized for the production of oil and/or gas on a daily basis will be re-seeded with the specified seed mixture.
- 2. The seed mixture used will be certified with no primary or secondary noxious weeds in seed mixtures. The seed labels from each bag shall be available for inspection while seed is being sown.
- 3. The operator shall accomplish seeding by drilling on the contour whenever practical or by other division-approved methods. The operator shall obtain vegetative cover that equals 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.
- 4. Hand seeding with hydro-mulch, excelsior netting or mulch with netting is required on the cut/fill slopes. Mulch will be spread at a rate of 2,000-3,000 pounds per acre.
- 5. Compacted areas determined by visual inspection will be shall be ripped to a depth of 12 inches below ground surface and disked to a depth of six (6) inches before seeding. Seeding shall be done with a disk type drill with two (2) boxes for various seed sizes. The drill rows shall be eight (8) to ten (10) inches apart. Seed shall be planted at no less than one-half (1/2) inch deep or more than one (1) inch deep. The seeder shall be followed with a drag, packer, or roller to ensure uniform coverage of the seed and adequate compaction. Drilling shall be done on the contour where possible, but not up and down the slope.
- 6. Where slopes are too steep for contour drilling a hand seeder shall be used. Seed shall be covered to the depth stated above by whatever means is practical. If the seed is unable to be covered by the means listed above, the prescribed seed mixture amount will be doubled.
- 7. Elm Ridge Exploration shall repeat seeding or planting until it successfully achieves the required vegetative cover of 70% of the native perennial vegetation cover.

8. Upon abandonment of a well site, if the retention of the access road is not considered necessary for the management and multiple uses of the natural resources, or by the surface owner, it will be ripped a minimum of 12 inches in depth. After ripping, water bars will be installed. All ripped surfaces are to be protected from vehicular travel by construction of a dead end ditch and earthen barricade at the entrance to these ripped areas. Re-seeding of areas affected by the ditch and barriers will be re-seeded if necessary.

. . .

9. Elm Ridge Exploration, or a contractor acting on behalf of Elm Ridge Exploration, will inform the division once successful re-vegetation has occurred.

#### **Elm Ridge Exploration**

#### San Juan Basin

#### **Below Grade Tank Maintenance and Operating Plan**

In accordance with Rule 19.15.17 the following information describes the operation and maintenance of a Below Grade Tank (BGT) on Elm Ridge Exploration locations. Elm Ridge Exploration will close this BGT within five (5) years, or upon failure of integrity, and replacing it with an above ground storage tank.

#### **GENERAL PLAN:**

. . .


- Elm Ridge Exploration, or a contractor representing Elm Ridge Exploration, will operate
  and maintain a BGT to contain liquids and solids to prevent contamination of fresh
  water and to protect public health and environment. This will be accomplished by
  performing monthly inspections of the BGT, any liners or leak detection if applicable,
  netting, secondary containment, fencing and maintaining adequate freeboard.
- 2. Elm Ridge Exploration, or a contractor representing Elm Ridge Exploration, shall not allow a BGT to overflow or allow surface water run-on to enter the BGT. This will be accomplished by a secondary containment consisting of a soil berm around the BGT that will be monitored by monthly inspections. Overflowing will be prevented by maintaining an adequate freeboard of eight (8) inches, maintained by monthly inspections. This process will be performed on the current BGT located at this well site.
- 3. Elm Ridge Exploration, or a contractor representing Elm Ridge Exploration, shall continuously remove any visible or measurable layer of oil from the fluid surface of a BGT in an effort to prevent the accumulation of oil over time.
- 4. Elm Ridge Exploration, or a contractor representing Elm Ridge Exploration, shall inspect the BGT at least once monthly and maintain a written record of each inspection for at least five (5) years. The monthly inspection form to be used by Elm Ridge Exploration is attached to this document.
- 5. Elm Ridge Exploration, or a contractor representing Elm Ridge Exploration, shall maintain adequate freeboard to prevent overtopping of the BGT. The standard freeboard to be maintained by Elm Ridge Exploration is eight (8) inches.

- 6. Elm Ridge Exploration, or a contractor representing Elm Ridge Exploration, shall maintain an expanded metal covering on the BGT.
- 7. Elm Ridge Exploration will not discharge into or store any hazardous wastes into the BGT.
- 8. If Elm Ridge Exploration, or a contractor representing Elm Ridge Exploration, determines that a BGT has developed a leak below the liquid's surface, then Elm Ridge Exploration, or a contractor representing Elm Ridge Exploration, will notify the appropriate division office within 48 hours of discovering the leak. Elm Ridge Exploration, or a contractor representing Elm Ridge Exploration, shall remove all liquids above the damage or leak line within 48 hours in accordance with Subsection A of 19.15.17.12 NMAC. The damaged tank will then be removed, and closure activities will begin in accordance with the submitted closure plan.
- 9. Elm Ridge Exploration will close any BGT within 60 days of cessation of the BGTs operation per Subsection A of 19.15.17.13 NMAC.
- 10. Elm Ridge Exploration, or a contractor representing Elm Ridge Exploration, will close the BGT within the NMOCD allotted five (5) years, within 60 days of cessation of operation of the BGT or upon failure of integrity, and put into service an above ground storage tank to meet the needs previously fulfilled by the BGT.

Figure A, Site Map

. . .

Attachment 1, Monthly BGT Inspection Form





PRO	JECT NO	03056-	0135			
			REVISIONS			
TLM						
NO.	DATE	BY	DESCRIPTION			
			100 (100 (100 (100 100 100 100 100 100 1			

5796 U.S. HIGHWAY 64, FARMINGTON, NM 87410 505-632-0615

### Elm Ridge Exploration, LLC

#### Monthly Below Grade Tank Inspection Form

Inspection Performed By:				Date:			
	Well Site	Name:					
Unit:	_ Section:	Township:	Range	:	County	/:	
	Quarter	Footage:					
	Latitude:		Longitude:_				
Below Grade T	ank						
Construction Mater	rial of BGT (circ	le one): Steel	Fiberglass Gal	lvanized	Other:		
Tank Capacity (BB	LS):						
Status of Tank (circ	ele one): N	A poor	fair good	excel	lent		
Leaks Detected (cir	cle one):	Yes No	Unknow	n			
Liquid level in tank	from the top: _						
Recent overflow de	tected (circle on	e): Yes	No Unkno	own			
BGT Cover present	:: Yes	No NA					
Cover Type (circle	one): wire	mesh steel	mesh fibrou	s netting	other:		
Berm Present (circl	e one):	Yes No	0				
Secondary Con	tainment						
Type of secondary	containment:			_			
Status of secondary	containment (ci	rcle one):	NA poor	fair	good	excellent	
Fencing							
Fencing Present (ci	rcle one):	Yes No					
Describe Fencing:							
Status of Fencing (	circle one):	NA poor	fair goo	od exc	cellent		

<sup>\*</sup>Maintain this document on record for a minimum of five (5) years from the date performed.

# OCD Aztec District III ELM RIDGE Checklist Below Grade Tank Closure Plans

19.15.17.9 Permit application
Signed C-144 (Page 5 of C-144)
Site Specific Hydrogeology (Iwaters)
19,15.17.10 Siting requirements
Proximity to watercourses (Topo map)
Proximity to Permanent Structure (Aerial Map)
Proximity to Flood Plain Map (Aerial Map)
Proximity to Subsurface Mines Map (Aerial Map)
19.15.17.13 Closure Plan
Below Grade Tank Closure Plan
19.15.17.12 Operating and Maintenance Plan
Below Grade Tank Operating and Maintenance Plan
Requirements: (Application Marked Closure Plan Only
The arrest of the state of the
Registration Date: VF CS
registration pate.