Form C-144 Revised April 3, 2017

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration NMOCD
Permit of a pit or proposed alternative method
Closure of a pit, below-grade tank, or proposed alternative method
Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below grade tank, or proposed alternative method
• •
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: NEBU 054
API Number: 3004510115 OCD Permit Number:
Center of Proposed Design: Latitude 36.855525 Longitude -107.570950 NAD83
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: ☐ Drilling ☐ Workover ☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management ☐ Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined ☐ Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other ☐ String-Reinforced ☐ Volume: bbl Dimensions: ☐ x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A
Volume: 10 bbl Type of fluid: Produced Water
Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ■ Other Single wall/ Double bottom; sidewalls not visible
Liner type: Thickness mil HDPE PVC Other
Elliet type. Thickness Illii Tibi E Tive Other
4. Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
5.
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)
Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
8. Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: □ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. □ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NM Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the document attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15 and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	nmac 5.17.9 NMAC
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the document attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
######################################	aocuments are
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
Alternative Proposed Closure Method:	
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	rce material are Please refer to
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beling the Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
e-mail address:	the closure report.
e-mail address: Telephone:	the closure report.

his closure report is true, accurate and complete to the best of my knowledge and
ure requirements and conditions specified in the approved closure plan.
Title: Field Environmental Coordinator
Date: June 25, 2018
Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

NEBU 054

API No. 3004510115

Unit Letter H Section 33 T 31N R 07W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	10 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.019
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.075
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	< 50
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

- Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.
 - The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.
- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-141

Revised April 3, 2017

			Rele	ease Notific	catio	n and Co	rrective A	ction	1			
						OPERA	ГOR		Initi	al Report		Final Report
				tion Company			Garifalos	70.40				
Facility Na			ırmıngto	n, NM 87401			No. (832) 609 e : Natural G					
Surface Ow				Mineral C		Federal	T T T C T C T C T C T C T C T C T C T C			.300451	0115	
Surface Ow	ner. Fedi	erar		•					AFINO	.300431	0113)
Unit Letter	Section	Township	Range	LOCA Feet from the		N OF REI	Feet from the	Foot/	West Line	County		
H	33	31N		2,580	Non		1,135	East		County	San	Juan
1 1	00	OTIV						La	<u></u>		<i>-</i>	oddii
			Latitud	_e 36.855525	L	ongitude	07.570950	NAD	83			
				NAT	URE	OF RELI	EASE					
Type of Rele	ase:: none)					Release: unknown			Recovered::		
Source of Re	belo	w grade ta	nk - 10	obl		n/a		Je:	n/a	Hour of Dis	covery.	
Was Immedia	ate Notice (Vec 7	No Not Re	anired	If YES, To	Whom?					
By Whom?			105	NO LI NOUNC	equired	Date and H	lour					
Was a Water	course Read						lume Impacting t	the Wat	ercourse.			
			Yes ✓									
If a Watercou	irse was Im	pacted, Descr	ibe Fully.*									
Describe Cau	ise of Proble	em and Remed	dial Action	Taken.*	olina (of the soil	beneath the	RGT	was do	no durin	a ron	noval
					_		d for Chloric				0	
							ield reports					
Describe Are	a Affected :	and Cleanup A	Action Tak	en.*					, .			
						cessary. F on is requi	inal laborate	ory a	naiysis d	determin	ed no	
				remedia	actic	il is requi	ireu.					
I hereby certi	fy that the i	information gi	ven above	is true and comp	lete to t	he best of my	knowledge and u	ındersta	nd that purs	suant to NM	OCD ru	iles and
regulations a	l operators	are required to	report an	d/or file certain re	elease n	otifications ar	nd perform correct	ctive act	ions for rele	eases which	may en	danger
				e of a C-141 repo investigate and re								
or the environ	nment. In a		CD accep	tance of a C-141								
					T		OIL CON	SERV	ATION	DIVISIO	N	
l	run a	Wilhalo	4									
Signature:	0					Approved by	Environmental S	pecialis	t:			
Signature:	Erin G	arifalos				11						
		onmenta		dinator		Approval Date	e:		Expiration 1	Date:		
		garifalos				Conditions of			piration			
						Conditions 01	Apploval:			Attached		
Date: June	20, 2018)	Phone:	(832) 609-70	140							

^{*} Attach Additional Sheets If Necessary

bp



BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

May 7, 2018

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: NORTHEAST BLANCO UNIT 054 API# - 3004510115

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 10, 2018. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From:

Buckley, Farrah (CH2M HILL)

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa, Fields@state.nm.us)

Cc: Subject: jeffcblagq@aol.com; blagq_njv@yahoo.com; Garifalos, Erin BP Pit Close Notification - NORTHEAST BLANCO UNIT 054

Date:

Monday, May 07, 2018 2:56:52 PM

BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

May 7, 2018

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

NORTHEAST BLANCO UNIT 054 API# 30-45-10115 (H) Section 33 – T31N – R07W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around May 10, 2018.

Should you have any questions, please feel free to contact BP at our Durango office.

Sincerely,

Erin Garifalos

 $Field\ Environmental\ Coordinator-San\ Juan$

Cell: 832-609-7048

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	P. 31N RING 7W PM. NM CNTY. RA ST. NM 135'E SE/NE LEASE TYPE FEDERAL STATE (FEE / INDIAN STRIKE PROD, FORMATION: MV CONTRACTOR BP - J. GONZALES STRIKE PROD, FORMATION: MV CONTRACTOR BP - J. GONZALES STRIKE SPECIALIST(S): NJV TI: WELL HEAD (WH) GPS COORD. 36.855525 X 107.570995 GPS COORD. GP	TANK ID A	
FIELD REPORT:		/ OTHER:	
SITE INFORMATION QUAD/UNIT: H SEC: 33 TWP:	31N RNG: 7W PM: NM CNTY: RAB5'E SE/NE LEASE TYPE: FEDERAL/STAT	E / FEE / INDIAN	DATE FINISHED: ENVIRONMENTAL
	PROD. FORMATION: MV CONTRACTOR: BP-J. (GONZALES	
1)10 BGT (SW/DB)3)	GPS COORD.: 36.855525 X 107.57095 GPS COORD.: GPS COORD.:	DISTANCE/BEA DISTANCE/BEA DISTANCE/BEA	RING FROM W.H.: 38', S21E RING FROM W.H.:
SAMPLING DATA: 1) SAMPLE ID: 5PC - TB @ 3.5 2) SAMPLE ID: 4) SAMPLE ID: 5) SAMPLE ID: 5	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: (10) SAMPLE DATE: 05/10/18 SAMPLE TIME: 1330 SAMPLE DATE: SAMPLE TIME: SAMPLE	LAB ANALYSIS: 80° LAB ANALYSIS: LAB ANALYSIS: LAB ANALYSIS: LAB ANALYSIS: LAB ANALYSIS:	OVM READING (ppm) NA
SOIL COLOR: COHESION (ALL OTHERS): NON COHESIVE (SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LO MOISTURE: DRY (SLIGHTLY MOIST) MOIST / W. SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED: YES NOT BELEASE OBSERVED: APPARENT EVIDENCE OF A RELEASE OBSERVED EQUIPMENT SET OVER RECLAIMED AREA:	BP BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-11199 Control one Bet Confernation Release incess cannot Other Control one Release Re		
SITE SKETCH BERM 95 BGT - FE NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	BGT Located: off on site PLOT PLAN W.H. PBGTL T.B. ~ 3.5' B.G. NCE BERM PENCE PENCE SEPARATOR NDEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~ = APPRO	circle: attached OMM TIME W R V P P OX.; WH. = WELL HEAD;	CALIB. READ. = NA ppm CALIB. GAS = NA ppm CALI
APPLICABLE OR NOT AVAILABLE; SW - SINGLI	WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM.	<u>IV</u>	lagnetic declination: 10 E

revised: 11/26/13 BEI1005E-6.SKF

Analytical Report

Lab Order 1805628

Date Reported: 5/14/2018

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 3.5' (10)

Project: NEBU 54

Collection Date: 5/10/2018 1:30:00 PM

Lab ID: 1805628-001

Matrix: SOIL

Received Date: 5/11/2018 7:00:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	MRA
Chloride	ND	30	mg/Kg	20	5/11/2018 11:02:30 AM	38068
EPA METHOD 8015M/D: DIESEL RANGE	ORGANICS				Analyst	Irm
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	5/11/2018 10:49:33 AM	38064
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	5/11/2018 10:49:33 AM	38064
Surr: DNOP	96.6	70-130	%Rec	1	5/11/2018 10:49:33 AM	38064
EPA METHOD 8015D: GASOLINE RANG	E				Analyst	NSB
Gasoline Range Organics (GRO)	ND	3.8	mg/Kg	1	5/11/2018 9:36:53 AM	38051
Surr: BFB	90.1	15-316	%Rec	1	5/11/2018 9:36:53 AM	38051
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.019	mg/Kg	1	5/11/2018 9:36:53 AM	38051
Toluene	ND	0.038	mg/Kg	1	5/11/2018 9:36:53 AM	38051
Ethylbenzene	ND	0.038	mg/Kg	1	5/11/2018 9:36:53 AM	38051
Xylenes, Total	ND	0.075	mg/Kg	1	5/11/2018 9:36:53 AM	38051
Surr: 4-Bromofluorobenzene	112	80-120	%Rec	1	5/11/2018 9:36:53 AM	38051

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

С	hain-	-of-Cu	stody Record	Turn-Around	Time:	KAINE				ш	AI		EN1	/T F	20	BIR	ME	BIT	CAI		
Client: (BLAGE	s ene	or. 189 AMERICA	☐ Standard		SAME				A	NA	LY	SI	S L	A	30				Y,	
Mailing	Address	P.0	. 80× 87	NE	EBU	# 54		490	01 H:				nviror				7109				
) 632-1199	Project #:							5-397			505				,			
Phone #	# :	1505	1 632-1199									Ana	lysis	Req	ues	t					
email or	r Fax#:			Project Mana	ger:			ly)	0				(4)								
QA/QC F			□ Level 4 (Full Validation)		GARAFA		₩B≒5 (8021)	TPH (Gas only)	RO / MRO)			SIMS)	PO ₄ ,SC	PCB's			CHLOS 100E			Composite	
Accredi	tation			Sampler: N	suson VE	LEZ gus	整	H	/ DRO	=		ő	Q	082			3			5 =	_
□ NEL	AP	□ Othe	r	On Ice:	X Yes ∴	□ No	17	+	2	18.		8270	3,5	3/8		F	3			8 2	5
□ EDD	(Type)			Sample Tem	perature:	190		BE	(6	4 pc	2d 5	O or	N.	ide	8	-40	V			3	5
Date	Time	Matrix	Sample Request ID	neather	Preservative Type	HEAL NO.	BTEX+MTB	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method	PAH'S (8310 or	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHAT	25		S PT. ComPos	
8/16/18	1330	SOIL	5PC-TB@3.5 (10)	4021	CooL	-001	V		1								\checkmark			\langle	
							-			-	+		-						_	+	_
								_	-	+	+	+	+	-	_				-	+	_
							-		-	-	+	+	+	-				\vdash	\dashv	+	_
							+			-	+	+	+	-				\vdash	\dashv	+	
										+	+	+	+	-		_	7			+	
																				_	
											_			\perp						\perp	
Date:	Time:	Relinquish	land	Received by:	lat 1	Date Time 5/10/18 1640	Rer	nark: حن ز	S: B	ich oci	8 F VH_7	eri Kar	105 2 6 1 5 V	TL RR 11	ドイ	, LQ	5/1	/a.se	se l	Hrxo	hi
7/10/18	1811		Wilt Wilt	CU	n	205/11/18		REI	F. 6	# :	P	- 1	00	3							

Hall Environmental Analysis Laboratory, Inc.

WO#: 1805628 14-May-18

Client:

Blagg Engineering

Project:

NEBU 54

Sample ID MB-38068

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

Prep Date:

PBS

Batch ID: 38068 Analysis Date: 5/11/2018 RunNo: 51214

SeqNo: 1664864

Units: mg/Kg HighLimit

%RPD **RPDLimit**

Qual

Analyte Chloride

Client ID:

Prep Date:

Result **PQL** ND 1.5

LCSS

5/11/2018

5/11/2018

SampType: Ics

TestCode: EPA Method 300.0: Anions

SPK value SPK Ref Val %REC LowLimit

Sample ID LCS-38068

Batch ID: 38068 Analysis Date: 5/11/2018

RunNo: 51214

SeqNo: 1664865

Units: mg/Kg

%RPD

Qual

Chloride

15.00

SPK value SPK Ref Val %REC

0

94.2

90

Analyte

14

1.5

HighLimit

110

RPDLimit

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Holding times for preparation or analysis exceeded H

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

Е Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH Not In Range

RL Reporting Detection Limit

Sample container temperature is out of limit as specified

Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1805628

14-May-18

Client:

Blagg Engineering

Project:

NEBU 54

Sample ID LCS-38064	SampT	ype: LC	S	Tes	TestCode: EPA Method 8015M/D: Diesel Range Organics							
Client ID: LCSS	Batch	1D: 38	064	RunNo: 51216								
Prep Date: 5/11/2018	ep Date: 5/11/2018 Analysis Date: 5/11/2018 SeqNo: 1664533 Units: mg/Kg											
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range Organics (DRO)	50	10	50.00	0	99.7	70	130					
Surr: DNOP	4.9		5.000		97.2	70	130					
Sample ID MB-38064	SampT	уре: МЕ	BLK	Tes	Code: E	PA Method	8015M/D: Die	esel Rang	e Organics			
Client ID: PBS	Batch	ID: 38	064	F	unNo: 5	1216						

Client ID: PBS	Batch	ID: 38	064	F	RunNo: 5	1216					
Prep Date: 5/11/2018	Analysis D	Analysis Date: 5/11/2018 SeqNo: 1664534				664534	Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Diesel Range Organics (DRO)	ND	10									
Motor Oil Range Organics (MRO)	ND	50									
Surr: DNOP	9.1		10.00		90.9	70	130				

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 3 of 5

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

Page 4 of 5

1805628

14-May-18

Client:

Blagg Engineering

Project: NEBU 54	4						
Sample ID MB-38051	SampType: MBLK	TestCode: EPA Method 8015D: Gasoline Range					
Client ID: PBS	Batch ID: 38051	RunNo: 51207					
Prep Date: 5/10/2018	Analysis Date: 5/11/2018	SeqNo: 1664656	Units: mg/Kg				
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual			
Gasoline Range Organics (GRO)	ND 5.0						
Surr: BFB	900 1000	89.8 15	316				
Sample ID LCS-38051	SampType: LCS TestCode: EPA Method 8015D: Gasoline Range						
Client ID: LCSS	Batch ID: 38051	RunNo: 51207					
Prep Date: 5/10/2018	Analysis Date: 5/11/2018	Units: mg/Kg					
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual			
Gasoline Range Organics (GRO)	26 5.0 25.00	0 104 75.9	131				
Surr: BFB	1100 1000	109 15	316				
Sample ID RB	SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range						
Client ID: PBS	Batch ID: G51207 RunNo: 51207						
Prep Date:	Analysis Date: 5/11/2018	SeqNo: 1664680	Units: %Rec				
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual			
Surr: BFB	920 1000	91.5 15	316				
Sample ID 2.5UG GRO LCS	SampType: LCS TestCode: EPA Method 8015D: Gasoline Range						
Client ID: LCSS	Batch ID: G51207	RunNo: 51207					
Prep Date:	Analysis Date: 5/11/2018	SeqNo: 1664681	Units: %Rec				
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual			
Surr: BFB	1000 1000	105 15	316				

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix

Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

В Analyte detected in the associated Method Blank

Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH Not In Range

RL Reporting Detection Limit

Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1805628

14-May-18

Client:

Blagg Engineering

Project:

NEBU 54

Sample ID MB-38051	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batch ID: 38051		RunNo: 51207							
Prep Date: 5/10/2018	Analysis Date: 5/11/2018			SeqNo: 1664717			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.1		1.000		110	80	120			

Sample ID LCS-38051	SampT	ype: LC	s	Tes						
Client ID: LCSS	Batcl	n ID: 38	051	RunNo: 51207						
Prep Date: 5/10/2018	Analysis D	ate: 5/	11/2018	8	SeqNo: 1	664718	Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.95	0.025	1.000	0	95.1	77.3	128			
Toluene	0.98	0.050	1.000	0	98.2	79.2	125			
Ethylbenzene	0.97	0.050	1.000	0	96.8	80.7	127			
Xylenes, Total	3.0	0.10	3.000	0	98.9	81.6	129			
Surr: 4-Bromofluorobenzene	1.1		1.000		110	80	120			

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits

Page 5 of 5

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Ord	er Number: 180	5628		RcptNo	: 1
Received By: Anne Thorn	ne 5/11/2018 7	:00:00 AM		anne Am		
Completed By: Anne Thorn	ne 5/11/2018 7	:07:33 AM		anne An		
Reviewed By 30 Labeled by: A	05/11/18					
Chain of Custody			*			
1. Is Chain of Custody comple	te?	Yes	~	No 🗆	Not Present	
2. How was the sample delive	red?	Cou	rier ·			
Log In						
3. Was an attempt made to co	ol the samples?	Yes	✓.	No 🗆	NA 🗆	
4. Were all samples received a	at a temperature of >0° C to 6.	0°C Yes	✓	No 🗆	NA 🗆	
5. Sample(s) in proper contain	er(s)?	Yes	✓.	No 🗆		
6. Sufficient sample volume for	indicated test(s)?	Yes	✓	No 🗌		
7. Are samples (except VOA ar		Yes	V	No 🗆		
8. Was preservative added to b		Yes		No 🗹	NA 🗆	
VOA vials have zero headsp	ace?	Yes		No 🗌	No VOA Vials ✓	
10. Were any sample containers		Yes		No 🗹		
11. Does paperwork match bottle		Yes	✓	No 🗆	# of preserved bottles checked for pH:	
(Note discrepancies on chair		165		110		>12 unless noted)
12. Are matrices correctly identif	ied on Chain of Custody?	Yes	\checkmark	No 🗌	Adjusted?	
13. Is it clear what analyses were		Yes	\checkmark	No 🗌		
 Were all holding times able t (If no, notify customer for aut 		Yes	~	No 🗆	Checked by:	
Special Handling (if appli	*					
15. Was client notified of all disc	crepancies with this order?	Yes		No 🗀 .	NA 🗹	-
Person Notified:		Date				
By Whom:		Via: eM	ail Pho	one Fax	☐ In Person	
Regarding: Client Instructions:		er skilde Frak som en men skilde Fra januar sp. sp.		The second second	The same distance with the same same and	
	1 100 100 100 100 100 100 100 100 100 1	<i>A</i>				
16. Additional remarks:						
17. Cooler Information					* = *	
	Condition Seal Intact Sea Good Yes	No Seel D	are S	ligned By		
Lu						



