District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Proposed Alternative Method Permit or Closure Plan Application
Type of action:  Below grade tank registration  Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method  Modification to an existing permit/or registration  Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the nvironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: BOLACK D 001
API Number:         3004523429         OCD Permit Number:
Center of Proposed Design: Latitude 36.865180 Longitude -107.764273 NAD83
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Pit:       Subsection F, G or J of 19.15.17.11 NMAC         Temporary:       Drilling       Workover         Permanent       Emergency       Cavitation       P&A       Multi-Well Fluid Management       Low Chloride Drilling Fluid       yes       no         Lined       Unlined       Liner type:       Thickness       mil       LLDPE       HDPE       PVC       Other         String-Reinforced         Liner Seams:       Welded       Factory       Other       Volume:       bbl       Dimensions:       L       x W       x D
Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A  Volume: 95
Secondary containment with leak detection   Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off  Visible sidewalls and liner   Visible sidewalls only   Other   Single wall/ Double bottom; sidewalls not visible  Liner type: Thickness   mil   HDPE   PVC   Other
4.  Alternative Method:  Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

23

Alternate. Please specify

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC  12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  Signed in compliance with 19.15.16.8 NMAC	
Nation State Stat	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	eptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. ( <b>Does not apply to below grade tanks</b> )  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NI Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.  Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 15.17.9 NMAC
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Previously Approved Design (attach copy of design) API Number:  or Permit Number:	15.17.9 NMAC

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Climatological Factors Assessment  Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H₂S, Prevention Plan  Emergency Response Plan  Oil Field Waste Stream Characterization  Monitoring and Inspection Plan  Erosion Control Plan  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
<u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative  Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	attached to the
closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No

<ul> <li>adopted pursuant to NMSA 1978, Section 3-27-3, as amended.</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul>	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plans a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC 15.17.11 NMAC
Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe the certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe the certification.  Title:	
e-mail address: Date:  Telephone:	
e-mail address:  Telephone:  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature:  Approval Date:	312018
e-mail address: Telephone:  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	312018
e-mail address:  Telephone:  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature:  Approval Date:	
e-mail address:    Telephone:	t complete this

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with the belief. I also certify that the closure complies with all applicable closure.	is closure report is true, accurate and complete to the best of my knowledge and re requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Signature:UTIN SUTIFIALOS-	Date: June 25, 2018
e-mail address: erin.garifalos@bpx.com	Telephone: (832) 609-7048

## BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

#### **BOLACK D 001**

API No. 3004523429

Unit Letter O Section 27 T 31N R 09W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

## General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

#### Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

#### Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

# All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

## The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

## All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.018
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.073
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	< 50
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

#### C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

- 14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.
  - The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.
- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141

Revised April 3, 2017

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

			Rele	ease Notific	cation	and Co	orrective A	ction	1			
						OPERA'	ΓOR		Initi	al Report		Final Report
				tion Compan			n Garifalos	7040				
Facility Na			irmingto	n, NM 87401			No. (832) 609 De : Natural G		ell			
Surface Ow				Mineral (						.300452	2420	
Surface Ow	ner. Feur	erar							AFTING	.300432	3429	
Unit Letter	Section	Township	Range	LOCA Feet from the		South Line	Feet from the	Foot/	West Line	County		
Ont Letter	27	31N		1,120	Sou		1,530	East		County	an	Juan
O	21	OTIV						La			ari	oddii
			Latitud	<sub>e</sub> 36.865180	L	ongitude1	07.764273	NAD	83			
				NAT	URE	OF REL	EASE					
Type of Rele	ase:: none	)					Release:: unkn			Recovered::		
Source of Re	belo	w grade ta	nk - 95	bbl		n/a	Iour of Occurrence	ce:	n/a	Hour of Disc	covery:	
Was Immedia	ate Notice (		Vac 7	No Not R	aguirad	If YES, To	Whom?					
By Whom?			ies v	NO LI NOUN	equired	Date and H	lour					
Was a Water	course Read						olume Impacting	the Wat	ercourse.			
			Yes ✓	No								
If a Watercou	irse was Im	pacted, Descr	ibe Fully.*									
Describe Cau	se of Probl	em and Remed	dial Action	Taken.*	nling	of the soil	bonooth the	PCT	woo de	no durin	a rom	ovol
							beneath the d for Chloric			,		
					-		Field reports					
Describe Are	a Affected	and Cleanup A	Action Tak	en.*			·					
				No actio			inal laborate	ory a	nalysis	determine	ed no	
				remedia	actio	n is requ	irea.					
I haraby aarti	fy that the	information ai	van ahava	is true and some	lata to th	a bast of my	knowledge and u	ndorsto	nd that nur	mont to NMC	OCD mil	lac and
regulations a	l operators	are required to	o report an	d/or file certain r	elease no	otifications ar	nd perform correct	ctive act	ions for rel	eases which r	may end	danger
							arked as "Final R on that pose a thr					
or the environ	nment. In a	ddition, NMO	CD accep				e the operator of					
federal, state,	or local lav	ws and/or regu	ilations.				OIL CON	SFRV	ATION	DIVISIO	N	
1	Tin a	willalo	4				OIL COIN	<u>SLIC v</u>	ATION	DIVISIO	11	
Signature:	0.18	arifalo				Annroyed by	Environmental S	necialis	t·			
Printed Name	Erin G	arifalos				Approved by	Environmental 3	pecialis				
		onmenta		rdinator	1	Approval Dat	e:		Expiration	Date:		
E-mail Addre	ss: erin.	garifalos	@bpx	com		Conditions of	Approval:			Attached		
Date: June	25, 2018	3	Phone:	(832) 609-70	048					7 tttdeffed		
* Attach Addit	ional Shee	ets If Necess	arv									

# bp



BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

May 11, 2018

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

#### VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: BOLACK D 001 API# - 3004523429

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 14, 2018. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From: Buckley, Farrah (CH2M HILL)

To: Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)

Cc: jeffcblagq@aol.com; blagq\_njv@yahoo.com; Garifalos, Erin

Subject: BP Pit Close Notification - BOLACK D 001

Date: Friday, May 11, 2018 10:11:53 AM

BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

# SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

May 11, 2018

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

BOLACK D 001 API# 30-45-23429 (O) Section 27 – T31N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around May 14, 2018.

Should you have any questions, please feel free to contact BP at our Durango office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator - San Juan

Cell: 832-609-7048

# Farrah Buckley BGT Project Support

970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	(circle one): BGT CONFIRMATION] RELEASE INVESTIGATION / OTHER:  PAGE # 1 of  DATE STARTED.  DATE STARTED.  DATE FINISHED.  PAGE # 1 of  DATE FINIS	_										
	(50	5) 632-1199			A							
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTH	HER:	PAGE #: <b>1</b>	of							
SITE INFORMATION	I: SITE NAME: BOLAC	K D #1		DATE STARTED: 05	/14/18							
				DATE FINISHED:								
Annual Control of the			EE / INDIAN									
	NM013685 PROD. FORMATION: PC CONTRACTOR: BP - J. GONZALES											
REFERENCE POINT		-										
1) 95 BGT (SW/DB)	GPS COORD.: <b>36.</b> 0	865180 X 107.764273	DISTANCE/BEAR	RING FROM W.H.: 73.5,	N18E							
2)												
			DISTANCE/BEAR	RING FROM W.H.:	OVM							
SAMPLING DATA:  1) SAMPLE ID: 5PC - TB @ 5'			801	5B/8021B/300.0 (CI)	(ppm)							
	•			obrodz rarodio (ci)	IVA							
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: U										
SAMPLE ID:      SAMPLE ID:												
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLY MOIST/ MOIST/ W	DOSE   FIRM   DENSE / VERY DENSE   ET / SATURATED / SUPER SATURATED   FOR PTS	HC ODOR DETECTED: YES NO EX	XPLANATION -									
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:	LOST INTEGRITY OF EQUIPMENT ED AND/OR OCCURRED: YES NO EXPL YES NO EXPLANATION -	Anation:										
EXCAVATION DIMENSION ESTIMATION:	<b>NA</b> ft. X <b>NA</b>	ft. X NA ft.	EXCAVATION EST	IMATION (Cubic Yards) :	NA							
DEPTH TO GROUNDWATER: >100' N	EAREST WATER SOURCE: >1,000	NEAREST SURFACE WATER:	<1,000' NMOC	D TPH CLOSURE STD: 1	,000 ppm							
SITE SKETCH	BGT Located: off on sit	e PLOT PLAN circle:	: attached OVM	CALIB. READ. = NA	ppm RF =1.00							
			<b>♦</b> ovm	CALIB. GAS = NA								
то			TIME	<b>NA</b> am/pm DATE:	NA							
✓ METER RUN	BG X	FENCE	' [	MISCELL. NO	TES							
		//_	w	O:								
	BERM											
					2							
	SEPARA	ATOR	1 -		2/40							
			Tan	k OVM = Organic Vapor N	Weter							
		X	- S.P.D.	BGT Sidewalls Visible: Y	/ N							
	ON DEPRESSION; B.G. = BELOW GRADE; B = BI	ELOW; T.H. = TEST HOLE; $\sim$ = APPROX.; W.H	H. = WELL HEAD;									
			ALL; NA - NOT M	agnetic declination: 1	0 E							
NOTES: GOOGLE EARTH IMAGI		ONSITE: 05/14/18	3									

### **Analytical Report**

### Lab Order 1805769

Date Reported: 5/18/2018

# Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (95)

Collection Date: 5/14/2018 11:15:00 AM

**Project:** BOLACK D 1 **Lab ID:** 1805769-001

Matrix: SOIL Received Date: 5/15/2018 6:30:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analys	t: MRA
Chloride	ND	30	mg/Kg	20	5/15/2018 10:08:53 AM	A 38115
EPA METHOD 8015M/D: DIESEL RAN	IGE ORGANICS	;			Analys	t: Irm
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	5/15/2018 9:58:47 AM	38113
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	5/15/2018 9:58:47 AM	38113
Surr: DNOP	113	70-130	%Rec	1	5/15/2018 9:58:47 AM	38113
EPA METHOD 8015D: GASOLINE RAI	NGE				Analys	t: NSB
Gasoline Range Organics (GRO)	ND	3.6	mg/Kg	1	5/15/2018 11:33:38 AM	A 38094
Surr: BFB	87.1	15-316	%Rec	1	5/15/2018 11:33:38 AM	1 38094
EPA METHOD 8021B: VOLATILES					Analys	t: NSB
Benzene	ND	0.018	mg/Kg	1	5/15/2018 11:33:38 AM	1 38094
Toluene	ND	0.036	mg/Kg	1	5/15/2018 11:33:38 AM	1 38094
Ethylbenzene	ND	0.036	mg/Kg	1	5/15/2018 11:33:38 AM	1 38094
Xylenes, Total	ND	0.073	mg/Kg	1	5/15/2018 11:33:38 AM	38094
Surr: 4-Bromofluorobenzene	101	80-120	%Rec	1	5/15/2018 11:33:38 AM	1 38094

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

CI	hain-d	of-Cus	stody Record		Turn-Around T	Time:	SAME					IAI		<b>E</b> 1	MX	TE	20	BLE B	ИE	RIT	CAI	
Client:	BLAG	G ENGR.	/ BP AMERICA		☐ Standard	✓ Rush _	DAY	) ;											RA			
					Project Name:							wwv									<b>J</b> N	V 88 5
Mailing Ad	ddress:	P.O. BO	X 87		1	BOLACK D	#1		49	01 H									3 <b>71</b> 09	)		
		BLOOM	FIELD, NM 87413		Project #:						)5-34							-410				
Phone #:		(505) 63	32-1199		1				Н,		7-						lues	-				1
email or F	ax#:				Project Manag	jer:									(1				1)			
QA/QC Pad	_		Level 4 (Full Valida	tion)		ERIN GARI	FALOS	(8021B)	+ TPH (Gas only)	MRO)			5)		O4,SO	PCB's			ar - 300.1)			
Accreditat	ion:		`		Sampler:	NELSON VI	LEZ	38	Gas	RO/	1)	7	SIM		О2,Р	3082			water			mple
□ NELAP	)	□ Other			On Ice:	⊉′Yes	ta No − %		F	0/0	418.	504	3270		03,N	8/8		(A)	0.00		1	e sa
□ EDD (T	уре)				Sample Tempo	erature 4.		1		(GRC	pou	pou	or	etals	CI,N	cide	(A)	i-VC	11-3(		e	osit
Date	Time	Matrix	Sample Reques	st ID	Container Type and # MeiHki	Preservative Type	HEAL NO	BTEX +	BTEX + MTBE	TPH 8015B (GRO / DRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO <sub>3</sub> ,NO <sub>2</sub> ,PO <sub>4</sub> ,SO <sub>4</sub> )	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /		Grab sample	5 pt. composite sample
5/14/18	1115	SOIL	5PC-TB@ 5'	(95)	4 oz 1	Cool	701	٧		٧									٧			٧
																					$\neg$	$\neg$
, ,																					$\neg$	$\neg$
	,						4.														$\neg$	$\neg$
																					$\neg$	$\dashv$
																				_		$\dashv$
		<b></b>						+				$\neg$								+	7	$\dashv$
					<del>                                     </del>			+				$\dashv$	_					$\vdash$		1	$\dashv$	$\dashv$
								+	_			-	+							+	$\dashv$	$\dashv$
								+	$\vdash$			-	-	-			-		$\vdash$	+	$\dashv$	$\dashv$
Date: 5/14/18 Date: 5/14/18	Time: 1751 Time: 1840	Relinquish	hay-		Received by:  Received by:	iheter 5	Pate Time	′ (		ACT: VID:	8 REF ERIN VHIX	GAF	CE#V RIFAL VB2	NHEN LOS /	APP	LICAE	BLE;		VTH.C	ORRE:	SPON	DING
117/18	1070	TUL	the Wall Environmental	may be a	i haantrastad to ather	annudited laboratoria	This serves as nation	of this			ar arch			lota u	ill ha	oloorh	notat	ad an	the one	htical	mnor	

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1805769 18-May-18

Client:

Blagg Engineering

Project:

**BOLACK D1** 

Sample ID MB-38115

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 38115

RunNo: 51286

Prep Date: 5/15/2018 Analysis Date: 5/15/2018

SeqNo: 1668095

HighLimit

Units: mg/Kg

%RPD

Qual

Analyte Chloride

Result PQL ND 1.5

Sample ID LCS-38115

SampType: Ics

TestCode: EPA Method 300.0: Anions

Client ID:

LCSS

Batch ID: 38115

RunNo: 51286

Prep Date: 5/15/2018 Analysis Date: 5/15/2018

SeqNo: 1668096

%REC LowLimit

Units: mg/Kg HighLimit

**RPDLimit** 

Analyte

1.5

0

90

**RPDLimit** 

SPK value SPK Ref Val

SPK value SPK Ref Val

%REC 95.1

Chloride

14

15.00

110

Qual

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Holding times for preparation or analysis exceeded H

ND Not Detected at the Reporting Limit

Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

Value above quantitation range E

J Analyte detected below quantitation limits

P Sample pH Not In Range

Reporting Detection Limit

Sample container temperature is out of limit as specified

Page 2 of 5

# Hall Environmental Analysis Laboratory, Inc.

WO#: **1805769** 

18-May-18

Client:

Blagg Engineering

Project:

BOLACK D 1

Sample ID MB-38113	SampT	ype: M	BLK	Tes	tCode: E	PA Method	8015M/D: Die	esel Rang	e Organics	
Client ID: PBS	Batch	1D: 38	113	F	RunNo: 5	1235				
Prep Date: 5/15/2018	Analysis D	ate: 5/	15/2018	S	SeqNo: 1	667045	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	10		10.00		104	70	130			
Sample ID LCS-38113	SampT	ype: LC	s	Tes	Code: E	PA Method	8015M/D: Die	esel Rang	e Organics	
Client ID: LCSS	Batch	1D: 38	113	F	unNo: 5	1235				
D D 1	A		4 = 10040			007000	11-11			

Client ID: LCSS	Batch	ID: 38	113	F	RunNo: 5	1235				
Prep Date: 5/15/2018	Analysis D	ate: 5/	15/2018	S	SeqNo: 1	667066	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	46	10	50.00	0	92.1	70	130			
Surr: DNOP	5.3		5.000		106	70	130			

#### Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 3 of 5

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

# Hall Environmental Analysis Laboratory, Inc.

26

1100

5.0

25.00

1000

WO#:

1805769

18-May-18

Client:

Gasoline Range Organics (GRO)

Surr: BFB

Blagg Engineering

Project:

BOLACK D 1

Project: BOLAC	LK D I			
Sample ID MB-38094	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Rang	ie .
Client ID: PBS	Batch ID: 38094	RunNo: 51281		
Prep Date: 5/14/2018	Analysis Date: 5/15/2018	SeqNo: 1667276	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Gasoline Range Organics (GRO)	ND 5.0			
Surr: BFB	830 1000	83.2 15	316	
Sample ID LCS-38094	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Rang	е
Client ID: LCSS	Batch ID: 38094	RunNo: 51281		
Prep Date: 5/14/2018	Analysis Date: 5/15/2018	SeqNo: 1667277	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual

0

103

112

75.9

15

131

316

#### Qualifiers:

\* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 4 of 5

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

# Hall Environmental Analysis Laboratory, Inc.

WO#: **1805769** 

18-May-18

Client: Blagg Engineering
Project: BOLACK D 1

Sample ID MB-38094	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batch ID: 38094			RunNo: 51281						
Prep Date: 5/14/2018	Analysis D	)ate: 5/	15/2018	S	SeqNo: 1	667299	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.99		1.000		99.2	80	120			

Sample ID LCS-38094	Sampl	ype: LC	S	Tes	tCode: El	PA Method	8021B: Vola	tiles		
Client ID: LCSS	Batcl	n ID: 38	094	F	RunNo: 5	1281				
Prep Date: 5/14/2018	Analysis D	ate: 5/	15/2018	S	SeqNo: 1	667300	Units: mg/k	ζg		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.94	0.025	1.000	0	94.2	77.3	128			
Toluene	0.97	0.050	1.000	0	97.4	79.2	125			
Ethylbenzene	0.96	0.050	1.000	0	96.4	80.7	127			
Xylenes, Total	3.0	0.10	3.000	0	99.1	81.6	129			
Surr: 4-Bromofluorobenzene	1.0		1 000		104	80	120			

#### Qualifiers:

\* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 5 of 5

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified



#### Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

# Sample Log-In Check List

Client Name: BLAGG	Work Order Number	1805769		RcptNo:	1
Received By: Anne Thor	ne 5/15/2018 6:30:00 AM		anne Am		
Completed By: Anne Thor	ne 5/15/2018 6:49:56 AM		an Am		
Reviewed By: L. Label	led Ly A 05/15/12				***
Chain of Custody					٠,
1. Is Chain of Custody comple	ete?	Yes 🗸	No 🗌	Not Present	
2. How was the sample delive	ered?	Courier			
					(A)
Log In  3. Was an attempt made to co	pol the samples?	Yes 🗸	No 🗌	NA 🗆	
4. Were all samples received a	at a temperature of >0° C to 6.0°C	Yes 🗹	No 🗆	NA 🗆	
5. Sample(s) in proper contain	ner(s)?	Yes 🗹	No .	±	
6. Sufficient sample volume fo	r indicated test(s)?	Yes 🗸	No 🗌		
7. Are samples (except VOA a	nd ONG) properly preserved?	Yes 🗸	No 🗆		
8. Was preservative added to I	bottles?	Yes	No 🗸	NA 🗌	
9. VOA vials have zero headsp	pace?	Yes ·	No 🗆	No VOA Vials	
10. Were any sample container		Yes	No 🗹		
				# of preserved bottles checked	
<ol> <li>Does paperwork match bottl (Note discrepancies on chai</li> </ol>		Yes 🗸	No 🗆	for pH: (<2 or >	12 unless noted)
12. Are matrices correctly identi		Yes 🗸	No 🗌	Adjusted?	
3. Is it clear what analyses wer		Yes 🗸	No 🗌		
14. Were all holding times able		Yes 🗸	No 🗆	Checked by:	
(If no, notify customer for au	thorization.)			e .	
Special Handling (if appl	licable)				
15. Was client notified of all dis	crepancies with this order?	Yes	No 🗌	NA 🗹	
Person Notified:	Date			and the	
By Whom:	Via:	eMail Pho	one 🗌 Fax	In Person	
Regarding:	ACCUSE NO CONTROL CONT				
Client Instructions:	COLUMNOS II. III AMBER AMBORIO III AMBORIO III A III II. II. III III III III III I				•
16. Additional remarks:			120		
17. Cooler Information					
Cooler No Temp °C	Condition   Seal Intact   Seal No   S	eal Date S	igned By		19 N
1 4.5	Good Yes		A 7		
**************************************					



