District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application MOCD
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company Address: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: NEIL A 001
2004527510
API Number: 3004527519 OCD Permit Number:
Center of Proposed Design: Latitude 36.939898 Longitude -108.000011 NAD83
Surface Owner: 🔳 Federal 🗌 State 🗌 Private 🗌 Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management ☐ Low Chloride Drilling Fluid ☐ yes ☐ no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
■ Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A
Volume: 95 bbl Type of fluid: Produced Water
Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ■ Other Single wall/ Double bottom; sidewalls not visible
Liner type: Thicknessmil
4.
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
5.
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital,
institution or church)
Four foot height, four strands of barbed wire evenly spaced between one and four feet

24

Alternate. Please specify

6.							
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)							
Screen Netting Other							
Monthly inspections (If netting or screening is not physically feasible)							
7. Signs: Subsection C of 19.15.17.11 NMAC							
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers							
Signed in compliance with 19.15.16.8 NMAC							
Variances and Exceptions: Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.							
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source						
General siting							
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No						
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells							
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality							
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No						
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No						
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No						
Below Grade Tanks							
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)							
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No						
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No						
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image							
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site									
Temporary Pit Non-low chloride drilling fluid									
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site									
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image									
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Permanent Pit or Multi-Well Fluid Management Pit									
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No								
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No								
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site									
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:									
II.									
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC									

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are						
	documents are						
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit						
Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	Č						
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	attached to the						
waste Excavation and Removal Closure Fian Checkist: (19.13.17.13 NMAC) Instructions: Each of the following thems must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC							
15.							
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.							
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA						
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA						
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA						
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site							
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image							
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site							
Written confirmation or verification from the municipality; Written approval obtained from the municipality ☐ Yes ☐ No							
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	163 110						

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.								
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No							
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division								
Within an unstable area.								
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map								
Within a 100-year floodplain FEMA map Yes [
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC							
Operator Application Certification:								
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe	ef.							
Name (Print):								
Signature: Date:								
Signature: Date: e-mail address: Telephone:								
	810018							
e-mail address: Telephone:	the closure report.							
e-mail address: Telephone:	the closure report.							
e-mail address: Telephone:	the closure report. complete this							

Form C-144 Oil Conservation Division Page 5 of 6

22.	
Operator Closure Certification:	
	with this closure report is true, accurate and complete to the best of my knowledge and le closure requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Signature: UTIN Garifalas	Date: June 25, 2018
e-mail address: erin.garifalos@bpx.com	Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

NEIL A 001

API No. 3004527519

Unit Letter L Section 33 T 32N R 11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.019
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.078
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	< 50
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed when the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised April 3, 2017 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Release Notification and Corrective Action															
						OPERA	ГOR		Initia	al Report		Final Report			
Name of Company BP America Production Company Address 200 Energy Court, Farmington, NM 87401 Contact Erin Garifalos Telephone No. (832) 609-7048															
			rmingto	n, NM 87401		Telephone No. (832) 609-7048									
Facility Name NEIL A 001 Facility Type: Natural Gas Well															
Surface Ow	ner: Fed	eral		Mineral C	wner:	Federal			API No	.300452	7519)			
						OF RE	LEASE								
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the		West Line	County	000	luon			
L	33	32N	11W	2,140	Sou	ıth	910	We	st	5	an	Juan			
			Latitud	e 36.939898	Lo	ongitude -1	08.000011	NAD	83						
						OF RELI									
Type of Rele	ase:: none	9					Release:: unkno	own		Recovered::					
Source of Re	lease: belo	w grade ta	nk - 95	bbl		Date and H	Iour of Occurrence	ce:	Date and n/a	Hour of Disc	covery:				
Was Immedia		Given?				If YES, To	Whom?		11/4						
			Yes 🗸	No Not Re	equired										
By Whom? Was a Watero	Daurea Page	ahad?				Date and H	lour lume Impacting t	the Wet	282211822						
was a water	course Read		Yes 🗸	No		II 1E5, VC	nume impacting t	me wat	ercourse.						
If a Watercou	irse was Im	pacted, Descr	ibe Fully.*	·											
		1	,												
D 11 C	CD 11	I.D.	11 1 4 .1	T 1 4											
Describe Cau	se of Probl	em and Reme	dial Action	Samı Samı	oling c	of the soil	beneath the	BGT	was do	ne during	g ren	noval.			
				Soil	nalys	is resulte	d for Chloric	des, B	TEX, an	d TPH b	elow	BGT			
				closu	re sta	ndards. F	ield reports	and I	aborato	y results	are	attached.			
Describe Are	a Affected	and Cleanup A	Action Tak	en.*			"mal labarat			l = t =					
						-	inal laborate	ory a	naiysis c	tetermine	ea no)			
				remedia	actio	n is requ	irea.								
I hamahar aamti	C. that the	:C	von abovo	:. t 1		a baat a Cassa	lancardo de carada		. 1 41 4	want to NIM	OCD	lee and			
				is true and comp d/or file certain re											
public health	or the envi	ronment. The	acceptanc	e of a C-141 repo	rt by the	NMOCD m	arked as "Final R	eport" o	loes not reli	eve the opera	ator of	liability			
				investigate and retance of a C-141											
		ws and/or regu			1			•							
		arel 1					OIL CON	SERV	ATION	DIVISIO	N				
8:	run g	arifalo	4												
					A	Approved by	Environmental S	pecialis	t:						
		arifalos													
Title: Field	Envir	onmenta	I Coo	rdinator	F	Approval Dat	e:		Expiration I	Date:					
E-mail Addre	ss: erin.	garifalos	@bpx	.com	(Conditions of	Approval:			Attachad					
Date: June	25, 2018	3	Phone: (832) 609-7048												

^{*} Attach Additional Sheets If Necessary

bp



BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

May 3, 2018

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: NEIL A 001 API# - 3004527519

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 9, 2018. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From:

Buckley, Farrah (CH2M HILL)

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa, Fields@state.nm.us)

Cc:

jeffcblagg@aol.com; blagg_njv@yahoo.com; Garifalos, Erin

Subject: Date: BP Pit Close Notification - NEIL A 001 Thursday, May 03, 2018 4:17:02 PM

> BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

May 3, 2018

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

NEIL A 001 API# 30-45-27519 (L) Section 33 – T32N – R11W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around May 9, 2018.

Should you have any questions, please feel free to contact BP at our Durango office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator - San Juan

Cell: 832-609-7048

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

client: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413							
	(505) 632-1199	97.	TANK ID (if applicble):					
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGA	ATION / OTHER:	PAGE#:1 of1_					
SITE INFORMATION	I: SITE NAME: NEIL A #1		DATE STARTED: 05/09/18					
QUAD/UNIT: L SEC: 33 TWP	32N RNG: 11W PM: NM CNTY	SJ ST: NM	DATE FINISHED:					
1/4 -1/4/FOOTAGE: 2,140'S / 91 0		/ STATE / FEE / INDIAN	ENVIRONMENTAL					
LEASE #: SF078051	PROD. FORMATION: FT CONTRACTOR: BF	RIKE - J. GONZALES	SPECIALIST(S): NJV					
REFERENCE POIN	: WELL HEAD (W.H.) GPS COORD.:	36.94011 X 108.00003	GL ELEV.: 6,179'					
1) 95 BGT (SW/DB)	GPS COORD.: 36.939898 X 108.0	00011 DISTANCE/BEA	RING FROM W.H.: 86', S6.5E					
2)	GPS COORD.:	DISTANCE/BEA	RING FROM W.H.:					
3)	GPS COORD.:	DISTANCE/BEA	RING FROM W.H.:					
4)	GPS COORD.:	DISTANCE/BEA	SCHOOL OF SCHOOL SECURICAN					
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED:	HALL	OVM READING (ppm)					
1) SAMPLE ID: 5PC - TB @ 5	(95) SAMPLE DATE: 05/09/18 SAMPLE TIME:	1245 LAB ANALYSIS: 80°	15B/8021B/300.0 (CI) NA					
	SAMPLE DATE:SAMPLE TIME:							
	SAMPLE DATE: SAMPLE TIME: SAMPLE TIME: SAMPLE TIME:							
5) SAMPLE ID:	SAMPLE DATE:SAMPLE TIME:							
	Y COHESIVE / COHESIVE / HIGHLY COHESIVE DENSITY (COHESIVE							
MOISTURE: DRY/SLIGHTLYMOIST MOIST / NOIST / NO	ET / SATURATED / SUPER SATURATED # OF PTS	NG WETNESS: YES NO EXPLAI						
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERV EQUIPMENT SET OVER RECLAIMED AREA:	LOST INTEGRITY OF EQUIPMENT: YES NO EXPLANATED AND/OR OCCURRED: YES NO EXPLANATION:	ION -						
EXCAVATION DIMENSION ESTIMATION		ft. EXCAVATION ES	ΓΙΜΑΤΙΟΝ (Cubic Yards) : NA					
DEPTH TO GROUNDWATER: >100'	IEAREST WATER SOURCE: <u>>1,000'</u> NEAREST SURFAC	E WATER: <200' NMOO	CD TPH CLOSURE STD: 100 ppm					
SITE SKETCH	BGT Located: off on site PLOT PL	AN circle: attached OVM	CALIB. READ. = NA ppm RF =1.00					
	то w.н.	N TIME	CALIB. GAS = NA ppm ppm					
	1		MISCELL. NOTES					
	FENCE	R	EF#: P-966 1D: VHIXONEVB2 J#:					
	BERM (XXX) PBGTL T.B. ~ 5' B.G.	P O Tai II	ermit date(s): 06/08/10 CD Appr. date(s): 04/08/16 OVM = Organic Vapor Meter ppm = parts per million					
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BE	ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; OW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W.	= RETAINING WALL; NA - NOT	BGT Sidewalls Visible: Y / N Magnetic declination: 10° E					
APPLICABLE OR NOT AVAILABLE; SW-SING	EWALL; DW-DOUBLE WALL; SB-SINGLE BOTTOM; DB-DOUBLE BOTTO FRY DATE: 3/15/2015.	05/09/18						

revised: 11/26/13 BEI1005E-6.SKF

Analytical Report

Lab Order 1805565

Date Reported: 5/14/2018

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (95)

Collection Date: 5/9/2018 12:45:00 PM

Project: NEIL A 1 **Lab ID:** 1805565-001

Matrix: MEOH (SOIL) Received Date: 5/10/2018 7:50:00 AM

Analyses	Result	PQL Qua	ıl Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	MRA
Chloride	ND	30	mg/Kg	20	5/10/2018 10:20:06 AM	38038
EPA METHOD 8015D MOD: GASOLINE F	RANGE				Analyst	AG
Gasoline Range Organics (GRO)	ND	3.9	mg/Kg	1	5/10/2018 10:17:26 AM	A51185
Surr: BFB	118	70-130	%Rec	1	5/10/2018 10:17:26 AM	A51185
EPA METHOD 8015M/D: DIESEL RANGE	ORGANIC	S			Analyst	Irm
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	5/10/2018 12:49:39 PM	38036
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	5/10/2018 12:49:39 PM	38036
Surr: DNOP	96.0	70-130	%Rec	1	5/10/2018 12:49:39 PM	38036
EPA METHOD 8260B: VOLATILES SHOR	T LIST				Analyst	AG
Benzene	ND	0.019	mg/Kg	1	5/10/2018 10:17:26 AM	B51185
Toluene	ND	0.039	mg/Kg	1	5/10/2018 10:17:26 AM	B51185
Ethylbenzene	ND	0.039	mg/Kg	1	5/10/2018 10:17:26 AM	B51185
Xylenes, Total	ND	0.078	mg/Kg	1	5/10/2018 10:17:26 AM	B51185
Surr: 4-Bromofluorobenzene	128	70-130	%Rec	1	5/10/2018 10:17:26 AM	B51185
Surr: Toluene-d8	94.0	70-130	%Rec	1	5/10/2018 10:17:26 AM	B51185

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 6
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

C	hain-c	of-Cus	stody Record	Turn-Around	Time:	SAME				L	JAI			NIX.	/TE		B.F.F		N1	CAI		
Client:	BLAG	G ENGR.	/ BP AMERICA	Standard	Standard Rush DAY														IVI ATO			
				Project Name															***	<i>-</i> 10	V =	
Mailing A	ddress:	P.O. BO	X 87		NEIL A #	1	www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109															
		BLOOM	FIELD, NM 87413	Project #:)5-34							-410					
Phone #:		(505) 63	32-1199										nal	ysis	Rec	lues	t					
email or F	ax#:			Project Manag	ger:									(†				(F)		T	T	
QA/QC Pad Standa			Level 4 (Full Validation)		ERIN GARI	FALOS	(8021B)	only)	(MRO)			15)		05,50	PCB's			er - 300.1)			e	
Accreditat		□ Other		Sampler: On Ice:	NELSON V	ELEZ	1-1	PH (Gas	/ DRO /	418.1)	04.1)	270SIN		3,NO2,	5 / 8082		A)	0.0 / water			composite sample	î
□ EDD (1	Гуре)					-0.1(cr) 0 =	I	E+1	GRO	od 4	od 5	or 8	tals	I,NC	ide	F	0	1-30		e e	osite	(Y or
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type		BTEX +MEB	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO	TPH (Method	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /		Grab sample	5 pt. comp	Air Bubbles (Y or N)
5/9/18	1245	SOIL	5PC - TB @ 5 / (95)	4 oz 1	Cool	-001	٧		٧									٧			٧	
															,							
																					\neg	
																				\top	\top	-
																				十		
																				\top		
																				\neg	1	
																				\top	\neg	
																					\forall	
																				\top	\forall	
Date: 5/9/18	Time: 1650	Relinquish	Mus	Received by:	Walter	Date Time 5/9/12 /456		ont		BILL C	FEREN	CE#	WHEN	APP	LICAE	BLE;		<u>итн с</u>	CORRES	SPONE	DING	VID
Date: 5/9/12	Time:	Relinquish	ed by:	Received by:	(ourer 5/10)	Date Time	VID: VHIXONEVB2															
1.110	If necessary, samples submitted to Hall Environmental may be subcontracted to other accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report.																					

Hall Environmental Analysis Laboratory, Inc.

WO#:

1805565

14-May-18

Qual

Client:

Blagg Engineering

Project:

NEIL A 1

Sample ID MB-38038

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 38038

RunNo: 51177

SPK value SPK Ref Val %REC

Prep Date: 5/10/2018 Analysis Date: 5/10/2018

SeqNo: 1664082

Units: mg/Kg

HighLimit

Result PQL

Analyte Chloride

ND 1.5

Sample ID LCS-38038

SampType: Ics

TestCode: EPA Method 300.0: Anions

LowLimit

Client ID:

LCSS

Batch ID: 38038

RunNo: 51177

Units: mg/Kg

Prep Date: 5/10/2018 Analysis Date: 5/10/2018

SeqNo: 1664083 %REC

Analyte

SPK value SPK Ref Val

94.8

LowLimit 90

HighLimit %RPD

%RPD

Result PQL 14

15.00

0

RPDLimit

RPDLimit

Chloride

1.5

110

Qual

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix

Holding times for preparation or analysis exceeded H

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

В Analyte detected in the associated Method Blank

Value above quantitation range

J Analyte detected below quantitation limits

Page 2 of 6

P Sample pH Not In Range RL Reporting Detection Limit

Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1805565

14-May-18

Client:

Blagg Engineering

Project:

NEIL A 1

Project: NEIL A	1		
Sample ID MB-38036	SampType: MBLK	TestCode: EPA Method 8015M/D: [Diesel Range Organics
Client ID: PBS	Batch ID: 38036	RunNo: 51178	
Prep Date: 5/10/2018	Analysis Date: 5/10/2018	SeqNo: 1662834 Units: mg	/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit	%RPD RPDLimit Qual
Diesel Range Organics (DRO)	ND 10		
Motor Oil Range Organics (MRO)	ND 50		
Surr: DNOP	9.3 10.00	92.8 70 130	
Sample ID MB-38006	SampType: MBLK	TestCode: EPA Method 8015M/D: D	Diesel Range Organics
Client ID: PBS	Batch ID: 38006	RunNo: 51178	
Prep Date: 5/9/2018	Analysis Date: 5/10/2018	SeqNo: 1664175 Units: %R	ec
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit	%RPD RPDLimit Qual
Surr: DNOP	9.9 10.00	99.3 70 130	
Sample ID LCS-38006	SampType: LCS	TestCode: EPA Method 8015M/D: D	Diesel Range Organics
Client ID: LCSS	Batch ID: 38006	RunNo: 51178	
Prep Date: 5/9/2018	Analysis Date: 5/10/2018	SeqNo: 1664176 Units: %R	ec
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit	%RPD RPDLimit Qual
Surr: DNOP	4.5 5.000	89.2 70 130	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
 - S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits

Page 3 of 6

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

atory, Inc.

1805565 14-May-18

WO#:

Client: Blagg Engineering

Project: NEIL A 1

Sample ID 1805565-001ams	SampT	SampType: MS4 TestCode: EPA Method 8260B: Volatiles Short List								
Client ID: 5PC-TB @ 5' (95)	Batch	ID: B5	1185	F	RunNo: 51185					
Prep Date:	Analysis D	nalysis Date: 5/10/2018 SeqNo: 1663137 U				Units: mg/K	nits: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.65	0.019	0.7770	0	84.0	80	120			
Toluene	0.73	0.039	0.7770	0	94.1	80	120			
Ethylbenzene	0.81	0.039	0.7770	0	104	80	120			
Xylenes, Total	2.3	0.078	2.331	0.01543	99.6	80	120			
Surr: 4-Bromofluorobenzene	0.42		0.3885		107	70	130			
Surr: Toluene-d8	0.37		0.3885		96.0	70	130			

Sample ID 1805565-001ams	samp7	SampType: MSD4 TestCode: EPA Method 8260B: Vol							List	
Client ID: 5PC-TB @ 5' (95)	Batch	h ID: B5	1185	RunNo: 51185						
Prep Date:	Analysis D	Date: 5/	10/2018	5	SeqNo: 1	663138	Units: mg/F	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.64	0.019	0.7770	0	82.0	80	120	2.49	0	
Toluene	0.70	0.039	0.7770	0	89.5	80	120	5.10	0	
Ethylbenzene	0.75	0.039	0.7770	0	96.9	80	120	6.92	0	
Xylenes, Total	2.3	0.078	2.331	0.01543	97.0	80	120	2.66	0	
Surr: 4-Bromofluorobenzene	0.42		0.3885		108	70	130	0	0	
Surr: Toluene-d8	0.37		0.3885		96.4	70	130	0	0	

Sample ID rb	Sampl	уре: МЕ	BLK	TestCode: EPA Method 8260B: Volatiles Short List						
Client ID: PBS	Batcl	n ID: B5	1185	F	RunNo: 51185					
Prep Date:	Analysis D	Date: 5/	10/2018	5	SeqNo: 1	663141	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.58		0.5000		115	70	130			
Surr: Toluene-d8	0.51		0.5000		103	70	130			

Sample ID 100ng Ics	SampType: LCS4 TestCode: EPA I					PA Method	od 8260B: Volatiles Short List					
Client ID: BatchQC	Batch ID: B51185				RunNo: 5	1185						
Prep Date:	Analysis D	ate: 5/	10/2018	8	SeqNo: 1	663711	Units: mg/K	(g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	0.94	0.025	1.000	0	94.2	80	120					
Toluene	1.0	0.050	1.000	0	101	80	120					
Ethylbenzene	1.0	0.050	1.000	0	103	80	120					
Xylenes, Total	3.0	0.10	3.000	0	101	80	120					

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 4 of 6

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

0.52

WO#: 1805565

14-May-18

Client: Blagg Engineering

Project: NEIL A 1

Surr: Toluene-d8

Sample ID 100ng Ics SampType: LCS4 TestCode: EPA Method 8260B: Volatiles Short List

Client ID: BatchQC Batch ID: B51185 RunNo: 51185

Prep Date: Analysis Date: 5/10/2018 SeqNo: 1663711 Units: mg/Kg

0.5000

Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Surr: 4-Bromofluorobenzene	0.49		0.5000		98.7	70	130				Т

105

70

130

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 5 of 6

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1805565

14-May-18

Client:

Blagg Engineering

Project:

NEIL A 1

Sample ID 2.5ug gro lcs	SampT	ype: LC	S	TestCode: EPA Method 8015D Mod: Gasoline Range						
Client ID: LCSS	Batch	ID: A5	1185	R	RunNo: 5	1185				
Prep Date:	Analysis D	ate: 5/	10/2018	S	SeqNo: 1	663108	Units: mg/F	ζg		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	25	5.0	25.00	0	98.3	70	130			
Surr: BFB	490		500.0		97.8	70	130			

Sample ID rb	SampT	SampType: MBLK TestCode: EPA Method 8015D Mod: Gasoline Range							Range	
Client ID: PBS	Batch	ID: A5	1185	R	RunNo: 5	1185				
Prep Date:	Analysis D	ate: 5/	10/2018	S	SeqNo: 1	663111	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	530		500.0		106	70	130			

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 6 of 6

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Albuqueque, NM 87109 Sample Log-In Check List

Client Name: BLAGG Work Order Num	ber: 1805565		RcptNo:	1
માસાં જ હે જેવા, વધુ સુંધુ વર્ષો			1 - 1 1 ·	
Received By: Isaiah Ortiz 5/10/2018 7:50:00	AM	ION		
Completed By Isaiah Ortiz 5/10/2018 8:21:56	AM	ION		
Reviewed By: JU 31018				1
Label of By: Imo 5/16/18				
Chain of Custody		1.1		
1. Is Chain of Custody complete?	Yes 🗹	No 🗆	Not Present	
2. How was the sample delivered?	Courier			
<u>Log In</u>				
3. Was an attempt made to cool the samples?	Yes 🗸	No 🗌	NA 🗆	
4. Were all samples received at a temperature of >0° C to 6.0°C	Yes 🗸	No 🗀	. NA .	
5. Sample(s) in proper container(s)?	Yes 🔽	No 🗆		
		<u>.</u>	*	
6. Sufficient sample volume for indicated test(s)?	Yes 🗹	No 🗆		
7. Are samples (except VOA and ONG) properly preserved?	Yes 🔽	No 🗆	· ·	**
8. Was preservative added to bottles?	Yes 🗀	No 🗸	NA 🗌	
9. VOA vials have zero headspace?	Yes	No 🗌 No	VOA Vials	
10. Were any sample containers received broken?	Yes	No 🗸	of preserved	
		bo	ttles checked /	0
11. Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes 🗸	No 🗌 for	pH: (<2,01%	(20 less noted)
2. Are matrices correctly identified on Chain of Custody?	Yes 🗸	No 🗆	Adjustee	1
3. Is it clear what analyses were requested?	Yes 🗹	No 🗆	151	
4. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes 🗹	No 🗆	Checked by:	
Special Handling (if applicable)			· · · ·	
15. Was client notified of all discrepancies with this order?	Yes L	No L	NA 🗸	
Person Notified: Date:	Francisco consequent receive			
By Whom: Via:	eMail Pho	one Fax	In Person	
Regarding: Client Instructions:	Bit, at supplies process in the total of the responsed managing day, and the total of the	- Comment of the Comm	Market and a property of the second	
16. Additional remarks:		,		
17. Cooler Information Cooler No. Temp °C Condition Seal Intact Seal No.	Seal Date S	igned By		
1 0.7 Good Yes		ALLES DANGE		



