District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

<u>P</u> :	it, Below-Grade	Tank, or	
Proposed Alternative	Method Permit	or Closure Plan	Application

Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #: 778
Address: 200 Energy Court, Farmington, NM 87401
Facility or well name: GCU 061
API Number: 3004506939 OCD Permit Number:
U/L or Qtr/Qtr A Section 04 Township 27N Range 12W County: San Juan
Center of Proposed Design: Latitude 36.60970 Longitude -108.11099 NAD83
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: ☐ Drilling ☐ Workover ☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other ☐ String-Reinforced Liner Seams: ☐ Welded ☐ Factory ☐ Other Volume: bbl Dimensions: L x W x D
3. TANK A
Below-grade tank: Subsection 1 of 19.13.17.11 NNIAC
Volume: 95 bbl Type of fluid: Produced Water
Tank Construction material: Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off ☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other ☐ Double wall/ Double bottom; sidewalls not visible
Liner type: Thickness mil
Liner type: Tricknessinit ADFE FVC Other
4. Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
5.
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence from hospital,
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet
All Alternate. Please specify

t g X	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank:	
 □ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. □ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
9.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).	Yes No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Temporary Pit Non-low chloride drilling fluid									
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No								
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Permanent Pit or Multi-Well Fluid Management Pit									
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No								
ithin 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of tial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site ithin 500 feet of a wetland.									
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC Previously Approved Design (attach copy of design) API Number:									
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC									
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number:	.15.17.9 NMAC								

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are						
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC							
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.							
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F. Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit						
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC							
15.							
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.							
Ground water is less than 25 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA						
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells [[]							
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste.							
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	-well Fluid Management Pit -nust be attached to the MAC NMAC ble source material are ency. Please refer to Yes No NA Yes NO N						
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No						
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No						
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No						
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	□ Vec □ No						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ 162 ☐ 140						

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No							
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No							
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 								
Society; Topographic map Within a 100-year floodplain. - FEMA map								
16.								
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.1 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards car Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	7.11 NMAC 9.15.17.11 NMAC							
17. Operator Application Certification:								
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and be	elief.							
Name (Print): Title:								
Signature: Date:								
e-mail address: Telephone:								
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: OCD Permit Number:	36/2018							
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 6/26/2018								
20.								
Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed- If different from approved plan, please explain.	-loop systems only)							

22.						
Operator Closure Certification:						
	itted with this closure report is true, accurate and complete to the best of my knowledge and icable closure requirements and conditions specified in the approved closure plan.					
Name (Print): Erin Dunman Title: Field Environmental Coordinator						
Erin Dunman Signature:	Date: August 23, 2018					
e-mail address: erin.dunman@bpx.com	Telephone: (832) 609-7048					

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

GCU 061

API No. 3004506939

Unit Letter A Section 04 T 27N R 12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows:

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.016
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.063
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<47
Chlorides	US EPA Method 300.0 or 4500B	620	< 30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-141 Revised April 3, 2017 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

OPERATOR								Initia	al Report		Final Report			
Name of Company BP America Production Company							n Dunman							
Address 200 Energy Court, Farmington, NM 87401						Telephone No. (832) 609-7048								
Facility Nar	ne GCU (061				Facility Typ	e: Natural Ga	as We	911					
Surface Ow	ner: Fed	eral		Mineral C	wner:	Federal			API No	.300450	6939)		
				LOCA	OITA	N OF RE	LEASE							
Unit Letter	Section	Township	Range	Feet from the	North/	South Line	Feet from the	East/\	West Line	County		1		
Α	04	27N	12W	692	Nor	th	877	Eas	st	S	an	Juan		
Latitude 36.60970 Longitude -108.11099 NAD83														
				NAT	URE	OF REL	EASE							
Type of Release	ase:: none	9					Release: unkno			Recovered::				
Source of Re	lease: belo	w grade ta	nk - 95	bbl		Date and F	lour of Occurrence	ee:	Date and n/a	Hour of Dis	covery:			
Was Immedia	ate Notice (Given?				If YES, To	Whom?		- 100 M					
D 1111 0		Ш	Yes 🗸	No Not Re	equired	D								
By Whom? Was a Water	course Read	ched?				Date and H	lour lume Impacting t	he Wate	ercourse					
Was a water	ourse rea		Yes 🗸	No		II I LO, VC	nume impacting t	ine wat	creourse.					
If a Watercou	rse was Im	pacted, Descri	ibe Fully.*											
Describe Con	aa af Duah l	d D	dial Astic	T-1 *										
Describe Cau	se of Probl	em and Remed	aiai Actioi	Samı Samı	oling o	of the soil	beneath the	BGT	was do	ne durin	g ren	noval.		
				Soil a	analys	is resulte	d for Chlorid	les, B	TEX, an	d TPH b	elow	BGT		
				closu	re sta	ındards. F	Field reports	and I	aborato	y results	are	attached.		
Describe Area	a Affected	and Cleanup A	Action Tak	en.*			" -11-1		1		. 1			
						-	inal laborate	ory ar	naiysis c	letermin	ea na)		
				remediai	actio	n is requ	irea.							
T114	C - 41 41 1	· · · · · · · · · · · · · · · · · · ·	1	:	1-4- 4- 41	- 1 t - C	1111	. 1	141-4	A NO.	CD	11		
				is true and completed dor file certain re										
public health	or the envi	ronment. The	acceptanc	e of a C-141 repo	rt by the	e NMOCD m	arked as "Final R	eport" d	loes not reli	eve the oper	ator of	liability		
				investigate and retance of a C-141										
federal, state,	or local la	ws and/or regu	lations.	tance of a C-141	report di	oes not renev	e the operator or i	respons	ibility for Co	mphance w	itii aiiy	other		
0)						OIL CONS	SERV	ATION	DIVISIO	N			
(rin o	Dunm	an											
Signature:	_					Approved by	Environmental S	pecialis	i:					
Printed Name	Erin D	Dunman				11								
		onmenta	I Coo	rdinator		Approval Dat	e:		Expiration I	Date:				
E-mail Addre	ss: erin.	dunman	@bpx	.com		Conditions of			_					
Date: Augus				(832) 609-70						Attached				

^{*} Attach Additional Sheets If Necessary

bp



BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

June 15, 2018

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 061 API# - 3004506939

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about June 21, 2018. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

Erin Dunman

From:

Buckley, Farrah (CH2M HILL) <farrah.buckley@bp.com>

Sent:

Friday, June 15, 2018 1:32 PM

To:

Smith, Cory, EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)

Cc:

jeffcblagg@aol.com; blagg_njv@yahoo.com; Erin Garifalos

Subject:

BP Pit Close Notification - GCU 061

external-email:

0

BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

June 15, 2018

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 061 API# 30-045-06939 (A) Section 4 – T27N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around June 21, 2018.

Should you have any questions, please feel free to contact BP at our Durango office.

Sincerely,

Erin Garifalos

Field Environmental Coordinator – San Juan Cell: 832-609-7048

Farrah Buckley
BGT Project Support
970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	P.O. BOX 87, B	NGINEERING, IN LOOMFIELD, NN 05) 632-1199		API #: 3004506939 TANK ID (if applicble): A						
FIELD REPORT:	OTHER:	PAGE #:1 c	of 1							
SITE INFORMATION QUAD/UNIT: A SEC: 4 TWP: 1/4-1/4/FOOTAGE: 692'N / 877'E	27N RNG: 12W PM: NE/NE LEASE T	NM CNTY: SJ		DATE FINISHED: ENVIRONMENTAL	21/18					
LEASE #: SF078902 PROD. FORMATION: PC/FT CONTRACTOR: STRIKE BP - J. GONZALES SPECIALIST(S): NJV REFERENCE POINT: Well head (W.H.) GPS COORD.: 36.60958 X 108.11105 GL ELEV.: 5,774'										
1) 95 BGT (DW/DB) 2) 3) 4)		6.60970 X 108.11099	DISTANCE/BEAF	RING FROM W.H.:						
SAMPLING DATA: 1) SAMPLE ID: 5PC - TB @ 5' 2) SAMPLE ID: 4) SAMPLE ID: 5 5) SAMPLE ID: 5 5) SAMPLE ID: 5	SAMPLE DATE:	1/18		I5B/8021B/300.0 (CI)	OVM READING (ppm) NA					
SOIL COLOR: DARK YELL COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LO MOISTURE: DRY SLIGHTLY MOIST MOIST / M	SOIL DESCRIPTION: SOIL TYPE: SAND SILTY SAND SILTY SILTY CLAY / CLAY / GRAVEL / OTHER									
EXCAVATION DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <50' N SITE SKETCH	NA ft. X NA EAREST WATER SOURCE: >1,000 BGT Located: off on sit PBGTL T.B. ~ 5' B.G.		>1,000' NMOC	CALIB. GAS = NA pp	RF =1.00					
FENCE—3	RI VI P. Pe OV Tan	/O: EF #: P-983 ID: VHIXONEVB2 J #: ermit date(s): 06/1 CD Appr. date(s): 02/2 k OVM = Organic Vapor Me	2 4/10 6/18							
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELO APPLICABLE OR NOT AVAILABLE; SW-SINGLE	OW-GRADE TANK LOCATION; SPD = SAMPLE F E WALL; DW - DOUBLE WALL; SB - SINGLE BOT	ELOW; T.H. = TEST HOLE; ~ = APPROX.; POINT DESIGNATION; R.W. = RETAINING	WALL; NA - NOT M	BGT Sidewalls Visible: Y / BGT Sidewalls Visible: Y / lagnetic declination: 10	N					

Analytical Report

Lab Order 1806D75

Hall Environmental Analysis Laboratory, Inc. Date Reported: 6/26/2018

CLIENT: Blagg Engineering

Project:

GCU 61

Client Sample ID: 5PC - TB @ 5' (95)

Collection Date: 6/21/2018 2:40:00 PM

Lab ID: 1806D75-001 Matrix: MEOH (SOIL) Received Date: 6/22/2018 8:00:00 AM

Analyses	Result	PQL	L Qual Units		Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	MRA
Chloride	ND	30	mg/Kg	20	6/22/2018 1:59:42 PM	38838
EPA METHOD 8015M/D: DIESEL RANGE ORG	ANICS				Analyst	TOM
Diesel Range Organics (DRO)	ND	9.3	mg/Kg	1	6/22/2018 10:15:19 AM	38833
Motor Oil Range Organics (MRO)	ND	47	mg/Kg	1	6/22/2018 10:15:19 AM	38833
Surr: DNOP	104	70-130	%Rec	1	6/22/2018 10:15:19 AM	38833
EPA METHOD 8015D: GASOLINE RANGE					Analyst	NSB
Gasoline Range Organics (GRO)	ND	3.2	mg/Kg	1	6/22/2018 11:57:53 AM	38816
Surr: BFB	78.1	15-316	%Rec	1	6/22/2018 11:57:53 AM	38816
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.016	mg/Kg	1	6/22/2018 11:57:53 AM	38816
Toluene	ND	0.032	mg/Kg	1	6/22/2018 11:57:53 AM	38816
Ethylbenzene	ND	0.032	mg/Kg	1	6/22/2018 11:57:53 AM	38816
Xylenes, Total	ND	0.063	mg/Kg	1	6/22/2018 11:57:53 AM	38816
Surr: 4-Bromofluorobenzene	99.9	80-120	%Rec	1	6/22/2018 11:57:53 AM	38816

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Oualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- % Recovery outside of range due to dilution or matrix
- Analyte detected in the associated Method Blank
- Value above quantitation range E
- Analyte detected below quantitation limits Page 1 of 5 J

- P Sample pH Not In Range
- RL Reporting Detection Limit
- Sample container temperature is out of limit as specified

Chain-of-Custody Record			I urn-Around	ime:	SAME				Į-	A		F	NV	/TE	20	NE	ИF	NT	CAI			
Client:	BLAG	G ENGR.	/ BP AMERICA	☐ Standard	Rush _	DAY)	-												AT(
				Project Name:				×.														
Mailing A	ddress:	P.O. BO	X 87		GCU #6	1	www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109															
		BLOOM	FIELD, NM 87413	Project #:			Tel. 505-345-3975 Fax 505-345-4107															
Phone #:		(505) 63	2-1199						-			9.6	100	ysis	- 0	27 6					7, 6	
email or F	ax#:			Project Manag	jer:													ਜ਼				
QA/QC Pad Standa			Level 4 (Full Validation)		ERIN GARI	FALOS	(8021B)	(Gas only)	MRO)			(S)		04,50	PCB's			er - 300.1)			a l	
Accreditat	ion:			Sampler:	NELSON V	ELEZ	18 (8((Gas	DRO./	1)	1	SIN		02,	8082			/ water			sample	
□ NELAP)	□ Other		On lice	X-Yes	□ No · · · · · · · · · · · · · · · · · ·	TMB	TPH	_	418.	504	8270		03,0	3/8		(A)	0.00			e sa	S L
□ EDD (1	ype)			Sample Temp	eratures 197	经的数据	#	+	(GR	poc	pou	or	etal	CIN	icide	(A)	Ji-VC	oil-3		e e	osit	(۲٥
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX +**	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides /	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /		Grab sample	5 pt. composite	Air Bubbles (Y or N)
9/21/18	1440	SOIL	5PC-TB @ 5 (95)	4 oz 1	Cool	-001	٧		٧									٧			٧	
																				\forall		
																				\neg	\neg	
																				1		
														-					1	\neg		
																			7	\dashv	\neg	
		<u> </u>																	_	\neg	\neg	
									_										\dashv	\dashv	\neg	
Date:	Time:	Relinquish	ed by:	Received by:	.)	Date Time	Rem	narks	:								ACT V	VITH C	ORRE	SPON	DING	VID
6/21/18	1527	7	Milt	Khowatru	likela	1/21/18 1527	0	ONT	ACT.					VAI			N					
Date:	Time:	ne: Relinquished by:		Received by: Pate Time			CONTACT: ERIN GARIFALOS / VANCE HIXON VID: VHIXONEVB2															
121/18	1840	1 chil	ottre la Meles) dula			eren		-		983										
1-	If necessa	ary, samples s	ubmitted to Hall Environmental may be s	subcontracted to other	adcredited laboratorio	es. This serves as notice o	f this p	ossibi	ity. A	ny sub	-contr	acted	data v	vill be	clearly	notat	ed on	the an	alytical	repor	rt.	

Hall Environmental Analysis Laboratory, Inc.

WO#: 1806D75

26-Jun-18

Client:

Blagg Engineering

Project:

GCU 61

Sample ID MB-38838

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 38838

RunNo: 52169 SeqNo: 1709628

Units: mg/Kg

Qual

Analyte

Prep Date:

6/22/2018

Analysis Date: 6/22/2018 PQL

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD

RPDLimit

Chloride

Client ID:

Prep Date:

ND 1.5

Batch ID: 38838

Analysis Date: 6/22/2018

Sample ID LCS-38838

6/22/2018

LCSS

SampType: LCS

TestCode: EPA Method 300.0: Anions RunNo: 52169

SeqNo: 1709629

LowLimit

Units: mg/Kg

%RPD

Analyte

Result

Result

SPK value SPK Ref Val %REC PQL 1.5

15.00

92.2

RPDLimit

Qual

Chloride

14

90

HighLimit 110

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Holding times for preparation or analysis exceeded H

Not Detected at the Reporting Limit ND

PQL Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

В Analyte detected in the associated Method Blank

E Value above quantitation range

Analyte detected below quantitation limits

Page 2 of 5

P Sample pH Not In Range

RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

ND

ND

9.6

10

50

10.00

WO#:

1806D75

26-Jun-18

Client:

Blagg Engineering

Project: GCU 6	1					
Sample ID LCS-38824	SampType: LCS TestCode: EPA Method 8015M/D: Diesel Range Organics					
Client ID: LCSS	Batch ID: 38824 RunNo: 52154					
Prep Date: 6/21/2018	Analysis Date: 6/22/2018 SeqNo: 1708463 Units: %Rec					
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual					
Surr: DNOP	4.5 5.000 90.5 70 130					
Sample ID MB-38824	SampType: MBLK TestCode: EPA Method 8015M/D: Diesel Range Organics					
Client ID: PBS	Batch ID: 38824 RunNo: 52154					
Prep Date: 6/21/2018	Analysis Date: 6/22/2018 SeqNo: 1708464 Units: %Rec					
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual					
Surr: DNOP	9.9 10.00 98.7 70 130					
Sample ID LCS-38833	SampType: LCS TestCode: EPA Method 8015M/D: Diesel Range Organics					
Client ID: LCSS	Batch ID: 38833 RunNo: 52153					
Prep Date: 6/22/2018	Analysis Date: 6/22/2018 SeqNo: 1708471 Units: mg/Kg					
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual					
Diesel Range Organics (DRO)	46 10 50.00 0 92.0 70 130					
Surr: DNOP	4.5 5.000 90.0 70 130					
Sample ID MB-38833	SampType: MBLK TestCode: EPA Method 8015M/D: Diesel Range Organics					
Client ID: PBS	Batch ID: 38833 RunNo: 52153					
Prep Date: 6/22/2018	Analysis Date: 6/22/2018 SeqNo: 1708472 Units: mg/Kg					
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual					

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

PQL Practical Quanitative Limit

Diesel Range Organics (DRO)

Surr: DNOP

Motor Oil Range Organics (MRO)

% Recovery outside of range due to dilution or matrix

В Analyte detected in the associated Method Blank

Value above quantitation range

96.1

70

130

Analyte detected below quantitation limits

Page 3 of 5

P Sample pH Not In Range

RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#: 1806D75

26-Jun-18

Client:

Blagg Engineering

Project: GCU 6	1					
Sample ID MB-38816	SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range					
Client ID: PBS	Batch ID: 38816	RunNo: 52165				
Prep Date: 6/21/2018	Analysis Date: 6/22/2018	SeqNo: 1709404	Units: mg/Kg			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Gasoline Range Organics (GRO)	ND 5.0					
Surr: BFB	790 1000	79.5 15	316			
Sample ID LCS-38816	SampType: LCS TestCode: EPA Method 8015D: Gasoline Range					
Client ID: LCSS	Batch ID: 38816 RunNo: 52165					
Prep Date: 6/21/2018	Analysis Date: 6/22/2018	SeqNo: 1709405	Units: mg/Kg			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Gasoline Range Organics (GRO)	26 5.0 25.00	0 102 75.9	131			
Surr: BFB	910 1000	91.1 15	316			
Sample ID MB-38819	SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range					
Client ID: PBS	Batch ID: 38819	RunNo: 52165				
Prep Date: 6/21/2018	Analysis Date: 6/22/2018	SeqNo: 1709408	Units: %Rec			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Surr: BFB	840 1000	84.2 15	316			
Sample ID LCS-38819	SampType: LCS TestCode: EPA Method 8015D: Gasoline Range					
Client ID: LCSS	Batch ID: 38819	RunNo: 52165				
Prep Date: 6/21/2018	Analysis Date: 6/22/2018	SeqNo: 1709478	Units: %Rec			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Surr: BFB	900 1000	89.9 15	316			

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Η Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

PQL Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

В Analyte detected in the associated Method Blank

E Value above quantitation range

Analyte detected below quantitation limits

Page 4 of 5

P Sample pH Not In Range

Reporting Detection Limit RL

Hall Environmental Analysis Laboratory, Inc.

1806D75 WO#:

26-Jun-18

Client:

Blagg Engineering

Project:	GCU 61									
Sample ID MB-388	116 Samp	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles					
Client ID: PBS	Bat	Batch ID: 38816		RunNo: 52165						
Prep Date: 6/21/2	018 Analysis	Analysis Date: 6/22/2018		SeqNo: 1709437 Units: mg.		Units: mg/K	g			
Analyte	Result	PQL S	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorober	nzene 1.0		1.000		102	80	120			
Sample ID LCS-38	816 Samp	SampType: LCS TestCode: EPA Method 8021B: Volatiles								
Client ID: LCSS	Bat	Batch ID: 38816			RunNo: 52165					
Prep Date: 6/21/2	018 Analysis	Analysis Date: 6/22/2018			SeqNo: 1709438 Units: mg/Kg			g		
Analyte	Result	PQL S	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.95	0.025	1.000	0	95.4	77.3	128			
Toluene	0.97	0.050	1.000	0	96.9	79.2	125			
Ethylbenzene	0.96	0.050	1.000	0	95.8	80.7	127			
Xylenes, Total	2.9	0.10	3.000	0	98.1	81.6	129			
Surr: 4-Bromofluorober	nzene 1.0		1.000		103	80	120			
Sample ID MB-388	19 Samp	SampType: MBLK TestCode: EPA Method 8021B: Volatiles								
Client ID: PBS	Bat	Batch ID: 38819		R	RunNo: 52165					
Prep Date: 6/21/2	018 Analysis	Date: 6/22	2/2018	S	eqNo: 17	709454	Units: %Red	:		
Analyte	Result	PQL S	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorober	nzene 1.1		1.000		106	80	120			
Sample ID LCS-38	819 Samp	Type: LCS		Test	Code: EF	PA Method	8021B: Volat	iles		
Client ID: LCSS	Bat	ch ID: 3881	19	R	unNo: 52	2165				
Prep Date: 6/21/2	018 Analysis	Date: 6/22	2/2018	S	eqNo: 17	709455	Units: %Red	;		

SPK value SPK Ref Val %REC

1.000

Qualifiers:

Analyte

Surr: 4-Bromofluorobenzene

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix D

Holding times for preparation or analysis exceeded

Result

1.0

ND Not Detected at the Reporting Limit

Practical Quanitative Limit **PQL**

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

LowLimit

80

104

HighLimit

120

%RPD

RPDLimit

Qual

Е Value above quantitation range

Analyte detected below quantitation limits

Page 5 of 5

P Sample pH Not In Range

RL Reporting Detection Limit



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BL	AGG	Work Order Number: 1806D75				RcptNo: 1		
Received By: As	shley Gallegos	6/22/2018 8:00:00) AM	A				
Completed By: As	shley Gallegos	6/22/2018 8:18:01	! AM	A				
Reviewed By: E	NM	6/22/2018 8:18:0	Labe	led b	4. Mules	21/18		
Chain of Custod	'y							
1. Is Chain of Custon	Yes 🗹	No 🗌	Not Present					
2. How was the sam	2. How was the sample delivered?							
Log In								
Commence of the Commence of the	nade to cool the samples	?	Yes 🗹	No 🗌	NA 🗆			
4. Were all samples	Yes 🗹	No 🗆	na 🗆					
5. Sample(s) in proper container(s)?			Yes 🗹	No 🗌				
6. Sufficient sample v	Yes 🗹	No 🗌						
7. Are samples (except VOA and ONG) properly preserved?			Yes 🗸	No 🗆				
Was preservative added to bottles?			Yes	No 🗹	NA 🗌			
9. VOA vials have zero headspace?			Yes	No 🗆	No VOA Vials			
10. Were any sample containers received broken?			Yes	No 🗹				
11 Deep seesewalk -	ratab battle labela?		Yes 🗸	No 🗆	# of preserved bottles checked for pH:	118		
Does paperwork m (Note discrepancie)	res 💌	NO L	1549	12 unless noted)				
12, Are matrices correctly identified on Chain of Custody?			Yes 🗸	No 🗆	Adjusted			
13. Is it clear what analyses were requested?			Yes 🗹	No 🗆	MAG			
14. Were all holding times able to be met? (If no, notify customer for authorization.)			Yes 🗸	No 🗆	Checked by:			
Special Handling								
	of all discrepancies with	this order?	Yes	. No 🗆	NA 🗹			
Person Notif	ied:	Date	- I	A THE RESIDENCE OF THE PARTY OF]		
By Whom:		Via:	·	Phone Fax	☐ In Person			
Regarding:		LONGS CHANGE AND AND THE START SHARE AND AND AND AND ADDRESS OF THE START OF THE ST	THE RESIDENCE OF THE PARTY OF T		COLOR STATE OF THE			
Client Instruc	ctions:							
16. Additional remarks:								
17. Cooler Information Cooler No. 1.2	emp °C. Condition. S	eal Intact Seal No	Sea Date	Signed By				



