Form C-144 Revised April 3, 2017

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application									
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method									
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.									
Operator: BP America Production Company Address: 200 Energy Court, Farmington, NM 87401									
Facility or well name: GCU 580 API Number: 3004530679 U/L or Qtr/Qtr N Section 13 Township 28N Range 12W County: San Juan									
Center of Proposed Design: Latitude 36.65813 Longitude -108.06560 NAD83 Surface Owner: Federal State Private Tribal Trust or Indian Allotment									
☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: ☐ Drilling ☐ Workover ☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other ☐ String-Reinforced Liner Seams: ☐ Welded ☐ Factory ☐ Other Volume:									
Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: 95									
4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.									
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet									

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Temporary Pit Non-low chloride drilling fluid								
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No							
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image								
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site								
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Permanent Pit or Multi-Well Fluid Management Pit								
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No							
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No							
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No							
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No							
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:								
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC								
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number: or Permit Number:								

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Lak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are					
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit					
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC						
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.						
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA					
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA					
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA					
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site						
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image						
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site						
Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No						
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes☐ No					

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.										
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No									
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division - Y										
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological										
Society; Topographic map	☐ Yes ☐ No									
Within a 100-year floodplain FEMA map										
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plants are check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannumly Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC 15.17.11 NMAC									
17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believes.	ief.									
Name (Print): Title:										
Signature: Date:										
e-mail address: Telephone:										
OCD Approval: Permit Application (including closure plan) Closure Plan (only) Conditions (see attachment) OCD Representative Signature: OCD Permit Number:	27/18									
19. <u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting										
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.										
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not										
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this									

Form C-144 Oil Conservation Division Page 5 of 6

22.	
Operator Closure Certification:	
	d with this closure report is true, accurate and complete to the best of my knowledge and ble closure requirements and conditions specified in the approved closure plan.
Name (Print): Erin Garifalos	Title: Field Environmental Coordinator
Signature: Utin gwihalas	Date: July 19 2018
e-mail address: erin.garifalos@bpx.com	Telephone: (832) 609-7048

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

GCU 580

API No. 3004530679

Unit Letter N Section 13 T 28N R 12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

Notice is attached.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows:

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	10	< 0.019
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.078
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	< 50
Chlorides	US EPA Method 300.0 or 4500B	620	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for chloride, TPH and BTEX with all concentrations below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141.

C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate a release has not occurred. Attached is a laboratory report and C-141.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results indicate a release has not occurred. Attached is a laboratory report and field report. The location will be reclaimed when the well is plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

The area has been backfilled and BGT location's surface condition is clear, but within the site's operational area. The location will be reclaimed once the well is plugged and abandoned.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included including photos of reclamation completion.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II
811 S. First St., Artesia, NM 88210
District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-141 Revised April 3, 2017

			Rele	ease Notific	eatior	and Co	orrective A	ction	1		
						OPERA'	ГOR		Initia	al Report 🔳 Final Repor	
				tion Company			n Garifalos	7040			
Facility Na			rmingto	n, NM 87401			No. (832) 609- be: Natural Ga		ell		
Surface Ow	mer: Fed	eral		Mineral C)wner:	Federal			API No	.3004530679	
		orai				N OF RE	LEASE			0001000070	
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/	West Line	County	
Ν	13	28N	12W	1,080	Sou	ıth	1,840	We	st	San Juan	
			Latitud	_e 36.65813	Le	ongitude -1	08.06560	NAD	83		
						OF REL					
Type of Rele	ase:: none	9			CICL	Volume of	Release:: unkno			Recovered:: N/A	
Source of Re	lease: belo	w grade ta	nk - 95	obl		Date and F	Hour of Occurrence	e:	Date and n/a	Hour of Discovery:	
Was Immedi		Given?		y si-on		If YES, To	Whom?				
By Whom?			Yes 🗸	No Not Re	equired	Date and H	Iour				
Was a Water	course Read	ched?					olume Impacting t	he Wat	ercourse.		
			Yes 🗸	No							
If a Waterco	urse was Im	pacted, Descri	ibe Fully.*					_			
Describe Car	use of Probl	em and Remed	dial Action	Taken.*	. 1.	- f 11 11	I	DOT	·		
					_					one during removal. and TPH below BGT	
					-					ry results are attached.	
Describe Are	ea Affected	and Cleanup A	Action Tak	en.*						•	
2 000110 0 1 11		and creamp.		No actio		-		ory a	nalysis d	determined no	
				remedia	actio	n is requ	ired.				
I haraby aart	fy that the	information ai	von above	is true and comp	lata to th	no bast of my	knowledge and u	ndersto	nd that pure	suant to NMOCD rules and	
regulations a	ll operators	are required to	report an	d/or file certain re	elease n	otifications a	nd perform correc	tive act	ions for rele	eases which may endanger	
										eve the operator of liability , surface water, human health	
or the enviro	nment. In a	ddition, NMC	CD accep							ompliance with any other	
federal, state	, or local la	ws and/or regu	ilations.				OIL CONS	SERV	ATION	DIVISION	
1	rin a	wihalo	4				<u>oil coin</u>	<u>SEIC (</u>	7111011	DIVIDIOI	
Signature: Approved by Environmental Specialist:											
Printed Nam	e: Erin G	arifalos				i ipproved by		peerano			
Title: Field Environmental Coordinator Approval Date:							te:		Expiration 1	Date:	
		garifalos			Com Conditions of Approval:				_		
Date: July				(832) 609-70		Attached L					
		ets If Necess		(552) 555 76	, 10						

bp



BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

May 18, 2018

Bureau of Land Management Whitney Thomas 6251 College Suite A Farmington, NM 87402

VIA EMAIL

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 580 API# - 3004530679

Dear Mrs. Thomas,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 21, 2018. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (832)-609-7048.

Sincerely,

Erin Garifalos

BP America Production Company

From:

Buckley, Farrah (CH2M HILL)

To:

Smith, Corv. EMNRD; Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)

Cc: Subject: jeffcblagg@aol.com; blagg_njv@yahoo.com; Garifalos, Erin BP Pit Close Notification - GALLEGOS CANYON UNIT 580

Date:

Friday, May 18, 2018 10:50:25 AM

BP America Production Company 380 Airport Rd Durango, CO 81303 Phone: (970) 247 6800

SENT VIA E-MAIL TO: <u>CORY.SMITH@STATE.NM.US</u>; <u>VANESSA.FIELDS@STATE.NM.US</u>

May 18, 2018

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE:

Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 580 API# 30-45-30679 (N) Section 13 – T28N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around May 21, 2018.

Should you have any questions, please feel free to contact BP at our Durango office.

Sincerely,

Erin Garifalos

 $Field\ Environmental\ Coordinator-San\ Juan$

Cell: 832-609-7048

Farrah Buckley BGT Project Support 970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CLIENT: BP	BLAGG E P.O. BOX 87, B (50	API #: 3004: TANK ID (if applicble):	530679 A						
FIELD REPORT:	(circle one): BGT CONFIRMATION	RELEASE INVESTIGATION / O	THER:	PAGE #: 1	of 1 _				
SITE INFORMATION	I: SITE NAME: GCU #	580		DATE STARTED:	05/21/18				
QUAD/UNIT: N SEC: 13 TWP:		98 (899 10)	ST: NM	DATE FINISHED:					
1/4 -1/4/FOOTAGE: 1,080'S / 1,8									
	PROD. FORMATION: PC/FT C	CTDIVE		ENVIRONMENTAL SPECIALIST(S):	NJV				
REFERENCE POINT		36.5795		GLELEV:	5 709'				
1) 95 BGT (SW/SB)	GPS COORD.: 36			RING FROM W.H.: 88'					
2)		1000107(100100000		RING FROM W.H.:					
3)									
4)	·		DISTANCE/BEA	RING FROM W.H.:	OVM				
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # C				READING (ppm)				
1) SAMPLE ID: 5PC - TB @ 4'				15B/8021B/300.0 (CI) NA				
2) SAMPLE ID:									
	SAMPLE DATE: SAMPLE DATE:	SAMPLE TIME:							
5) SAMPLE ID:		SAMPLE TIME:							
SOIL COLOR: DARK YELLOWSH ORANGE SOIL COLOR: DARK YELLOWSH ORANGE COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY COHESIVE / HIGHLY COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE MOISTURE: DRY / SLIGHTLY MOIST / MOIST / WET / SATURATED / SUPER SATURATED SAMPLE TYPE: GRAB COMPOSITE # OF PTS. 5 ANY AREAS DISPLAYING WETNESS: YES NO EXPLANATION- DISCOLORATION/STAINING OBSERVED: YES / NO EXPLANATION- SITE OBSERVATIONS: LOST INTEGRITY OF EQUIPMENT: YES NO EXPLANATION- APPARENT EVIDENCE OF A RELEASE OBSERVED AND/OR OCCURRED: YES / NO EXPLANATION- GOULPMENT SET OVER RECLAIMED AREA: YES NO EXPLANATION - OTHER: NMOCD OR BLM REPS. NOT PRESENT TO WITNESS CONFIRMATION SAMPLING. EXCAVATION DIMENSION ESTIMATION: NA ft. X NA ft. EXCAVATION ESTIMATION (Cubic Yards): NA									
DEPTH TO GROUNDWATER: >100' N	EAREST WATER SOURCE: >1,000	NEAREST SURFACE WATER:	<1,000' NMOC	D TPH CLOSURE STD:	1,000 ppm				
SITE SKETCH	BGT Located: off on sit	e PLOT PLAN circ	le: attached OVM	CALIB. READ. = NA	ppm				
	SEPARATOR →	BERM METER RUN	N TIME	CALIB. GAS = NA :: NA am/pm DATE MISCELL. N VO:	ppm NA				
	T.B. ~ 4' B.G.		V	EF#: P-991 ID: VHIXONE	VB2				
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELAPPLICABLE OR NOT AVAILABLE; SW-SINGLENOTES: GOOGLE FARTH IMAG	OW-GRADE TANK LOCATION; SPD = SAMPLE F E WALL; DW - DOUBLE WALL; SB - SINGLE BOT	ELOW; T.H. = TEST HOLE; ~ = APPROX.; \ POINT DESIGNATION; R.W. = RETAINING	MALL; NA-NOT	OCD Appr. date(s): 0 nk OVM = Organic Va ppm = parts per m	illion :(Y) N : Y / N : Y / N				

Analytical Report

Lab Order 1805B34

Date Reported: 5/25/2018

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 4' (95)

Project: GCU 580

Collection Date: 5/21/2018 11:45:00 AM

Lab ID: 1805B34-001

Matrix: SOIL

Received Date: 5/22/2018 6:45:00 AM

Analyses	Result	PQL Qua	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	MRA
Chloride	ND	30	mg/Kg	20	5/22/2018 1:14:36 PM	38253
EPA METHOD 8015M/D: DIESEL RANGE	ORGANICS				Analyst	TOM
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	5/22/2018 12:27:06 PM	38242
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	5/22/2018 12:27:06 PM	38242
Surr: DNOP	99.9	70-130	%Rec	1	5/22/2018 12:27:06 PM	38242
EPA METHOD 8015D: GASOLINE RANG	E				Analyst	NSB
Gasoline Range Organics (GRO)	ND	3.9	mg/Kg	1	5/22/2018 12:18:11 PM	38240
Surr: BFB	92.1	15-316	%Rec	1	5/22/2018 12:18:11 PM	38240
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.019	mg/Kg	1	5/22/2018 12:18:11 PM	38240
Toluene	ND	0.039	mg/Kg	1	5/22/2018 12:18:11 PM	38240
Ethylbenzene	ND	0.039	mg/Kg	1	5/22/2018 12:18:11 PM	38240
Xylenes, Total	ND	0.078	mg/Kg	1	5/22/2018 12:18:11 PM	38240
Surr: 4-Bromofluorobenzene	102	80-120	%Rec	1	5/22/2018 12:18:11 PM	38240

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

Chain-of-Custody Record Client: BLAGG ENGR. / BP AMERICA			Standard Project Name	Rush _	SAME DAY												ME!			
Mailing Ad	ddress:	P.O. BO	X 87	- I roject Hame	GCU # 58	0	www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 8710													
			FIELD, NM 87413	Project #:	400 11 30						45-3						410 -410			
Phone #:		(505) 63		1				16	1. 30	JJ-3.	43-3	-				ques		7		
email or F	ax#:			Project Manag	ger:	VII VIII VIII VIII VIII VIII VIII VIII														100
QA/QC Pad	_		Level 4 (Full Validation)		ERIN GARII	FALOS	1218)	only)	MRO)			(S		04,504	PCB's			er - 300.1)		
Accreditat		□ Other		Sampler:	NELSON VE	LEZ No 947	₩85 (8021B)	+ TPH (Gas only)	/ DRO /	418.1)	04.1)	270SIM		3,NO ₂ ,F	/ 8082		7	0.0 / water		sample
□ EDD (T					erature: 10		I	+ 1	GRO	pd 4	od 5	or 8,	tals	NO,	ides	7	-40	- 300		e Site
Date	Time	Matrix	Sample Request ID	Container Type and # Mouth L	Preservative Type	HEAL NO.	BTEXMTB	BTEX + MTBE	TPH 8015B (GRO	TPH (Method	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0		Grab sample 5 pt. composite sample
5/21/18	1145	SOIL	5PC-ТВ @ 4 / (95)	4 oz 1	Cool	70	٧		٧									٧		V
Date: 5/z1/18	Time: 1340	Relinquishe	Mr V	10/0	- Wat =	10/18 101	Remarks: BILL DIRECTLY TO BP USING THE CONTACT WITH CORRES & REFERENCE # WHEN APPLICABLE; CONTACT: ERIN GARIFALOS / VANCE HIXON			RRESI	ONDIN									
Date:	Time: 1730	Relinquishe	both Walt	Received by:	n h	Date Time 05/22/18 _ 0645	VID: VHIXONEVB2 Reference # P - 991													

Hall Environmental Analysis Laboratory, Inc.

WO#: 1805B34

25-May-18

Client:

Blagg Engineering

Project:

GCU 580

Sample ID MB-38253

SampType: mblk

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 38253

RunNo: 51434

SPK value SPK Ref Val %REC LowLimit

Units: mg/Kg

Prep Date: Analyte

5/22/2018

Analysis Date: 5/22/2018

SeqNo: 1676144

HighLimit

RPDLimit Qual

Chloride

Result PQL ND 1.5

TestCode: EPA Method 300.0: Anions

%RPD

Sample ID LCS-38253

SampType: Ics

RunNo: 51434

Client ID: LCSS Batch ID: 38253

Units: mg/Kg

Prep Date: 5/22/2018 Analysis Date: 5/22/2018

SeqNo: 1676145

%RPD

Qual

Analyte

SPK value SPK Ref Val %REC 15.00

HighLimit

RPDLimit

Chloride

94.9

110

Result

LowLimit

1.5

PQL

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

Η Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Practical Quanitative Limit **PQL**

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

E Value above quantitation range

Analyte detected below quantitation limits

Page 2 of 5

P Sample pH Not In Range

Reporting Detection Limit RL

Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#: 1805B34

25-May-18

Client:

Blagg Engineering

Project: GCU 58	30		
Sample ID LCS-38242	SampType: LCS	TestCode: EPA Method 8015M/D: D	Diesel Range Organics
Client ID: LCSS	Batch ID: 38242	RunNo: 51394	
Prep Date: 5/22/2018	Analysis Date: 5/22/2018	SeqNo: 1674203 Units: mg	/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit	%RPD RPDLimit Qual
Diesel Range Organics (DRO)	48 10 50.00	0 96.8 70 130	
Surr: DNOP	4.1 5.000	82.2 70 130	
Sample ID MB-38242	SampType: MBLK	TestCode: EPA Method 8015M/D: D	Piesel Range Organics
Client ID: PBS	Batch ID: 38242	RunNo: 51394	
Prep Date: 5/22/2018	Analysis Date: 5/22/2018	SeqNo: 1674204 Units: mg/	'Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit	%RPD RPDLimit Qual
Diesel Range Organics (DRO)	ND 10		
Motor Oil Range Organics (MRO)	ND 50		
Surr: DNOP	8.9 10.00	88.6 70 130	
Sample ID LCS-38269	SampType: LCS	TestCode: EPA Method 8015M/D: D	liesel Range Organics
Client ID: LCSS	Batch ID: 38269	RunNo: 51394	
Prep Date: 5/22/2018	Analysis Date: 5/23/2018	SeqNo: 1676949 Units: %R	ec
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit	%RPD RPDLimit Qual
Surr: DNOP	5.3 5.000	105 70 130	
Sample ID MB-38269	SampType: MBLK	TestCode: EPA Method 8015M/D: D	iesel Range Organics
Client ID: PBS	Batch ID: 38269	RunNo: 51394	
Prep Date: 5/22/2018	Analysis Date: 5/23/2018	SeqNo: 1676950 Units: %R	ec
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit	%RPD RPDLimit Qual
Surr: DNOP	12 10.00	116 70 130	

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix D

Η Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

Analyte detected in the associated Method Blank

E Value above quantitation range

Analyte detected below quantitation limits

Page 3 of 5

Sample pH Not In Range

Reporting Detection Limit RL

Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

Client:

Blagg Engineering

Project: GCU 58	30						
Sample ID MB-38240	SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range						
Client ID: PBS	Batch ID: 38240 RunNo: 51433						
Prep Date: 5/21/2018	Analysis Date: 5/22/2018 SeqNo: 1674601 Units: mg/Kg						
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual						
Gasoline Range Organics (GRO)	ND 5.0						
Surr: BFB	890 1000 89.0 15 316						
Sample ID LCS-38240	SampType: LCS TestCode: EPA Method 8015D: Gasoline Range						
Client ID: LCSS	Batch ID: 38240 RunNo: 51433						
Prep Date: 5/21/2018	Analysis Date: 5/22/2018 SeqNo: 1674602 Units: mg/Kg						
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual						
Gasoline Range Organics (GRO)	29 5.0 25.00 0 115 75.9 131						
Surr: BFB	1100 1000 108 15 316						
Sample ID MB-38263	SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range						
Client ID: PBS	Batch ID: 38263 RunNo: 51480						
Prep Date: 5/22/2018	Analysis Date: 5/23/2018 SeqNo: 1676698 Units: %Rec						
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual						
Surr: BFB	910 1000 91.4 15 316						
Sample ID LCS-38263	SampType: LCS TestCode: EPA Method 8015D: Gasoline Range						
Client ID: LCSS	Batch ID: 38263 RunNo: 51480						
Prep Date: 5/22/2018	Analysis Date: 5/23/2018 SeqNo: 1676699 Units: %Rec						
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual						
Surr: BFB	1000 1000 105 15 316						

Qualifiers:

Value exceeds Maximum Contaminant Level.

Sample Diluted Due to Matrix D

Holding times for preparation or analysis exceeded H

Not Detected at the Reporting Limit ND

PQL Practical Quanitative Limit

% Recovery outside of range due to dilution or matrix

В Analyte detected in the associated Method Blank

Value above quantitation range

Analyte detected below quantitation limits

Page 4 of 5

WO#:

1805B34

25-May-18

P Sample pH Not In Range

Reporting Detection Limit

Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1805B34

25-May-18

Client:

Blagg Engineering

Project:

GCU 580

Project: GCU 5	80									
Sample ID MB-38240	SampTy	ре: МВ	BLK	TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batch ID: 38240			RunNo: 51433						
Prep Date: 5/21/2018	Analysis Da	te: 5/2	22/2018	5	SeqNo: 1	674638	Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.025								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120			
Sample ID LCS-38240	SampType: LCS TestCode: EPA Method 8021B: Volatiles									
Client ID: LCSS	Batch ID: 38240			RunNo: 51433						
Prep Date: 5/21/2018	Analysis Da	te: 5/2	22/2018	8	SeqNo: 1	674639	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.97	0.025	1.000	0	96.7	77.3	128			
Toluene	0.99	0.050	1.000	0	98.6	79.2	125			
Ethylbenzene	0.97	0.050	1.000	0	97.4	80.7	127			
Xylenes, Total	3.0	0.10	3.000	0	100	81.6	129			
Surr: 4-Bromofluorobenzene	1.1		1.000		107	80	120			-
Sample ID MB-38263	SampTy	SampType: MBLK TestCode: EPA Method 8021B: Volatiles								
Client ID: PBS	Batch I	Batch ID: 38263			RunNo: 51480					
Prep Date: 5/22/2018	Analysis Da	te: 5/2	23/2018	/2018 SeqNo: 1676739 Units: %Rec						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120			
Sample ID LCS-38263	SampTyp	SampType: LCS TestCode: EPA Method 8021B: Volatiles								
Client ID: LCSS	Batch I	Batch ID: 38263		RunNo: 51480						
Prep Date: 5/22/2018	Analysis Da	te: 5/2	23/2018	S	eqNo: 10	676740	Units: %Red	С		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual

Qualifiers:

Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

1.0

1.000

ND Not Detected at the Reporting Limit

PQL Practical Quanitative Limit

Surr: 4-Bromofluorobenzene

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

103

80

120

J Analyte detected below quantitation limits

Page 5 of 5

P Sample pH Not In Range

RL Reporting Detection Limit

W Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLA	Work Order N	umber: 1805B34	RcptNo: 1			
Received By: Ana	ne Thorne	5/22/2018 6:45:0	00 AM	Anne Am	_	
Completed By: Ann	ne Thorne	orne 5/22/2018 7:13:13		Om I.		
Reviewed By:	F05/22	5/22/18		Carra Ji Ca		
Chain of Custody						
1. Is Chain of Custody			Yes 🗸	No 🗌	Not Present	
2. How was the samp	le delivered?		Courier			
Log In						
Was an attempt ma	Yes 🗹	No 🗌	NA \square			
4. Were all samples re	ceived at a temperatur	e of >0° C to 6.0°C	Yes 🗹	No 🗆	NA 🗆	
5. Sample(s) in proper	container(s)?		Yes 🗹	No 🗆		
6. Sufficient sample vo	lume for indicated test	(s)?	Yes 🗹	No 🗆		
7. Are samples (except	Yes 🗹	No 🗌				
8. Was preservative ac	ided to bottles?		Yes	No 🗹	NA 🗌	
9. VOA vials have zero	headspace?		Yes	No \square	No VOA Vials 🗸	
10. Were any sample containers received broken?			Yes	No 🗹	# of preserved	
					bottles checked	
11. Does paperwork ma			Yes 🗹	No 🗌	for pH:	12 unless noted)
(Note discrepancies on chain of custody)			Yes 🗸	No 🗆	Adjusted?	12 unless noted)
12. Are matrices correctly identified on Chain of Custody? 13. Is it clear what analyses were requested?			Yes ✓ Yes ✓	No 🗆		
14. Were all holding times able to be met?			Yes 🗹	No 🗆	Checked by:	
(If no, notify custome			. 163			
Special Handling (i	if applicable)					
15. Was client notified of	of all discrepancies with	this order?	Yes	No 🗌	NA 🗸	
Person Notifie	d:	Da	te	A STATE OF THE STATE OF THE STATE OF		
By Whom:	The second secon	Via	a: eMail Ph	one Fax	☐ In Person	
Regarding:	Talan Mari Mari Madinasan in a mingapan di Nasio Adalah Mada Asar asar menjadi ing		AND			
Client Instruct	ions:	CO SEL MEL MEL MEL MEL MENTE SER COMPANION SER COMPANION CONTRACTOR CONTRACTO	AND STATE AND AND ADMINISTRATING TO STATE AND	in der den gest der	GALAN AN ANNA AN	
16. Additional remarks:						
17. Cooler Information	<u>n</u>					
Cooler No Ter	np °C Condition S	Seal Intact Seal No	Seal Date S	Signed By		
1 1.0	Good Y	es				



