Susana Martinez Governor

Ken McQueen Cabinet Secretary

Matthias Sayer Deputy Cabinet Secretary Heather Riley, Division Director Oil Conservation Division



New Mexico Oil Conservation Division approval and conditions listed below are made in accordance with OCD Rule 19.15.7.11 and are in addition to the actions approved by BLM on the following <u>3160-4 or 3160-5</u> form.

Operator Signature Date: 11/2/18 Well information: HILCORP ENERGY COMPANY SAN JUAN 27 5 UNIT #089, API# 30-039-07177

Application Type:

Drilling/Casing Change Location Change

Recomplete/DHC (For hydraulic fracturing operations review EPA Underground injection control Guidance #84; Submit Gas Capture Plan form prior to spudding or initiating recompletion operations)



P&A

Conditions of Approval:

- Notify the NMOCD 24hrs prior to beginning operations.
- Submit the CBL to the agencies for review and approval prior to any remediation or perforations.

Kuthuic Preh

NMOCD Approved by Signature

<u>11/29/18</u> Date

N							
Form 3160-5 (August 2007)	UNITED STAT DEPARTMENT OF THE BUREAU OF LAND MA	E INTERIO			OMB N	APPROVED lo. 1004-0137 July 31, 2010	C. Co
					5. Lease Serial No.	/ISF079393	13
	NDRY NOTICES AND REP				6. If Indian, Allottee or Tribe		
	se this form for proposals I well. Use Form 3160-3 (A						
	UBMIT IN TRIPLICATE - Other ins				7. If Unit of CA/Agreement, N	Jame and/or No.	
1. Type of Well							
Oil Well	X Gas Well Other				8. Well Name and No. San Ju	an 27-5 Unit 89	
2. Name of Operator		9. API Well No.					
3a. Address	Hilcorp Energy Compa	1	o. (include area c	ode)	30-039-07177 10. Field and Pool or Exploratory Area		
382 Road 3100, Aztec,		5	05-599-3400		Blanco Mesa	averde/Basin Da	kota
4. Location of Well <i>(Footage, Sec., T.,</i> Surface Unit L (R.,M., or Survey Description) NWSW) 1589'FSL & 800' F	WI Sec 4	T27N R05	w	11. Country or Parish, State Rio Arriba	New Mexic	0
	1000 1000 100 000 1	WL, 000	, 12/14, 100	••	No Amba	, New MEXIC	
12. CHECK	THE APPROPRIATE BOX(ES)) TO INDIC	ATE NATURE	OF NOT	TICE, REPORT OR OTH	ER DATA	
TYPE OF SUBMISSION			TYPE	OF AC	TION		
X Notice of Intent	Acidize	Deepen			roduction (Start/Resume)	Water Shut-Off	
Subsequent Report	Alter Casing Casing Repair	Fracture	Treat nstruction		eclamation .ecomplete	Well Integrity	
Subsequent Report	Change Plans		l Abandon		emporarily Abandon	Other	
Final Abandonment Notice	Convert to Injection	Plug Ba			Vater Disposal		
the existing Dakota. At	ny plans to recomplete the ttached is the MV C102, re ed prior to commingling. A e disturbing activities.	complete	procedure 8	wellb	ore schematic. The D	HC application	
	-	n	47.95×				
	NMOC	U			OVAL OR ACCEPTANCE	OF THIS	
	NOV 26	2018	ACTI	ON DOI	ES NOT RELIEVE THE L	ESSEE AND	
			ODE	DATOD	FROM OBTAINING ANY	OTHER	
	DISTRICT		N IN F	EDERA	L AND INDIAN LANDS		
14. I hereby certify that the foregoing i	s true and correct. Name (Printed/Typ	ped)					
Tammy Jones			Title Opera	tions/R	egulatory Technician - S	Sr.	
7	/						
Signature Jamy	mas		Date		11/2/2018	8	
	THIS SPACE FO	OR FEDER	AL OR STAT	TE OFF	ICE USE		
Approved by	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		Ti	tle	Æ	Date /1 /19	/18
Conditions of approval, if any, are attact that the applicant holds legal or equitable entitle the applicant to conduct operation	ble title to those rights in the subject leases thereon.	ase which wou	old O		FFO		
Title 18 U.S.C. Section 1001 and Title false, fictitious or fraudulent statements				d willfully	to make to any department or a	agency of the United St	ates any
(Instruction on page 2)		FY	B	P			

District I

-

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form	C-102
August	1, 2011

Permit 259255

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	3. Pool Name
30-039-07177	72319	BLANCO-MESAVERDE (PRORATED GAS)
4. Property Code	5. Property Name	6. Well No.
318920	SAN JUAN 27 5 UNIT	089
7. OGRID No.	8. Operator Name	9. Elevation
372171	HILCORP ENERGY COMPANY	6626

10. Surface Location

	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	L	. 4	27N	05W		1589	S	800	W	RIO ARRIBA
1										

11. Bottom Hole Location If Different From Surface										
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
12. Dedicated Acres 320.23		13. Joint or Infill		14. Consolidation Code 15. Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.
E-Signed By: <i>Tammy Jones</i> Title: Operations/Regulatory Technician - Sr. Date: 11/2/2018
SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.
Surveyed By: David Kilven
Date of Survey: 9/27/1962
Certificate Number: 1760

Hilcorp

. . .

HILCORP ENERGY COMPANY San Juan 27-5 Unit 89 MESA VERDE RECOMPLETION SUNDRY

	JOB PROCEDURES
· 1.	MIRU service rig and associated equipment; test BOP.
2.	TOOH with 2 3/8" tubing set at 7,831'.
3.	Set a 4-1/2" cast iron bridge plug at +/- 7,590' to isolate the Dakota.
4.	Load the hole and run a CBL from the CIBP to surface. Squueze as needed based on the CBL.
5.	Set a 4-1/2" cast iron bridge plug at +/- 5,890' to isolate the Stage Tool.
6.	Perforate the Mesa Verde (Top Perforation @ 5,024'; Bottom Perforation @ 5,828').
7.	RIH with a packer and 2-7/8" Frac string, setting depth TBD based on CBL results. NU Test Frac stack and frac string.
8.	Frac the Mesa Verde
9.	Nipple down frac stack, nipple up BOP and test.
10.	TOOH 2-7/8" Frac String.
11.	TIH with a mill.
12.	Clean out to Dakota isolation plug.
13.	Drill out Dakota isolation plug and cleanout to PBTD of 7,886'. TOOH.
14.	TIH and land production tubing at 7,831'.



•

· •

-

HILCORP ENERGY COMPANY San Juan 27-5 Unit 89 MESA VERDE RECOMPLETION SUNDRY

.. ..

 	ilcorp E	nergy Company	Current So	chematic - V	ersion 3					
	lame:	SAN JUAN 27-5 UNIT #89) Field Name			10000				
3003907		Surface Lagal Location 004-027N-005W-L	BASIN DAKOTA (PRO		Route 1310	State Province NEW ME	XICO	Well Configuration Type VERTICAL		
around Eleva		Original K5/RT Elevation (ft) 6,634,00	K3-Groun 12.00	nd Distance (ft)	K5-Casing Flange D	listance (ft)	KS-Tubing Hange	er Distance (11)		
		VEF	RTICAL, Original	Hole, 10/30/2	018 1:55:08	BPM				
MD (ftKB)	TVD (ftKB)									
12.1					فتساو و در اور و د دان المودة			nt; 12.0-314.0;		
313.0								with 232 sacks Regular bls to surface.		
314.0						1; Surface		0.19 in; 12.0 ftKB; 314.0		
323.1					Contraction of	ftKB				
610.2										
2,770.0		-OJO ALAMO (final)								
2,961.9		-KIRTLAND (final)								
3,214.9		FRUITLAND (final)								
3,214.9		(non band (intal)								
2,451.1								ement: 3,310.0-3,614.0		
3,551.0							2; Cemented 3310' (CBL 1	with 155 sacks Diamix - 2/16/1962)		
3,501.0		-LEWIS (final)					and the summer			
3,513.0										
3,559.1		Tubing; 2 3/8 in; 4.70 lb	v/ft; J-65; 12.1 ftKB:		D					
5,020.0		MESA VERDE (final)	7,796.2 ftKB							
5,121.1										
		MENEFEE (final)								
5,375.0		DONITI O OKOUT / C II				Intermedi	ate Casing C	ement: 5,376.0-5,850.0 wtih 190 Diamix A.		
5,515.1		POINT LOOKOUT (final)				TOC at 5	376' (CBL 12/	16/1962)		
5,777.9										
5,850.1										
5,895.0										
5,895.7										
5,945.9		OALLUD (Encl)								
		GALLUP (final)								
5,359.4 7,059.9				~~~		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~				
7,541.0		GREENHORN (final)						ement: 7,070.0-7,918.6 with 215 sacks Class		
7,541.0		GRANEROS (final)					t 7070" (CBL			
7,640.1		Tubing Pup Joint; 2 3/8	3 in: 4 70 lb/ft-1_55-1							
7,795.3		7,796.3	2 ftKB; 7,798.4 ftKB	15555	1 X5555	Dakota; 7	,640.0-7,850.	0: 12/17/1962		
7,798.6		Tubing; 2 3/8 in; 4.70 lb/ft;	J-55; 7,798.4 ftKB; 7,829.3 ftKB	2000X	30000 120000					
7,829.4		1.78 F-NIPPLE; 2 3/8	in; 4.70 lb/ft; J-55;	1000	122522					
7,830.4		7,829. Notched collar: 2 3/8	3 ftKB; 7,830.4 ftKB	20100	3330					
7,831,0			4 ftKB; 7,831.0 ftKB	2000	1920					
7,550.1				SADAX	10000					
7,370.1		Rathol= 36	below bottom perf.		1000					
7,885.2		inautore 30	PBTD; 7.886.0							
7,885.5			[1 D D, 7.000.0]							
7,588.1										
7,918.0										
7,918.0								; 4.00 in; 12.0 ftKB;		
7,919.9					Smith	7,918.6 ft	КĎ			
www.p	eloton.co	m		Page 1/1			Re	port Printed: 10/30/2018		