Form 3160-5 (June 2015)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018


SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an NMSF078459B

Lease Serial No.

abandoned well. Use form 3160-3 (APD) for such proposals.					6. If Indian, Allottee or	Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agreement, Name and/or No. 892000752A		
Type of Well					8. Well Name and No. ALLISON UNIT 7		
Name of Operator     HILCORP ENERGY COMPANY  Contact: PRISCILLA SHORTY E-Mail: pshorty@hilcorp.com  E-Mail: pshorty@hilcorp.com				9. API Well No. 30-045-11474-00-C1			
			(include area code) 4.5188		10. Field and Pool or Exploratory Area BASIN DAKOTA BLANCO MESAVERDE		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, State		
Sec 10 T32N R7W SESE 0990FSL 0990FEL 36.990230 N Lat, 107.548260 W Lon					SAN JUAN COUNTY, NM		
12. CHECK THE AF	PPROPRIATE BOX(ES) TO I	NDICATE NAT	URE OF	NOTICE,	REPORT, OR OTH	ER DATA	
TYPE OF SUBMISSION	TYPE OF SUBMISSION TYPE OF ACTION					-	
☐ Notice of Intent	☐ Acidize	□ Deepen	Deepen Pro		ion (Start/Resume)	☐ Water Shut-Off	8
	☐ Alter Casing	☐ Hydraulic Fracturing		□ Reclamation		■ Well Integrity	
Subsequent Report	☐ Casing Repair	■ New Construction		☐ Recomplete		Other	
☐ Final Abandonment Notice	☐ Change Plans	☐ Plug and Abandon		☐ Temporarily Abandon		Workover Operations	
	☐ Convert to Injection	☐ Plug Back		☐ Water Disposal			
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.  8/17/2018 - MIRU BHE 37. ND WH, NU BOPE. Function test BOP. PT BOP. Test good. PU and LD tbg hanger. Tag 70' of fill @ 8352'. SWI. SDFN.  8/20/2018 - TOOH 265 jts 2-3/8 tbg. PU 6-1/8" bit w/ 6-1/8" string mill and TIH. Tag @ 8189'. PU and RU power swivel. SWI. SDFN.  8/21/2018 - Est circ. Ream and clean out 6-1/8" open hole from 8185' to 8331'. LD 6 jts w/ tbg swivel. SWI. SDFN.  8/22/2018 - Est circ at 8150' csg shoe w/ air mist. Clean out bridge @ 8231'. Ream and clean out 6-1/8" open hole from 8275' to 8331'. Work tight hole. TOOH LD clean out assembly. PU BHA and TIH drifting tbg to 4577'. Pump 220 gals of PFR 2631 15% inhibited HCL down tbg. SWI. SDFN.							
14. I hereby certify that the foregoing is true and correct.  Electronic Submission #439886 verified by the BLM Well Information System  For HILCORP ENERGY COMPANY, sent to the Farmington  Committed to AFMSS for processing by JACK SAVAGE on 11/06/2018 (19JWS0028SE)							
Name (Printed/Typed) PRISCILLA SHORTY			OPERAT	IONS REG	BULATORY TECH		
Signature (Electronic S	Date	Date 10/16/2018					
	THIS SPACE FOR FE	EDERAL OR S	TATE O	FFICE US	SE		
Approved By ACCEPTED			CK SAVA TROLEU	IN ENGINEED		Date 11/06/2	018
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Farmington				
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s				villfully to ma	ke to any department or a	gency of the United	

\*\* BLM REVISED \*\*





## Additional data for EC transaction #439886 that would not fit on the form

## 32. Additional remarks, continued

8/23/2018 - Est circ w/ air mist. Circ out acid @ 8180'. Install tbg hanger, land in WH. Land 268 jts 2-3/8" tbg @ 8154'. SN 1.78 ID @ 8153'. PBTD @ 8231'. RD floor. ND BOPE. NU WH. PT tbg to 500 psi, test good. Pump off exp chk @ 1100 psi. RD RR BHE 37 @ 13:00 hrs on 8/23/2018.