

Chaco 2206 2H 225H API # 30-043-21149



Location

SHL: 1666' FNL 278' FEL Sec: 2 Twnshp: 22N Rge: 6W
BHL: 392' FNL 280' FWL Sec: 2 Twnshp: 22N Rge: 6W

Spud Date: 7/6/2013
Completion: 8/28/2013
Pool Name: Lybrook GL HZ
Tubing Length 4/18/2019

Wellbore updated 4/18/19 lg

Tops	MD	TVD
Ojo Alamo	1325'	1316'
Kirtland	1619'	1595'
Pictured Cliffs	1892'	1849'
Lewis	2015'	1962'
Chacara	2354'	2275'
Cliff House	3553'	3385'
Menefee	3588'	3417'
Point Lookout	4332'	4114'
Mancos	4524'	4302'
Gallup	4910'	4686'

HOLE SIZE	CASING	CEMENT	VOLUME	CMT TOP
12-1/4"	9-5/8"	256 sx	299 cu.ft.	Surface
8-3/4"	7"	940 sx	1297 cu. ft.	Surface
6-1/8"	4-1/2"	460 sx	669 cu. ft.	1370' TOC

Landed @ 5700' w/ 180 jnts of 2-3/8", 4.7# J55
RIH WITH RODS, REPLACED BAD RODS WHERE NEEDED, (ROD STRING RAN , 1 1/2" X 26'
POLISH ROD, 8' 8" X 7/8" PONY SUBS, 53 X 7/8" OLD GUIDED RODS, 11 X 7/8" NEW
MOLDED GUIDES W/4/PER, 48 X 3/4" GUIDED RODS, 20 X 7/8" NEW WITH MOLDED
GUIDES WITH 4/PER, 20 X 7/8" GUIDED OLD RODS WITH 6/PER, 10 X 7/8" NEW GUIDED
RODS W/6/PER, 10 X 1 1/4" K BARS WITH 4' X 7/8" STABILIZER ON EACH ONE, NEW 26K
SHEAR SUB, 2" X 1 1/4" X 20 RHBC WITH 1 1/4" X 15' DIP TUBE AND MAX 163" STROKE.

Frac and Perf- 6005-10162'

12 1/4"
Hole

8 3/4"
Hole

6 1/8"
Hole

RAN 10 JTS, 9-5/8", LT&C, 36#, J-55, CSG
SET @ 429', SHOE @ 427', FC @ 385' Casing -
Hole Size: 12-1/4"

Run 131 jts 7", 23#, K-55, LT&C csg. Landed
@ 5985', FC @ 5935'
Intermediate Casing - Hole Size: 8-3/4"

RUN 272 JTS 4-1/2" 11.6#, N-80, 8RD LT&C
CASING. SET @ 10208' MD (5344' TVD),
MARKER JTS @ 8489', 6802' AND 4961' MD.
FC SET @ 10167' Production Casing - Hole
Size: 6-1/8"

TD @ 10219'

PBTD @ 10167'