This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

perator Hilo	orp Energ	y Company	Leas	e Name SAN	JUAN 27-5 UN	IIT	Well No. 61A
ocation of W	ell: Unit L	etter I S	ec 05	Twp 027N	Rge	005W API	# 30-039-21859
	Na	ame of Reservoir or Poo	I	Type of Prod		Method of Prod	Prod Medium
Upper Completion	PC	PC		Gas			Casing
Lower Completion	MV		Gas	Gas		ial Lift	Tubing
			Pre-Flow S	Shut-In Pressı	ure Data		
Upper Completion Lower Completion	4/30/2019 er Hour, Date, Shut-In			Length of Time Shut-In		192 ss. PSIG 138	Stabilized?(Yes or No) Yes Stabilized?(Yes or No) Yes
			Flo	ow Test No. 1			
Commenced	at: 5/6/20	019		Zone Pro	oducing (Upper	r or Lower): UP	PER
Time (date/time)		Lapsed Time Since*	Upper zone	SSURE Lower zone	Prod Zone Temperature		Remarks
5/6/2019 10:57 AM		0	110	138		ST- 107 Flow RT meter Csg 110	
5/6/2019 11:00 AM		1	106	138		St 107 Flow RT 100 Csg 106	
5/6/2019 11:05 AM		1	103	103 138		St 107 Flow RT 83 CSG 103	
oduction rat	e during te	est					
il:	BPOD Based on:		Bbls. In	s. In Hrs.		Grav. GOR	
as		MCFPD; Test th	nru (Orifice or N	Meter)			
			Mid-Tost 9	Shut In Bross	uro Data		
Upper Completion	Hour, Dat	Hour, Date, Shut-In		d-Test Shut-In Pressure Data Length of Time Shut-In		ss. PSIG	Stabilized?(Yes or No)
Lower Completion	Hour, Date, Shut-In					ss. PSIG	Stabilized?(Yes or No)

(Continue on reverse side)



Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Commenced at:			Zone Pro	Zone Producing (Upper or Lower)			
Time (date/time)	Lapsed Time Since*	PRESSURE		Prod Zone Temperature	Remarks		
(date/time)	Since	Upper zone	Lower zone	remperature	Remarks		
				-			
Production rate during Oil:BPOD		Phie in	Ure	,	Grav. GOR		
Gas	MCFPD; Test t	hru (Orifice or M	eter)				
Remarks:							
·							
		contained is true	and complete	to the best of	my knowledge.		
		contained is true	-		my knowledge. Energy Company		
I hereby certify that the Approved: 19-M/New Mexico 91 Co	91-7 nservation Division	_	Opera		Energy Company		
Approved: 14-M/	91-7 nservation Division	_	Opera	tor: <u>Hilcorp E</u> Danny Trujill	Energy Company		

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

A packer leakage test shall be commenced on each multiply completed well within seven days after actual
completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.
Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or
chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or
the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when
requested by the Division.

District #3

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).