District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

MAG	MA	BLEIGH	THORY	TAT	ART
GAS	(A	PII	I K H		. A

Date: 5/20/2019		GAS CAI	TURE PLAN			
☑ Original☐ Amended - Reason f	or Amendment:		& OGRID No.: <u>Hil</u>	corp Energy	y Company	372171
new completion (new dr	rill, recomplete	to new zone, re-frac				
Well(s)/Production Fac	•	•	ling 60 days allowed by Rule (S	ыоѕесноп A ој	19.15.18.121	VMAC).
The well(s) that will be	located at the pr	roduction facility ar	e shown in the table below	'.		
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
NYE 10E	3004524872	G, 12, 30N, 11W	1540' FNL, 1530' FEL	345	Vented	

Gathering System and Pipeline Notification

This is a recompletion of a producing gas well. Gas production, sales and transportation infrastructure is already in place. The gas is dedicated to Harvest and will be connected to their gathering system located in San Juan County, New Mexico. Gas from these wells will be processed at Kutz Processing Plant located in Sec 13, Twn. 28N, Rng. 11W, San Juan County, New Mexico.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be routed to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Harvest</u> system at that time. Based on current information, it is <u>Hilcorp's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

MAY 2 2 2019

DISTRICT III

NMOCD

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines



