Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

5. Lease Serial No.

Do not use th	NMSF079162	A SECTION OF THE PROPERTY OF T					
abandoned we	6. If Indian, Allottee	or Tribe Name					
SUBMIT IN	7. If Unit or CA/Agr	7. If Unit or CA/Agreement, Name and/or No.					
Type of Well ☐ Oil Well	8. Well Name and No MKL 13	8. Well Name and No. MKL 13					
Name of Operator CROSS TIMBERS ENERGY	9. API Well No. 30-039-06615-	9. API Well No. 30-039-06615-00-S1					
3a. Address #36 ROAD 350 FLORA VISTA, NM 87415		3b. Phone No. (include area code) Ph: 827-334-7747		Field and Pool or Exploratory Area SOUTH BLANCO PICTURED CLIFFS			
4. Location of Well (Footage, Sec., 7	11. County or Parish	11. County or Parish, State					
Sec 7 T26N R7W NENE 782F 36.505417 N Lat, 107.607758	RIO ARRIBA (RIO ARRIBA COUNTY, NM					
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICATE NATURE O	F NOTICE, REPORT, OR OT	THER DATA			
TYPE OF SUBMISSION	TYPE OF ACTION						
Notice of Intent	☐ Acidize	☐ Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off			
☐ Notice of Intent	☐ Alter Casing	☐ Hydraulic Fracturing	□ Reclamation	■ Well Integrity			
Subsequent Report	☐ Casing Repair	■ New Construction	☐ Recomplete	☐ Other			
☐ Final Abandonment Notice	☐ Change Plans	□ Plug and Abandon	□ Temporarily Abandon				
G.C	☐ Convert to Injection ☐ Plug Back		☐ Water Disposal				
Attach the Bond under which the wor following completion of the involved	ally or recomplete horizontally rk will be performed or provide Loperations. If the operation re pandonment Notices must be fi	give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco	g date of any proposed work and approper and true vertical depths of all pertical depths of all pertical depths of all pertical depths of all pertical depths must be suppletion in a new interval, a Form 31 ing reclamation, have been completed	inent markers and zones. e filed within 30 days 60-4 must be filed once			
11/25/19 - RU Rig & Pump Ed LD rods, sinker bars,pump. NI 11/26/19 - TIH w string mill to ok.	D WH, NU BOP. TOH W	ts, tbs, sn & OEMA. TIH w stri	ng mill to 2100'				
Plug 1: 2182'-2128'. M&P 16 s capacity. TOOH. LD stinger. F	sx of Class G cmt. Displa RU WL. RIH w CBL tool to	ce w/frsh wtr to CR. Sting out, o 2128'. RD WL. Wait on NMO	reverse tbg CD to review log.				
RIH w HSC and perf 3 holes	@ 110'. TIH w tag sub to	2128'. Est circ w 5 bbls.					
Plug 1A: 2128'- 2025' M&P 8 sx of Class G cmt. Displace w/frsh wtr							

DEC 19 2019

14. I hereby certify that the foregoing is true and correct. Electronic Submission #496086 verifie For CROSS TIMBERS ENERGY Committed to AFMSS for processing by JOH			d by the BLM Well Information \$trink CT / LLC, sent to the Farmington N HOFFMAN on 12/18/2019 (19AMW0315SE)		111_			
Name (Printed/Typed)	SAMANNTHA AVARELLO	Title	REGULATORY TECHNICIAN					
Signature	(Electronic Submission)	Date	12/17/2019					
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								
Approved By ACCEPTED			OHN HOFFMAN ETROLEUM ENGINEER		Date 12/18/2019			
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office	Farmington					

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.





Additional data for EC transaction #496086 that would not fit on the form

32. Additional remarks, continued

Plug 2: 1869'- 1664'. M&P 16 sx of Class G cmt.

Plug 3: 1599'- 1253'. M&P 27 sx of Class B cmt.

11/27/2019 Plug 4: 386'- 110'. M&P 22 sx of Class G cmt.

Plug 5: 110'- 0'. M&P 42 sx of Class G cmt Wait on cmt sample. Dig out WH. Cut and remove WH. Found TOC @ surface inside 4.5". TOC inside 7" @ 45'. TOC inside 10 3/4" @ 80'. To off surface with 34 sks. Weld and install DHM @ 36* 30'22"N / 107* 36'30"W. RD Rig & Pump Equip. Clean and Secure location.

12/2/2019 - Top off 4 1/2" w/ 24 sks 1.15 G cmt, clean PT and RDMO.

RD Rig & Pump Equip. Clean and Secure location.

See attached CBL and WBD. We respectfully request expedited approval