

# State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

#### GAS CAPTURE PLAN

Date:4	/1	8/	<b>20</b>	19

⊠ Original	Operator & OGRID No.: DJR Operating LLC.; 371838
☐ Amended - Reason for Amendment:	

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

## Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location	Footages	Expected	Flared or	Comments
		(ULSTR)		MCF/D	Vented	
North Alamito Unit 332H		NWSE,Section 31, T23N, R7W	2178' FSL, 2564' FEL	1100	Flared	
North Alamito Unit 333H		NWSE,Section 31, T23N, R7W	2215' FSL, 2531' FEL	1450	Flared	
North Alamito Unit 559H		NWSE, Section 31, T23N, R7W	2193' FSL, 2550' FEL	1450	Flared	
North Alamito Unit 528H		NWSE, Section 31, T23N, R7W	2229' FSL, 2517' FEL	1100	Flared	
North Alamito Unit 529H	21334	NWSE, Section 31, T23N, R7W	2244' FSL, 2504' FEL	1450	Flared	

### **Gathering System and Pipeline Notification**

### Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on **Enterprise** system at that time. Based on current information, it is **DJR Operating LLC.'s** belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

### **Alternatives to Reduce Flaring**

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

