Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

5 Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on page 2					NMNM36943 6. If Indian, Allottee or Tribe Name		
					7. If Unit or CA/Agreement, Name and/or No.		
					NMNM135229A		
1. Type of Well ☐ Oil Well ☐ Gas Well ☐ Other					8. Well Name and No. NORTH ALAMITO UNIT 238H		
2. Name of Operator Contact: SHAW-MARIE FORD DJR OPERATING LLC E-Mail: sford@djrllc.com					9. API Well No. 30-043-21211-00-X1		
3a. Address 1 ROAD 3263 AZTEC, NM 87410	2-3476 ALAN		10. Field and Pool or E ALAMITO GALL BASIN MANCOS	ÚP			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, State		
Sec 30 T23N R7W SWSE 0429FSL 1341FEL 36.191683 N Lat, 107.611077 W Lon					SANDOVAL COUNTY, NM		
12. CHECK THE AF	PPROPRIATE BOX(ES)	TO INDICAT	TE NATURE O	F NOTICE,	REPORT, OR OTH	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
☐ Notice of Intent	☐ Acidize	□ Deep	☐ Deepen ☐ Productio		on (Start/Resume)	■ Water Shut-Off	
	☐ Alter Casing	☐ Hydr	raulic Fracturing		ntion	■ Well Integrity	
Subsequent Report	□ Casing Repair	□ New	Construction	☐ Recomp	lete	⊘ Other	
☐ Final Abandonment Notice	☐ Change Plans	Plug	lug and Abandon Tempor		rarily Abandon Drilling Operations		
36	Convert to Injection ☐ Plug Back ☐ Wat		☐ Water D	Disposal			
13. Describe Proposed or Completed Ope If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Abdetermined that the site is ready for final Production Liner & Cement 1/6/20: PT High 3000 psi 10 m choke manifold, IBOP, grey values in choke manifold.	ally or recomplete horizontally, good will be performed or provide to operations. If the operation restandonment Notices must be file inal inspection. In braden head, pipe ramalve. Low 250 psi 5 min: btd, IBOP, grey valve. PT 7 in the world will be provided to the prov	give subsurface I the Bond No. on ults in a multiple d only after all r as, stinger fle raden head, p nch casing to	ocations and measu file with BLM/BIA completion or reco equirements, includ c hose, all outer ope rams, stinge	red and true ve . Required sub impletion in a r ing reclamation valves in er flex hose,	rtical depths of all pertine sequent reports must be sew interval, a Form 3160 a, have been completed an	ent markers and zones. filed within 30 days 0-4 must be filed once	
good and recorded on chart (3rd party Willson Services). 1/7/20: Drill 6.125 inch hole to 5649 ft.					NMOCD		
1/8/20: Drill 6.125 inch hole to 9187 ft. 1/9/20: Drill 6.125 inch hole to 13805 ft. TOH							
1/10/20: RU BJ casing crew. Run 190 jts, 4 marker jts, 3 pups o <u>f 4.5 inch 11.6 lb P110 B</u> TC production liner casing from TOL: 5448 ft to BOL: 13800 ft. Float collar at 13785 (PBTD), Alpha							
Sleeve at 13763 ft. 1/11/20: RU BJ cement crew. PT lines to 5000 psi. Test good. 10 bbls FW spacer followed by 40 bbls DISTRICT							
14. I hereby certify that the foregoing is	Electronic Submission #4	ERATING LL¢	sent to the Farr	nington			
Name (Printed/Typed) SHAW-MARIE FORD			Title REGULATORY SPECIALIST				
Signature (Electronic S	Date 01/13/20	020					
	THIS SPACE FO	R FEDERA	L OR STATE	OFFICE US	SE		
Approved By ACCEPTED			JOHN HOP Title PETROLE		EER	Date 01/14/2020	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Farming	ton			
T							

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)
** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

Additional data for EC transaction #498979 that would not fit on the form

32. Additional remarks, continued

IntraGuard EZ II spacer. Cement with (50% excess) 196 bbls (705 sx) at 13.3 ppg, 1.56 yield at 7.70 gps. Displaced with 168 bbls FW with biocide. Bump plug. Check floats. Floats held. 55 bbls good cement back to surface. TOC: 5448 BOC: 13800. ND BOP. Install secure well cap. Rig Released 1/11/20 at 18:00.