

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

### GAS CAPTURE PLAN

Date: <u>5/10/2019</u>		
○ Original	C	Operator & OGRID No.: DJR Operating LLC.; 371838
Amandad Day	agan far A mandmant.	

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

#### Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
	NWSW,Section 31, T23N, R7W	1989' FSL, 675' FWL	1,450	Flared	
	NWSW,Section 31, T23N, R7W	2002' FSL, 713' FWL	1,100	Flared	
	NWSW,Section 31, T23N, R7W	1996' FSL, 694' FWL	1,450	Flared	
43-21342	NWSW,Section 31, T23N, R7W	2009' FSL, 732' FWL	1,100	Flared	
	43-	(ULSTR)  NWSW,Section 31, T23N, R7W  NWSW,Section 31, T23N, R7W  NWSW,Section 31, T23N, R7W  WSW,Section	(ULSTR)  NWSW,Section 31, T23N, R7W 675' FWL  NWSW,Section 2002' FSL, 713' FWL  NWSW,Section 1996' FSL, 694' FWL  WSW,Section 2009' FSL, 694' FWL	(ULSTR)       MCF/D         NWSW,Section 31, T23N, R7W       1989' FSL, 675' FWL       1,450         NWSW,Section 31, T23N, R7W       2002' FSL, 713' FWL       1,100         NWSW,Section 31, T23N, R7W       1996' FSL, 694' FWL       1,450         WSW,Section 2009' FSL, 1,100       1,100	(ULSTR)         MCF/D         Vented           NWSW,Section 31, T23N, R7W         1989' FSL, 675' FWL         1,450         Flared           NWSW,Section 31, T23N, R7W         2002' FSL, 713' FWL         1,100         Flared           NWSW,Section 31, T23N, R7W         1996' FSL, 694' FWL         1,450         Flared           WSW,Section 31, T23N, R7W         694' FWL         1,100         Flared           WSW,Section 2009' FSL, 1,100         Flared

## **Gathering System and Pipeline Notification**

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to <a href="Enterprise Field Services"><u>Enterprise Field Services, LLC (Enterprise)</u></a> and will be connected to <a href="Enterprise"><u>Enterprise's low/high</u></a> pressure gathering system located in <a href="Sandoval"><u>Sandoval County</u></a>, New Mexico. It will require approximately <a href="54">54'</a> of pipeline to connect the facility to DJR Operating LLC. low/high pressure Existing Pipeline in Sec. <a href="31">31</a>, <a href="T23N">T23N</a>, <a href="R7W">R7W</a> which ties into <a href="Enterprise">Enterprise'</a> existing pipeline in <a href="Section 25">Section 25</a>, <a href="T23N">T23N</a>, <a href="R7W">R7W</a>. <a href="DJR Operating LLC.">DJR Operating LLC.</a> provides (periodically) to <a href="Enterprise">Enterprise</a> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, <a href="DJR Operating LLC.">DJR Operating LLC.</a> and <a href="Enterprise">Enterprise</a> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at the <a href="Chaco Processing Plant">Chaco Processing Plant</a> located in Sec. <a href="16">16</a>, Twn <a href="26N">26N</a>, Rng <a href="12W">12W</a>, <a href="San Juan">San Juan</a> County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

#### Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on **Enterprise** system at that time. Based on current information, it is **DJR Operating LLC.'s** belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

### Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

